

Logical functions

DAX IN POWER BI



Carl Rosseel
Curriculum Manager

Overview of logical functions

Logical functions act upon an expression to return information about the values or sets in the expression.

The most used logical functions are:

- `IF()`
- `AND()`, `OR()`, `NOT()`
- `SWITCH()`

IF() is one of the most commonly used logic functions

Structure:

- `IF(<logical_test>, <value_if_true>[, <value_if_false>])`

Example:

- `Performance = IF([Total Sales] >= 50 000, "Target Reached", "Target Not Reached")`

IF() is one of the most commonly used logic functions

Structure:

- `IF(<logical_test>, <value_if_true>[, <value_if_false>])`

Example:

- `Performance = IF([Total Sales] >= 50 000, "Target Reached", "Target Not Reached")`

| Name | Total Sales |
|--------|-------------|
| Jenny | 48,431 |
| Jane | 76,528 |
| Dwayne | 24,167 |
| Thomas | 52,125 |

IF() is one of the most commonly used logic functions

Structure:

- `IF(<logical_test>, <value_if_true>[, <value_if_false>])`

Example:

- `Performance = IF([Total_Sales] >= 50 000, "Target Reached", "Target Not Reached")`

| Name | Total Sales | Performance |
|--------|-------------|--------------------|
| Jenny | 48,431 | Target not Reached |
| Jane | 76,528 | Target Reached |
| Dwayne | 24,167 | Target Not Reached |
| Thomas | 52,125 | Target Reached |

AND(), OR() & NOT() operators

All three operators return `TRUE` or `FALSE` as the output.

- `AND(<logical1>, <logical2>)`
 - Returns `TRUE` if both conditions are `TRUE`
 - *Example:* `AND(5 < 4, 5 < 6) = AND(FALSE, TRUE) = FALSE`
- `OR(<logical1>, <logical2>)`
 - Returns `TRUE` if at least one condition is `TRUE`
 - *Example:* `OR(5 < 4, 5 < 6) = OR(FALSE, TRUE) = TRUE`
- `NOT(<logical>)`
 - Changes `TRUE` to `FALSE` and vice versa
 - *Example:* `NOT(OR(5 < 4, 5 < 6)) = NOT(TRUE) = FALSE`

AND(), OR() & NOT() operators

AND can be replaced by &&

- `AND(5 < 4, 5 < 6) = 5 < 4 && 5 < 6`

OR can be replaced by ||

- `OR(5 < 4, 5 < 6) = 5 < 4 || 5 < 6`

The power of SWITCH()

Evaluates an expression against a list of values and returns one of multiple possible result expressions.

- `SWITCH(<expression>, <value>, <result>[, <value>, <result>] ... [, <else>])`
- Often preferred over nested `IF()` functions

```
Performance = SWITCH(TRUE,  
  [Total_Sales] < 25 000, "Poor",  
  [Total_Sales] < 50 000, "Below expectations",  
  [Total_Sales] < 75 000, "Above expectations",  
  "Exceptional")
```


The power of SWITCH()

```
Performance = SWITCH(TRUE,  
[Total_Sales] < 25 000, "Poor",  
[Total_Sales] < 50 000, "Below expectations",  
[Total_Sales] < 75 000, "Above expectations",  
"Exceptional")
```

| Name | Total Sales |
|--------|-------------|
| Jenny | 48,431 |
| Jane | 76,528 |
| Dwayne | 24,167 |
| Thomas | 52,125 |

The power of SWITCH()

```
Performance = SWITCH(TRUE,  
[Total_Sales] < 25 000, "Poor",  
[Total_Sales] < 50 000, "Below expectations",  
[Total_Sales] < 75 000, "Above expectations",  
"Exceptional")
```

| Name | Total Sales | Performance |
|--------|-------------|--------------------|
| Jenny | 48,431 | Below Expectations |
| Jane | 76,528 | Exceptional |
| Dwayne | 24,167 | Poor |
| Thomas | 52,125 | Above expectations |

The power of SWITCH()

```
DISCOUNT = SWITCH([Clothing Type],  
    "T-shirt", 0.15,  
    "Pants", 0.20,  
    "Belts", 0.30,  
    "Shoes", 0.25)
```

| Clothing Type |
|---------------|
| T-shirt |
| Pants |
| Belt |
| Shoes |

The power of SWITCH()

```
DISCOUNT = SWITCH([Clothing Type],  
    "T-shirt", 0.15,  
    "Pants", 0.20,  
    "Belts", 0.30,  
    "Shoes", 0.25)
```

| Clothing Type | Discount |
|---------------|----------|
| T-shirt | 15% |
| Pants | 20% |
| Belt | 30% |
| Shoes | 25% |

Let's switch it up!

DAX IN POWER BI

Logical functions in Power BI

DAX IN POWER BI



Carl Rosseel
Curriculum Manager

Let's practice!
DAX IN POWER BI

Row-level security

DAX IN POWER BI



Carl Rosseel
Curriculum Manager

What is row-level security?

Row-level security (RLS) in Power BI can be used to restrict data access for given users:

- Way to restrict data access for the logged in user
- You can define roles and rules with Power BI desktop
- A dashboard could look completely different depending on the person accessing it

What is row-level security?

Row-Level Security (RLS) uses filters to restrict data at the row level

| Name | Total Sales | Region |
|--------|-------------|--------|
| Jenny | 48,431 | East |
| Jane | 76,528 | West |
| Dwayne | 24,167 | West |
| Thomas | 52,125 | East |

```
Region = East
```

What is row-level security?

Row-Level Security (RLS) uses filters to restrict data at the row level

| Name | Total Sales | Region |
|--------|-------------|--------|
| Jenny | 48,431 | East |
| Jane | 76,528 | West |
| Dwayne | 24,167 | West |
| Thomas | 52,125 | East |

Region = East


| Name | Total Sales | Region |
|--------|-------------|--------|
| Jenny | 48,431 | East |
| Thomas | 52,125 | East |

Use cases of row-level security in Power BI

- Row-level security has multiple use cases:
 - User access requirements based on role (such as sales)
 - Restricting access requirements for a specific user or group of users
 - User wants specific/filtered data presented (such as a customer)


Use cases of row-level security in Power BI

- Row-Level Security has multiple use cases:
 - **User access requirements based on role (such as sales)**
 - Restricting access requirements for a specific user
 - User wants specific/filtered data presented (such as a customer)
- Switzerland Sales dashboard




Use cases of row-level security in Power BI

- Row-Level Security has multiple use cases:
 - User access requirements based on role (such as sales)
 - **Restricting access requirements for a specific user or group of users**
 - User wants specific/filtered data presented (such as a customer)
- Non sales dashboard



Use cases of row-level security in Power BI

- Row-Level Security has multiple use cases:
 - User access requirements based on role (such as sales)
 - Restricting access requirements for a specific user or group of users
 - **User wants specific/filtered data presented (such as a customer)**
- General Manager



DAX and row-level security

Row-level security utilizes DAX to:

- Provide filtered values at a row level
- Filter on fact or dimension tables
- *Example:* `[Is Salesperson] = True`

Dynamic row-level security

Ensures users only see the information appropriate for their roles

DAX has two main functions to enable this:

- `USERPRINCIPALNAME()`
 - Returns the user principal name (UPN), which is equal to the email address
 - Gives the same result in Power BI Desktop and Power BI Service
 - Preferred method
- `USERNAME()`
 - Alternative method to enable RLS with its own use cases
 - Outside the scope of this course

You can use these functions to create **personalized dashboards!**

Let's secure it!

DAX IN POWER BI

Managed roles in Power BI

DAX IN POWER BI



Carl Rosseel
Curriculum Manager

Let's practice!

DAX IN POWER BI