Stacking DataFrames

RESHAPING DATA WITH PANDAS



Maria Eugenia Inzaugarat

Data Scientist



Row multi-indices

		height	weight
Last	First		
Wick	John	185	68
	Julien	164	61
Shelley	Mary	164	59
	Frank	155	58

Setting the index

churn

```
credit_score age country num_products exited
0 619 43 France 1 Yes
1 608 34 Germany 0 No
2 502 23 France 1 Yes
```



Setting the index

```
churn.set_index(['country', 'age'], inplace=True)
```

```
credit_score num_products exited
age country
43 France 619 1 Yes
34 Germany 608 0 No
23 France 502 1 Yes
```

Multilndex from array

```
new_array = [['yes', 'no', 'yes'], ['no', 'yes', 'yes']]
churn.index = pd.MultiIndex.from_arrays(new_array, names=['member', 'credit_card'])
churn
```

```
credit_score age country num_products exited
member credit_card
                            619 43
                                                             Yes
                                     France
               no
  yes
                            608 34
                                                              No
                                    Germany
              yes
   no
                            502 23
                                     France
                                                             Yes
              yes
  yes
```

Multilndex DataFrames

		20	19	20	20
		height	weight	height	weight
Last	First				
Wick	John	185	68	185	70
	Julien	164	61	164	60
Shelley	Mary	164	59	164	60
	Frank	155	65	155	58

Multilndex DataFrames

```
2019
                                 2020
           year
        feature age weight age weight
          first
  last
  Wick
           John
                 25
                        68
                           26
                                   72
         Julien
                 31
                        72
                           32
                                   73
Shelley
           Mary
                 41
                       68
                           42
                                  69
          Frank
                 32
                        75
                            33
                                   74
```

The .stack() method

					Wick	John	height
		height	weight				weight
.ast	First			\longrightarrow		Julien	height
Nick	John	185	68			Janen	
	Julien	164	61				weight
Shelley	Mary	164	59		Shelley	Mary	height
	Frank	155	58				weight
						Frank	height
							weight

Last

First

df.stack()

The .stack() method

Rearrange a level of the columns to obtain a reshaped DataFrame with a new inner-most level row index

				Last	First	
		height	weight	Wick	John	height
Last	First	neight	Weight			weight
Wick	John	185	68		Julien	height
WICK	Julien	164	61			weight
Shelley	Mary	164	59	Shelley	Mary	height
Silelley	Frank	155	58			weight
	Halik	155	30		Frank	height
						weight

Stack into a series

churn

	credit_score	age	country	num_products	exited	
0	619	43	France	1	Yes	
1	608	34	Germany	0	No	
2	502	23	France	1	Yes	

churned_stacked = churn.stack()
churned_stacked.head(10)

member	credit_card		
yes	no	credit_score	619
		age	43
		country	France
		num_products	1
		churn	Yes
no	yes	credit_score	608
		age	34
		country	Germany
		num_products	0
		churn	No



Stack into a DataFrame

patients

	year		2019		2020
	feature	age	weight	age	weight
last	first				
Wick	John	25	68	26	72
	Julien	31	72	32	73
Shelley	Mary	41	68	42	69
	Frank	32	75	33	74

patients_stacked = patients.stack()
patients_stacked

		year	2019	2020
last	first	feature		
Wick	John	age	25	26
		weight	68	72
	Julien	age	31	32
		weight	72	73
Shelley	Mary	age	41	42
		weight	68	69
	Frank	age	32	33
		weight	75	74

Stack a level by number

patients

	year		2019		2020
	feature	age	weight	age	weight
last	first				
Wick	John	25	68	26	72
	Julien	31	72	32	73
Shelley	Mary	41	68	42	69
	Frank	32	75	33	74

patients.stack(level=0)

		feature	age	weight
last	first	year		
Wick	John	2019	25	68
		2020	26	72
	Julien	2019	31	72
		2020	32	73
Shelley	Mary	2019	41	68
		2020	42	69
	Frank	2019	32	75
		2020	33	74



Stack a level by name

patients

	year		2019		2020
	feature	age	weight	age	weight
last	first				
Wick	John	25	68	26	72
	Julien	31	72	32	73
Shelley	Mary	41	68	42	69
	Frank	32	75	33	74

patients.stack(level='year')

		feature	age	weight	
last	first	year			
Wick	John	2019	25	68	
		2020	26	72	
	Julien	2019	31	72	
		2020	32	73	
Shelley	Mary	2019	41	68	
		2020	42	69	
	Frank	2019	32	75	
		2020	33	74	

Let's practice!

RESHAPING DATA WITH PANDAS



Unstacking DataFrames

RESHAPING DATA WITH PANDAS



Maria Eugenia Inzaugarat

Data Scientist



Review



df.stack()

Undoing stacking process

Last	First		
Wick	John	height	185
		weight	68
	Julien	height	164
	Julien		
		weight	61
Shelley	Mary	height	164
		weight	59
	Frank	boight	155
	Frank	height	155
		weight	58


The .unstack() method

Last	First		
Wick	John	height	185
		weight	68
	Julien	height	164
	Julien.		
		weight	61
Shelley	Mary	height	164
		weight	59
	Frank	height	155
		weight	58

df.unstack()

The .unstack() method

Rearrange a level of the row index into the columns to obtain a reshaped DataFrame with a new inner-most level column index.



Unstack Series

churn_stacked

member	credit_card		
yes	no	credit_score	619
		age	43
		country	France
		num_products	1
		churn	Yes
no	yes	credit_score	608
		age	34
		country	Germany
		num_products	0
		churn	No
yes	yes	credit_score	502
		age	23
		country	France
		num_products	1
		churn	Yes



Unstack Series

churned_stacked.unstack()

			credit_score	age	country	num_products	ex	ited
membe	r credit	_card						
n	0	yes	608	34	Germany	0		No
ye	S	no	619	43	France	1		Yes
		yes	502	23	France	1		Yes



Unstacking a DataFrame

patients_stacked

```
2019 2020
                 year
 first
         last feature
  Wick
                         25
                             26
         John
                  age
               weight
                         68
                             72
       Julien
                  age
                         31
                             32
                         72
                             73
               weight
Shelley
                         41
                             42
         Mary
                  age
               weight
                              69
                         68
        Frank
                         32
                              33
                  age
               weight
                         75
                              74
```


Unstacking a DataFrame

patients_stacked.unstack()

```
2019
                                 2020
               age weight age weight
       feature
         first
  last
Shelley
         Frank
                        75 33
                                   74
                 32
                 41
                                  69
          Mary
                        68 42
  Wick
                 25
                                   72
          John
                        68 26
        Julien
                        72 32
                                   73
```



Unstack a level



df.unstack(level=1) or df.unstack(level='First')

Unstack level by number

churn_stacked.head(10)

member	credit_card			
yes	no	credit_score	619	
		age	43	
		country	France	
		num_products	1	
		churn	Yes	
no	yes	credit_score	608	
		age	34	
		country	Germany	
		num_products	0	
		churn	No	

churn_stacked.unstack(level=0)

	member	no no	yes
credit_card			
no	credit_score	NaN	619
	age	NaN	43
	country	NaN	France
	num_products	NaN	1
	churn	NaN	Yes
yes	credit_score	608	502
	age	34	23
	country	Germany	France
	num_products	0	1
	churn	No	Yes



Unstack level by name

churn_stacked.head(10)

member	credit_card			
yes	no	credit_score	619	
		age	43	
		country	France	
		num_products	1	
		churn	Yes	
no	yes	credit_score	608	
		age	34	
		country	Germany	
		num_products	0	
		churn	No	

churn_stacked.unstack(level='credit_card')

credit_card	no	yes
member		
no credit_score	NaN	608
age	NaN	34
country	NaN	Germany
num_products	NaN	0
churn	NaN	No
yes credit_score	619	NaN
age	43	NaN
country	France	NaN
num_products	1	NaN
churn	Yes	NaN



Sort index

```
patients_stacked.unstack().sort_index(ascending=False)
```

	year		2019		2020
	feature	age w	eight	age	weight
last	first				
Wick	Julien	31	72	32	73
	John	25	68	26	72
Shelley	Mary	41	68	42	69
	Frank	32	75	33	74

Rearranging levels

patients_stacked

```
2019 2020
                year
 first
         last feature
  Wick
         John
                        25 26
                 age
              weight
                        68
                           72
       Julien
                        31 32
                 age
              weight
                        72 73
Shelley
         Mary
                           42
                        41
                 age
              weight
                           69
                        68
        Frank
                            33
                        32
                 age
              weight
                        75
                            74
```

patients_stacked.unstack(level=1).stack(level=0)

first			Frank	John	Julien	Mary	
last	feature	year					
Shelley	age	2019	32.0	NaN	NaN	41.0	
		2020	33.0	NaN	NaN	42.0	
	weight	2019	75.0	NaN	NaN	68.0	
		2020	74.0	NaN	NaN	69.0	
Wick	age	2019	NaN	25.0	31.0	NaN	
		2020	NaN	26.0	32.0	NaN	
	weight	2019	NaN	68.0	72.0	NaN	
		2020	NaN	72.0	73.0	NaN	

Let's practice!

RESHAPING DATA WITH PANDAS



Working with multiple levels

RESHAPING DATA WITH PANDAS



Maria Eugenia Inzaugarat
Instructor



Review

- Stack and unstack DataFrames and Series
- Choose a level to stack or unstack by name or number
- Rearrange levels by combining unstack and stack

Rearranging multiple levels

- Swap levels
- Stack and unstack multiple levels at the same time

Swap levels



df.swaplevel(0, 2)

Swap levels

cars

			2019	2020
price	Golf	VW	25	26
sold	Golf	VW	68	72
price	Passat	VW	31	32
sold	Passat	VW	72	73
price	A-class	Mercedes	41	42
sold	A-class	Mercedes	68	69
price	C-class	Mercedes	32	33
sold	C-class	Mercedes	75	74

Swap levels

cars

			2019	2020
price	Golf	VW	25	26
sold	Golf	VW	68	72
price	Passat	VW	31	32
sold	Passat	VW	72	73
price	A-class	Mercedes	41	42
sold	A-class	Mercedes	68	69
price	C-class	Mercedes	32	33
sold	C-class	Mercedes	75	74

cars.swaplevel(0, 2)

			2010	2020
			2019	2020
VW	Golf	price	25	26
		sold	68	72
	Passat	price	31	32
		sold	72	73
Mercedes	A-class	price	41	42
		sold	68	69
	C-class	price	32	33
		sold	75	74

Swap levels and unstack

cars

```
2019 2020
        Golf
                        25
price
                             26
                            72
sold
        Golf
                       68
price Passat
                            32
                       31
sold Passat
                       72
                            73
price A-class Mercedes
                       41
                             42
sold A-class Mercedes
                             69
                       68
price C-class Mercedes
                       32
                            33
sold C-class Mercedes
                        75
                             74
```

cars.swaplevel(0, 2).unstack()

			2019		2020
		price	sold	price	sold
Mercedes	A-class	41	68	42	69
	C-class	32	75	33	74
VW	Golf	25	68	26	72
	Passat	31	72	32	73

Swap levels and unstack

cars

			2019	2020
price	Golf	VW	25	26
sold	Golf	VW	68	72
price	Passat	VW	31	32
sold	Passat	VW	72	73
price	A-class	Mercedes	41	42
sold	A-class	Mercedes	68	69
price	C-class	Mercedes	32	33
sold	C-class	Mercedes	75	74

cars.unstack()

		Mercedes	VW	Mercedes	VW
		2019	2019	2020	2020
price	A-class	41.0	NaN	42.0	NaN
	C-class	32.0	NaN	33.0	NaN
	Golf	NaN	25.0	NaN	26.0
	Passat	NaN	31.0	NaN	32.0
sold	A-class	68.0	NaN	69.0	NaN
	C-class	75.0	NaN	74.0	NaN
	Golf	NaN	68.0	NaN	72.0
	Passat	NaN	72.0	NaN	73.0

Swap levels and unstack

cars

			2019	2020
price	Golf	VW	25	26
sold	Golf	VW	68	72
price	Passat	VW	31	32
sold	Passat	VW	72	73
price	A-class	Mercedes	41	42
sold	A-class	Mercedes	68	69
price	C-class	Mercedes	32	33
sold	C-class	Mercedes	75	74

cars.unstack().swaplevel(0, 1, axis=1)

			2019		2020
		Mercedes	VW	Mercedes	VW
price	A-class	41.0	NaN	42.0	NaN
	C-class	32.0	NaN	33.0	NaN
	Golf	NaN	25.0	NaN	26.0
	Passat	NaN	31.0	NaN	32.0
sold	A-class	68.0	NaN	69.0	NaN
	C-class	75.0	NaN	74.0	NaN
	Golf	NaN	68.0	NaN	72.0
	Passat	NaN	72.0	NaN	73.0

Swap levels and stack

cars

			2019	2020
price	Golf	VW	25	26
sold	Golf	VW	68	72
price	Passat	VW	31	32
sold	Passat	VW	72	73
price	A-class	Mercedes	41	42
sold	A-class	Mercedes	68	69
price	C-class	Mercedes	32	33
sold	C-class	Mercedes	75	74

cars.stack()

price	Golf	VW	2019	25	
			2020	26	
sold	Golf	VW	2019	68	
			2020	72	
price	Passat	VW	2019	31	
			2020	32	
sold	Passat	VW	2019	72	
			2020	73	
price	A-class	Mercedes	2019	41	
			2020	42	
sold	A-class	Mercedes	2019	68	
			2020	69	

Swap levels and stack

cars

			2019	2020
price	Golf	VW	25	26
sold	Golf	VW	68	72
price	Passat	VW	31	32
sold	Passat	VW	72	73
price	A-class	Mercedes	41	42
sold	A-class	Mercedes	68	69
price	C-class	Mercedes	32	33
sold	C-class	Mercedes	75	74

cars.stack().swaplevel(0, 2)

VW	Golf	price	2019	25	
			2020	26	
		sold	2019	68	
			2020	72	
	Passat	price	2019	31	
			2020	32	
		sold	2019	72	
			2020	73	
Mercedes	A-class	price	2019	41	
			2020	42	
		sold	2019	68	
			2020	69	

Multiple levels

			da	у		nig	ht
		20	19	20	20	20	20
		high	low	high	low	high	low
Last	First						
Wick	John	110	68	120	70	110	70
	Julien	120	61	121	60	115	60
Shelley	Mary	90	59	90	60	100	60
	Frank	100	65	92	58	105	58

Unstacking multiple levels

cars

year			2019	2020
brand	model	feature		
VW	Golf	price	25	26
		sold	68	72
	Passat	price	31	32
		sold	72	73
Mercedes	A-class	price	41	42
		sold	68	69
	C-class	price	32	33
		sold	75	74



Unstacking levels by number

```
cars.unstack(level=[0, 1])
```

		year		2019				2020
brand		VW	Mer	cedes		VW	Me	ercedes
model	Golf	Passat	A-class C-	class	Golf P	assat	A-class (C-class
feature								
price	25	31	41	32	26	32	42	33
sold	68	72	68	75	72	73	69	74



Unstacking levels by name

```
cars.unstack(level=['brand', 'model'])
```

		year		2019				2020
brand		VW	Mer	cedes		VW	Me	rcedes
model	Golf	Passat	A-class C-	class	Golf P	assat	A-class C	-class
feature	:							
price	25	31	41	32	26	32	42	33
sold	68	72	68	75	72	73	69	74



Stacking multiple levels

cars_unstacked

- 1									
	year				2019				2020
	brand		VW	Mo	ercedes		VW	1	Mercedes
	model	Golf	Passat	A-class (C-class	Golf	Passat	A-class	C-class
	feature								
	price	25	31	41	32	26	32	42	33
	sold	68	72	68	75	72	73	69	74

Stacking by name or number

cars_unstacked.stack(level=[0, 1])

	model	A-class	C-class	Golf	Passat	
feature year	brand					
price 2019	Mercedes	41.0	32.0	NaN	NaN	
	VW	NaN	NaN	25.0	31.0	
2020	Mercedes	42.0	33.0	NaN	NaN	
	VW	NaN	NaN	26.0	32.0	
sold 2019	Mercedes	68.0	75.0	NaN	NaN	
	VW	NaN	NaN	68.0	72.0	
2020	Mercedes	69.0	74.0	NaN	NaN	
	VW	NaN	NaN	72.0	73.0	

cars_unstacked.stack(levels=['year', 'brand'])

		model	A-class	C-class	Golf	Passat	
featu	re year	brand					
pri	ce 2019	Mercedes	41.0	32.0	NaN	NaN	
		VW	NaN	NaN	25.0	31.0	
	2020	Mercedes	42.0	33.0	NaN	NaN	
		VW	NaN	NaN	26.0	32.0	
SO SO	ld 2019	Mercedes	68.0	75.0	NaN	NaN	
		VW	NaN	NaN	68.0	72.0	
	2020	Mercedes	69.0	74.0	NaN	NaN	
		VW	NaN	NaN	72.0	73.0	

Let's practice!

RESHAPING DATA WITH PANDAS



Handling missing data

RESHAPING DATA WITH PANDAS



Maria Eugenia Inzaugarat

Data Scientist



Review

- Stack and unstack DataFrames:
 - All columns index levels
 - A row index level
 - Choose which levels to stack or unstack

Subgroups do not have the same set of labels

animals

```
jump run fly
class
         order
                       name
Mammalia carnivora
                       dog
                                  No
                                      Yes
                                            No
         Diprotodontia Kangaroo
                                 Yes
                                       No
                                            No
Aves
         hervibora
                       bird
                                  No
                                           Yes
                                       No
```



Subgroups do not have the same set of labels

```
animals
```

```
jump run fly
class
        order
                      name
  Mammalia carnivora
                                    No Yes
                         dog
                                              No <--
        Diprotodontia Kangaroo
                                           No
                                Yes
                                      No
Aves
        hervibora
                      bird
                                 No
                                      No
                                          Yes
```



Subgroups do not have the same set of labels

```
animals.unstack(level='class')
```

```
jump
                                                                fly
                                                  run
                         Aves Mammalia Aves Mammalia Aves Mammalia
        clas
        order
                    name
 Diprotodontia Kangaroo
                                        NaN
                                                      NaN
                                                                 No
                          NaN
                                   Yes
      carnivora
                     Dog
                          NaN
                                        NaN
                                                      NaN
                                                                 No
                                    No
                                                  Yes
Charadriiformes
                  Avocet
                                                      Yes
                           No
                                   NaN
                                         No
                                                  NaN
                                                                NaN
```



Subgroups do not have the same set of labels

```
animals.unstack(level='class')
```

```
jump
                                                        fly
                                            run
                      Aves Mammalia Aves Mammalia Aves Mammalia
       clas
       order
                 name
 Diprotodontia Kangaroo NaN Yes NaN
                                             No NaN
                                                         No
     carnivora Dog NaN <-- No
                                   NaN
                                            Yes NaN
                                                         No
Charadriiformes
               Avocet
                               NaN
                                    No
                                            NaN Yes
                                                        NaN
```



Handling NaN with unstack

```
animals.unstack(level='class', fill_value= )
```



Handling NaN with unstack

```
animals.unstack(level='class', fill_value='No')
```



Handling NaN with unstack

```
animals.unstack(level='class', fill_value='No').sort_index(level=['order', 'name'], ascending=[True, False])
```

```
jump
                                                              fly
                                                run
                        Aves Mammalia Aves Mammalia Aves Mammalia
       clas
       order
                   name
 Diprotodontia Kangaroo
                                                               No
                                  Yes
                                                 No
                                                      No
     carnivora
                    Dog
                          No
                                   No
                                        No
                                                Yes
                                                      No
                                                               No
Charadriiformes
                                        No
                                                 No Yes
                 Avocet
                                   No
                                                               No
```



Combinations of index and column values missing from the original DataFrame

petals Stigma
number size
rose 40 NaN
Lily 8 big



Combinations of index and column values missing from the original DataFrame

```
flowers.stack()
```

```
Stigma petals
rose number NaN 40.0
Lily number NaN 8.0
size 5 NaN
```

Combinations of index and column values missing from the original DataFrame

```
flowers.stack(dropna=True)
```

```
Stigma petals
rose number NaN 40.0
Lily number NaN 8.0
size 5 NaN
```



Combinations of index and column values missing from the original DataFrame

```
flowers.stack(dropna=False)
```

```
Stigma petals
rose number NaN 40.0
size NaN NaN <--
Lily number NaN 8.0
size 5 NaN
```

Handling NaN with stack

```
flowers.stack(dropna=False).fillna(0)
```

```
Stigma petals
rose number 0 40.0
size 0 0
Lily number 0 8.0
size 5 0
```



Let's practice!

RESHAPING DATA WITH PANDAS

