All Competitions > c2c2017-3 > Merge List

Merge List   🔒 locked

👤 by amititkgp

Problem	Submissions	Leaderboard	Discussions

Shashank is very excited after learning about the *linked list*. He learned about how to *merge* two linked lists. When we merge two linked lists, the order of the elements of each list doesn't change. For example, if we merge $[1, 2, 3]$ and $[4, 5, 6]$, $[1, 4, 2, 3, 5, 6]$ is a valid merge, while $[1, 4, 3, 2, 5, 6]$ is not a valid merge because 3 appears before 2.

Shashank wants you to solve a problem for him: You are given two lists having sizes N and M. How many ways can we merge both the lists? It is given that all $N + M$ elements are distinct. As your answer can be quite large, Shashank wants you to print it $\mod 10^9 + 7$.

Input Format

The first line contains an integer T, the number of test cases.
Each of the next T lines contains two integers N and M.

Constraints

- $1 \leq T \leq 10$
- $1 \leq N \leq 100$
- $1 \leq M \leq 100$

Output Format

Print the value of the answer $\mod 10^9 + 7$.

Sample Input 0

```
1
2 2
```

Sample Output 0

```
6
```

Explanation 0

Suppose the two lists are $[1, 2]$ and $[3, 4]$. The different ways of merging these lists are given below:

$[1, 2, 3, 4]$
$[1, 3, 2, 4]$
$[3, 4, 1, 2]$
$[3, 1, 4, 2]$
$[1, 3, 4, 2]$
$[3, 1, 2, 4]$

f 🐦 in

Submissions: 10
Max Score: 40

Difficulty: Medium

Rate This Challenge:

☆ ☆ ☆ ☆ ☆

More

| Current Buffer (saved locally, editable)   ⅄ 🕓 | | Python 3   ⌄ | ⤢ ⚙ |

```
1
```

⬆ Upload Code as File   ☐ Test against custom input

Run Code   Submit Code

Join us on IRC at #hackerrank on freenode for hugs or bugs.

Contest Calendar | Interview Prep | Blog | Scoring | Environment | FAQ | About Us | Support | Careers | Terms Of Service | Privacy Policy | Request a Feature