



LIFELINE ENTERPRISES

105, Joavan Tower, Opp. Bata Showroom, Bara Bazar, G. S. Road, Shillong- 793 002
☎ 2220280, 2221817 ☎ 8259012021 ✉ lifelineshillong@gmail.com 🌐 www.lifelineworld.in

Ref: LE/02/O01/25

Dated: 01.11.2025

To,
M/s Promark Techsolutions Pvt. Ltd.
Promark Mansion, E-250, Phase 8B,
Industrial Area, Sector 91,
Mohali,
PUNJAB - 160 071

Kind Attn: Shri Rajiv Kanda, 8224800002

Dear Sir,

We are pleased to hereby place our order for the below mentioned items.

Bill To:		Despatch To:	Advance Payment: 1,80,000.00	
M/s Lifeline Enterprises 105, Joavan Towers G.S.Road, Shillong 793 002		Self	Credited to your Axix Bank Account No. : 923030039181937 UTR No. : Dated: 01.11.2025	
GST No. 17ADXPB5656P1ZN		Delivery Instructions: Immediate Shipment By: Your Designated Courier (Charges on actuals)		
Sr. No	Description	Qty. (Nos.)	Rate ₹	Amount (₹)
1	PROMARK PRO-VCC-20XP PTZ Camera	7	43,000	3,01,000.00
2				0.00
3				0.00
4				0.00
5				0.00
Rupees Three Lakh FiftyFive Thousand One Hundred Eighty Only		Total		3,01,000.00
		Add GST @ 18%		54,180.00
		CD @ 1%		0.00
		Grand Total		3,55,180.00

Note:

1. Please send the Original Invoice to us directly by Post / Courier.
2. Payment of 50% being made now, and balance 50% on dispatch.

We now look forward to your IMMEDIATE action and dispatch

Thanking You

Yours Faithfully,
for **LIFELINE ENTERPRISES**

(SARAD BAWRI)

PRO-HD-20XP



1080p 30fps



4 Mic array



20x Optical
zoom



10 Meters
voice pickup



Voice
Tracking



IR Remote
control

PROMARK STANDS FOR : PROGRESSIVE, PROACTIVE & PROFICIENT

www.promark.co.in

Product Specification

Camera, Lens parameters

Image Sensor	1/2.8inch CMOS
Min Lux	0.1Lux(F1.2)
Effective Pixel	2.2 MP
Zoom	20X Optical
Shutter Speed	1 to 1/10000s
Field of View	61° (W) ~3.64° (T)
Frame Rate	1920×1080,1280×720, 640×480
Focus Mode	Auto
Aperture Mode	Auto
Backlight Compensation	Support
Wide Dynamic	Support
Picture Adjustment	Brightness、 Chroma、 Saturation、 Contrast、 Acutance

Microphone parameters

MIC Array Quantity	4
MIC Array Form	linear
Microphone Spacing	45.8mm
Sampling Rate	16KHz/48KHz
Sensitivity	-26dBfs
Far-field Pick up Voice Distance	0-10meters
Horizontal Voice Pick up Angle	Horizontal 180°
SNR	65.5dB
Communication Mode	full duplex

Interface Parameter

Video Interface	USB3.0 HDMI
Video Compressed Format	MJPEG/H.264
Control Interface	RS-232, USB2.0, UVC
Control Agreement	VISCA/PELCO-D/PELCO-P
Communicate Baud Rate	2400/4800/9600/11520/19200/38400
Power Interface	DC-038 power socket (DC12V)

PTZ Parameter	Pan Rotation	-170° ~ +173°
	Tilt Rotation	-30° ~ +90°
	Horizontal Rotate Speed	0.1~100°/second
	Vertical Rotate Speed	0.1~80°/ second
Other Parameters	Power Adapter	Input AC100V~AC240V Output DC12V/2A
	Decoder	Built in
	Input voltage	DC12V
	Power Consumption	12W(MAX)
	Storage Temperature and Humidity	-10°C ~ +60°C / 20% ~ 95%
	Working temperature and Humidity	-10°C ~ +50°C / 20% ~ 80%
	Operating Environment	Indoor
	Size	180*180*172mm
	Weight	1360g

PROMARK TECHSOLUTIONS PRIVATE LIMITED

CORPORATE OFFICE:
Promark Corporate Mansion,
Plot No E-250, Industrial Area 8-B,
Mohali, Punjab, India-160071

FACTORY:
Ludhiana Highway (NH-(95) Morinda By-Pass,
Village Madouli, Morinda, Distt. Ropar Punjab-140413

DELHI OFFICE:
A-14, GF, Okhla Industrial
Area, Phase-2, New Delhi 110020

Branch offices—Jammu, Srinagar, Chandigarh, Delhi, Raipur, Patna, Lucknow, Bareilly, Guwahati, Bhubaneswar, Ranchi, Kolkata and Jaipur

**For any inquiries
contact us at:**

www.promark.co.in

✉ sales@promark.co.in

☎ 1800 103 8878