

Question 1
Correct
Marked out of 1.00
Flag question

Objective
In this challenge, we're going to use loops to help us do some simple math. Check out the Tutorial tab to learn more.

Task
Given an integer, n , print its first 10 multiples. Each multiple $n \times i$ (where $1 \leq i \leq 10$) should be printed on a new line in the form: $n \times i = \text{result}$

Input Format
A single integer, n .

Constraints
 $2 \leq n \leq 20$

Output Format
Print 10 lines of output; each line i (where $1 \leq i \leq 10$) contains the **result** of $n \times i$ in the form:
 $n \times i = \text{result}$.

Sample Input
2

Sample Output
2 x 1 = 2
2 x 2 = 4
2 x 3 = 6
2 x 4 = 8
2 x 5 = 10
2 x 6 = 12
2 x 7 = 14
2 x 8 = 16
2 x 9 = 18
2 x 10 = 20

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,i,t;
5     scanf("%d",&n);
6     for(i=1;i<=10;i++)
7     {
8         t=n*i;
9         printf("%d x %d = %d\n",n,i,t);
10    }
11 }
```

| | Input | Expected | Got | |
|---|-------|---|---|---|
| ✓ | 2 | 2 x 1 = 2 2 x 2 = 4 2 x 3 = 6 2 x 4 = 8 2 x 5 = 10 2 x 6 = 12 2 x 7 = 14 2 x 8 = 16 2 x 9 = 18 2 x 10 = 20 | 2 x 1 = 2 2 x 2 = 4 2 x 3 = 6 2 x 4 = 8 2 x 5 = 10 2 x 6 = 12 2 x 7 = 14 2 x 8 = 16 2 x 9 = 18 2 x 10 = 20 | ✓ |

Passed all tests! ✓

Question 2
Correct
Marked out of
1.00
Flag question

A nutritionist is labeling all the bad power foods in the market. Every food item arranged in a single line, will have a value beginning from 1 and increasing by 1 for each, until all items have a value associated with them. An item's value is the same as the number of macronutrients it has. For example, food item with value 1 has 1 macronutrient, food item with value 2 has 2 macronutrients, and incrementing in this fashion.

The nutritionist has to recommend the best combination to patients, i.e. maximum total of macronutrients. However, the nutritionist must avoid prescribing a particular sum of macronutrients (an 'unhealthy' number), and this sum is known. The nutritionist chooses food items in the increasing order of their value. Compute the highest total of macronutrients that can be prescribed to a patient, without the sum matching the given 'unhealthy' number.

Here's an illustration:

Given 4 food items (hence values: 1,2,3 and 4), and the unhealthy sum being 8 macronutrients, on choosing items 1,2,3 \rightarrow the sum is 6, which matches the 'unhealthy' sum. Hence, one of the three needs to be skipped. Thus, the best combination is from among:

- 1. $2 + 3 + 4 = 9$
- 1. $1 + 3 + 4 = 8$
- 1. $1 + 2 + 4 = 7$

Since $2 + 3 + 4 = 9$, allows for maximum number of macronutrients, 9 is the right answer.

Complete the code in the editor below, it must return an integer that represents the maximum total of macronutrients, modulo $1000000007 (10^9 + 7)$.

It has the following:

n: an integer that denotes the number of food items

k: an integer that denotes the unhealthy number

Constraints

- 1. $1 \leq n \leq 10^5$
- 1. $1 \leq k \leq 10^{11}$

Input Format For Custom Testing

The first line contains an integer, *n*, that denotes the number of food items.

The second line contains an integer, *k*, that denotes the unhealthy number.

Sample Input 0

2
2

Sample Output 0

3

Explanation 0

The following sequence of *n* = 2 food items:

1. Item 1 has 1 macronutrients.
2. $1 + 2 = 3$; observe that this is the max total, and having avoided having exactly *k* = 2 macronutrients.

Sample Input 1

2
1

Sample Output 1

2

Explanation 1

1. Cannot use item 1 because *k* = 1 and sum $\geq k$ has to be avoided at any time.
2. Hence, max total is achieved by sum = $0 + 2 = 2$.

Sample Case 2

Sample Input For Custom Testing

Sample Input 2

3
3

Sample Output 2

5

Explanation 2

2 + 3 = 5, is the best case for maximum nutrients.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     long n,k,sum=0;
5     scanf("%ld\n%ld",&n,&k);
6     for(int i=1;i<=n;i++)
7     {
8         sum+=i;
9         if(sum==k)
10             sum=1;
11     }
12     printf("%ld",sum%1000000007);
13 }
```

| | Input | Expected | Got | |
|---|--------|----------|-----|---|
| ✓ | 2 2 | 3 | 3 | ✓ |
| ✓ | 2 1 | 2 | 2 | ✓ |
| ✓ | 3 3 | 5 | 5 | ✓ |

Passed all tests! ✓

Q3)

Question 3
Correct
Marked out of 1.00
Flag question

Determine all positive integer values that evenly divide into a number n 's factors. Return the p^{th} element of your list, sorted ascending. If there is no p^{th} element, return 0.

For example, given the number $n = 20$, its factors are $\{1, 2, 4, 5, 10, 20\}$. Using 1-based indexing if $p = 3$, return 4. If $p > 6$, return 0.

Complete the code in the editor below. The function should return a long integer value of the p^{th} integer factor of n .

It has the following:

n : an integer
 p : an integer

Constraints

- $1 \leq n \leq 10^{15}$
- $1 \leq p \leq 10^3$

Input Format: for Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer n , the number to factor.

The second line contains an integer p , the 1-based index of the factor to return.

Sample Input 0

10
3

Sample Output 0

5

Explanation 0

Factoring $n = 10$ we get $\{1, 2, 5, 10\}$. We then return the $p = 3^{\text{rd}}$ factor as our answer.

Sample Input 1

10
5

Sample Output 1

0

Explanation 1

Factoring $n = 10$ we get $\{1, 2, 5, 10\}$. There are only 4 factors and $p = 5$. We return 0 as our answer.

Sample Input 2

1
1

Sample Output 2

1

Explanation 2

Factoring $n = 1$ we get $\{1\}$. We then return the $p = 1^{\text{st}}$ factor as our answer.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 long findpthfactor(long n,long p)
3 {
4     long count=0;
5     for(long i=1;i<=n;i++)
6     {
7         if(n%i==0)
8         {
9             count++;
10            if(count==p)
11            {
12                return i;
13            }
14        }
15    }
16    return 0;
17 }
18 int main()
19 {
20     long n,p;
21     scanf("%ld %ld",&n,&p);
22     printf("%ld\n",findpthfactor(n,p));
23 }
```

| | Input | Expected | Got | |
|---|---------|----------|-----|---|
| ✓ | 10 3 | 5 | 5 | ✓ |
| ✓ | 10 5 | 0 | 0 | ✓ |
| ✓ | 1 1 | 1 | 1 | ✓ |

Passed all tests! ✓

| | |
|-----------|-----------------------------------|
| Status | Finished |
| Started | Monday, 23 December 2024, 5:33 PM |
| Completed | Friday, 13 December 2024, 1:11 PM |
| Duration | 10 days 4 hours |

Question 1
Correct
Marked out of 1.00
Flag question

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[i] - A[j] = k$, $i \neq j$.

Input Format

1. First line is number of test cases T. Following T lines contain:
2. N, followed by N integers of the array
3. The non-negative integer k

Output format

Print 1 if such a pair exists and 0 if it doesn't.

Example

Input:

```
1
3 1 3 5
4
```

Output:

```
1
```

Input:

```
1
3 1 3 5
99
```

Output:

```
0
```

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int t;
5     scanf("%d",&t);
6     while(t-->0)
7     {
8         int n;
9         scanf("%d",&n);
10        int a[n];
11        for(int i=0;i<n;i++)
12        {
13            scanf("%d",&a[i]);
14        }
15        int k;
16        scanf("%d",&k);
17        int flag=0;
18        for(int i=0;i<n;i++)
19        {
20            for(int j=i+1;j<n;j++)
21            {
22                if(a[i]-a[j]==k||a[j]-a[i]==k)
23                {
24                    flag=1;
25                    break;
26                }
27            }
28            if(flag)
29                break;
30        }
31        printf("%d\n",flag);
32    }
33 }
```

| | Input | Expected | Got | |
|---|--------------------|----------|-----|---|
| ✓ | 1 3 1 3 5 4 | 1 | 1 | ✓ |
| ✓ | 1 3 1 3 5 99 | 0 | 0 | ✓ |

Passed all tests! ✓

Duration: 45
Correct
Marked out of
1.00
Flag question

Sam loves chocolates and starts buying from the 1st day of the year. Each day of the year, he is handed with 1 to N candies and he has to eat all of them. He has to eat all the chocolates.

Complete the code in the editor so that for each day hi (where 1 ≤ x ≤ N ≤ Y), in array arr, the number of chocolates Sam purchased (during days 1 through N) is printed on a new line. This is a function only challenge, so input is handled for you by the locked stub code in the editor.

Input Format

The program takes an array of integers as a parameter.

The locked code in the editor handles reading the following input from stdin, assembling it into an array of integers (arr), and calling calculate(arr).

The first line of input contains an integer, T, the number of test cases. Each line i of the T subsequent lines describes the ith test case as an integer, Ni, the number of days.

Constraints

1 ≤ T ≤ 2 × 10⁵
1 ≤ N ≤ 2 × 10⁵
1 ≤ x ≤ N ≤ Y

Output Format

For each test case, Ni in arr, your calculate method should print the total number of chocolates Sam purchased by day Ni on a new line.

Sample Input 0

3
1
2
3

Sample Output 0

1
1
4

Explanation

Test Case 0: N = 1

Sam buys 1 chocolate on day 1, giving us a total of 1 chocolate. Thus, we print 1 on a new line.

Test Case 1: N = 2

Sam buys 1 chocolate on day 1 and 0 on day 2. This gives us a total of 1 chocolate. Thus, we print 1 on a new line.

Test Case 2: N = 3

Sam buys 1 chocolate on day 1, 0 on day 2, and 3 on day 3. This gives us a total of 4 chocolates. Thus, we print 4 on a new line.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int t;
5     scanf("%d",&t);
6     while(t-->0)
7     {
8         int n,c=0;
9         scanf("%d",&n);
10        for(int i=0;i<=n;i++)
11        {
12            if(i%2!=0)
13                c=c+i;
14        }
15        printf("%d\n",c);
16    }
17 }
```

| | Input | Expected | Got | |
|---|---|--|--|---|
| ✓ | 3 1 2 3 | 1 1 4 | 1 1 4 | ✓ |
| ✓ | 10 71 100 86 54 40 9 77 9 13 98 | 1296 2500 1849 729 400 25 1521 25 49 2401 | 1296 2500 1849 729 400 25 1521 25 49 2401 | ✓ |

Passed all tests! ✓

Question 3

Unattempted

Marked out of 7.00

Flag question

The number of goals achieved by two football teams in matches in a league is given in the form of two lists. Consider:

- Football team A, has played three matches, and has scored (1 , 2 , 3) goals in each match respectively.
- Football team B, has played two matches, and has scored (2 , 4) goals in each match respectively.
- Your task is to compute, for each match of team B, the total number of matches of team A, where team A has scored less than or equal to the number of goals scored by team B in that match.
- In the above case:
 - For 2 goals scored by team B in its first match, team A has 2 matches with scores 1 and 2.
 - For 4 goals scored by team B in its second match, team A has 2 matches with scores 1, 2 and 3.

Hence, the answer [2, 3].

Complete the code in the editor below. The program must return an array of m positive integers, one for each `maxes[i]` representing the total number of elements `nums[j]` satisfying `nums[j] ≤ maxes[i]` where $0 ≤ j < n$ and $0 ≤ i < m$, in the given order.

It has the following:

`nums[nums[0]...nums[n-1]]`: first array of positive integers
`maxes[maxes[0]...maxes[m-1]]`: second array of positive integers

Constraints

- $2 ≤ n, m ≤ 10^5$
- $1 ≤ nums[j] ≤ 10^9$, where $0 ≤ j < n$.
- $1 ≤ maxes[i] ≤ 10^9$, where $0 ≤ i < m$.

Input format for Custom testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer n, the number of elements in nums.
The next n lines each contain an integer describing `nums[i]` where $0 ≤ i < n$.
The next line contains an integer m, the number of elements in maxes.
The next m lines each contain an integer describing `maxes[i]` where $0 ≤ i < m$.

Sample Case 0

Sample Input 0

4
1
4
2
4
2
3
5

Sample Output 0

2
4

Explanation 0

We are given `n = 4`, `nums = [1, 4, 2, 4]`, `m = 2`, and `maxes = [3, 5]`.

- For `maxes[0] = 3`, we have 2 elements in `nums` (`nums[0] = 1` and `nums[2] = 2`) that are $≤ maxes[0]$.
- For `maxes[1] = 5`, we have 4 elements in `nums` (`nums[0] = 1`, `nums[1] = 4`, `nums[2] = 2`, and `nums[3] = 4`) that are $≤ maxes[1]$.

Thus, the function returns the array [2, 4] as the answer.

Sample Case 1

Sample Input 1

5
2
10
5
4
8
4
3
1
7
8

Sample Output 1

1
0
3
4

Explanation 1

We are given, `n = 5`, `nums = [2, 10, 5, 4, 8]`, `m = 4`, and `maxes = [3, 1, 7, 8]`.

- For `maxes[0] = 3`, we have 1 element in `nums` (`nums[0] = 2`) that is $≤ maxes[0]$.

1
7
8

Sample Output 1

1
0
3
4

Explanation 1

We are given, $n = 5$, $nums = [2, 10, 5, 4, 8]$, $m = 4$, and $maxes = [3, 1, 7, 8]$.

1. For $maxes[0] = 3$, we have 1 element in $nums$ ($nums[0] = 2$) that is $\leq maxes[0]$.
2. For $maxes[1] = 1$, there are 0 elements in $nums$ that are $\leq maxes[1]$.
3. For $maxes[2] = 7$, we have 3 elements in $nums$ ($nums[0] = 2$, $nums[2] = 5$, and $nums[3] = 4$) that are $\leq maxes[2]$.
4. For $maxes[3] = 8$, we have 4 elements in $nums$ ($nums[0] = 2$, $nums[2] = 5$, $nums[3] = 4$, and $nums[4] = 8$) that are $\leq maxes[3]$.

Thus, the function returns the array $[1, 0, 3, 4]$ as the answer.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int s1,s2,ans;
5     scanf("%d",&s1);
6     int ta[s1];
7     for(int i=0;i<s1;i++)
8         scanf("%d",&ta[i]);
9     scanf("%d",&s2);
10    int tb[s2];
11    for(int i=0;i<s2;i++)
12        scanf("%d",&tb[i]);
13    for(int j=0;j<s2;j++)
14    {
15        ans=0;
16        for(int i=0;i<s1;i++)
17        {
18            if(tb[j]>=ta[i])
19                ans++;
20        }printf("%d\n",ans);
21    }
22 }
```

| | Input | Expected | Got | |
|---|--|------------------|------------------|---|
| ✓ | 4 1 4 2 4 2 3 5 | 2 4 | 2 4 | ✓ |
| ✓ | 5 2 10 5 4 8 4 3 1 7 8 | 1 0 3 4 | 1 0 3 4 | ✓ |

Passed all tests! ✓

Question 1

Correct

Marked out of 1.00

Flag question

Status

Finished

Started

Friday, 27 December 2024, 5:40 PM

Completed

Friday, 27 December 2024, 6:00 PM

Duration

19 mins 57 secs

Given an array of numbers and a window of size k. Print the maximum of numbers inside the window for each step as the window moves from the beginning of the array.

Input Format

Input contains the array size, no of elements and the window size

Output Format

Print the maximum of numbers

Constraints

1 <= size <= 1000

Sample Input 1

8

1 3 5 2 1 8 6 9

3

Sample Output 1

5 5 8 8 9

For example:

| Input | Result |
|--------------------------------|---------------|
| 8 1 3 5 2 1 8 6 9 3 | 5 5 8 8 9 |
| 10 3 7 5 1 2 9 0 5 3 2 3 | 7 7 5 9 9 8 5 |

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,k;
5     scanf("%d",&n);
6     int arr[n];
7     for(int i=0;i<n;i++)
8     {
9         scanf("%d",&arr[i]);
10    }
11    scanf("%d",&k);
12    for(int a=0;a<=n-k;a++)
13    {
14        int max=arr[a];
15        for(int b=a;b<a+k;b++)
16        {
17            if(arr[b]>max)
18            {
19                max=arr[b];
20            }
21        }
22        printf("%d ",max);
23    }
24 }
```

Given an array and a threshold value find the output.

Input: {5,8,10,13,6,2}

Threshold = 3

Output count = 17

Explanation:

| Number | Parts | Counts |
|--------|-------------|--------|
| 5 | {3,2} | 2 |
| 8 | {3,3,2} | 3 |
| 10 | {3,3,3,1} | 4 |
| 13 | {3,3,3,3,1} | 5 |
| 6 | {3,3} | 2 |
| 2 | {2} | 1 |

Input Format

N - no of elements in an array

Array of elements

Threshold value

Output Format

Display the count

Sample Input 1

6

5 8 10 13 6 2

3

Sample Output 1

17

For example:

| Input | Result |
|---------------------------------|--------|
| 6 5 8 10 13 6 2 3 | 17 |
| 7 20 35 57 30 56 87 30 10 | 33 |

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,t,count=0;
5     scanf("%d",&n);
6     int arr[n];
7     for(int i=0;i<n;i++)
8     {
9         scanf("%d",&arr[i]);
10    }
11    scanf("%d",&t);
12    for(int j=0;j<n;j++)
13    {
14        while(arr[j]>0)
15        {
16            arr[j]-=t;
17            count++;
18        }
19    }
20    printf("%d",count);
21 }
```

| | Input | Expected | Got | |
|---|---------------------------------|----------|-----|---|
| ✓ | 6 5 8 10 13 6 2 3 | 17 | 17 | ✓ |
| ✓ | 7 20 35 57 30 56 87 30 10 | 33 | 33 | ✓ |

Passed all tests! ✓

Question 3
Correct
Marked out of
1.00
Flag question

Output is a merged array without duplicates.

Input Format

N1 - no of elements in array 1

Array elements for array 1

N2 - no of elements in array 2

Array elements for array2

Output Format

Display the merged array

Sample Input 1

5

1 2 3 6 9

4

2 4 5 10

Sample Output 1

1 2 3 4 5 6 9 10

For example:

| Input | Result |
|---------------------------------|------------------|
| 5 1 2 3 6 9 4 2 4 5 10 | 1 2 3 4 5 6 9 10 |

Answer: (penalty regime: 0 %)

```

1 #include<stdio.h>
2 int main()
3 {
4     int a,b;
5     scanf("%d",&a);
6     int arr1[a];
7     for(int i=0;i<a;i++)
8         scanf("%d",&arr1[i]);
9     scanf("%d",&b);
10    int arr2[b];
11    for(int i=0;i<b;i++)
12        scanf("%d",&arr2[i]);
13    int p=0,q=0;
14    while((p<a)&&(q<b))
15    {
16        if(arr1[p]<arr2[q])
17        {
18            printf("%d ",arr1[p]);
19            p++;
20        }
21        else if(arr1[p]>arr2[q])
22        {
23            printf("%d ",arr2[q]);
24            q++;
25        }
26        else
27        {
28            printf("%d ",arr1[p]);
29            p++;
30            q++;
31        }
32    }
33    for(int j=p;j<a;j++)
34    {
35        printf("%d ",arr1[j]);
36    }
37    for(int j=q;j<b;j++)
38    {
39        printf("%d ",arr2[j]);
40    }
41 }
```