CSA0508

DATABASE MANAGEMENT SYSTEMS

NAME: AKSHAYA SEKAR

REGNO: 1911260204

1.Create a table name STUDENT with the following structures.

COMMAND:

CREATE TABLE STUDENT (regno int (3), name varchar (15), gender char (1), DOB date,mobileno int (10), city varchar (15));

OUTPUT:

```
Database changed
mysql> create table STUDENT(regno int(3),name varchar(15),gender char(1),DOB date,mobileno int(10),city varchar(15));
Query OK, 0 rows affected, 2 warnings (0.07 sec)

mysql> select * from STUDENT;
Empty set (0.02 sec)

mysql> desc STUDENT;
+----------+-------------+------+-----+---------+-------+
| Field    | Type        | Null | Key | Default | Extra |
+----------+-------------+------+-----+---------+-------+
| regno    | int         | YES  |     | NULL    |       |
| name     | varchar(15) | YES  |     | NULL    |       |
| gender   | char(1)     | YES  |     | NULL    |       |
| DOB      | date        | YES  |     | NULL    |       |
| mobileno | int         | YES  |     | NULL    |       |
| city     | varchar(15) | YES  |     | NULL    |       |
+----------+-------------+------+-----+---------+-------+
6 rows in set (0.03 sec)
```

2.Create a table name FACULTY with the following structure.

COMMAND:

CREATE TABLE FACULTY (name varchar (20),FacNo varchar (4),FacName varchar (15), gender char (1), DOB date,DOJ date,MobileNo int (10));

OUPUT:

```
mysql> CREATE TABLE FACULTY(name varchar(20),FacNo varchar(4),FacName varchar(15),gender char(1),DOB date,DOJ date,MobileNo int(10));
Query OK, 0 rows affected, 1 warning (0.05 sec)

mysql> desc FACULTY;
+----------+-------------+------+-----+---------+-------+
| Field    | Type        | Null | Key | Default | Extra |
+----------+-------------+------+-----+---------+-------+
| name     | varchar(20) | YES  |     | NULL    |       |
| FacNo    | varchar(4)  | YES  |     | NULL    |       |
| FacName  | varchar(15) | YES  |     | NULL    |       |
| gender   | char(1)     | YES  |     | NULL    |       |
| DOB      | date        | YES  |     | NULL    |       |
| DOJ      | date        | YES  |     | NULL    |       |
| MobileNo | int         | YES  |     | NULL    |       |
+----------+-------------+------+-----+---------+-------+
7 rows in set (0.00 sec)
```

3.Create a table name DEPARTMENT with the following structure.

COMMAND:

CREATE TABLE DEPARTMENT (name varchar (20), DeptNo varchar (4),DeptName varchar (15),DeptHead varchar (4));

OUTPUT:

```
mysql> CREATE TABLE DEPARTMENT(name varchar(20),DeptNo varchar(4),DeptName varchar(15),DeptHead varchar(4));
Query OK, 0 rows affected (0.05 sec)

mysql> desc DEPARTMENT;
+----------+-------------+------+-----+---------+-------+
| Field    | Type        | Null | Key | Default | Extra |
+----------+-------------+------+-----+---------+-------+
| name     | varchar(20) | YES  |     | NULL    |       |
| DeptNo   | varchar(4)  | YES  |     | NULL    |       |
| DeptName | varchar(15) | YES  |     | NULL    |       |
| DeptHead | varchar(4)  | YES  |     | NULL    |       |
+----------+-------------+------+-----+---------+-------+
4 rows in set (0.00 sec)
```

4. Create a table name COURSE with the following structure.

COMMAND:

CREATE TABLE COURSE (name varchar (20),CourseNo varchar (3),CourseDesc varchar (14),CourseType char(1),SemNo char (1),Hallno varchar (4),FacNo varchar(4));

OUTPUT:

```
mysql> CREATE TABLE COURSE(name varchar(20),CourseNo varchar(3),CourseDesc varchar(14),CourseType char(1),SemNo char(1),Hallno varchar(4),FacNo varchar(4));

Query OK, 0 rows affected (0.03 sec)

mysql> desc COURSE;
+------------+-------------+------+-----+---------+-------+
| Field      | Type        | Null | Key | Default | Extra |
+------------+-------------+------+-----+---------+-------+
| name       | varchar(20) | YES  |     | NULL    |       |
| CourseNo   | varchar(3)  | YES  |     | NULL    |       |
| CourseDesc | varchar(14) | YES  |     | NULL    |       |
| CourseType | char(1)     | YES  |     | NULL    |       |
| SemNo      | char(1)     | YES  |     | NULL    |       |
| Hallno     | varchar(4)  | YES  |     | NULL    |       |
| FacNo      | varchar(4)  | YES  |     | NULL    |       |
+------------+-------------+------+-----+---------+-------+
7 rows in set (0.00 sec)
```

5. Modify the table FACULTY by adding a column name Dept of datatype VARCHAR (10).

COMMAND:

ALTER TABLE FACULTY add column Dept varchar (10);

OUTPUT:

```
mysql> ALTER TABLE FACULTY add column Dept varchar(10);
Query OK, 0 rows affected (0.10 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> desc faculty;
+----------+-------------+------+-----+---------+-------+
| Field    | Type        | Null | Key | Default | Extra |
+----------+-------------+------+-----+---------+-------+
| name     | varchar(20) | YES  |     | NULL    |       |
| FacNo    | varchar(4)  | YES  |     | NULL    |       |
| FacName  | varchar(15) | YES  |     | NULL    |       |
| gender   | char(1)     | YES  |     | NULL    |       |
| DOB      | date        | YES  |     | NULL    |       |
| DOJ      | date        | YES  |     | NULL    |       |
| MobileNo | int         | YES  |     | NULL    |       |
| Dept     | varchar(10) | YES  |     | NULL    |       |
+----------+-------------+------+-----+---------+-------+
8 rows in set (0.00 sec)
```