Started on	Wednesday, 9 September 2026, 1:50 PM
State	Finished
Completed on	Wednesday, 9 September 2026, 1:59 PM
Time taken	8 mins 57 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
int main()
{
int n;
scanf("%d",&n);
int a[n],b[n];
for(int i=0;i<n;i++)
{
scanf("%d",&a[i]);
}
for(int i=0;i<n;i++)
{
scanf("%d",&b[i]);
}
for(int i=0;i<n-1;i++)
{
for(int j=i+1;j<n;j++)
{
if(a[i]>a[j])
{
int temp = a[i];
a[i] = a[j];
a[j]=temp;
}
}
}
for(int i=0;i<n-1;i++)
{
for(int j=i+1;j<n;j++)
{
if(b[i]<b[j])
{
int temp = b[i];
b[i]=b[j];
b[j]=temp;
}
}
}
long long sum =0;
for(int i=0;i<n;i++)
{
sum = sum +(long long)a[i]*b[i];
}
printf("%lld",sum);
return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.