

5.1.1. Stacked Plot 99.43

Create a stacked area plot to visualize the temperature variations for three different cities (City A, City B, and City C) across the months of the year. The temperature data is provided for each city in the editor.

- Your task is to:
- Create a stacked area plot using the data.
 - Label the x-axis as "Month", the y-axis as "Temperature", and provide the title "Temperature Variation" for the plot.
 - Display the plot showing the temperature variation for each city throughout the months of the year.

Sample Test Cases

stackedpl...

```
1 import matplotlib.pyplot as plt
2 import pandas as pd
3
4 # Data for Months and Temperature for three cities
5 data = {
6     'Month': ['January', 'February', 'March', 'April', 'May', 'June', 'July', 'August',
7             'September', 'October', 'November', 'December'],
8     'City_A_Temperature': [5, 7, 10, 13, 17, 20, 22, 21, 18, 12, 8, 6],
9     'City_B_Temperature': [2, 3, 5, 6, 10, 14, 16, 17, 12, 9, 5, 3],
10    'City_C_Temperature': [3, 4, 6, 8, 9, 12, 15, 14, 10, 7, 4, 2]
11 }
12
13 # Write your code...
14 plt.stackplot(data['Month'], data['City_A_Temperature'], data['City_B_Temperature'], data['City_C_Temperature'])
15 plt.xlabel('Month')
16 plt.ylabel('Temperature')
17 plt.title('Temperature Variation')
18 plt.show()
```

Average time
0.130 s
130.00 ms

Maximum time
0.130 s
130.00 ms

1 out of 1 shown test case(s) passed

Test case 1 130 ms Debug

Expected output

Actual output

Terminal

Test cases

5.2.1. Titanic Dataset

01:40

Write a Python program to analyze and visualize data from the Titanic dataset based on the following instructions:

Dataset Information:

The dataset is stored in a CSV file named `titanic.csv` and has been loaded using the `pandas` library. It contains the following columns:

- `Pclass`: Passenger class (1 = First, 2 = Second, 3 = Third).
- `Gender`: Gender of the passenger (male/female).
- `Age`: Age of the passenger.
- `Survived`: Survival status (0 = Did not survive, 1 = Survived).
- `Fare`: Ticket fare paid by the passenger.

Visualization:

To represent these trends, you will create 5 visualizations using Matplotlib. The visualizations should be arranged in a 3x2 grid (3 rows and 2 columns).

Visualization Details:

Write the code to create a series of visualizations as follows:

Bar Plot (Pclass Distribution):

- Create a bar plot to show the distribution of passengers across the different passenger classes (`Pclass`).
- Use the color `skyblue` for the bars.
- Title the plot as **"Passenger Class Distribution"**.
- Label the x-axis as **"Pclass"** and the y-axis as **"Count"**.

Pie Chart (Gender Distribution):

- Create a pie chart to display the distribution of male and female passengers.
- Use `lightblue` for males and `lightcoral` for females.
- Include percentages on the slices (use `autopct='%1.1f%%'`).
- Title the plot as **"Gender Distribution"**.

Histogram (Age Distribution):

- Create a histogram to visualize the distribution of passengers' ages.
- Use `lightgreen` for the bars with black edges (`edgecolor = 'black'`).
- Set the number of bins to **8** for the histogram.
- Title the plot as **"Age Distribution"**.

titanicDat...

Submit

```
1 import pandas as pd
2 import matplotlib.pyplot as plt
3
4 # Load the Titanic dataset from the CSV file
5 df = pd.read_csv('titanic.csv')
6
7 # Set up the figure for 5 subplots
8 fig, axes = plt.subplots(3, 2, figsize=(12, 12))
9
10 count=df['Pclass'].value_counts().sort_index()
11 count_gen=df['Gender'].value_counts()
12 count_s=df['Survived'].value_counts().sort_index()
13
14 axes[0,0].bar(count.index,count.values,color=['skyblue'])
15 axes[0,0].set_title('Passenger Class Distribution')
16 axes[0,0].set_xlabel('Pclass')
17 axes[0,0].set_ylabel('Count')
18
19
20 axes[0,1].pie(count_gen.values,labels=['male','female'],colors=
```

Average time

0.576 s
576.00 ms

Maximum time

0.576 s
576.00 ms

1 out of 1 shown test case(s) passed

Test case 1 5/6 ms

Debug

Expected output



Actual output



Terminal

Test cases

5.2.2. Histogram of passenger information of Titanic

Write a Python code to plot a histogram for the distribution of the 'Age' column from the Titanic dataset. The histogram should display the frequency of different age ranges with the following specifications:

- 1. Use **30 bins** for the histogram.
- 2. Set the **edge color** of the bars to **black (k)**.
- 3. Label the x-axis as **'Age'** and the y-axis as **'Frequency'**.
- 4. Add the title **"Age Distribution"** to the histogram.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S											
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C											
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S											
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S											
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S											
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q											
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S											
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S											
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S											
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C											

Note: Refer to the visible test case for better reference.

Sample Test Cases

1import pandas as pd
2import matplotlib.pyplot as plt
3
4# Load the Titanic dataset
5data = pd.read_csv('Titanic-Dataset.csv')
6
7# Data Cleaning
8data['Age'].fillna(data['Age'].median(), inplace=True)
9data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
10data.drop('Cabin', axis=1, inplace=True)
11
12# Convert categorical features to numeric
13data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
14data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
15
16# Write your code here for Histogram
17plt.hist(data['Age'].dropna(),bins=30,edgecolor='k')
18plt.xlabel('Age')
19plt.ylabel('Frequency')
20plt.title('Age Distribution')

Average Time
0.162 s
162.00 ms

Maximum time
0.162 s
162.00 ms

1 out of 1 shown test case(s) passed

Test case 1 162 ms Debug

Expected output

Actual output

Terminal Test cases

5.2.3. Bar plot of survival rate of passengers

Write a Python code to plot a bar chart that shows the count of passengers who survived and did not survive in the Titanic dataset. The chart should display the following specifications:

- 1. Use the 'Survived' column to show the count of survivors (0 = Did not survive, 1 = Survived).
- 2. Set the chart type to 'bar'.
- 3. Add the title "Survival Count" to the chart.
- 4. Label the x-axis as 'Survived' and the y-axis as 'Count'.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
1,0,3,"Braund, Mr. Owen Harris"	male	22,1,0,A/5	21171,7.25,,S								
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)"	female	38,1,0,PC	17599,71.2833,C85,C								
3,1,3,"Heikkinen, Miss. Laina"	female	26,0,0,STON/O2.	3101282,7.925,,S								
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)"	female	35,1,0,113803	53.1,C123,S								
5,0,3,"Allen, Mr. William Henry"	male	35,0,0,373450	8.05,,S								
6,0,3,"Moran, Mr. James"	male	0,0,0,330877	8.4583,,Q								
7,0,1,"McCarthy, Mr. Timothy J"	male	54,0,0,17463	51.8625,E46,S								
8,0,3,"Palsson, Master. Gosta Leonard"	male	2,3,1,349909	21.075,,S								
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)"	female	27,0,2,347742	11.1333,,S								
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)"	female	14,1,0,237736	30.0708,,C								

Note: Refer to the visible test case for better reference.

Sample Test Cases

BarPlotOf...

```
1 import pandas as pd
2 import matplotlib.pyplot as plt
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6
7 # Data Cleaning
8 data['Age'].fillna(data['Age'].median(), inplace=True)
9 data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
10 data.drop('Cabin', axis=1, inplace=True)
11
12 # Convert categorical features to numeric
13 data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
14 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
15
16 # Write your code here for Bar Plot for Survival Rate
17 survival_counts = data['Survived'].value_counts()
18 survival_counts.plot(kind='bar')
19 plt.title('Survival Count')
20 plt.xlabel('Survived')
```

Average time0.198 s198.00 ms

Maximum time0.198 s198.00 ms

1 out of 1 shown test case(s) passed

Test case 1198 ms

Debug

Expected output

Actual output

Terminal

Test cases

5.2.4. Bar Plot for Survival by Gender

Write a Python code to plot a stacked bar chart that shows the count of passengers who survived and did not survive, grouped by gender, in the Titanic dataset. The chart should display the following specifications:

- 1. Group the data by the 'Sex' column, then use the value_counts() function to count the occurrences of survivors (0 = Did not survive, 1 = Survived) for each gender.
- 2. Use a stacked bar chart to display the survival counts.
- 3. Add the title "Survival by Gender" to the chart.
- 4. Label the x-axis as 'Gender' and the y-axis as 'Count'.
- 5. The legend should indicate 'Not Survived' and 'Survived'.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

```
PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Note: Refer to the visible test case for better reference.

Sample Test Cases

BarPlotOf...

```
1 import pandas as pd
2 import matplotlib.pyplot as plt
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6
7 # Data Cleaning
8 data['Age'].fillna(data['Age'].median(), inplace=True)
9 data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
10 data.drop('Cabin', axis=1, inplace=True)
11
12 # Convert categorical features to numeric
13 data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
14 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
15
16
17 survival_counts=data.groupby('Sex')['Survived'].value_counts().unstack()
18 survival_counts.plot(kind='bar',stacked=True)
19 plt.title('Survival by Gender')
20
```

Average time
0.210 s
210.00 ms


Maximum time
0.210 s
210.00 ms

1 out of 1 shown test case(s) passed


Test case 1 210 ms

Debug

Expected output



Actual output



Terminal

Test cases

5.2.5. Bar Plot for Survival by Pclass

Write a Python code to plot a stacked bar chart that shows the count of passengers who survived and did not survive, grouped by passenger class (**Pclass**), in the Titanic dataset. The chart should display the following specifications:

1. Group the data by the **Pclass** column and count the number of survivors (0 = Did not survive, 1 = Survived) for each class using **value_counts()**.
2. Use a **stacked bar chart** to display the survival counts.
3. Add the title **"Survival by Pclass"** to the chart.
4. Label the x-axis as **'Pclass'** and the y-axis as **'Count'**.
5. The legend should indicate **'Not Survived'** and **'Survived'**.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

```
PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,340909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nesser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Note:

- Refer to the visible test case for better reference.
- Ensure you use the **groupby()** function with **value_counts()** to count the survivors and non-survivors for each **Pclass**.
- Do not manually use **size()** or **unstack()** without **value_counts()**. Use the **value_counts()** method for counting survival status directly.

BarPlotOf...

```
1 import pandas as pd
2 import matplotlib.pyplot as plt
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6
7 # Data Cleaning
8 data['Age'].fillna(data['Age'].median(), inplace=True)
9 data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
10 data.drop('Cabin', axis=1, inplace=True)
11
12 # Convert categorical features to numeric
13 data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
14 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
15
16 # Write your code here for Bar Plot for Survival by Pclass
17
18 survival_counts=data.groupby('Pclass')['Survived'].value_counts().unstack()
19 survival_counts.plot(kind='bar',stacked=True)
20 plt.title('Survival by Pclass')
```

Average time

0.215 s

215.00 ms

Maximum time

0.215 s


215.00 ms

1 out of 1 shown test case(s) passed


Test case 1 215 ms

Debug

Expected output



Actual output



Terminal

Test cases

5.2.6. Bar Plot for Survival by Embarked

Write a Python code to plot a stacked bar chart showing the survival count for passengers based on their embarkation location in the Titanic dataset.

The chart should display the following specifications:

- 1. Use the **Embarked** column to determine the embarkation location. After converting this column into dummy variables (using **pd.get_dummies()**), plot the survival count based on the **Embarked_Q** column (representing passengers who embarked from Queenstown) in relation to survival.
- 2. Set the chart type to 'bar' and make it stacked.
- 3. Add the title **"Survival by Embarked "** to the chart.
- 4. Label the x-axis as **'Embarked'** and the y-axis as **'Count'**.
- 5. Include a legend to distinguish between survivors and non-survivors (label the legend as **'Survived'** and **'Not Survived'**).

The Titanic dataset contains columns as shown below,

Passe ngerId	Surviv ed	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

BarPlotOf...

```
1 import pandas as pd
2 import matplotlib.pyplot as plt
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6
7 # Data Cleaning
8 data['Age'].fillna(data['Age'].median(), inplace=True)
9 data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
10 data.drop('Cabin', axis=1, inplace=True)
11
12 # Convert categorical features to numeric
13 data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
14 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
15
16 # Write your code here for Bar Plot for Survival by Embarked
17 sc=data.groupby('Embarked_Q')['Survived'].value_counts().unstack()
18 sc.plot(kind='bar',stacked=True)
19 plt.title('Survival by Embarked')
20 plt.xlabel('Embarked')
```

Average time0.217 s217.00 msMaximum time0.217 s217.00 ms1 out of 1 shown test case(s) passed

Test case 1217 msDebug

Expected output

Actual output

TerminalTest cases

< PrevResetSubmitNext >

5.2.7. Box plot for Age Distribution

Write a Python code to plot a boxplot that shows the distribution of the 'Age' column from the Titanic dataset across different passenger classes. The boxplot should display the following specifications:

- 1. Use the **Pclass** column to group the data for the boxplot.
- 2. Set the title of the plot to **"Age by Pclass"**.
- 3. Remove the default subtitle with **plt.suptitle("")**.
- 4. Label the x-axis as **"Pclass"** and the y-axis as **"Age"**.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.


Sample Test Cases

BoxPlotF...

```
1 import pandas as pd
2 import matplotlib.pyplot as plt
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6
7 # Data Cleaning
8 data['Age'].fillna(data['Age'].median(), inplace=True)
9 data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
10 data.drop('Cabin', axis=1, inplace=True)
11
12 # Convert categorical features to numeric
13 data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
14 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
15
16 # Write your code here for Box Plot for Age by Pclass
17 data.boxplot(column='Age',by='Pclass')
18 plt.title('Age by Pclass')
19 plt.suptitle('')
20 plt.xlabel
```

Average time0.208 s208.00 msMaximum time0.208 s208.00 ms1 out of 1 shown test case(s) passed

Test case 1208 msDebug



TerminalTest cases

5.2.8. Box Plot for Age by Survived

Write a Python code to plot a boxplot that shows the distribution of the 'Age' column from the Titanic dataset based on whether passengers survived or not. The boxplot should display the following specifications:

- 1. Use the **Survived** column to group the data for the boxplot (0 = Did not survive, 1 = Survived).
- 2. Set the title of the plot to **"Age by Survival"**.
- 3. Remove the default subtitle with **plt.suptitle("")**.
- 4. Label the x-axis as **'Survived'** and the y-axis as **'Age'**.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
1,0,3,"Braund, Mr. Owen Harris"	male	22,1,0,A/5	21171,7.25,,S								
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)"	female	38,1,0,PC	17599,71.2633,C85,C								
3,1,3,"Heikkinen, Miss. Laina"	female	26,0,0,STON/O2.	3101282,7.925,,S								
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)"	female	35,1,0,113803,	53.1,C123,S								
5,0,3,"Allen, Mr. William Henry"	male	35,0,0,373450,	8.05,,S								
6,0,3,"Moran, Mr. James"	male	0,0,330877,	8.4583,,0								
7,0,1,"McCarthy, Mr. Timothy J"	male	54,0,0,17463,	51.8625,E46,S								
8,0,3,"Palsson, Master. Gosta Leonard"	male	2,3,1,349909,	21.075,,S								
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)"	female	27,0,2,347742,	11.1333,,S								
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)"	female	14,1,0,237736,	30.0708,,C								

Note: Refer to the visible test case for better reference.

Sample Test Cases

BoxPlotF...

```
1 import pandas as pd
2 import matplotlib.pyplot as plt
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6
7 # Data Cleaning
8 data['Age'].fillna(data['Age'].median(), inplace=True)
9 data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
10 data.drop('Cabin', axis=1, inplace=True)
11
12 # Convert categorical features to numeric
13 data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
14 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
15
16 # Write your code here for Box Plot for Age by Survived
17
18 data.boxplot(column='Age',by='Survived')
19 plt.title('Age by Survival')
20 plt.suptitle('')
```

Average time0.206 s206.00 ms

Maximum time0.206 s206.00 ms

1 out of 1 shown test case(s) passed

Test case 1206 msDebug

Expected output

Actual output

Terminal

Test cases

5.2.9. Box Plot for Fare by Pclass

Write a Python code to plot a boxplot that shows the distribution of the 'Fare' column from the Titanic dataset based on the passenger class (Pclass). The boxplot should display the following specifications:

- 1. Use the **Pclass** column to group the data for the boxplot
- 2. Set the title of the plot to **"Fare by Pclass"**.
- 3. Remove the default subtitle with **plt.suptitle("")**.
- 4. Label the x-axis as **'Pclass'** and the y-axis as **'Fare'**.

The Titanic dataset contains columns as shown below,

Passe ngerId	Surviv ed	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

```
PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,C
```

Note: Refer to the visible test case for better reference.

Sample Test Cases

BoxPlotF... Submit

1 import pandas as pd
2 import matplotlib.pyplot as plt
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6
7 # Data Cleaning
8 data['Age'].fillna(data['Age'].median(), inplace=True)
9 data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
10 data.drop('Cabin', axis=1, inplace=True)
11
12 # Convert categorical features to numeric
13 data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
14 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
15
16 # Write your code here for Box Plot for Fare by Pclass
17
18 # Write your code here for Box Plot for Fare by Pclass
19 data.boxplot(column='Fare', by='Pclass')
20 plt.title('Fare by Pclass')

Average time 0.208 s 208.00 ms Maximum time 0.208 s 208.00 ms 1 out of 1 shown test case(s) passed

Test case 1 208 ms Debug

Expected output Actual output

Terminal Test cases

< Prev Reset Submit Next >

5.2.10. Scatter Plot for Age vs. Fare

Write a Python code to plot a scatter plot showing the relationship between the 'Age' and 'Fare' columns in the Titanic dataset. The scatter plot should display the following specifications:

- 1. Use the **Age** column for the x-axis and the **Fare** column for the y-axis.
- 2. Set the title of the plot to **"Age vs. Fare"**.
- 3. Label the x-axis as **'Age'** and the y-axis as **'Fare'**.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

```
PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,C
```

Note: Refer to the visible test case for better reference.

Sample Test Cases

AgeFareS... Submit

```
1 import pandas as pd
2 import matplotlib.pyplot as plt
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6
7 # Data Cleaning
8 data['Age'].fillna(data['Age'].median(), inplace=True)
9 data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
10 data.drop('Cabin', axis=1, inplace=True)
11
12 # Convert categorical features to numeric
13 data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
14 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
15
16 # Write your code here for Scatter Plot for Age vs. Fare
17 plt.scatter(data['Age'], data['Fare'])
18 plt.title("Age vs. Fare")
19 plt.xlabel("Age")
20 plt.ylabel("Fare")
```

Average time0.155 s155.00 msMaximum time0.155 s155.00 ms1 out of 1 shown test case(s) passed

Test case 1155 ms Debug

Expected output

Actual output

TerminalTest cases

5.2.11. Scatter Plot for Age vs. Fare by Survived

Write a Python code to plot a scatter plot showing the relationship between the 'Age' and 'Fare' columns in the Titanic dataset, with points color-coded by survival status. The scatter plot should display the following specifications:

- 1. Use the **Age** column for the x-axis and the **Fare** column for the y-axis.
- 2. Color the points based on the **Survived** column: **Red** for passengers who did not survive (**Survived = 0**). **Blue** for passengers who survived (**Survived = 1**).
- 3. Set the title of the plot to **"Age vs. Fare by Survival"**.
- 4. Label the x-axis as **'Age'** and the y-axis as **'Fare'**.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

```
PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Note: Refer to the visible test case for better reference.

Sample Test Cases

AgeFareS...

```
1 import pandas as pd
2 import matplotlib.pyplot as plt
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6
7 # Data Cleaning
8 data['Age'].fillna(data['Age'].median(), inplace=True)
9 data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
10 data.drop('Cabin', axis=1, inplace=True)
11
12 # Convert categorical features to numeric
13 data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
14 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
15 # Write your code here for Scatter Plot for Age vs. Fare by Survived
16 colors = data['Survived'].map({0: 'red', 1: 'blue'})
17 plt.scatter(data['Age'], data['Fare'], c=colors)
18 plt.title('Age vs. Fare by Survival')
19 plt.xlabel('Age')
20 plt.ylabel('Fare')
```

Average time
0.174 s
174.00 ms

Maximum time
0.174 s
174.00 ms

1 out of 1 shown test case(s) passed

Test case 1

174 ms

Debug

Expected output



Actual output



Terminal

Test cases