

Clustering

Lecture 14

David Sontag
New York University

Slides adapted from Luke Zettlemoyer, Vibhav Gogate,
Carlos Guestrin, Andrew Moore, Dan Klein

Clustering


Clustering:

- Unsupervised learning
- Requires data, but no labels
- Detect patterns e.g. in
 - Group emails or search results
 - Customer shopping patterns
 - Regions of images
- Useful when don't know what you're looking for
- But: can get gibberish





Clustering

- **Basic idea:** group together similar instances
- **Example:** 2D point patterns




Clustering

- **Basic idea:** group together similar instances
- **Example:** 2D point patterns



Clustering

- **Basic idea:** group together similar instances
- **Example:** 2D point patterns




- **What could “similar” mean?**
 - One option: small Euclidean distance (squared)
$$\text{dist}(\vec{x}, \vec{y}) = ||\vec{x} - \vec{y}||_2^2$$
 - Clustering results are crucially dependent on the measure of similarity (or distance) between “points” to be clustered

Clustering algorithms


- Partition algorithms (Flat)

- K-means
- Mixture of Gaussian
- Spectral Clustering



- Hierarchical algorithms

- Bottom up – agglomerative
- Top down – divisive



Clustering examples

Image segmentation


Goal: Break up the image into meaningful or perceptually similar regions



[Slide from James Hayes]

Clustering examples


Clustering gene expression data



Eisen et al, PNAS 1998


K-Means

- An iterative clustering algorithm
 - **Initialize:** Pick K random points as cluster centers
 - **Alternate:**
 1. Assign data points to closest cluster center
 2. Change the cluster center to the average of its assigned points
 - **Stop** when no points' assignments change




K-Means

- An iterative clustering algorithm
 - **Initialize:** Pick K random points as cluster centers
 - **Alternate:**
 1. Assign data points to closest cluster center
 2. Change the cluster center to the average of its assigned points
 - **Stop** when no points' assignments change




K-means clustering: Example



- Pick K random points as cluster centers (means)

Shown here for $K=2$


K-means clustering: Example



Iterative Step 1

- Assign data points to closest cluster center


K-means clustering: Example



Iterative Step 2


- Change the cluster center to the average of the assigned points

K-means clustering: Example




- Repeat until convergence


K-means clustering: Example



K-means clustering: Example



K-means clustering: Example



Properties of K-means **algorithm**

- Guaranteed to converge in a finite number of iterations
- Running time per iteration:
 1. Assign data points to closest cluster center
 $O(KN)$ time
 2. Change the cluster center to the average of its assigned points
 $O(N)$

What properties should a distance measure have?

- Symmetric
 - $D(A,B)=D(B,A)$
 - Otherwise, we can say A looks like B but B does not look like A
- Positivity, and self-similarity
 - $D(A,B) \geq 0$, and $D(A,B)=0$ iff $A=B$
 - Otherwise there will different objects that we cannot tell apart
- Triangle inequality
 - $D(A,B)+D(B,C) \geq D(A,C)$
 - Otherwise one can say “A is like B, B is like C, but A is not like C at all”

Kmeans Convergence

Objective

$$\min_{\mu} \min_C \sum_{i=1}^k \sum_{x \in C_i} |x - \mu_i|^2$$

1. Fix μ , optimize C :

$$\min_C \sum_{i=1}^k \sum_{x \in C_i} |x - \mu_i|^2 = \min_c \sum_i^n |x_i - \mu_{x_i}|^2$$

Step 1 of kmeans

2. Fix C , optimize μ :

$$\min_{\mu} \sum_{i=1}^k \sum_{x \in C_i} |x - \mu_i|^2$$

- Take partial derivative of μ_i and set to zero, we have

$$\mu_i = \frac{1}{|C_i|} \sum_{x \in C_i} x$$

Step 2 of kmeans

Kmeans takes an alternating optimization approach, each step is guaranteed to decrease the objective – thus guaranteed to converge

Example: K-Means for Segmentation

K=2



Goal of Segmentation is to partition an image into regions each of which has reasonably homogenous visual appearance.

Original



Example: K-Means for Segmentation

K=2



K=3



Original



Example: K-Means for Segmentation

K=2



K=3




K=10



Original



4%



8%



17%



Example: Vector quantization





FIGURE 14.9. *Sir Ronald A. Fisher (1890 – 1962) was one of the founders of modern day statistics, to whom we owe maximum-likelihood, sufficiency, and many other fundamental concepts. The image on the left is a 1024×1024 grayscale image at 8 bits per pixel. The center image is the result of 2×2 block VQ, using 200 code vectors, with a compression rate of 1.9 bits/pixel. The right image uses only four code vectors, with a compression rate of 0.50 bits/pixel*

[Figure from Hastie *et al.* book]


Initialization

- K-means **algorithm** is a heuristic
 - Requires initial means
 - It does matter what you pick!
 - What can go wrong?
 - Various schemes for preventing this kind of thing: variance-based split / merge, initialization heuristics




K-Means Getting Stuck

A local optimum:



Would be better to have
one cluster here



... and two clusters here

Extra

- K-means Applets:
 - http://home.dei.polimi.it/matteucc/Clustering/tutorial_html/AppletKM.html
 - <http://www.cs.washington.edu/research/imagedatabase/demo/kmcluster/>