# Introduction





Silberschatz, Galvin and Gagne ©2018

# Chapter 1: Introduction

- What Operating Systems Do
- Computer-System Organization
- Computer-System Architecture
- Operating-System Operations
- Resource Management
- Security and Protection
- Virtualization
- Distributed Systems
- Kernel Data Structures
- Computing Environments
- Free/Libre and Open-Source Operating Systems

# Objectives

- Describe the general organization of a computer system and the role of interrupts
- Describe the components in a modern, multiprocessor computer system
- Illustrate the transition from user mode to kernel mode
- Discuss how operating systems are used in various computing environments
- Provide examples of free and open-source operating systems

# What Does the Term Operating System Mean?

- An operating system is “fill in the blanks”
- What about:
  - Car
  - Airplane
  - Printer
  - Washing Machine
  - Toaster
  - Compiler
  - Etc.

# What is an Operating System?

- A program that acts as an intermediary between a user of a computer and the computer hardware
- Operating system goals:
  - Execute user programs and make solving user problems easier
  - Make the computer system convenient to use
  - Use the computer hardware in an efficient manner

# Computer System Structure

- Computer system can be divided into four components:
  - Hardware – provides basic computing resources
    - CPU, memory, I/O devices
  - Operating system
    - Controls and coordinates use of hardware among various applications and users
  - Application programs – define the ways in which the system resources are used to solve the computing problems of the users
    - Word processors, compilers, web browsers, database systems, video games
  - Users
    - People, machines, other computers

# Abstract View of Components of Computer



# What Operating Systems Do

- Depends on the point of view
- Users want convenience, **ease of use** and **good performance**
  - Don't care about **resource utilization**
- But shared computer such as **mainframe** or **minicomputer** must keep all users happy
  - Operating system is a **resource allocator** and **control program** making efficient use of HW and managing execution of user programs
- Users of dedicate systems such as **workstations** have dedicated resources but frequently use shared resources from **servers**
- Mobile devices like smartphones and tables are resource poor, optimized for usability and battery life
  - Mobile user interfaces such as touch screens, voice recognition
- Some computers have little or no user interface, such as embedded computers in devices and automobiles
  - Run primarily without user intervention

# Defining Operating Systems

- Term OS covers many roles
  - Because of myriad designs and uses of OSes
  - Present in toasters through ships, spacecraft, game machines, TVs and industrial control systems
  - Born when fixed use computers for military became more general purpose and needed resource management and program control

# Operating System Definition

- No universally accepted definition
- "Everything a vendor ships when you order an operating system" is a good approximation
  - But varies wildly
- "The one program running at all times on the computer" is the **kernel,** part of the operating system
- Everything else is either
  - A ***system program*** (ships with the operating system, but not part of the kernel) , or
  - An ***application program***, all programs not associated with the operating system
- Today's OSes for general purpose and mobile computing also include ***middleware*** – a set of software frameworks that provide additional services to application developers such as databases, multimedia, graphics

# Overview of Computer System Structure

# Computer System Organization

- Computer-system operation
  - One or more CPUs, device controllers connect through common **bus** providing access to shared memory
  - Concurrent execution of CPUs and devices competing for memory cycles



# Computer-System Operation

- I/O devices and the CPU can execute concurrently
- Each device controller is in charge of a particular device type
- Each device controller has a local buffer
- Each device controller type has an operating system **device driver** to manage it
- CPU moves data from/to main memory to/from local buffers
- I/O is from the device to local buffer of controller
- Device controller informs CPU that it has finished its operation by causing an **interrupt**

# Common Functions of Interrupts

- Interrupt transfers control to the interrupt service routine generally, through the **interrupt vector**, which contains the addresses of all the service routines
- Interrupt architecture must save the address of the interrupted instruction
- A **trap** or **exception** is a software-generated interrupt caused either by an error or a user request
- An operating system is **interrupt driven**

# Interrupt Timeline



# Interrupt Handling

- The operating system preserves the state of the CPU by storing the registers and the program counter
- Determines which type of interrupt has occurred:
- Separate segments of code determine what action should be taken for each type of interrupt

# Interrupt-drive I/O Cycle



# I/O Structure

- Two methods for handling I/O
  - After I/O starts, control returns to user program only upon I/O completion
  - After I/O starts, control returns to user program without waiting for I/O completion

# I/O Structure (Cont.)

- After I/O starts, control returns to user program only upon I/O completion
  - Wait instruction idles the CPU until the next interrupt
  - Wait loop (contention for memory access)
  - At most one I/O request is outstanding at a time, no simultaneous I/O processing
- After I/O starts, control returns to user program without waiting for I/O completion
  - **System call** – request to the OS to allow user to wait for I/O completion
  - **Device-status table** contains entry for each I/O device indicating its type, address, and state
  - OS indexes into I/O device table to determine device status and to modify table entry to include interrupt

# Storage Structure

# Storage Structure

- Main memory – only large storage media that the CPU can access directly
  - **Random access**
  - Typically **volatile**
  - Typically **random-access memory** in the form of **Dynamic Random-access Memory (DRAM)**
- Secondary storage – extension of main memory that provides large **nonvolatile** storage capacity

# Storage Structure (Cont.)

- **Hard Disk Drives** (**HDD**) – rigid metal or glass platters covered with magnetic recording material
  - Disk surface is logically divided into **tracks**, which are subdivided into **sectors**
  - The **disk controller** determines the logical interaction between the device and the computer
- **Non-volatile memory** (**NVM**) devices– faster than hard disks, nonvolatile
  - Various technologies
  - Becoming more popular as capacity and performance increases, price drops

# Storage Definitions and Notation Review

The basic unit of computer storage is the **bit**. A bit can contain one of two values, 0 and 1. All other storage in a computer is based on collections of bits. Given enough bits, it is amazing how many things a computer can represent: numbers, letters, images, movies, sounds, documents, and programs, to name a few. A **byte** is 8 bits, and on most computers it is the smallest convenient chunk of storage. For example, most computers don't have an instruction to move a bit but do have one to move a byte. A less common term is **word**, which is a given computer architecture's native unit of data. A word is made up of one or more bytes. For example, a computer that has 64-bit registers and 64-bit memory addressing typically has 64-bit (8-byte) words. A computer executes many operations in its native word size rather than a byte at a time.

Computer storage, along with most computer throughput, is generally measured and manipulated in bytes and collections of bytes. A **kilobyte**, or KB , is 1,024 bytes; a **megabyte**, or **MB**, is $1{,}024^2$ bytes; a **gigabyte**, or **GB**, is $1{,}024^3$ bytes; a **terabyte**, or **TB**, is $1{,}024^4$ bytes; and a **petabyte**, or **PB**, is $1{,}024^5$ bytes. Computer manufacturers often round off these numbers and say that a megabyte is 1 million bytes and a gigabyte is 1 billion bytes. Networking measurements are an exception to this general rule; they are given in bits (because networks move data a bit at a time).

# Storage Hierarchy

- Storage systems organized in hierarchy
  - Speed
  - Cost
  - Volatility
- **Caching** – copying information into faster storage system; main memory can be viewed as a cache for secondary storage
- **Device Driver** for each device controller to manage I/O
  - Provides uniform interface between controller and kernel

# Storage-Device Hierarchy



# How a Modern Computer Works




*A von Neumann architecture*

# Functions of OS



# Functions of OS

## 1. Memory Management

- It is the management of the main or primary memory.
- Whatever program is executed, it has to be present in the main memory.
- Main memory is a quick storage area that may be accessed directly by the CPU. When the program is completed, the memory region is released and can be used by other programs.
- Therefore, there can be more than one program present at a time. Hence, it is required to manage the memory.

  - Allocates and deallocates the memory.
  - Keeps a record of which part of primary memory is used by whom and how much.
  - Distributes the memory while multiprocessing.
  - In multiprogramming, the operating system selects which processes acquire memory when and how much memory they get.

# Functions of OS

## 2. Processor Management/Scheduling

- Every software that runs on a computer, whether in the background or in the frontend, is a process.
- Processor management is an execution unit in which a program operates.
- The operating system determines the status of the processor and processes, selects a job and its processor, allocates the processor to the process, and de-allocates the processor after the process is completed.

When more than one process runs on the system the OS decides how and when a process will use the CPU. Hence, the name is also **CPU Scheduling**.

# Functions of OS

The OS:

- Allocates and deallocates processor to the processes.
- Keeps record of CPU status.

Certain algorithms used for CPU scheduling are as follows:

- First Come First Serve (FCFS)
- Shortest Job First (SJF)
- Round-Robin Scheduling
- Priority-based scheduling etc.

# Functions of OS

**Purpose of CPU scheduling**

The purpose of CPU scheduling is as follows:

•Proper utilization of CPU. Since the proper utilization of the CPU is necessary. Therefore, the OS makes sure that the CPU should be as busy as possible.

•Since every device should get a chance to use the processor. Hence, the OS makes sure that the devices get fair processor time.

•Increasing the efficiency of the system.

# Functions of OS

## 3. Device Management

- An operating system regulates device connection using drivers.
- The processes may require devices for their use.
- This management is done by the OS.

The OS:

•Allocates and deallocates devices to different processes.

•Keeps records of the devices.

•Decides which process can use which device for how much time.

## 4. File Management

The operating system manages resource allocation and de-allocation. It specifies which process receives the file and for how long. It also keeps track of information, location, uses, status, and so on. These groupings of resources are referred to as file systems. The files on a system are stored in different directories.

The OS:

•Keeps records of the status and locations of files.

•Allocates and deallocates resources.

•Decides who gets the resources.

# Functions of OS

**5. Storage Management**

**4. File Management**

The operating system manages resource allocation and de-allocation.
It specifies which process receives the file and for how long. It also keeps track of information, location, uses, status, and so on.
These groupings of resources are referred to as file systems. The files on a system are stored in different directories.
The OS:
•Keeps records of the status and locations of files.
•Allocates and deallocates resources.
•Decides who gets the resources.

- The operating system is in charge of storing and accessing files.
- The creation of files, the creation of directories, the reading and writing of data from files and directories, as well as the copying of the contents of files and directories from one location to another are all included in storage management.

# Design Issues

Efficiency
Generality

# Protection and Security

- **Protection** – any mechanism for controlling access of processes or users to resources defined by the OS
- **Security** – defense of the system against internal and external attacks
  - Huge range, including denial-of-service, worms, viruses, identity theft, theft of service
- Systems generally first distinguish among users, to determine who can do what
  - User identities (**user IDs**, security IDs) include name and associated number, one per user
  - User ID then associated with all files, processes of that user to determine access control
  - Group identifier (**group ID**) allows set of users to be defined and controls managed, then also associated with each process, file
  - **Privilege escalation** allows user to change to effective ID with more rights

# Virtualization

- Allows operating systems to run applications within other OSes
  - Vast and growing industry
- **Emulation** used when source CPU type different from target type (i.e. PowerPC to Intel x86)
  - Generally slowest method
  - When computer language not compiled to native code – **Interpretation**
- **Virtualization** – OS natively compiled for CPU, running **guest** OSes also natively compiled
  - Consider VMware running WinXP guests, each running applications, all on native WinXP **host** OS
  - **VMM** (virtual machine Manager) provides virtualization services

# Virtualization (cont.)

- Use cases involve laptops and desktops running multiple OSes for exploration or compatibility
  - Apple laptop running Mac OS X host, Windows as a guest
  - Developing apps for multiple OSes without having multiple systems
  - Quality assurance testing applications without having multiple systems
  - Executing and managing compute environments within data centers
- VMM can run natively, in which case they are also the host
  - There is no general-purpose host then (VMware ESX and Citrix XenServer)

# Computing Environments - Virtualization



# Distributed Systems

- Collection of separate, possibly heterogeneous, systems networked together
  - **Network** is a communications path, **TCP/IP** most common
    - **Local Area Network** (**LAN**)
    - **Wide Area Network** (**WAN**)
    - **Metropolitan Area Network** (**MAN**)
    - **Personal Area Network** (**PAN**)
- **Network Operating System** provides features between systems across network
  - Communication scheme allows systems to exchange messages
  - Illusion of a single system

# Computer System Architecture

# Computer-System Architecture

- Most systems use a single general-purpose processor
  - Most systems have special-purpose processors as well
- **Multiprocessors** systems growing in use and importance
  - Also known as **parallel systems**, **tightly-coupled systems**
  - Advantages include:
    1. **Increased throughput**
    2. **Economy of scale**
    3. **Increased reliability** – graceful degradation or fault tolerance
  - Two types:
    1. **Asymmetric Multiprocessing** – each processor is assigned a specie task.
    2. **Symmetric Multiprocessing** – each processor performs all tasks

# Symmetric Multiprocessing Architecture



# Dual-Core Design

- Multi-chip and **multicore**
- Systems containing all  chips
  - Chassis containing multiple separate systems



# Non-Uniform Memory Access System



# Clustered Systems

- Like multiprocessor systems, but multiple systems working together
  - Usually sharing storage via a **storage-area network** (**SAN**)
  - Provides a **high-availability** service which survives failures
    - **Asymmetric clustering** has one machine in hot-standby mode
    - **Symmetric clustering** has multiple nodes running applications, monitoring each other
  - Some clusters are for **high-performance computing** (**HPC**)
    - Applications must be written to use **parallelization**
  - Some have **distributed lock manager** (**DLM**) to avoid conflicting operations

# Clustered Systems



# PC Motherboard

Consider the desktop PC motherboard with a processor socket shown below:




This board is a fully-functioning computer, once its slots are populated. It consists of a processor socket containing a CPU, DRAM sockets, PCIe bus slots, and I/O connectors of various types. Even the lowest-cost general-purpose CPU contains multiple cores. Some motherboards contain multiple processor sockets. More advanced computers allow more than one system board, creating NUMA systems.

# Computer System Environments

# Computing Environments

- Traditional
- Mobile
- Client Server
- Peer-to-Peer
- Cloud computing
- Real-time Embedded

# Traditional

- Stand-alone general-purpose machines
- But blurred as most systems interconnect with others (i.e., the Internet)
- **Portals** provide web access to internal systems
- **Network computers** (**thin clients**) are like Web terminals
- Mobile computers interconnect via **wireless networks**
- Networking becoming ubiquitous – even home systems use **firewalls** to protect home computers from Internet attacks

# Mobile

- Handheld smartphones, tablets, etc.
- What is the functional difference between them and a "traditional" laptop?
- Extra feature – more OS features (GPS, gyroscope)
- Allows new types of apps like ***augmented reality***
- Use IEEE 802.11 wireless, or cellular data networks for connectivity
- Leaders are **Apple iOS** and **Google Android**

# Client Server

- Client-Server Computing
  - Dumb terminals supplanted by smart PCs
  - Many systems now **servers**, responding to requests generated by **clients**
    - **Compute-server system** provides an interface to client to request services (i.e., database)
    - **File-server system** provides interface for clients to store and retrieve files



# Peer-to-Peer

- Another model of distributed system
- P2P does not distinguish clients and servers
  - Instead all nodes are considered peers
  - May each act as client, server or both
  - Node must join P2P network
    - Registers its service with central lookup service on network, or
    - Broadcast request for service and respond to requests for service via ***discovery protocol***
  - Examples include Napster and Gnutella, **Voice over IP** (**VoIP**) such as Skype



# Cloud Computing

- Delivers computing, storage, even apps as a service across a network
- Logical extension of virtualization because it uses virtualization as the base for it functionality.
  - Amazon **EC2** has thousands of servers, millions of virtual machines, petabytes of storage available across the Internet, pay based on usage

# Cloud Computing (Cont.)

- Many types
  - **Public cloud** – available via Internet to anyone willing to pay
  - **Private cloud** – run by a company for the company's own use
  - **Hybrid cloud** – includes both public and private cloud components
  - Software as a Service (**SaaS**) – one or more applications available via the Internet (i.e., word processor)
  - Platform as a Service (**PaaS**) – software stack ready for application use via the Internet (i.e., a database server)
  - Infrastructure as a Service (**IaaS**) – servers or storage available over Internet (i.e., storage available for backup use)

# Cloud Computing (cont.)

- Cloud computing environments composed of traditional OSes, plus VMMs, plus cloud management tools
  - Internet connectivity requires security like firewalls
  - Load balancers spread traffic across multiple applications



# Real-Time Embedded Systems

- Real-time embedded systems most prevalent form of computers
  - Vary considerable, special purpose, limited purpose OS, **real-time OS**
  - Use expanding
- Many other special computing environments as well
  - Some have OSes, some perform tasks without an OS
- Real-time OS has well-defined fixed time constraints
  - Processing ***must*** be done within constraint
  - Correct operation only if constraints met

# Free and Open-Source Operating Systems

- Operating systems made available in source-code format rather than just binary **closed-source** and **proprietary**
- Counter to the **copy protection** and **Digital Rights Management** (**DRM**) movement
- Started by **Free Software Foundation** (**FSF**), which has "copyleft" **GNU Public License** (**GPL**)
  - Free software and open-source software are two different ideas championed by different groups of people
    - **https://www.gnu.org/philosophy/open-source-misses-the-point.en.html**
- Examples include **GNU/Linux** and **BSD UNIX** (including core of **Mac OS X**), and many more
- Can use VMM like VMware Player (Free on Windows), Virtualbox (open source and free on many platforms - http://www.virtualbox.com)
  - Use to run guest operating systems for exploration

# The Study of Operating Systems

There has never been a more interesting time to study operating systems, and it has never been easier. The open-source movement has overtaken operating systems, causing many of them to be made available in both source and binary (executable) format. The list of operating systems available in both formats includes Linux, BUSD UNIX, Solaris, and part of macOS. The availability of source code allows us to study operating systems from the inside out. Questions that we could once answer only by looking at documentation or the behavior of an operating system we can now answer by examining the code itself.

Operating systems that are no longer commercially viable have been open-sourced as well, enabling us to study how systems operated in a time of fewer CPU, memory, and storage resources. An extensive but incomplete list of open-source operating-system projects is available from https://curlie.org/Computers/Software/Operating_Systems/Open_Source/

In addition, the rise of virtualization as a mainstream (and frequently free) computer function makes it possible to run many operating systems on top of one core system. For example, VMware (http://www.vmware.com) provides a free "player" for Windows on which hundreds of free "virtual appliances" can run. Virtualbox (http://www.virtualbox.com) provides a free, open-source virtual machine manager on many operating systems. Using such tools, students can try out hundreds of operating systems without dedicated hardware.

The advent of open-source operating systems has also made it easier to make the move from student to operating-system developer. With some knowledge, some effort, and an Internet connection, a student can even create a new operating-system distribution. Just a few years ago, it was difficult or impossible to get access to source code. Now, such access is limited only by how much interest, time, and disk space a student has.

# Kernel Data Structure

# Kernel Data Structures

- Many similar to standard programming data structures
- ***Singly linked list***




- ***Doubly linked list***




- ***Circular linked list***



# Kernel Data Structures

- **Binary search tree**
  left <= right
  - Search performance is *O(n)*
  - **Balanced binary search tree** is *O(lg n)*



# Kernel Data Structures

- **Hash function** can create a **hash map**




- **Bitmap** – string of *n* binary digits representing the status of *n* items
- Linux data structures defined in ***include*** files `<linux/list.h>`, `<linux/kfifo.h>`, `<linux/rbtree.h>`

# End of Chapter 1





Silberschatz, Galvin and Gagne ©2018