Clifford networks do not improve Ramsey sensitivity

Akshit*

October 2026

Abstract

A Clifford layer does not improve quantum sensitivity. On a simulated planar Ramsey magnetometer it matches a least-squares inversion of the known likelihood, sits on the Cramér–Rao bound at 512 shots (rms/$\sqrt{\text{CRB}} \approx 0.99$), and loses to a plain linear net on hard-iron / soft-iron calibration. The one place it is decisive is the product a vector sensor already computes, (readout $-\frac{1}{2}$) $\times$ axis. Given the raw pieces and not the product, a 68-parameter Cl$(2,0)$ net is at the noise floor with 20 labeled fields (field MSE ≈ 0.002). A parameter-matched tanh MLP is still at 0.32 after 500 fields. That is a decoder result. The qubit does not get quieter.

1 The claim

Sensing is the extraction of a field B from shots [Degen et al., 2017, Helstrom, 1969]. On a single-fringe Ramsey protocol that extraction is already solved by arcsin and a 2×2 solve [Ramsey, 1950, Taylor et al., 2008]. A network that matches that solve has inverted the record. It has not improved the sensor.

Clifford (geometric-algebra) layers are a natural candidate for the decoder anyway. A magnetic field is a grade-1 object. A vector magnetometer reports it in the sensor frame, so a platform rotation R sends $B \mapsto RB$ and the measurement axes with it. The geometric product respects that action: $R(ab)\tilde{R} = (Ra\tilde{R})(Rb\tilde{R})$ [Doran and Lasenby, 2003, Ruhe et al., 2023a]. Spin-$\frac{1}{2}$ precession is a rotor in Cl$(3,0)$. This note stays in Cl$(2,0)$. A 3D Bloch magnetometer is a later algebra, not a better first measurement.

Machine-learning inverses for atomic and NV magnetometers already exist [Meng et al., 2023, Zhang et al., 2024]. Equivariant and physics-informed nets for platform magnetometry exist too. Clifford networks have been shown on n-body, fluids, and Lorentz-equivariant HEP [Ruhe et al., 2023b,a, Brandstetter et al., 2023]. What is thin is the combination: a Clifford layer, a Ramsey likelihood, a classical estimator, and a Cramér–Rao number on the same simulated shots. That is the measurement this note reports.

The first sweep is a tie by construction. Once any model is handed the vector observation $v_k = (P_k - \frac{1}{2})u_k$, every estimator is doing the same linear inversion. The architectures only come apart when that product is taken away, or when the classical fit believes the wrong sensor.

*akshitcasual1@gmail.com. Code: https://github.com/akshitj11/clifford-based-network.

2 Protocol

A spin-$\frac{1}{2}$ runs a Ramsey sequence along each of $m = 6$ unit axes u_k, biased to the steepest point of the fringe (control phase $-\pi/2$):

$$\phi_k = \gamma T\,(B \cdot u_k), \tag{1}$$

$$P_k = \tfrac{1}{2}\big(1 + V \sin\phi_k\big) + \text{noise}, \qquad V = \exp(-T/T_2). \tag{2}$$

Default numbers: $\gamma = 1$, $T = 1$, $T_2 = 5$ so $V \approx 0.82$, Gaussian readout $\sigma = 0.02$ unless replaced by binomial shot noise. Fields are drawn uniformly in the disk $|B| \le 0.8$, which keeps $|\phi| \le 0.8\,\text{rad}$. sin is monotonic there. The record is invertible. That is the regime in which least squares is allowed to be strong [Taylor et al., 2008, Maze et al., 2008].

An optional device defect is applied before projection, $B_{\text{eff}} = \text{diag}(s)B + h$, with soft-iron gain s (default $(1, 1)$) and hard-iron bias h (default 0). This is the usual hard-iron / soft-iron (Tolles–Lawson) distortion of a vector magnetometer. Defects are a property of the sensor, constant across samples. Fields and orientations vary.

The classical estimator inverts the fringe,

$$\text{proj}_k = \arcsin\big(\text{clip}((2P_k - 1)/V)\big)/(\gamma T), \tag{3}$$

and solves the 2×2 normal equations for B_{eff}. An oracle then undoes the true (s, h). A naive fit assumes $s = 1$, $h = 0$, and the nominal T_2.

Learned models share one topology: a shared per-axis message, a sum over the six axes, a shared update that reads a 2D field. `CliffordMag` carries $\text{Cl}(2, 0)$ multivector channels through geometric products. `FlatMag` is a parameter-matched real linear net (68 vs 70 scalars). Training is full-batch analytic SGD, 400 epochs, learning rate 0.1, three seeds unless noted. The stack is CPU-only Rust, single-threaded, hand-written geometric-product VJPs, splitmix64 data. A sweep finishes in minutes.

Field MSE is the mean of $(\Delta B_x)^2 + (\Delta B_y)^2$ on 500 held-out samples. RMS field error is its square root. Equivariance error is the RMS gap between rotating the estimate and estimating on the rotated apparatus.

3 Clean inversion is a tie

On the default Gaussian protocol, least squares, Clifford, and flat all report field MSE ≈ 0.00191 on the held-out set. At 1000 training fields the two nets are 0.001877 (mean over seeds). That is the readout-noise floor of this protocol, not a model ranking.

The slope of the fringe near zero field is $dP/dB \approx \frac{1}{2}V \approx 0.41$. $\sigma = 0.02$ is then about 0.05 of field error on one axis. Six axes, least-squares combined, put the two-component MSE near 0.0016 in the linear approximation. The measured 0.00191 is a little worse because sin flattens at larger phase and T_2 has already cut 18% of the contrast.

What splits the nets is rotation, not accuracy. At $N = 1000$, equivariance error is 0.00092 (Clifford) versus 0.00152 (flat). At $N = 100$ the same gap is 0.0044 versus 0.0067. The classical inversion is at 6×10^{-8}. Clifford is the closer of the two learned models to the group action. It is not a more accurate field estimate.

4 A wrong classical model is beatable. Geometry is not why.

A real device has a bias, a gain, and a T_2 you do not know exactly. The honest baseline is a lab fit that assumes an ideal sensor.

Defect level d sets $h = (0.2d, -0.15d)$, $s = (1 + 0.3d,\ 1 - 0.2d)$, $T_2 = 5(1 - 0.2d)$, and the naive fit still believes $h = 0$, $s = 1$, $T_2 = 5$.

Table 1: Held-out field MSE versus defect level d. Oracle least squares is given the true (s, h, T_2).

d	naive LS	oracle LS	Clifford	flat
0.0	0.00191	0.00191	0.00188	0.00188
0.5	0.0221	0.00199	0.00611	0.00207
1.0	0.0761	0.00240	0.0171	0.00278

At $d = 1$ the naive fit is about $40\times$ the noise floor. The oracle is essentially back on the floor. The flat net tracks the oracle (0.00278). Clifford beats the naive fit (0.017 versus 0.076) and loses to the flat net by about $6\times$.

The defect is a world-frame diagonal scale plus an offset. That is not a rotor. A linear map on v_k plus a constant channel can absorb s and h. The flat net does that. Learned models beat a misspecified likelihood. The architecture that won is the one without geometric structure.

Equivariance error rises with d for every estimator that tries to undo the defect (0.30 for the oracle at $d = 1$). Soft-iron in world axes breaks the rotation symmetry of the record. The naive fit stays numerically "equivariant" because it is consistently wrong in a rotation-covariant way.

5 Take the product away

`CliffordMag` and `FlatMag` were handed $v_k = (P_k - \frac{1}{2})u_k$. A single linear layer can finish the job. That is why they tied at $N = 100$.

`CliffordMagRaw` is given two separate channels, scalar$(P_k - \frac{1}{2})$ and vector(u_k), and forms the observable with one geometric product. No weights in that product. The rest of the net is the same 68-parameter message/update pair. `FlatMlpMag` sees $[P_k - \frac{1}{2},\ u_x,\ u_y]$ through a tanh hidden layer (67 parameters) and has to learn the bilinear map. Five seeds, 600 epochs, training sizes 20/50/100/500.

Table 2: Field MSE when the model must form $(P - \frac{1}{2})u$ itself. Mean $\pm$ std over five seeds.

N	Clifford raw	tanh MLP
20	0.00196 ± 0.00004	0.432 ± 0.057
50	0.00195 ± 0.00005	0.353 ± 0.022
100	0.00192 ± 0.00003	0.332 ± 0.006
500	0.00188 ± 0.00001	0.323 ± 0.002

0.32 is the MSE of a model that predicts near-zero field on this disk. The MLP never forms the product in this budget. Clifford is on the floor at the first point in the sweep. Equivariance follows the same split. At $N = 20$, Clifford is 0.004–0.010; the MLP is 0.18–0.40. At $N = 500$, Clifford is 0.0002–0.002; the MLP is still 0.02–0.06.

The geometric product is the map the sensor physics already uses. A generic nonlinearity of the same width does not find it from a few hundred examples. There is no crossover in the range we ran. Saying the gap closes as N grows would be a prediction, not a measurement. A wider MLP, an explicit multiply, or a kernel would be a stronger baseline. Those are not in this sweep.

6 Shot noise against the bound

Gaussian σ is a convenience. A projective readout of n shots is a binomial count. Fisher information for this Ramsey model, per axis, is

$$\frac{dP}{dB_{\text{proj}}} = \tfrac{1}{2} V \gamma T \cos\phi_k, \tag{4}$$

$$\mathrm{Var}(\hat{P}) = P_k(1-P_k)/n, \tag{5}$$

$$F = \sum_k \frac{(dP/dB)(dP/dB)^\top}{\mathrm{Var}_k}, \qquad \mathrm{CRB} = \mathrm{tr}(F^{-1}). \tag{6}$$

The figure that should travel is rms/$\sqrt{\text{CRB}}$, plus the shot-scaled sensitivity $\gamma T\sqrt{n}\cdot$ rms [Degen et al., 2017, Helstrom, 1969]. A ratio near 1 means the estimator used the shots. A ratio of 0.5 would be a claim of super-classical information and a reason to stop and find the bug.

Table 3: RMS field error versus $\sqrt{\text{CRB}}$ under binomial readout.

n	class. rms	Cliff. rms	flat rms	$\sqrt{\text{CRB}}$	class./bnd	Cliff./bnd
32	0.192	0.169	0.169	0.182	1.056	0.929
128	0.0925	0.0898	0.0899	0.0910	1.016	0.987
512	0.0448	0.0449	0.0449	0.0454	0.986	0.988

Error scales as $1/\sqrt{n}$. Sixteen times more shots ($32 \to 512$) cut RMS by about four ($0.192 \to 0.045$). Sensitivity sits at 1.01–1.09 in these units. At 512 shots all three estimators are on the bound.

At 32 shots the nets sit about 7% under the unbiased CRB. The Cramér–Rao statement is for unbiased estimators [Helstrom, 1969]. A net trained on MSE shrinks toward the mean of the training disk. That can beat an unbiased bound on squared error without extracting more information than the likelihood contains. The classical inversion stays just above the bound (1.056), which is the shape you want from a correctly derived Fisher matrix.

Nobody here improved the sensor. They used the shots.

7 What is allowed

On a known Ramsey likelihood, a Clifford net is an efficient function class for the inverse, not a better estimator than least squares. When the inverse requires multiplying a scalar readout onto a direction, that product is cheap in $\mathrm{Cl}(2,0)$ and expensive for a small flat MLP. When the inverse requires undoing a world-frame gain and bias, a flat net is the better function class. Under binomial readout, both nets match the Cramér–Rao scaling. Sensitivity is set by n, V, and T, not by the layer type.

The claim that does not survive: that a Clifford network is an upgrade to quantum sensing.

Simulation only. There is no NV-center, fluxgate, or SQUID dataset in the repository. Noise and T_2 are modeled; they are not measured. The sensor is an ideal planar vector magnetometer. An NV-center has fixed crystal axes [Zhang et al., 2024]. Full rotation equivariance does not hold for that device. You would pass the axes in as data, which this model already does, and you would stop claiming the network is equivariant by construction.

The operating point stays inside one fringe. Multiple evolution times, phase wrapping, and adaptive Ramsey are out of scope. Those are the regimes where a learned inverse sometimes earns its keep against a misspecified or multimodal likelihood. They are also the regimes where a classical estimator has to become a proper maximum-likelihood search, not a 2×2 solve.

$\mathrm{Cl}(3,0)$ is not implemented. A 3D Bloch magnetometer on the same easy inverse would reproduce the clean-data tie. It becomes interesting only after the product-removal and shot-noise tests are restated in 3D.

Reproduce with `cargo test`. The four release binaries are `train_magnetometer`, `train_mag_misspec`, `train_mag_efficiency`, and `train_mag_shots`. CSVs land in `results/`.

The next measurement that could still change the story is not "add $\mathrm{Cl}(3,0)$ and rerun the easy inverse." It is a wrapped-fringe, multi-T protocol, or a real vector-magnetometer log, with the same three estimators and the same refusal to call a noise-floor tie a sensing win.

References

Johannes Brandstetter, Rianne van den Berg, Max Welling, and Jayesh K. Gupta. Clifford Neural Layers for PDE Modeling. In *International Conference on Learning Representations*, 2023. arXiv:2209.04934.

C. L. Degen, F. Reinhard, and P. Cappellaro. Quantum sensing. *Reviews of Modern Physics*, 89: 035002, 2017.

Chris Doran and Anthony Lasenby. *Geometric Algebra for Physicists*. Cambridge University Press, 2003.

Carl W. Helstrom. Quantum detection and estimation theory. *Journal of Statistical Physics*, 1: 231–252, 1969.

J. R. Maze, P. L. Stanwix, J. S. Hodges, S. Hong, J. M. Taylor, P. Cappellaro, L. Jiang, M. V. G. Dutt, E. Togan, A. S. Zibrov, A. Yacoby, R. L. Walsworth, and M. D. Lukin. Nanoscale magnetic sensing with an individual electronic spin in diamond. *Nature*, 455:644–647, 2008.

Xin Meng, Youwei Zhang, Xichang Zhang, Shenchao Jin, Tingran Wang, Liang Jiang, Liantuan Xiao, Suotang Jia, and Yanhong Xiao. Machine learning assisted vector atomic magnetometry. *Nature Communications*, 14:6105, 2023. doi: 10.1038/s41467-023-41676-x.

Norman F. Ramsey. A Molecular Beam Resonance Method with Separated Oscillating Fields. *Physical Review*, 78:695–699, 1950.

David Ruhe, Johannes Brandstetter, and Patrick Forré. Clifford Group Equivariant Neural Networks. In *Advances in Neural Information Processing Systems*, volume 36, 2023a.

David Ruhe, Jayesh K. Gupta, Steven de Keninck, Max Welling, and Johannes Brandstetter. Geometric Clifford Algebra Networks. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 29306–29337, 2023b.

J. M. Taylor, P. Cappellaro, L. Childress, L. Jiang, D. Budker, P. R. Hemmer, A. Yacoby, R. L. Walsworth, and M. D. Lukin. High-sensitivity diamond magnetometer with nanoscale resolution. *Nature Physics*, 4:810–816, 2008.

Enrui Zhang, Wenzhe Zhang, Xiaofeng Jiang, and Xi Qin. Deep-neural-network-based magnetic-field acquisition method for quantum sensing with nitrogen-vacancy centers. *Physical Review A*, 110:052417, 2024.