

# *MSR3* – Sparse Relaxed Regularized Regression for Linear Mixed-Effect Models

Aleksei Sholokhov

Together with James V. Burke, Peng Zheng, Damian Santomauro,  
and Aleksandr Aravkin

Friday 2<sup>nd</sup> June, 2023



# Research Objectives and Plan of the Talk

## Objectives:

- ▶ Extend  $\mathcal{SR}3$  relaxation to linear mixed-effects models -  $\mathcal{MSR}3$  (see<sup>1</sup>).
- ▶ Develop theoretical foundations for it (see<sup>2</sup>).
- ▶ Implement it as a scikit-learn-compatible Python package – `pysr3` (see<sup>3</sup>).

## Plan of the Talk:

1. Proximal Gradient Descent (PGD) for Linear Mixed-Effects Models (LMEs)
2.  $\mathcal{MSR}3$  – PGD on  $\mathcal{SR}3$ -relaxation for LMEs
3.  $\mathcal{MSR}3$ -fast – practical algorithm for feature selection

---

<sup>1</sup>Sholokhov, J. V. Burke, et al., A Relaxation Approach to Feature Selection for Linear Mixed Effects Models.


<sup>2</sup>Aravkin et al., Analysis of Relaxation Methods for Feature Selection in Mixed Effects Models.

<sup>3</sup>Sholokhov, Zheng, and Aravkin, "pysr3: A Python Package for Sparse Relaxed Regularized Regression".

## Mixed-Effect Models

Mixed-effect models

- ▶ Used for analyzing **combined data** across a range of **groups**.
  - ▶ **Borrow strength** across groups to estimate key statistics.
  - ▶ Use covariates to separate the **population variability** from the **group variability**.



<sup>4</sup>Picture is taken from covid19.healthdata.org

# Linear Mixed-Effect (LME) Models

Dataset:  $m$  groups  $(X_i, Z_i, y_i)$ ,  $i = 1, \dots, m$ , each has  $n_i$  observations

- ▶  $X_i \in \mathbb{R}^{n_i \times p}$  – group  $i$  design matrix for fixed features
- ▶  $Z_i \in \mathbb{R}^{n_i \times q}$  – group  $i$  design matrix for random features
- ▶  $y_i \in \mathbb{R}^{n_i}$  – group  $i$  observations
- ▶  $u_i \in \mathbb{R}^q$  – random effects
- ▶  $\Gamma \in \mathbb{R}^{q \times q}$  – covariance matrix of random effects, often  $\Gamma = \text{diag}((\gamma))$
- ▶  $\Lambda_i \in \mathbb{R}^{n_i \times n_i}$  – covariance matrix for observation noise


Model:

$$y_i = X_i \beta + Z_i u_i + \varepsilon_i$$

$$\varepsilon_i \sim \mathcal{N}(0, \Lambda_i)$$

$$u_i \sim \mathcal{N}(0, \Gamma)$$

Unknowns:  $\beta$ ,  $u_i$ ,  $\gamma$ , sometimes  $\Lambda_i$ .



# Negative Log-Likelihood for Mixed-Effect Models

Optimization problem:

$$\mathcal{FS} - \mathcal{LME} \quad \min_{\beta \in \mathbb{R}^p, \gamma \in \mathbb{R}_+^q} \mathcal{L}(\beta, \gamma) + R(\beta, \gamma) \quad (1)$$

Where  $\mathcal{L}$ :

$$\begin{aligned} \mathcal{L}(\beta, \gamma) = & \sum_{i=1}^m \frac{1}{2} (y_i - X_i \beta)^T (Z_i \Gamma Z_i^T + \Lambda_i)^{-1} (y_i - X_i \beta) + \\ & + \frac{1}{2} \log \det (Z_i \Gamma Z_i^T + \Lambda_i), \quad \Gamma = \text{diag}((\gamma)) \end{aligned} \quad (2)$$

- ▶  $\mathcal{L}(\beta, \gamma)$  is smooth on its domain, quadratic w.r.t.  $\beta$  and  $\bar{\eta}$ -weakly-convex w.r.t.  $\gamma$ .
- ▶  $R(\beta, \gamma)$  is closed, proper, with easily computed *prox operator*

## Regularization

$R(\beta, \gamma)$  is closed, proper, with easily computed *prox operator*

$$\text{prox}_{\alpha R + \delta_{\mathcal{C}}}(\tilde{\beta}, \tilde{\gamma}) := \underset{(\beta, \gamma) \in \mathcal{C}}{\operatorname{argmin}} R(\beta, \gamma) + \frac{1}{2\alpha} \|(\beta, \gamma) - (\tilde{\beta}, \tilde{\gamma})\|_2^2, \quad (3)$$

where  $\mathcal{C} := \mathbb{R}^p \times \mathbb{R}_+^q$




Figure: Four commonly-used regularizers which promote sparsity

# Proximal Gradient Descent for Feature Selection in MLE

Let

$$x := [\beta, \gamma], \quad \mathcal{C} := \mathbb{R}^p \times R_+^q \quad (4)$$

Optimization problem  $\mathcal{FS} - \mathcal{LME}$ :

$$\min_{x \in \mathcal{C}} \mathcal{L}(x) + R(x) \quad (5)$$

# Proximal Gradient Descent for Feature Selection in MLE

Let

$$x := [\beta, \gamma], \quad \mathcal{C} := \mathbb{R}^p \times R_+^q \quad (4)$$

Optimization problem  $\mathcal{FS} - \mathcal{LME}$ :

$$\min_{x \in \mathcal{C}} \mathcal{L}(x) + R(x) \quad (5)$$

---

---

1 **Algorithm:** PGD for standard LMEs

```
2  $\beta^+ \leftarrow \beta_0, \quad \gamma^+ \leftarrow \gamma_0, \quad \alpha \leftarrow 1/L$  // Initialization
3  $x^+ = [\beta^+, \gamma^+];$ 
4 while making progress do
5    $| \quad x^+ \leftarrow \text{prox}_{\alpha^{-1}R+\delta_{\mathcal{C}}} (x^+ - \alpha \nabla_x \mathcal{L}(x^+))$  // PGD iterations
6 end
7 return  $x^+ = [\beta^+, \gamma^+]$ 
```

---

# Proximal Gradient Descent for Feature Selection in MLE

---

```
1 Algorithm: PGD for standard LMEs
2  $\beta^+ \leftarrow \beta_0, \gamma^+ \leftarrow \gamma_0, \alpha \leftarrow 1/L$                                 // Initialization
3  $x^+ = [\beta^+, \gamma^+];$ 
4 while making progress do
5   |  $x^+ \leftarrow \text{prox}_{\alpha^{-1}R + \delta_C}(x^+ - \alpha \nabla_x \mathcal{L}(x^+))$           // PGD iterations
6 end
7 return  $x^+ = [\beta^+, \gamma^+]$ 
```

---

Basic Assumptions for the PGD Algorithm (Theorem 10.15 from<sup>5</sup>):

1.  $R$  is a closed proper convex function
2.  $\mathcal{L}$  is closed and proper,  $\text{dom } \mathcal{L}$  convex,  $\text{dom } R \subset \text{int}(\text{dom } \mathcal{L})$ , and  $\mathcal{L}$  is  $L$ -smooth over  $\text{int}(\text{dom } \mathcal{L})$ . [x].
3. The problem has an optimal solution<sup>6</sup> with an optimal value  $\mathcal{L}^*$

Algorithm converges with backtracking<sup>7</sup>.

---

<sup>5</sup> Beck, First-Order Methods in Optimization.

<sup>6</sup> Aravkin et al., Analysis of Relaxation Methods for Feature Selection in Mixed Effects Models.

<sup>7</sup> J. Burke and Engle, "Line Search and Trust-Region Methods for Convex-Composite Optimization".

# Proximal Gradient Descent for Feature Selection in MLE

---


1 **Algorithm:** PGD for standard LMEs

```
2  $\beta^+ \leftarrow \beta_0, \gamma^+ \leftarrow \gamma_0, \alpha \leftarrow 1/L$  // Initialization  
3  $x^+ = [\beta^+, \gamma^+];$   
4 while making progress do  
5    $x^+ \leftarrow \text{prox}_{\alpha^{-1}R+\delta_C}(x^+ - \alpha \nabla_x \mathcal{L}(x^+))$  // PGD iterations  
6 end  
7 return  $x^+ = [\beta^+, \gamma^+]$ 
```

---

Synthetic Benchmark:


- ▶ 100 randomly-generated problems.
- ▶  $p = q = 20$ .
- ▶  $\beta = \gamma = \frac{1}{2}[1, 2, 3, \dots, 10, 0, \dots, 0]$
- ▶ 9 groups from 3 to 15 observations
- ▶  $X_i \sim \mathcal{N}(0, I)^p, Z_i = X_i, \varepsilon_i \sim \mathcal{N}(0, 0.3^2 I)$
- ▶ Golden search for  $\lambda \in [0, 10^5]$
- ▶ Final model is chosen to maximize BIC



# Sparse Relaxed Regularized Regression ( $\mathcal{SR}3$ )<sup>5</sup>

Original  $\rightarrow$  Decoupled  $\rightarrow$  Value Function

$$\min_x f(x) + R(x) \quad \rightarrow \quad \min_{x, w} f(x) + \frac{\eta}{2} \|x - w\|_2^2 + R(w) \quad \rightarrow \quad \min_w v_\eta(w) + R(w)$$



<sup>5</sup>Zheng and Aravkin, "Relax-and-split method for nonconvex inverse problems!".

## SR3-Relaxation for Mixed-Effect Models ( $MSR3$ )

Original problem  $\mathcal{FS} - \mathcal{LME}$ :

$$\min_{x \in \mathcal{C}} \mathcal{L}(x) + R(x) \quad (4)$$

## SR3-Relaxation for Mixed-Effect Models ( $MSR3$ )

Original problem  $\mathcal{FS} - \mathcal{LME}$ :

$$\min_{x \in \mathcal{C}} \mathcal{L}(x) + R(x) \quad (4)$$

Decoupled problem:

$$\min_{x, w \in \mathcal{C}} \mathcal{L}(x) + \frac{\eta}{2} \|x - w\|_2^2 + R(w) \quad (5)$$

where  $w = [\tilde{\beta}, \tilde{\gamma}]$ .

## SR3-Relaxation for Mixed-Effect Models ( $MSR3$ )

Original problem  $\mathcal{FS} - \mathcal{LME}$ :

$$\min_{x \in \mathcal{C}} \mathcal{L}(x) + R(x) \quad (4)$$

Decoupled problem:

$$\min_{x, w \in \mathcal{C}} \mathcal{L}(x) + \frac{\eta}{2} \|x - w\|_2^2 + R(w) \quad (5)$$

where  $w = [\tilde{\beta}, \tilde{\gamma}]$ .

By partially minimizing w.r.t.  $x$  we get a value function  $v_\eta(w)$ :

$$v_\eta(w) := \min_{x \in \mathcal{C}} \mathcal{L}(x) + \frac{\eta}{2} \|x - w\|_2^2 \quad (6)$$

so  $\mathcal{SR3}$ -formulation (5) becomes

$$\min_{w \in \mathcal{C}} v_\eta(w) + R(w) \quad (7)$$

## SR3-Relaxation for Mixed-Effect Models ( $MSR3$ )

Original problem  $\mathcal{FS} - \mathcal{LME}$ :

$$\min_{x \in \mathcal{C}} \mathcal{L}(x) + R(x) \quad (4)$$

Decoupled problem:

$$\min_{x, w \in \mathcal{C}} \mathcal{L}(x) + \frac{\eta}{2} \|x - w\|_2^2 + R(w) \quad (5)$$

where  $w = [\tilde{\beta}, \tilde{\gamma}]$ .

By partially minimizing w.r.t.  $x$  we get a value function  $v_\eta(w)$ :

$$v_\eta(w) := \min_{x \in \mathcal{C}} \mathcal{L}(x) + \frac{\eta}{2} \|x - w\|_2^2 \quad (6)$$

so  $\mathcal{SR3}$ -formulation (5) becomes

$$\min_{w \in \mathcal{C}} v_\eta(w) + R(w) \quad (7)$$

**NB:**  $v_\eta(w)$  is smooth on  $\mathcal{C}$  and can be evaluated using Interior Point (IP) method

## Value Function of $\mathcal{MSR}3$

$\mathcal{MSR}3$ -relaxation replaces the original likelihood  $\mathcal{L}$  with a *value function*  $v_{\eta,\mu}$ :





$$v_{\eta,\mu}(w) := \min_{x \in \mathcal{C}} \mathcal{L}(x) + \frac{\eta}{2} \|x - w\|_2^2 + \phi_\mu(x) \quad (8)$$

where *perspective mapping*  $\phi_\mu$  replaces  $\gamma \geq 0$  with a log-barrier

$$\phi_\mu(x) = \phi_\mu(\gamma) := \begin{cases} -\mu \sum_{i=1}^q \ln(\gamma_i/\mu), & \mu > 0 \\ \delta_{\mathbb{R}_+^q}(\gamma), & \mu = 0 \\ +\infty, & \mu < 0 \end{cases} \quad (9)$$

# Value Function of $MSR3$

$$\min_{\beta, \gamma \in C} \mathcal{L}(\beta, \gamma) + R(\beta, \gamma) \quad \text{vs} \quad \min_{\tilde{\beta}, \tilde{\gamma} \in C} v_{\eta, \mu}(\tilde{\beta}, \tilde{\gamma}) + R(\tilde{\beta}, \tilde{\gamma})$$



## $\mathcal{MSR}3$ : Algorithm

---

1 **Algorithm:** PGD for  $\mathcal{MSR}3$

2  $\tilde{\beta}^+ \leftarrow \tilde{\beta}_0, \quad \tilde{\gamma}^+ \leftarrow \tilde{\gamma}_0, \quad \alpha \leftarrow 1/\eta, \quad \eta > \bar{\eta}$  // Initialization

3  $\tilde{w}^+ := [\tilde{\beta}^+, \tilde{\gamma}^+], \quad x^+ := [\beta, \gamma]$

4 **while** making progress in  $\tilde{w}$  **do**

5    $x^+ \leftarrow \text{IP on } \mathcal{L}_{\eta, \mu}(x^+, \tilde{w}^+) \text{ s.t. } x^+ \in \mathcal{C} \text{ and } \mu \rightarrow 0$  // IP Iterations

6    $\nabla_{\tilde{w}} v_{\eta, 0}(\tilde{w}^+) \leftarrow \nabla_{\tilde{w}} \mathcal{L}_{\eta, 0}(x^+, \tilde{w}^+)$  // Evaluate Gradient of VF

7    $\tilde{w}^+ \leftarrow \text{prox}_{\alpha^{-1}R + \delta_C}(\tilde{w}^+ - \alpha \nabla_{\tilde{w}} v_{\eta, 0}(\tilde{w}^+))$  // PGD on Value Function

8 **end**

9 **return**  $\tilde{w}^+ = [\tilde{\beta}^+, \tilde{\gamma}^+]$

---

# $\mathcal{MSR}3$ : Algorithm

---

1 **Algorithm:** PGD for  $\mathcal{MSR}3$

```
2  $\tilde{\beta}^+ \leftarrow \tilde{\beta}_0, \quad \tilde{\gamma}^+ \leftarrow \tilde{\gamma}_0, \quad \alpha \leftarrow 1/\eta, \quad \eta > \bar{\eta}$  // Initialization
3  $\tilde{w}^+ := [\tilde{\beta}^+, \tilde{\gamma}^+], \quad x^+ := [\beta, \gamma]$ 
4 while making progress in  $\tilde{w}$  do
5    $x^+ \leftarrow \text{IP on } \mathcal{L}_{\eta, \mu}(x^+, \tilde{w}^+) \text{ s.t. } x^+ \in \mathcal{C} \text{ and } \mu \rightarrow 0$  // IP Iterations
6    $\nabla_{\tilde{w}} v_{\eta, 0}(\tilde{w}^+) \leftarrow \nabla_{\tilde{w}} \mathcal{L}_{\eta, 0}(x^+, \tilde{w}^+)$  // Evaluate Gradient of VF
7    $\tilde{w}^+ \leftarrow \text{prox}_{\alpha^{-1}R + \delta_{\mathcal{C}}}(\tilde{w}^+ - \alpha \nabla_{\tilde{w}} v_{\eta, 0}(\tilde{w}^+))$  // PGD on Value Function
8 end
9 return  $\tilde{w}^+ = [\tilde{\beta}^+, \tilde{\gamma}^+]$ 
```

---


Theoretical Results<sup>6</sup>:

1. When  $\eta > \bar{\eta}$  the problem has an optimal solution  $\Phi^*$  (**Theorem 5**)
2.  $v_{\eta, \mu}$  is well-defined (**Theorem 5**) and continuously differentiable (**Theorem 10**)
3. When  $R$  is 1-coercive  $\nabla v_{\eta, \mu}$  is locally  $\widetilde{L}$ -continuous (**Theorem 14**)
4. Algorithm converges to a stationary point of  $v_{\eta, \mu}$  (**Theorem 15**)
5. As  $\mu \rightarrow 0$  (**Theorem 6**) or  $\eta \rightarrow \infty$  (**Theorem 7**), cluster points of solutions to  $\mathcal{MSR}3$  are FOSPs for  $\mathcal{FS} - \mathcal{LME}$

---

<sup>6</sup> Aleksandr Aravkin et al. Analysis of Relaxation Methods for Feature Selection in Mixed Effects Models. 2022.  
arXiv: 2209.10575 [stat.ME].

# MSR3: Results



## $\mathcal{MSR}3$ : Algorithm

---

1 **Algorithm:** PGD for  $\mathcal{MSR}3$

2  $\tilde{\beta}^+ \leftarrow \tilde{\beta}_0, \quad \tilde{\gamma}^+ \leftarrow \tilde{\gamma}_0, \quad \alpha \leftarrow 1/\eta, \quad \eta > \bar{\eta}$  // Initialization

3  $\tilde{w}^+ := [\tilde{\beta}^+, \tilde{\gamma}^+], \quad x^+ := [\beta, \gamma]$

4 **while** making progress in  $\tilde{w}$  **do**

5     $x^+ \leftarrow \text{IP on } \mathcal{L}_{\eta, \mu}(x^+, \tilde{w}^+) \text{ s.t. } x^+ \in \mathcal{C} \text{ and } \mu \rightarrow 0$  // IP Iterations

6     $\nabla_{\tilde{w}} v_{\eta, 0}(\tilde{w}^+) \leftarrow \nabla_{\tilde{w}} \mathcal{L}_{\eta, 0}(x^+, \tilde{w}^+)$  // Evaluate Gradient

7     $\tilde{w}^+ \leftarrow \text{prox}_{\alpha^{-1}R + \delta_C}(\tilde{w}^+ - \alpha \nabla_{\tilde{w}} v_{\eta, 0}(\tilde{w}^+))$  // PGD on Value Function

8 **end**

9 **return**  $\tilde{w}^+ = [\tilde{\beta}^+, \tilde{\gamma}^+]$

---

## $\mathcal{MSR}3$ : Algorithm

---

1 **Algorithm:** PGD for  $\mathcal{MSR}3$

```
2  $\tilde{\beta}^+ \leftarrow \tilde{\beta}_0, \quad \tilde{\gamma}^+ \leftarrow \tilde{\gamma}_0, \quad \alpha \leftarrow 1/\eta, \quad \eta > \bar{\eta}$  // Initialization
3  $\tilde{w}^+ := [\tilde{\beta}^+, \tilde{\gamma}^+], \quad x^+ := [\beta, \gamma]$ 
4 while making progress in  $\tilde{w}$  do
5    $x^+ \leftarrow \text{IP on } \mathcal{L}_{\eta, \mu}(x^+, \tilde{w}^+) \text{ s.t. } x^+ \in \mathcal{C} \text{ and } \mu \rightarrow 0$  // IP Iterations
6    $\nabla_{\tilde{w}} v_{\eta, 0}(\tilde{w}^+) \leftarrow \nabla_{\tilde{w}} \mathcal{L}_{\eta, 0}(x^+, \tilde{w}^+)$  // Evaluate Gradient
7    $\tilde{w}^+ \leftarrow \text{prox}_{\alpha^{-1}R + \delta_{\mathcal{C}}}(\tilde{w}^+ - \alpha \nabla_{\tilde{w}} v_{\eta, 0}(\tilde{w}^+))$  // PGD on Value Function
8 end
9 return  $\tilde{w}^+ = [\tilde{\beta}^+, \tilde{\gamma}^+]$ 
```

---

**Key Observation:**  $\nabla_{\tilde{w}} v(\tilde{w})$  does not need to be evaluated exactly. We only need to come close enough to the central path.

## $\mathcal{MSR}3$ -fast: Algorithm

---


1 **Algorithm:**  $\mathcal{MSR}3$ -fast

```
2  $\tilde{\beta}^+ \leftarrow \tilde{\beta}_0, \quad \tilde{\gamma}^+ \leftarrow \tilde{\gamma}_0, \quad \alpha \leftarrow 1/\eta, \quad \eta > \bar{\eta}$  // Initialization
3  $\tilde{w}^+ := [\tilde{\beta}^+, \tilde{\gamma}^+], \quad x^+ := [\beta, \gamma]$ 
4 while making progress do
5   while not close enough to the central path do
6      $x^+ \leftarrow$  IP iteration on  $\mathcal{L}_{\eta, \mu}(x^+, \tilde{w}^+)$  s.t.  $x^+ \in \mathcal{C}$  // IP Iterations
7   end
8   Decrease  $\mu$ 
9    $\nabla_{\tilde{w}} v_{\eta, \mu}(\tilde{w}^+) \leftarrow \nabla_{\tilde{w}} \mathcal{L}_{\eta, \mu}(x^+, \tilde{w}^+)$  // Evaluate Gradient
10   $\tilde{w}^+ \leftarrow \text{prox}_{\alpha^{-1}\mathcal{R} + \delta_{\mathcal{C}}}(\tilde{w}^+ - \alpha \nabla_{\tilde{w}} v_{\eta, \mu}(\tilde{w}^+))$  // PGD on Value Function
11 end
12 return  $\tilde{w}^+ = [\tilde{\beta}^+, \tilde{\gamma}^+]$ 
```

---

## *MSR3-fast: Results*

- The number of fixed effects  $p$  and random effects  $q$  is 20.
- $\beta = \gamma = \frac{1}{2}[1, 2, 3, \dots, 10, 0, \dots, 0]$
- 9 groups with sizes [10, 15, 4, 8, 3, 5, 18, 9, 6]
- $X_i \sim \mathcal{N}(0, I)^p$ ,  $Z_i = X_i$ ,  $\varepsilon_i \sim \mathcal{N}(0, 0.3^2 I)$
- Each experiment is repeated 100 times.
- Grid-search for  $\eta \in [10^{-4}, 10^2]$ , golden search for  $\lambda \in [0, 10^5]$
- Final model is chosen to maximize BIC



- + *MSR3-relaxation improves feature selection performance of the original likelihood.*
- + *MSR3-fast optimization accelerates the compute time by  $\sim 10^2$ .*
- Initialization of  $\eta$  is problem-specific

## Comparison to Other Libraries

Algorithm	MSR3-Fast ( $\ell_1$ )	glmmLasso <sup>78</sup>	lmmLasso <sup>910</sup>	PGD ( $\ell_1$ )
Accuracy, %	<b>88</b>	48	66	73
FE Accuracy, %	<b>86</b>	52	47	56
RE Accuracy, %	<b>91</b>	45	84	<b>91</b>
Time, sec	<b>0.19</b>	1.37	11.51	38.39
Iterations, num	34	50	-	7693


<sup>7</sup><https://rdrr.io/cran/glmmLasso/man/glmmLasso.html>

<sup>8</sup>Groll and Tutz, "Variable selection for generalized linear mixed models by L 1-penalized estimation".


<sup>9</sup><https://rdrr.io/cran/lmmlasso/>

<sup>10</sup>Schelldorfer, Bühlmann, and DE GEER, "Estimation for high-dimensional linear mixed-effects models using L1-penalization".

## Choice of $\eta$



## $\ell_0$ -based Covariate Selection for Bullying Study from GBD



**Figure:** Fixed and random covariate selection for Bullying dataset<sup>11</sup>. The model selected 9 covariates, 7 of which were historically significant, and did not select 4 covariates, 1 of which was historically significant.

<sup>11</sup>Institute for Health Metrics and Evaluation (IHME). Bullying Victimization Relative Risk Bundle GBD 2020. Seattle, United States of America (USA), 2021.

Thank you!

The screenshot shows the PySR3 mobile application's main screen. At the top, there is a blue header bar with the PySR3 logo. Below the header is a search bar containing the placeholder text "Search docs". The main content area has a dark background. It features several sections with white text: "GETTING STARTED" (with "Quickstart", "Installation", "Requirements", and "Usage" listed under it), "Models Overview", "DEVELOPERS" (with "Community Guidelines" and "Modules" listed under it), and a footer section with "PySR3" and "Version 0.1.0" at the bottom.

 / Quickstart with pysr3 [View page source](#)

---

[license](#) [GNU GPLv3](#) [pypi](#) [v0.3.5](#) [build](#) [passing](#) [docs](#) [here](#)  [codecov](#) [92%](#)  [code quality](#)   
[JOSS](#) [10.21105/joss.05155](#)

# Quickstart with `pysr3`

SR3 is a relaxation method designed for accurate feature selection. It currently supports:

- Linear Models (L0, LASSO, A-LASSO, CAD, SCAD)
- Linear Mixed-Effect Models (L0, LASSO, A-LASSO, CAD, SCAD)

## Installation

pysr3 can be installed via

The code is available on GitHub: <https://github.com/aksholokhov/pysr><sup>12</sup>

- ▶ All estimators are fully compatible to scikit-learn library.
  - ▶ Implements SR3 for linear, generalized-linear, and linear mixed-effect models.
  - ▶ Has tutorials, tests, and documentation.

<sup>12</sup> Aleksei Sholokhov, Peng Zheng, and Aleksandr Aravkin. "pyrsr3: A Python Package for Sparse Relaxed Regularized Regression". In: Journal of Open Source Software 8.84 (2023), p.5155.

# Data-Driven Modeling of Physical Systems

---

<sup>13</sup>Wikipedia: Navier-Stokes

<sup>14</sup>tibco.com

<sup>15</sup>COMSOL Simulations

# Data-Driven Modeling of Physical Systems

## First-Principle Models

- ▶ Require extensive knowledge of the phenomenon
- ▶ Require a lot of compute for simulating large-scale phenomena

$$\begin{cases} \rho \frac{\partial \mathbf{u}}{\partial t} + \rho(\mathbf{u} \cdot \nabla) \mathbf{u} - \nabla \cdot \boldsymbol{\sigma}(\mathbf{u}, p) = \mathbf{f} & \text{in } \Omega \times (0, T) \\ \nabla \cdot \mathbf{u} = 0 & \text{in } \Omega \times (0, T) \\ \mathbf{u} = \mathbf{g} & \text{on } \Gamma_D \times (0, T) \\ \boldsymbol{\sigma}(\mathbf{u}, p) \hat{\mathbf{n}} = \mathbf{h} & \text{on } \Gamma_N \times (0, T) \\ \mathbf{u}(0) = \mathbf{u}_0 & \text{in } \Omega \times \{0\} \end{cases}$$

<sup>13</sup>Wikipedia: Navier-Stokes

<sup>14</sup>tibco.com

<sup>15</sup>COMSOL Simulations

# Data-Driven Modeling of Physical Systems


## First-Principle Models

- ▶ Require extensive knowledge of the phenomenon
- ▶ Require a lot of compute for simulating large-scale phenomena

$$\begin{cases} \rho \frac{\partial \mathbf{u}}{\partial t} + \rho(\mathbf{u} \cdot \nabla) \mathbf{u} - \nabla \cdot \boldsymbol{\sigma}(\mathbf{u}, p) = \mathbf{f} & \text{in } \Omega \times (0, T) \\ \nabla \cdot \mathbf{u} = 0 & \text{in } \Omega \times (0, T) \\ \mathbf{u} = \mathbf{g} & \text{on } \Gamma_D \times (0, T) \\ \boldsymbol{\sigma}(\mathbf{u}, p) \hat{\mathbf{n}} = \mathbf{h} & \text{on } \Gamma_N \times (0, T) \\ \mathbf{u}(0) = \mathbf{u}_0 & \text{in } \Omega \times \{0\} \end{cases}$$

## Data-Driven Models

- ▶ Require a lot of data
- ▶ Often struggle to extrapolate



<sup>13</sup>Wikipedia: Navier-Stokes

<sup>14</sup>tibco.com

<sup>15</sup>COMSOL Simulations

# Data-Driven Modeling of Physical Systems


## First-Principle Models

- ▶ Require extensive knowledge of the phenomenon
- ▶ Require a lot of compute for simulating large-scale phenomena

$$\begin{cases} \rho \frac{\partial \mathbf{u}}{\partial t} + \rho (\mathbf{u} \cdot \nabla) \mathbf{u} - \nabla \cdot \boldsymbol{\sigma}(\mathbf{u}, p) = \mathbf{f} & \text{in } \Omega \times (0, T) \\ \nabla \cdot \mathbf{u} = 0 & \text{in } \Omega \times (0, T) \\ \mathbf{u} = \mathbf{g} & \text{on } \Gamma_D \times (0, T) \\ \boldsymbol{\sigma}(\mathbf{u}, p) \hat{\mathbf{n}} = \mathbf{h} & \text{on } \Gamma_N \times (0, T) \\ \mathbf{u}(0) = \mathbf{u}_0 & \text{in } \Omega \times \{0\} \end{cases}$$


## Data-Driven Models

- ▶ Require a lot of data
- ▶ Often struggle to extrapolate



## Hybrid Models

- ▶ Incorporate elements of both approaches
- ▶ Supplement data with knowledge or priors



Pictures sources: <sup>13</sup>, <sup>14</sup>, <sup>15</sup>,

<sup>13</sup>Wikipedia: Navier-Stokes

<sup>14</sup>tibco.com

<sup>15</sup>COMSOL Simulations

# Incorporating Knowledge of Physics into Neural Networks

---

<sup>16</sup>Geiger and Smidt, “e3nn: Euclidean neural networks”.

<sup>17</sup>Finzi et al., “Generalizing convolutional neural networks for equivariance to lie groups on arbitrary continuous data”.

<sup>18</sup>Chidester, Do, and Ma, Rotation Equivariance and Invariance in Convolutional Neural Networks.

<sup>19</sup>Champion et al., “Data-driven discovery of coordinates and governing equations”.


<sup>20</sup>Schmidt and Lipson, “Distilling free-form natural laws from experimental data”.

<sup>21</sup>Raissi, Perdikaris, and Karniadakis, “Physics informed deep learning (part i): Data-driven solutions of nonlinear partial differential equations”.

<sup>22</sup>Rackauckas et al., “Universal differential equations for scientific machine learning”.

# Incorporating Knowledge of Physics into Neural Networks

1. **Symmetry Based:** incorporate symmetries and conservation laws as hard constraints into a network: E3NNs<sup>16</sup>, LieConv<sup>17</sup>, RiCNN<sup>18</sup>



---

<sup>16</sup>Geiger and Smidt, "e3nn: Euclidean neural networks".

<sup>17</sup>Finzi et al., "Generalizing convolutional neural networks for equivariance to lie groups on arbitrary continuous data".

<sup>18</sup>Chidester, Do, and Ma, Rotation Equivariance and Invariance in Convolutional Neural Networks.

<sup>19</sup>Champion et al., "Data-driven discovery of coordinates and governing equations".


<sup>20</sup>Schmidt and Lipson, "Distilling free-form natural laws from experimental data".

<sup>21</sup>Raissi, Perdikaris, and Karniadakis, "Physics informed deep learning (part i): Data-driven solutions of nonlinear partial differential equations".

<sup>22</sup>Rackauckas et al., "Universal differential equations for scientific machine learning".

# Incorporating Knowledge of Physics into Neural Networks

1. **Symmetry Based:** incorporate symmetries and conservation laws as hard constraints into a network: E3NNs<sup>16</sup>, LieConv<sup>17</sup>, RiCNN<sup>18</sup>
2. **Model Discovery Based:** use a library of terms to discover simple equations: SINDy<sup>19</sup>, Genetic Programming<sup>20</sup>



<sup>16</sup>Geiger and Smidt, "e3nn: Euclidean neural networks".

<sup>17</sup>Finzi et al., "Generalizing convolutional neural networks for equivariance to lie groups on arbitrary continuous data".

<sup>18</sup>Chidester, Do, and Ma, Rotation Equivariance and Invariance in Convolutional Neural Networks.

<sup>19</sup>Champion et al., "Data-driven discovery of coordinates and governing equations".


<sup>20</sup>Schmidt and Lipson, "Distilling free-form natural laws from experimental data".

<sup>21</sup>Raissi, Perdikaris, and Karniadakis, "Physics informed deep learning (part i): Data-driven solutions of nonlinear partial differential equations".

<sup>22</sup>Rackauckas et al., "Universal differential equations for scientific machine learning".

# Incorporating Knowledge of Physics into Neural Networks

1. **Symmetry Based:** incorporate symmetries and conservation laws as hard constraints into a network: E3NNs<sup>16</sup>, LieConv<sup>17</sup>, RiCNN<sup>18</sup>
2. **Model Discovery Based:** use a library of terms to discover simple equations: SINDy<sup>19</sup>, Genetic Programming<sup>20</sup>
3. **Equations Based:** incorporate first-principle models to aid training of networks: PINNs<sup>21</sup>, UDEs<sup>22</sup>



<sup>16</sup>Geiger and Smidt, "e3nn: Euclidean neural networks".

<sup>17</sup>Finzi et al., "Generalizing convolutional neural networks for equivariance to lie groups on arbitrary continuous data".

<sup>18</sup>Chidester, Do, and Ma, Rotation Equivariance and Invariance in Convolutional Neural Networks.

<sup>19</sup>Champion et al., "Data-driven discovery of coordinates and governing equations".

<sup>20</sup>Schmidt and Lipson, "Distilling free-form natural laws from experimental data".

<sup>21</sup>Raissi, Perdikaris, and Karniadakis, "Physics informed deep learning (part i): Data-driven solutions of nonlinear partial differential equations".


<sup>22</sup>Rackauckas et al., "Universal differential equations for scientific machine learning".

# Reduced-Order Models (ROMs)

$$x \in \mathbb{R}^n$$

$$\frac{dx}{dt} = f(x)$$

$$x_0$$



## Reduced-Order Models (ROMs)



$$x \in \mathbb{R}^n$$

$$\frac{dx}{dt} = f(x)$$

$$x_T = x_0 + \int_0^T f(x) dt$$

$x_0$

$x_T$




# Reduced-Order Models (ROMs)

$$x \in \mathbb{R}^n$$

$$\frac{dx}{dt} = f(x)$$

$$x_0$$



$$z \in \mathbb{R}^m$$

$$m \ll n$$

$$\varphi(x)$$

Encoder



$$\frac{dz}{dt} = h(z)$$

$$z_T$$


$$\psi(z)$$

Decoder

$$x_T$$



# Reduced-Order Models (ROMs)



# Physics-Informed Loss

Using chain rule:

$$\frac{dz}{dt} = \frac{dz}{dx} \frac{dx}{dt} = \nabla \varphi(x)^T f(x)$$

# Physics-Informed Loss

Using chain rule:

$$\frac{dz}{dt} = \frac{dz}{dx} \frac{dx}{dt} = \nabla \varphi(x)^T f(x) \quad \frac{dz}{dt} = h(\varphi(x))$$

# Physics-Informed Loss

Using chain rule:

$$\frac{dz}{dt} = \frac{dz}{dx} \frac{dx}{dt} = \nabla \varphi(x)^T f(x) \quad \frac{dz}{dt} = h(\varphi(x))$$

$$\mathcal{L}^{physics}(\tilde{x}) = \|\nabla \varphi(\tilde{x})^T f(\tilde{x}) - h(\varphi(\tilde{x}))\|_2^2 + \|\tilde{x} - \psi(\varphi(\tilde{x}))\|_2^2$$

Physics-Informed Loss = Latent Gradient Loss + Collocation Reconstruction Loss

# Physics-Informed Loss

Using chain rule:

$$\frac{dz}{dt} = \frac{dz}{dx} \frac{dx}{dt} = \nabla \varphi(x)^T f(x) \quad \frac{dz}{dt} = h(\varphi(x))$$

$$\mathcal{L}^{physics}(\tilde{x}) = \|\nabla \varphi(\tilde{x})^T f(\tilde{x}) - h(\varphi(\tilde{x}))\|_2^2 + \|\tilde{x} - \psi(\varphi(\tilde{x}))\|_2^2$$


Physics-Informed Loss = Latent Gradient Loss + Collocation Reconstruction Loss

1  $-u_t = u_{xx} + u_{xxxx} + \frac{1}{2}u_x^2 \Rightarrow \dot{x} = f(x)$

$$u(x) = \frac{a}{1 + e^{-k(x-x_0)}} - \frac{a}{1 + e^{-k(x-x_1)}}, \quad x_0 < x_1$$

$$u(x) = \sum_{w=1}^{30} a(w) \sin(2\pi x) + b(w) \cos(2\pi x)$$

$$u(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{\frac{-(x-x_0)^2}{2\sigma^2}}$$



# Physics-Informed Loss

Using chain rule:

$$\frac{dz}{dt} = \frac{dz}{dx} \frac{dx}{dt} = \nabla \varphi(x)^T f(x) \quad \frac{dz}{dt} = h(\varphi(x))$$

$$\mathcal{L}^{physics}(\tilde{x}) = \|\nabla \varphi(\tilde{x})^T f(\tilde{x}) - h(\varphi(\tilde{x}))\|_2^2 + \|\tilde{x} - \psi(\varphi(\tilde{x}))\|_2^2$$




Physics-Informed Loss = Latent Gradient Loss + Collocation Reconstruction Loss

1  $-u_t = u_{xx} + u_{xxxx} + \frac{1}{2}u_x^2 \Rightarrow \dot{x} = f(x)$

$$u(x) = \frac{a}{1 + e^{-k(x-x_0)}} - \frac{a}{1 + e^{-k(x-x_1)}}, \quad x_0 < x_1$$

$$u(x) = \sum_{w=1}^{30} a(w) \sin(2\pi x) + b(w) \cos(2\pi x)$$

$$u(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x-x_0)^2}{2\sigma^2}}$$



# Physics-Informed, Data-Driven, and Hybrid Models

## Results: Extrapolation to Unknown Regions

Duffing Oscillator on a low-dimensional (2D) manifold:

$$\begin{aligned}\frac{dz_1}{dt} &= z_2 \\ \frac{dz_2}{dt} &= z_1 - z_1^3\end{aligned}\tag{10}$$

Projection to a high-dimensional (128) space:

$$x := \mathcal{A}(z) = Az^3, \quad A \in \mathbb{R}^{128 \times 2}, \quad A_{ij} \sim_{i.i.d.} \mathcal{N}(0, 1)\tag{11}$$


## Results: Extrapolation to Unknown Regions

Duffing Oscillator on a low-dimensional (2D) manifold:


$$\begin{aligned}\frac{dz_1}{dt} &= z_2 \\ \frac{dz_2}{dt} &= z_1 - z_1^3\end{aligned}\tag{10}$$

Projection to a high-dimensional (128) space:



$$x := \mathcal{A}(z) = Az^3, \quad A \in \mathbb{R}^{128 \times 2}, \quad A_{ij} \sim_{i.i.d.} \mathcal{N}(0, 1)\tag{11}$$



## Results: Stable Long-Term Predictions



# Results: Stable Long-Term Predictions



## Results: Burgers' Equation

Burgers' Equation:


$$\begin{aligned} u_t + uu_x &= \nu u_{xx} \\ u(-\pi, t) &= u(\pi, t), \quad \forall t \in [0, T] \end{aligned} \tag{12}$$

# Results: Burgers' Equation


Burgers' Equation:

$$u_t + uu_x = \nu u_{xx} \quad (12)$$
$$u(-\pi, t) = u(\pi, t), \quad \forall t \in [0, T]$$


Harmonic: Solution



Bell-Curve: Solution



Bumps: Solution




# Results: Burgers' Equation


Burgers' Equation:

$$\begin{aligned} u_t + uu_x &= \nu u_{xx} \\ u(-\pi, t) &= u(\pi, t), \quad \forall t \in [0, T] \end{aligned} \tag{12}$$






Harmonic: Solution




Bell-Curve: Solution



Bumps: Solution



# Results: Learning From Collocations



## Discussion and Limitations


We showed that:

- ▶ Physics-informed loss improves accuracy and forecasting stability of ROMs
- ▶ Collocations can supplement data to improve model's performance for unseen initial conditions.


Limitations:

- ▶ Optimal choice of collocations is problem-specific
- ▶ Need a lot of collocations
  - ▶ Seems possible to overcome with smarter sampling techniques

# Single-Pixel Imaging




# Single-Pixel Imaging



# Compressive Sensing with Reduced-Order Models

**Offline Step:** Train a Data-Driven Reduced-Order Model




**Online Step:** Reconstruct Complete Observations by Optimizing in Latent Space

$$\begin{aligned} \text{Reconstruction Loss} & \quad \text{Compressive Sensing Loss} & \text{Loss for Prediction in Latent space} \\ \mathcal{L}^{recon.}(z) &= \|y - A\psi(z)\| + \lambda \left\| z - (z_0 + \int_0^T h(z) dz) \right\| \\ \text{Latent-space representation of the trajectory} & \quad \text{"What the data tells us the trajectory should be"} & \text{"What the model thinks the trajectory should be"} \end{aligned}$$


# Results: Burger's Equation

When we capture 32 samples per frame:




# Results: Burger's Equation


When we capture 32 samples per frame:



When we capture 2 samples per frame:




# Results: Burger's Equation




## Results: Kolmogorov Flow


## Results: Kolmogorov Flow





## Results: Interpretation



## Results: Interpretation





## Results: Interpretation




## Results: Kolmogorov Flow


## Results: Interpretation



## Results: Interpretation




## Results: Interpretation




## Results: Kolmogorov Flow


## Results: Interpretation



## Results: Interpretation



## Results: Interpretation



## Results: Kolmogorov Flow

## Results: Gas Monitoring

## Conclusion and Acknowledgments

## Designing an Algorithm

$G_{\nu, \eta}$  encodes both gradient of a Lagrangian (lines 1-2) and the complementarity condition (line 3):

$$G_{\nu, \eta}((\beta, \gamma, \nu), (\tilde{\beta}, \tilde{\gamma})) := \begin{bmatrix} \nabla_\beta \mathcal{L}(\beta, \gamma) + \eta(\beta - \tilde{\beta}) \\ \nabla_\gamma \mathcal{L}(\beta, \gamma) + \eta(\gamma - \tilde{\gamma}) - \nu \\ \nu \odot \gamma - \mu \mathbf{1} \end{bmatrix} \quad (13)$$

We apply Newton method to  $G$  while geometrically decreasing  $\mu$ .

**Lemma:** For every  $(\mu, \eta) \in \mathbb{R}_+ \times \mathbb{R}_{++}$ ,

$$\begin{aligned} (\hat{\beta}, \hat{\gamma}) &= \operatorname{argmin}_{(\beta, \gamma)} \mathcal{L}_{\eta, \mu}((\beta, \gamma), (\tilde{\beta}, \tilde{\gamma})) \\ &\iff \exists \hat{\nu} \in \mathbb{R}_+^q \text{ s.t. } G_{\nu, \eta}((\beta, \gamma, \hat{\nu}), (\tilde{\beta}, \tilde{\gamma})) = 0 \end{aligned} \quad (14)$$

If  $\mu > 0$ , then  $\hat{\nu} = -\nabla \phi_\mu(\hat{\gamma})$ , and if  $\mu = 0$ , then  $\hat{\nu}$  is the unique KKT multiplier associated with the constraint  $0 \leq \gamma$ .

```

1 progress ← True; iter = 0;
2  $\beta^+, \tilde{\beta}^+ \leftarrow \beta_0; \gamma^+, \tilde{\gamma}^+ \leftarrow \gamma_0; v^+ \leftarrow 1 \in \mathbb{R}^q; \mu \leftarrow \frac{v^{+T}\gamma^+}{10q}$ 
3 while iter < max_iter and  $\|G_\mu(\beta^+, \gamma^+, v^+)\| > tol$  and progress
do
4    $\beta \leftarrow \beta^+; \gamma \leftarrow \gamma^+; \tilde{\beta} \leftarrow \tilde{\beta}^+; \tilde{\gamma} \leftarrow \tilde{\gamma}^+$ 
5    $[dv, d\beta, d\gamma] \leftarrow \nabla G_\mu((\beta, \gamma, v), (\tilde{\beta}, \tilde{\gamma}))^{-1} G_\mu((\beta, \gamma, v), (\tilde{\beta}, \tilde{\gamma}))$ 
      $\alpha \leftarrow 0.99 \times \min \left( 1, -\frac{\gamma_i}{d\gamma_i}, \forall i : d\gamma_i < 0 \right)$ 
6    $\beta^+ \leftarrow \beta + \alpha d\beta; \gamma^+ = \gamma + \alpha d\gamma; v^+ \leftarrow v + \alpha dv$ 
7   if  $\|\gamma^+ \odot v^+ - q^{-1} \gamma^{+T} v^+ \mathbf{1}\| > 0.5q^{-1} v^{+T} \gamma^+$  then continue;
8   else
9      $\tilde{\beta}^+ = \text{prox}_{\alpha R}(\beta^+); \tilde{\gamma}^+ = \text{prox}_{\alpha R + \delta_{\mathbb{R}_+}}(\gamma^+); \mu = \frac{1}{10} \frac{v^{+T}\gamma^+}{q}$ 
10  end
11 progress = ( $\|\beta^+ - \beta\| \geq tol$  or  $\|\gamma^+ - \gamma\| \geq tol$  or  $\|\tilde{\beta}^+ - \tilde{\beta}\| \geq tol$  or
     $\|\tilde{\gamma}^+ - \tilde{\gamma}\| \geq tol$ )
12 iter += 1
13 end
14 return  $\tilde{\beta}^+, \tilde{\gamma}^+$ 

```

---

## References I

-  Aravkin, Aleksandr et al. Analysis of Relaxation Methods for Feature Selection in Mixed Effects Models. 2022. arXiv: 2209.10575 [stat.ME].
-  Beck, Amir. First-Order Methods in Optimization. MOS-SIAM Series on Optimization. SIAM, 2017. ISBN: 9781611974980. DOI: 10.1137/1.9781611974997.
-  Burke, J.V. and A. Engle. "Line Search and Trust-Region Methods for Convex-Composite Optimization". In: arXiv:1806.05218 (2018). DOI: <https://doi.org/10.48550/arXiv.1806.05218>.
-  Champion, Kathleen et al. "Data-driven discovery of coordinates and governing equations". In: Proceedings of the National Academy of Sciences 116.45 (2019), pp. 22445–22451.
-  Chidester, Benjamin, Minh N. Do, and Jian Ma. Rotation Equivariance and Invariance in Convolutional Neural Networks. 2018. arXiv: 1805.12301 [stat.ML].
-  Finzi, Marc et al. "Generalizing convolutional neural networks for equivariance to lie groups on arbitrary continuous data". In: 37th International Conference on Machine Learning, ICML 2020 PartF16814 (2020), pp. 3146–3157. arXiv: 2002.12880.
-  Geiger, Mario and Tess Smidt. "e3nn: Euclidean neural networks". In: arXiv preprint arXiv:2207.09453 (2022).
-  Groll, Andreas and Gerhard Tutz. "Variable selection for generalized linear mixed models by L 1-penalized estimation". In: Statistics and Computing 24.2 (2014), pp. 137–154.

## References II

-  Rackauckas, Christopher et al. "Universal differential equations for scientific machine learning". In: [arXiv preprint arXiv:2001.04385](#) (2020).
-  Raissi, Maziar, Paris Perdikaris, and George Em Karniadakis. "Physics informed deep learning (part i): Data-driven solutions of nonlinear partial differential equations". In: [arXiv preprint arXiv:1711.10561](#) (2017).
-  Schelldorfer, Jürg, Peter Bühlmann, and SARA VAN DE GEER. "Estimation for high-dimensional linear mixed-effects models using l1-penalization". In: [Scandinavian Journal of Statistics](#) 38.2 (2011), pp. 197–214.
-  Schmidt, Michael and Hod Lipson. "Distilling free-form natural laws from experimental data". In: [science](#) 324.5923 (2009), pp. 81–85.
-  Sholokhov, Aleksei, James V. Burke, et al.  
A Relaxation Approach to Feature Selection for Linear Mixed Effects Models. [2022. arXiv: 2205.06925 \[stat.ME\]](#).
-  Sholokhov, Aleksei, Peng Zheng, and Aleksandr Aravkin. "pysr3: A Python Package for Sparse Relaxed Regularized Regression". In: [Journal of Open Source Software](#) 8.84 (2023), p. 5155.
-  Zheng, Peng and Aleksandr Aravkin. "Relax-and-split method for nonconvex inverse problems". In: [Inverse Problems](#) 36.9 (2020). ISSN: 13616420. DOI: [10.1088/1361-6420/aba417](https://doi.org/10.1088/1361-6420/aba417).