

# BinaryTree

February 27, 2017

```
In [1]: class TreeNode(object):
    def __init__(self):
        self.data = None
        self.left = None
        self.right = None
    def set_left(self, left_node):
        self.left = left_node
    def get_left(self):
        return self.left
    def get_right(self):
        return self.right
    def set_right(self, right_node):
        self.right = right_node
    def set_data(self, data):
        self.data = data
    def get_data(self):
        return self.data

In [79]: class BST(object):
    def __init__(self):
        self.root = None
    def insert(self, node):
        if node == None:
            print "node passed is None"
        node_data = node.get_data()
        if self.root == None:
            self.root = node
        else:
            curr = self.root
            pred = None
            while curr != None:
                if node_data < curr.get_data():
                    pred = curr
                    curr = curr.get_left()
                elif node_data > curr.get_data():
                    pred = curr
                    curr = curr.get_right()
```

```

        elif node_data == curr.get_data():
            node.set_left(curr.get_left())
            curr.set_left(node)
            return
    assert curr == None
    if pred.get_data() >= node_data:
        pred.set_left(node)
    else:
        pred.set_right(node)

def display_preorder(self, node):
    queue = list()
    queue.append(node)
    while len(queue) > 0:
        curr = queue[0]
        print curr.get_data()
        queue = queue[1:]
        left = curr.get_left()
        if left:
            queue.append(curr.get_left())
        right = curr.get_right()
        if right:
            queue.append(curr.get_right())

def display_postorder(self, node):
    curr = node
    visited = set()
    stack = list()
    # curr gets visited for the first time means curr gets touched
    # if curr has a left NOT in visited, then visit left
    # if curr has right NOT in visited, then visit right
    # if curr has no left and no right, then print curr and add curr to visited
    # unstack and check if left is visited, if left is not visited, then visit left
    while curr != None or len(stack) > 0:
        stack.append(curr)
        left = curr.get_left()
        right = curr.get_right()
        #Base condition: leaf node
        if ((left == None) or left in visited) and ((right == None) or right in visited):
            visited.add(curr)
            print curr.get_data()
            if len(stack) > 1:
                stack.pop()
                curr = stack.pop()
                continue
            else:
                return
        if (left != None) and (left not in visited):

```

```

        curr = left
    if (right != None) and (right not in visited):
        curr = right

def display(self, node):
    curr = node
    if curr != None:
        self.display(curr.left)
        print curr.get_data()
        self.display(curr.right)
def display_non_recursive(self, node):
    stack = list()
    curr = node
    while True:
        while curr != None:
            stack.append(curr)
            curr = curr.get_left()
        if len(stack) == 0:
            return
        curr = stack.pop()
        print curr.get_data()
        curr = curr.get_right()
def display_nr2(self, node):
    stack = list()
    curr = node
    while True:
        while curr != None:
            stack.append(curr)
            curr = curr.get_left()
        if len(stack) == 0:
            return
        curr = stack.pop()
        print curr.get_data()
        curr = curr.get_right()

def get_root(self):
    return self.root

def height(self, root):
    count = 0
    if root == None:
        return count
    elif (root.get_left() != None) and (root.get_right() == None):
        return 1 + self.height(root.get_left())
    elif (root.get_left() == None) and (root.get_right() != None):
        return 1 + self.height(root.get_right())
    else:

```

```

        return 1 + max(self.height(root.get_left()), self.height(root.get_right()))

In [104]: nodes = [2, 1, 3, 7, 2.5]
          #nodes = [1, 0, 2, 12, -3, -14, 14, 23, 21, 22, 2]

In [105]: bst = BST()
          for node_data in nodes:
              node = TreeNode()
              node.set_data(node_data)
              bst.insert(node)

In [106]: bst.display(bst.get_root())

1
2
2.5
3
7

In [107]: bst.display_non_recursive(bst.get_root())

1
2
2.5
3
7

In [108]: bst.display_nr2(bst.get_root())

1
2
2.5
3
7

In [109]: bst.display_preorder(bst.get_root())

2
1
3
2.5
7

In [110]: bst.display_postorder(bst.get_root())

```

```
7  
2.5  
3  
1  
2
```

```
In [111]: bst.height(bst.get_root())
```

```
Out[111]: 3
```