

Code Explanation: calculator.py


Version: v1.0.0 | Date: 2026-02-20 | File: calculator.py

1. Analogy — The Vending Machine

Think of this calculator like a **vending machine**:

- The **menu screen** (`show_menu`) shows what is available.
- You **press a button** (`choice = input(...)`) to pick an operation.
- The machine **asks for your coins** (`get_number`) — and keeps asking if you put in a banana instead of a coin.
- It **dispenses the result** (add or subtract) and displays it.
- Press the **exit button** (`q`) to walk away — or keep using it, the loop runs until you quit.

2. Program Flow Diagram



3. Step-by-Step Code Walkthrough

add(a, b) — Lines 1–2

```
def add(a, b):  
    return a + b
```

The simplest possible function. Takes two numbers, returns their sum. Pure math, no side effects.

subtract(a, b) — Lines 5–6

```
def subtract(a, b):  
    return a - b
```

Same shape as add. Subtracts b from a. Pure and simple.

get_number(prompt) — Lines 9–15

```
def get_number(prompt):  
    while True:  
        user_input = input(prompt).strip()  
        try:  
            return float(user_input)  
        except ValueError:  
            print(' Invalid number. Please try again.')
```

Line	What it does
while True:	Loop forever until a valid number is entered
input(prompt).strip()	Show prompt, read text, remove surrounding whitespace
return float(user_input)	Convert text to decimal; return and exit loop if successful
except ValueError:	Catch conversion failures (e.g., user typed 'abc')
print('Invalid...')	Notify user and loop back to ask again

show_menu() — Lines 18–23

```
def show_menu():  
    print('\n--- Simple Calculator ---')  
    print(' + : Addition')  
    print(' - : Subtraction')  
    print(' q : Quit')  
    print('-----')
```

Pure display code. Prints the menu each loop. The \n adds a blank line for visual breathing room between iterations.

main() — Lines 26–47

```
def main():  
    print('Welcome to the Simple Calculator!')  
  
    while True:  
        show_menu()  
        choice = input('Choose an operation: ').strip()  
  
        if choice == 'q':  
            print('Goodbye!')  
            break
```

```

        elif choice in ('+', '-'):
            a = get_number('Enter first number: ')
            b = get_number('Enter second number: ')

            if choice == '+':
                result = add(a, b)
                print(f' {a} + {b} = {result}')
            else:
                result = subtract(a, b)
                print(f' {a} - {b} = {result}')
        else:
            print(' Invalid option. Please choose +, -, or q.')
    
```

- 1. Greet the user once.
- 2. Enter a while True loop — runs until the user quits.
- 3. Show menu, then read a choice.
- 4a. 'q' → say goodbye, break, program ends.
- 4b. '+' or '-' → ask for two numbers, compute, display.
- 4c. Anything else → tell the user the input was invalid, loop again.

if __name__ == "__main__": — Lines 50–51

```

if __name__ == "__main__": # pragma: no cover
    main()

```

Only runs `main()` when the file is executed directly — not when imported by the test suite. The `# pragma: no cover` tells the coverage tool to skip this line during automated testing.

4. Gotcha — Float Output Surprises

When you enter whole numbers like **1** and **2**, the result prints as **1.0 + 2.0 = 3.0** — not **3**.

Why? Because `get_number` converts all input to float. So '1' becomes 1.0, and `add(1.0, 2.0)` returns 3.0.

To display integers cleanly, you could write:

```

# Display as int if result is a whole number
display = int(result) if result == int(result) else result

```

But this is intentionally left simple — float handles both integers and decimals without two separate code paths. Clarity over cosmetics.

Summary

Function	Role	Key Pattern
add	Pure math	Simple return
subtract	Pure math	Simple return
get_number	Input validation	while True + try/except

show_menu	Display	Side-effect only (print)
main	Orchestrator	while True + branching

The code follows a clean **separation of concerns**: math functions do not do I/O, input functions do not do math, and main() ties everything together.