

# Introduction to Code Generation

Note by Baris Aktemur:

Our slides are adapted from Cooper and Torczon's slides that they prepared for COMP 412 at Rice.

Copyright 2010, Keith D. Cooper & Linda Torczon, all rights reserved.

Students enrolled in Comp 412 at Rice University have explicit permission to make copies of these materials for their personal use.

Faculty from other educational institutions may use these materials for nonprofit educational purposes, provided this copyright notice is preserved.

## Generating Code for Expressions

```
expr(node) {
  int result, t1, t2;
  switch (type(node)) {
    case x, +, -, *:
      t1 ← expr(left child(node));
      t2 ← expr(right child(node));
      result ← NextRegister();
      emit(op(node), t1, t2, result);
      break;
    case IDENTIFIER:
      t1 ← base(node);
      t2 ← offset(node);
      result ← NextRegister();
      emit(loadAO, t1, t2, result);
      break;
    case NUMBER:
      result ← NextRegister();
      emit(loadI, val(node), none, result);
      break;
  }
  return result;
}
```

### The Concept

- Assume an **AST** as input & **ILOC** as output
- Use a **postorder treewalk** evaluator (*visitor pattern* in OOD)
  - Visits & evaluates children
  - Emits code for the op itself
  - Returns register with result
- Bury complexity of addressing names in routines that it calls
  - **base()**, **offset()**, & **val()**
- Works for simple expressions
- Easily extended to other operators
- Does not handle control flow


## Generating Code for Expressions

```

expr(node) {
  int result, t1, t2;
  switch (type(node)) {
    case x, +, -, *:
      t1 ← expr(left child(node));
      t2 ← expr(right child(node));
      result ← NextRegister();
      emit (op(node), t1, t2, result);
      break;
    case IDENTIFIER:
      t1 ← base(node);
      t2 ← offset(node);
      result ← NextRegister();
      emit (loadAO, t1, t2, result);
      break;
    case NUMBER:
      result ← NextRegister();
      emit (loadl, val(node), none, result);
      break;
  }
  return result;
}

```

Example:



Produces:

```

expr("x") →
loadl    @x    ⇒ r1
loadAO   r_arp,r1 ⇒ r2
expr("y") →
loadl    @y    ⇒ r3
loadAO   r_arp,r3 ⇒ r4
NextRegister() → r5
Emit(add,r2,r4,r5) →
add      r2,r4 ⇒ r5

```

Comp 412, Fall 2010

2


## Generating Code for Expressions

```

expr(node) {
  int result, t1, t2;
  switch (type(node)) {
    case x, +, -, *:
      t1 ← expr(left child(node));
      t2 ← expr(right child(node));
      result ← NextRegister();
      emit (op(node), t1, t2, result);
      break;
    case IDENTIFIER:
      t1 ← base(node);
      t2 ← offset(node);
      result ← NextRegister();
      emit (loadAO, t1, t2, result);
      break;
    case NUMBER:
      result ← NextRegister();
      emit (loadl, val(node), none, result);
      break;
  }
  return result;
}

```

Example:



Produces:

```

loadl    @x    ⇒ r1
loadAO   r_arp,r1 ⇒ r2
loadl    2      ⇒ r3
loadl    @y    ⇒ r4
loadAO   r_arp,r4 ⇒ r5
mult     r3,r5  ⇒ r6
sub      R2,r6  ⇒ r7

```

Comp 412, Fall 2010

3

## Extending the Simple Treewalk Algorithm

### Adding other operators

- Evaluate the operands, then perform the operation
- Complex operations may turn into library calls
- Handle assignment as an operator

### Mixed-type expressions

- Insert conversions as needed from conversion table
- Most languages have symmetric & rational conversion tables
  - Original PL/I had asymmetric tables for BCD & binary integers

Typical Table for Addition	+	Integer	Real	Double	Complex
	Integer	Integer	Real	Double	Complex
	Real	Real	Real	Double	Complex
	Double	Double	Double	Double	Complex
	Complex	Complex	Complex	Complex	Complex

Comp 412, Fall 2010

4

## Generating Code in the Parser

### Need to generate an initial IR form

- Chapter 4 talks about ASTs & ILoc
- Might generate an AST, use it for some high-level, near-source work such as type checking and optimization, then traverse it and emit a lower-level IR similar to ILoc for further optimization and code generation

### The Big Picture

- Recursive treewalk performs its work in a bottom-up order
  - Actions on non-leaves occur after actions on children

Comp 412, Fall 2010

5

## Handling Assignment (just another operator)

$lhs \leftarrow rhs$

### Strategy

- Evaluate  $rhs$  to a **value** (an *rvalue*)
- Evaluate  $lhs$  to a **location** (an *lvalue*)
  - $lvalue$  is a register  $\Rightarrow$  move  $rhs$
  - $lvalue$  is an address  $\Rightarrow$  store  $rhs$
- If  $rvalue$  &  $lvalue$  have different types
  - Evaluate  $rvalue$  to its “natural” type
  - Convert that value to the type of  $*lvalue$

Unambiguous scalars go into registers

Ambiguous scalars or aggregates go into memory

Comp 412, Fall 2010

Keeping ambiguous values in memory lets the hardware sort out the addresses.

6

## Handling Assignment

What if the compiler cannot determine the type of the  $rhs$ ?

- Issue is a property of the language & the specific program
- For type-safety, compiler must insert a run-time check
  - Some languages & implementations ignore safety (bad idea)
- Add a *tag* field to the data items to hold type information
  - Explicitly check tags at runtime

Code for assignment becomes more complex

```
evaluate rhs
if type(lhs)  $\neq$  rhs.tag
then
    convert rhs to type(lhs) or
    signal a run-time error
lhs  $\leftarrow$  rhs
```

Choice between conversion & a runtime exception depends on details of language & type system

Much more complex than static checking, plus costs occur at runtime rather than compile time

Comp 412, Fall 2010

7

## Handling Assignment

---

### Compile-time type-checking

- Goal is to eliminate the need for both tags & runtime checks
- Determine, at compile time, the type of each subexpression
- Use runtime check only if compiler cannot determine types

### Optimization strategy

- If compiler knows the type, move the check to compile-time
- Unless tags are needed for garbage collection, eliminate them
- If check is needed, try to overlap it with other computation


*Can design the language so all checks are static*

---

## Object-Oriented Languages

## What is an Object?

*An object is an abstract data type that encapsulates data, operations and internal state behind a simple, consistent interface.*



Comp 412, Fall 2010

10

## OOLs & the Procedure Abstraction

### What is the shape of an OOL's name space?

- Local storage in objects (*both public & private*)
- Storage defined in methods (*they are procedures*)
  - Local values inside a method
  - Static values with lifetimes beyond methods
- Methods shared among multiple objects
- Global name space for global objects and (*some?*) code

In some OOLs, everything is an object.  
In others, variables co-exist with objects & inside objects.

### Classes

- Objects with the same ~~state~~ <sup>members</sup> are grouped into a class
  - Same **code**, same **data**, same **naming environment**
  - Class members are static & shared among instances of the class
- Allows abstraction-oriented naming
- Should foster code reuse in both source & implementation

Comp 412, Fall 2010

11

## Implementing Object-Oriented Languages

So, what can an executing method access?

The fundamental question

- Names defined by the method
  - And its surrounding lexical context
- The receiving object's data members
  - Smalltalk terminology: *instance variables*
- The code & data members of the class that defines it
  - And its context from inheritance
  - Smalltalk terminology: *class variables and methods*
- Any object defined in the global name space

Inheritance adds some twists.

The method might need the address for any of these objects

Comp 412, Fall 2010

12

## Concrete Example: The Java Name Space

Code within a method *M* for object *O* of class *C* can see:

- Local variables declared within *M* (lexical scoping)
- All instance variables & class variables of *C*
- All public and protected variables of any superclass of *C*
- Classes defined in the same package as *C* or in any explicitly imported package
  - public class variables and public instance variables of imported classes
  - package class and instance variables in the package containing *C*
- Class declarations can be nested!
  - These member declarations hide outer class declarations of the same name (lexical scoping)
  - Accessibility: public, private, protected, package

class hierarchy

lexical

Both lexical nesting & class hierarchy at play

Superclass is an ancestor in the inheritance hierarchy

Comp 412, Fall 2010

13

## The Java Name Space

```
Class Point {  
    public int x, y;  
    public void draw();  
}  
Class ColorPoint extends Point {  
    Color c;                // inherits x, y, & draw() from Point  
    public void draw() {...} // local data  
    public void test() { y = x; draw(); } // override (hide) Point's draw  
                                // local code  
}  
Class C {  
    int x, y;                // independent of Point & ColorPoint  
    public void m()          // local data  
    {  
        Point p = new ColorPoint(); // uses ColorPoint, and, by inheritance  
        y = p.x;                // the definitions from Point  
        p.draw();  
    }  
}
```


We will use and  
extend this example

Comp 412, Fall 2010

14

## OOL Symbol Tables

### Conceptually



Search Order: lexical, class, global

Comp 412, Fall 2010

15



## Runtime Structures for OOLs


### Object lifetimes are independent

of method lifetimes,  
of lifetimes of other objects ...

- Each object needs an object record (OR) to hold its state
  - Independent allocation and deallocation
- Classes are objects, too
  - ORs of classes instantiate the class hierarchy

### Object Records

- Static private storage for members
- Need fast, consistent access
  - Known constant offsets from OR pointer
- Provision for initialization



Comp 412, Fall 2010

16

## Object Record Layout

### Assume a Fixed-size OR

- Data members are at known fixed offsets from OR pointer
- Code members occur only in objects of class "class"
  - Code vector is a data-member of the class
  - Method pointers are at known fixed offsets in the code vector
  - Method-local storage kept in method's AR, as in an ALL
- Variable-sized members  $\Rightarrow$  store descriptor to space in heap

### Locating ORs

- For a receiver, the OR pointer is implicit
- For a receiver's class, the receiver's OR has a class pointer
- Top-level classes and static classes can be accessed by name
  - Mangle the class name & use it as a relocatable symbol
  - Handle nested classes as we would nested blocks in an ALL

Comp 412, Fall 2010

17


## What About Inheritance?

### Impact on OR Layout


- OR needs slots for each member declared, all the way up the class hierarchy (class, superclass, super-superclass, ...)
- Can use **prefixing of storage** to lay out the OR

### Back to Our Java Example — Class Point

```
Class Point {  
    public int x, y;  
    ...  
}
```



```
Class ColorPoint extends Point {  
    Color c;  
    ...  
}
```



What happens if we cast a ColorPoint to a Point?

Take the word extends literally.

18

## Open World versus Closed World

Prefixing assumes that the class structure is known when layout is performed. Two common cases occur.

### Closed-World Assumption

(Compile time)

- Class structure is known and closed prior to runtime
- Can lay out ORs in the compiler and/or the linker

### Open-World Assumption

(Interpreter or JIT)

- Class structure can change at runtime
- Cannot lay out ORs until they are allocated
  - Walk class hierarchy at allocation

C++ has a closed class structure.

Java as an open class structure.

Comp 412, Fall 2010

19


## What About Code Members?

How does the language's runtime environment find the code for a given method invocation?

### Closed Class Structure

- Mapping of names to methods is static and known (C++)
  - Fixed offsets & indirect calls
- Virtual functions force runtime resolution

If ColorPoint inherited draw from Point, its code vector would refer to Point's draw.



UL finds draw at offset 0 in ColorPoint's code vector

20