

# **Introduction to Pandas in Python**

Estimated time needed: 15 minutes

# **Objectives**

After completing this lab you will be able to:

· Use Pandas to access and view data

## Table of Contents

- About the Dataset (https://https://data/?
  - utm\_medium=Exinfluencer&utm\_source=Exinfluencer&utm\_content=000026UJ&utm\_term=10006555&utm\_ic SkillsNetwork-Channel-
  - SkillsNetworkCoursesIBMDeveloperSkillsNetworkPY0101ENSkillsNetwork19487395-2021-01-01set/? utm\_medium=Exinfluencer&utm\_source=Exinfluencer&utm\_content=000026UJ&utm\_term=10006555&utm\_ic SkillsNetwork-Channel-
  - SkillsNetworkCoursesIBMDeveloperSkillsNetworkPY0101ENSkillsNetwork19487395-2021-01-01)
- Introduction of Pandas (https://pandas/?
  - utm\_medium=Exinfluencer&utm\_source=Exinfluencer&utm\_content=000026UJ&utm\_term=10006555&utm\_ic SkillsNetwork-Channel-
  - SkillsNetworkCoursesIBMDeveloperSkillsNetworkPY0101ENSkillsNetwork19487395-2021-01-01)
- Viewing Data and Accessing Data (data)
- Quiz on DataFrame (https://quiz/?
- utm\_medium=Exinfluencer&utm\_source=Exinfluencer&utm\_content=000026UJ&utm\_term=10006555&utm\_ic SkillsNetwork-Channel-
  - SkillsNetworkCoursesIBMDeveloperSkillsNetworkPY0101ENSkillsNetwork19487395-2021-01-01)

## **About the Dataset**

The table has one row for each album and several columns.

- artist: Name of the artist
- album: Name of the album
- released\_year: Year the album was released
- length\_min\_sec: Length of the album (hours,minutes,seconds)
- genre: Genre of the album
- music\_recording\_sales\_millions: Music recording sales (millions in USD) on [SONG://DATABASE] (http://www.song-database.com/?

utm\_medium=Exinfluencer&utm\_source=Exinfluencer&utm\_content=000026UJ&utm\_term=10006555&utm\_id=I SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkPY0101ENSkillsNetwork19487395-2021-01-01?

utm\_medium=Exinfluencer&utm\_source=Exinfluencer&utm\_content=000026UJ&utm\_term=10006555&utm\_id=l SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkPY0101ENSkillsNetwork19487395-2021-01-01)

- claimed\_sales\_millions: Album's claimed sales (millions in USD) on [SONG://DATABASE] (http://www.songdatabase.com/)
- date\_released: Date on which the album was released
- soundtrack: Indicates if the album is the movie soundtrack (Y) or (N)
- rating\_of\_friends: Indicates the rating from your friends from 1 to 10

You can see the dataset here:

Artist	Album	Released	Length	Genre	Music recording sales (millions)	Claimed sales (millions)	Released	Soundtrack	Rating (friends)	
Michael Jackson	Thriller	1982	00:42:19	Pop, rock, R&B	46	65	30-Nov- 82		10.0	
AC/DC	Back in Black	1980	00:42:11	Hard rock	26.1	50	25-Jul-80		8.5	
Pink Floyd	The Dark Side of the Moon	1973	00:42:49	Progressive rock	24.2	45	01-Mar- 73		9.5	
Whitney Houston	The Bodyguard	1992	00:57:44	Soundtrack/R&B, soul, pop	26.1	50	25-Jul-80	Υ	7.0	
Meat Loaf	Bat Out of Hell	1977	00:46:33	Hard rock, progressive rock	20.6	43	21-Oct- 77		7.0	
Eagles	Their Greatest Hits (1971- 1975)	1976	00:43:08	Rock, soft rock, folk rock	32.2	42	17-Feb- 76		9.5	
Bee Gees	Saturday Night Fever	1977	1:15:54	Disco	20.6	40	15-Nov- 77	Υ	9.0	

## **Introduction of Pandas**

```
In [1]:
```

```
# Dependency needed to install file
!pip install xlrd
```

Requirement already satisfied: xlrd in /opt/conda/envs/Python-3.8-main/lib/pyth on3.8/site-packages (2.0.1)

#### In [2]:

```
# Import required library
import pandas as pd
```

After the import command, we now have access to a large number of pre-built classes and functions. This assumes the library is installed; in our lab environment all the necessary libraries are installed. One way pandas allows you to work with data is a dataframe. Let's go through the process to go from a comma separated values (.csv) file to a dataframe. This variable csv\_path stores the path of the .csv, that is used as an argument to the read\_csv function. The result is stored in the object df, this is a common short form used for a variable referring to a Pandas dataframe.

#### In [34]:

```
# Read data from CSV file
csv path = 'https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBMDeveloperSki
df = pd.read_csv(csv_path)
```

We can use the method head() to examine the first five rows of a dataframe:

## In [4]:

# Print first five rows of the dataframe

df.head()

Out[4]:

	Artist	Album	Released	Length	Genre	Music Recording Sales (millions)	Claimed Sales (millions)	Released.1	Soundtrac
0	Michael Jackson	Thriller	1982	0:42:19	pop, rock, R&B	46.0	65	30-Nov-82	Nal
1	AC/DC	Back in Black	1980	0:42:11	hard rock	26.1	50	25-Jul-80	Nal
2	Pink Floyd	The Dark Side of the Moon	1973	0:42:49	progressive rock	24.2	45	01-Mar-73	Nal
3	Whitney Houston	The Bodyguard	1992	0:57:44	R&B, soul, pop	27.4	44	17-Nov-92	,
4	Meat Loaf	Bat Out of Hell	1977	0:46:33	hard rock, progressive rock	20.6	43	21-Oct-77	Nal

We use the path of the excel file and the function read\_excel . The result is a data frame as before:

### In [35]:

# Read data from Excel File and print the first five rows

xlsx\_path = 'https://s3-api.us-geo.objectstorage.softlayer.net/cf-courses-data/CognitiveClass/

df = pd.read\_excel(xlsx\_path) df.head()

### Out[35]:

	Artist	Album	Released	Length	Genre	Music Recording Sales (millions)	Claimed Sales (millions)	Released.1	Soundtra
0	Michael Jackson	Thriller	1982	00:42:19	pop, rock, R&B	46.0	65	1982-11-30	Na
1	AC/DC	Back in Black	1980	00:42:11	hard rock	26.1	50	1980-07-25	Na
2	Pink Floyd	The Dark Side of the Moon	1973	00:42:49	progressive rock	24.2	45	1973-03-01	Na
3	Whitney Houston	The Bodyguard	1992	00:57:44	R&B, soul, pop	27.4	44	1992-11-17	
4	Meat Loaf	Bat Out of Hell	1977	00:46:33	hard rock, progressive rock	20.6	43	1977-10-21	Nŧ

We can access the column **Length** and assign it a new dataframe **x**:

```
In [6]:
```

```
# Access to the column Length
x = df[['Length']]
```

### Out[6]:

#### Length

- 00:42:19
- 00:42:11
- 00:42:49
- 00:57:44
- 00:46:33
- 00:43:08
- 01:15:54
- 7 00:40:01

The process is shown in the figure:

# x=df[ ['Length'] ]

	Artist	Album	Released	Length	ienre	Music Recording Sales (millions)	Claimed Sales (millions)	Released.1	Soundtrack	Rating
0	Michael Jackson	Thriller	1982	0:42:19	op, rock, R&B	46.0	65	30-Nov-82	NaN	10.0
1	AC/DC	Back in Black	1980	0:42:11	ard rock	26.1	50	25-Jul-80	NaN	9.5
2	Pink Floyd	The Dark Side of the Moon	1973	0:42:49	rogressive rock	24.2	45	01-Mar-73	NaN	9.0
3	Whitney Houston	The Bodyguard	1992	0:57:44	l&B, soul, pop	27.4	44	17-Nov-92	Y	8.5
4	Meat Loaf	Bat Out of Hell	1977	0:46:33	ard rock, rogressive rock	20.6	43	21-Oct-77	NaN	8.0
5	Eagles	Their Greatest Hits (1971-1975)	1976	0:43:08	ock, soft rock, olk rock	32.2	42	17-Feb-76	NaN	7.5
6	Bee Gees	Saturday Night Fever	1977	1:15:54	isco	20.6	40	15-Nov-77	Υ	7.0
7	Fleetwood Mac	Rumours	1977	0:40:01	oft rock	27.9	40	04-Feb-77	NaN	6.5

		Length
	0	0:42:19
	1	0:42:11
	2	0:42:49
•	3	0:57:44
	4	0:46:33
	5	0:43:08
	6	1:15:54
	7	0:40:01

Χ

# **Viewing Data and Accessing Data**

You can also get a column as a series. You can think of a Pandas series as a 1-D dataframe. Just use one bracket:

```
In [7]:
# Get the column as a series
x = df['Length']
Out[7]:
0
     00:42:19
1
     00:42:11
2
     00:42:49
3
     00:57:44
4
     00:46:33
5
     00:43:08
6
     01:15:54
7
     00:40:01
Name: Length, dtype: object
```

You can also get a column as a dataframe. For example, we can assign the column Artist:

### In [8]:

```
# Get the column as a dataframe
x = df[['Artist']]
type(x)
```

### Out[8]:

pandas.core.frame.DataFrame

You can do the same thing for multiple columns; we just put the dataframe name, in this case, df, and the name of the multiple column headers enclosed in double brackets. The result is a new dataframe comprised of the specified columns:

```
In [9]:
```

```
# Access to multiple columns
y = df[['Artist','Length','Genre']]
```

### Out[9]:

	Artist	Length	Genre
0	Michael Jackson	00:42:19	pop, rock, R&B
1	AC/DC	00:42:11	hard rock
2	Pink Floyd	00:42:49	progressive rock
3	Whitney Houston	00:57:44	R&B, soul, pop
4	Meat Loaf	00:46:33	hard rock, progressive rock
5	Eagles	00:43:08	rock, soft rock, folk rock
6	Bee Gees	01:15:54	disco
7	Fleetwood Mac	00:40:01	soft rock

The process is shown in the figure:

# y=df[['Artist','Length','Genre']]

Artist	llbum	Release	Length	Genre	Music Recording Sales (millions)	Claimed Sales (millions)	Released.1	Soundtrack	Rating
Michael Jackson	hriller	1982	0:42:19	pop, rock, R&B	46.0	65	30-Nov-82	NaN	10.0
AC/DC	ack in Black	1980	0:42:11	hard rock	26.1	50	25-Jul-80	NaN	9.5
Pink Floyd	he Dark Side of the loon	1973	0:42:49	progressive rock	24.2	45	01-Mar-73	NaN	9.0
Whitney Houston	he Bodyguard	1992	0:57:44	R&B, soul, pop	27.4	44	17-Nov-92	Y	8.5
Meat Loaf	Bat Out of Hell	1977	0:46:33	hard rock, progressive rock	20.6	43	21-Oct-77	NaN	8.0
Eagles	heir Greatest Hits 1971-1975)	1976	0:43:08	rock, soft rock, folk rock	32.2	42	17-Feb-76	NaN	7.5
Bee Gees	aturday Night Fever	1977	1:15:54	disco	20.6	40	15-Nov-77	Υ	7.0
, Fleetwood Mac	Rumours	1977	0:40:01	soft rock	27.9	40	04-Feb-77	NaN	6.5



_			
	Artist	Length	Genre
0	Michael Jackson	0:42:19	pop, rock, R&B
1	AC/DC	0:42:11	hard rock
2	Pink Floyd	0:42:49	progressive rock
3	Whitney Houston	0:57:44	R&B, soul, pop
4	Meat Loaf	0:46:33	hard rock, progressive rock
5	Eagles	0:43:08	rock, soft rock, folk rock
6	Bee Gees	1:15:54	disco
7	Fleetwood Mac	0:40:01	soft rock

One way to access unique elements is the iloc method, where you can access the 1st row and the 1st column as follows:

### In [10]:

```
# Access the value on the first row and the first column
df.iloc[0, 0]
```

### Out[10]:

'Michael Jackson'

You can access the 2nd row and the 1st column as follows: In [11]: # Access the value on the second row and the first column df.iloc[1,0] Out[11]: 'AC/DC' You can access the 1st row and the 3rd column as follows: In [12]: # Access the value on the first row and the third column df.iloc[0,2] Out[12]: 1982 In [13]: # Access the value on the second row and the third column df.iloc[1,2] Out[13]: 1980 In [ ]:

This is shown in the following image

# df.iloc[0,0]:'Michael Jackson' df.iloc[0,2]:1982

# df.iloc[1,0]: 'AC/DC'

## df.iloc[1,2]:1980

	Artist	Album	Released	Length	Genre	Music recording sales (millions)	Claimed sales (millions)	Released	Soundtrack	Rating (friends)
0	Michael Jackson	Thriller	1982	00:42:19	Pop, rock, R&B	46	65	30-Nov-82		10.0
1	AC/DC	Back in Black	1980	00:42:11	Hard rock	26.1	50	25-Jul-80		8.5
2	Pink Floyd	The Dark Side of the Moon	1973	00:42:49	Progressive rock	24.2	45	01-Mar-73		9.5
3	Whitney Houston	The Bodyguard	1992	00:57:44	Soundtrack/R&B, soul, pop	26.1	50	25-Jul-80	Υ	7.0
4	Meat Loaf	Bat Out of Hell	1977	00:46:33	Hard rock, progressive rock	20.6	43	21-Oct-77		7.0
5	Eagles	Their Greatest Hits (1971- 1975)	1976	00:43:08	Rock, soft rock, folk rock	32.2	42	17-Feb-76		9.5
6	Bee Gees	Saturday Night Fever	1977	1:15:54	Disco	20.6	40	15-Nov-77	Υ	9.0
7	Fleetwood Mac	Rumours	1977	00:40:01	Soft rock	27.9	40	04-Feb-77		9.5

You can access the column using the name as well, the following are the same as above:

```
In [14]:
```

```
# Access the column using the name
df.loc[1, 'Artist']
Out[14]:
'AC/DC'
In [15]:
# Access the column using the name
df.loc[1, 'Artist']
Out[15]:
'AC/DC'
In [17]:
# Access the column using the name
df.loc[0, 'Released']
Out[17]:
1982
```

### In [16]:

# Access the column using the name

df.loc[1, 'Released']

Out[16]:

1980

df.loc[0, 'Artist']:'Michael Jackson' df.loc[0, 'Released']:1982 df.loc[1, 'Artist']:'AC/DC' df.loc[1, 'Released']:1980

	Artist	Album	Released	Length	Genre	Music Recording Sales (millions)	Claimed Sales (millions)	Released.1	Soundtrack	Rating
0	Michael Jackson	Thriller	1982	0:42:19	pop, rock, R&B	46.0	65	30-Nov-82	NaN	10.0
1	AC/DC	Back in Black	1980	0:42:11	hard rock	26.1	50	25-Jul-80	NaN	9.5
2	Pink Floyd	The Dark Side of the Moon	1973	0:42:49	progressive rock	24.2	45	01-Mar-73	NaN	9.0
3	Whitney Houston	The Bodyguard	1992	0:57:44	R&B, soul, pop	27.4	44	17-Nov-92	Υ	8.5
4	Meat Loaf	Bat Out of Hell	1977	0:46:33	hard rock, progressive rock	20.6	43	21-Oct-77	NaN	8.0
5	Eagles	Their Greatest Hits (1971-1975)	1976	0:43:08	rock, soft rock, folk rock	32.2	42	17-Feb-76	NaN	7.5
6	Bee Gees	Saturday Night Fever	1977	1:15:54	disco	20.6	40	15-Nov-77	Υ	7.0
7	Fleetwood Mac	Rumours	1977	0:40:01	soft rock	27.9	40	04-Feb-77	NaN	6.5

You can perform slicing using both the index and the name of the column:

### In [18]:

# Slicing the dataframe

df.iloc[0:2, 0:3]

### Out[18]:

	Artist	Album	Released
0	Michael Jackson	Thriller	1982
1	AC/DC	Back in Black	1980

# z=df.iloc[0:2, 0:3]

	Artist	Album	Released	Length	Genre	Music Recording Sales (millions)	Claimed Sales (millions)	Released.1	Soundtrack	Rating
c	Michael Jackson	Thriller	1982	0:42:19	pop, rock, R&B	46.0	65	30-Nov-82	NaN	10.0
1	AC/DC	Back in Black	1980	0:42:11	hard rock	26.1	50	25-Jul-80	NaN	9.5
2	Pink Floyd	The Dark Side of the Moon	1973	0:42:49	progressive rock	24.2	45	01-Mar-73	NaN	9.0
3	Whitney Houston	The Bodyguard	1992	0:57:44	R&B, soul, pop	27.4	44	17-Nov-92	Y	8.5
4	Meat Loaf	Bat Out of Hell	1977	0:46:33	hard rock, progressive rock	20.6	43	21-Oct-77	NaN	8.0
5	Eagles	Their Greatest Hits (1971-1975)	1976	0:43:08	rock, soft rock, folk rock	32.2	42	17-Feb-76	NaN	7.5
E	Bee Gees	Saturday Night Fever	1977	1:15:54	disco	20.6	40	15-Nov-77	Y	7.0
7	Fleetwood Mac	Rumours	1977	0:40:01	soft rock	27.9	40	04-Feb-77	NaN	6.5



	Artist	Album	Released
0	Michael Jackson	Thriller	1982
1	AC/DC	Back in Black	1980

## In [19]:

# Slicing the dataframe using name

df.loc[0:2, 'Artist':'Released']

## Out[19]:

	Artist	Album	Released
0	Michael Jackson	Thriller	1982
1	AC/DC	Back in Black	1980
2	Pink Floyd	The Dark Side of the Moon	1973

	Artist	Album	Released	Length	Genre	Music Recording Sales (millions)	Claimed Sales (millions)	Released.1	Soundtrack	Rating
0	Michael Jackson	Thriller	1982	0:42:19	pop, rock, R&B	46.0	65	30-Nov-82	NaN	10.0
1	AC/DC	Back in Black	1980	0:42:11	hard rock	26.1	50	25-Jul-80	NaN	9.5
2	Pink Floyd	The Dark Side of the Moon	1973	0:42:49	progressive rock	24.2	45	01-Mar-73	NaN	9.0
3	Whitney Houston	The Bodyguard	1992	0:57:44	R&B, soul, pop	27.4	44	17-Nov-92	Y	8.5
4	Meat Loaf	Bat Out of Hell	1977	0:46:33	hard rock, progressive rock	20.6	43	21-Oct-77	NaN	8.0
5	Eagles	Their Greatest Hits (1971-1975)	1976	0:43:08	rock, soft rock, folk rock	32.2	42	17-Feb-76	NaN	7.5
6	Bee Gees	Saturday Night Fever	1977	1:15:54	disco	20.6	40	15-Nov-77	Υ	7.0
7	Fleetwood Mac	Rumours	1977	0:40:01	soft rock	27.9	40	04-Feb-77	NaN	6.5



		Artist	Album	Released	
	0	Michael Jackson	Thriller	1982	
	1	AC/DC	Back in Black	1980	
	2	Pink Floyd	The Dark Side of the Moon	1973	

# **Quiz on DataFrame**

Use a variable q to store the column Rating as a dataframe

```
In [20]:
# Write your code below and press Shift+Enter to execute
q = df[['Rating']]
```

### Out[20]:

	Rating
0	10.0
1	9.5
2	9.0
3	8.5
4	8.0
5	7.5
6	7.0
7	6.5

Click here for the solution

```
q = df[['Rating']]
q
```

Assign the variable q to the dataframe that is made up of the column **Released** and **Artist**:

```
In [21]:
```

```
# Write your code below and press Shift+Enter to execute
q = df[['Released', 'Artist']]
```

### Out[21]:

Artist	Released	
Michael Jackson	1982	0
AC/DC	1980	1
Pink Floyd	1973	2
Whitney Houston	1992	3
Meat Loaf	1977	4
Eagles	1976	5
Bee Gees	1977	6
Fleetwood Mac	1977	7

Click here for the solution

```
q = df[['Released', 'Artist']]
q
```

Access the 2nd row and the 3rd column of df:

### In [22]:

```
# Write your code below and press Shift+Enter to execute
df.iloc[1,2]
```

### Out[22]:

1980

Click here for the solution

```
df.iloc[1, 2]
```

Use the following list to convert the dataframe index df to characters and assign it to df\_new; find the element corresponding to the row index  $\,$  a and column 'Artist'  $\,$ . Then select the rows  $\,$  a  $\,$  through  $\,$  d  $\,$  for the column 'Artist'

```
In [38]:
new index=['a','b','c','d','e','f','g','h']
df new = df
df new.index = new index
df_new.loc['a', 'Artist']
df new.loc['a':'d', 'Artist']
Out[38]:
     Michael Jackson
                AC/DC
b
          Pink Floyd
c
d
     Whitney Houston
Name: Artist, dtype: object
Click here for the solution
    df new=df
    df_new.index=new_index
    df_new.loc['a', 'Artist']
    df_new.loc['a':'d', 'Artist']
```

### The last exercise!

Congratulations, you have completed your first lesson and hands-on lab in Python. However, there is one more thing you need to do. The Data Science community encourages sharing work. The best way to share and showcase your work is to share it on GitHub. By sharing your notebook on GitHub you are not only building your reputation with fellow data scientists, but you can also show it off when applying for a job. Even though this was your first piece of work, it is never too early to start building good habits. So, please read and follow this article (https://cognitiveclass.ai/blog/data-scientists-stand-out-by-sharing-your-notebooks/? utm\_medium=Exinfluencer&utm\_source=Exinfluencer&utm\_content=000026UJ&utm\_term=10006555&utm\_id=NA-SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkPY0101ENSkillsNetwork19487395-2021-01-01) to learn how to share your work.

# **Authors:**

Joseph Santarcangelo (https://www.linkedin.com/in/joseph-s-50398b136/? utm\_medium=Exinfluencer&utm\_source=Exinfluencer&utm\_content=000026UJ&utm\_term=10006555&utm\_id=NA-SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkPY0101ENSkillsNetwork19487395-2021-01-01)

Joseph Santarcangelo has a PhD in Electrical Engineering, his research focused on using machine learning, signal processing, and computer vision to determine how videos impact human cognition. Joseph has been working for IBM since he completed his PhD.

# **Change Log**

Date (YYYY-MM-DD)	Version	Changed By	Change Description
2020-08-26	2.0	Lavanya	Moved lab to course repo in GitLab
2020-11-24	3.0	Nayef	Added new images

© IBM Corporation 2020. All rights reserved.