ICPC Notebook

template
hash.sh 1
settings.sh 1
template.hpp 1
data-structure
BIT.hpp 2
FastSet.hpp 2
math
BinaryGCD.hpp 2
ExtGCD.hpp 2
modint
BarrettReduction.hpp 2
modint.hpp 2
FPS
FFT.hpp 3
FFT_fast.hpp 3
graph
graph/tree
flow
燃やす埋める.md 3
string
KMP.hpp 3
Manacher.hpp 3
RollingHash.hpp 4
SuffixArray.hpp 4
Zalgorithm.hpp 4
algorithm
geometry
memo
Primes.md 4

template

hash.sh

```
# 使い方: sh hash.sh -> コピペ -> Ctrl + D
# コメント・空白・改行を削除して md5 でハッシュする
g++ -dD -E -P -fpreprocessed - | tr -d '[:space:]' | md5sum |
cut -c-6
```

settings.sh

```
# CLion の設定
Settings → Build → CMake → Reload CMake Project
add_compile_options(-D_GLIBCXX_DEBUG)
# Caps Lock を Ctrl に変更
setxkbmap -option ctrl:nocaps
```

template.hpp

md5: d016e8

```cpp
#include <iostream>   // cout, endl, cin
#include <string>     // string, to_string, stoi
#include <vector>     // vector
#include <algorithm>  // min, max, swap, sort, reverse,
lower_bound, upper_bound
#include <utility>    // pair, make_pair
#include <tuple>      // tuple, make_tuple
#include <cstdint>    // int64_t, int*_t
#include <cstdio>     // printf
#include <map>        // map
#include <queue>      // queue, priority_queue
#include <set>        // set
#include <stack>      // stack
#include <deque>  // deque #include <unordered_map> //
unordered_map #include <unordered_set> // unordered_set
#include <bitset> // bitset
#include <cctype>  // isupper, islower, isdigit, toupper,
tolower
#include <math.h>
#include <iomanip>
#include <functional>
#include <unordered_map>
#include <random>
#include <bitset>
#include <cassert>
#include <chrono>
// #include <bits/stdc++.h>
using namespace std;
#define rep(i, n) for(int i = 0; i < (int)(n); i++)
#define repi(i, a, b) for(int i = (int)(a); i < (int)(b); i++)
// #define endl '\n'
#define all(x) (x).begin(), (x).end()
#define arr(x) (x).rbegin(), (x).rend()
typedef long long ll;
typedef unsigned long long ull;
const ll inf = 4e18;
using vi = vector<int>;
using P = pair<ll, ll>;
using vvi = vector<vi>;
using vll = vector<ll>;
using vvll = vector<vll>;
using vp = vector<P>;

int vx[] = {0, 1, 0, -1, -1, 1, 1, -1}, vy[] = {1, 0, -1, 0, 1,
1, -1, -1};
void solve(int test) {}
// cat cf.cpp | pbcopy
// g++ cf.cpp -std=c++17 -I .
int main() {
   cin.tie(0);
   ios::sync_with_stdio(false);
   int t = 1;  // cin >>t;
   rep(test, t) solve(test);
}
```

data-structure

BIT.hpp

md5: 8133c8

```cpp
struct BIT {
   vector<ll> a;
   BIT(ll n) : a(n + 1) {}
   void add(ll i, ll x) {  // A[i] += x
      i++;
      while(i < sz(a)) {
         a[i] += x;
         i += i & -i;
      }
   }
   ll sum(ll r) {
      ll s = 0;
      while(r) {
         s += a[r];
         r -= r & -r;
      }
      return s;
   }
   ll sum(ll l, ll r) {  // sum of A[l, r)
      return sum(r) - sum(l);
   }
};
```

FastSet.hpp

md5: 2cb8c9

```cpp
// using u64 = uint64_t;
const u64 B = 64;
struct FastSet {
   u64 n;
   vector<vector<u64>> a;
   FastSet(u64 n_) : n(n_) {
      do a.emplace_back(n_ = (n_ + B - 1) / B);
      while(n_ > 1);
   }
   // bool operator[](ll i) const { return a[0][i / B] >> (i %
B) & 1; }
   void set(ll i) {
      for(auto& v : a) {
         v[i / B] |= 1ULL << (i % B);
         i /= B;
      }
   }
   void reset(ll i) {
      for(auto& v : a) {
         v[i / B] &= ~(1ULL << (i % B));
         if(v[i / B]) break;
         i /= B;
      }
   }
   ll next(ll i) {  // i を超える最小の要素
      rep(h, 0, sz(a)) {
         i++;
         if(i / B >= sz(a[h])) break;
         u64 d = a[h][i / B] >> (i % B);
         if(d) {
            i += countr_zero(d);
            while(h--) i = i * B + countr_zero(a[h][i]);
            return i;
         }
         i /= B;
      }
      return n;
   }
   ll prev(ll i) {  // i より小さい最大の要素
      rep(h, 0, sz(a)) {
         i--;
         if(i < 0) break;
         u64 d = a[h][i / B] << (~i % B);
         if(d) {
            i -= countl_zero(d);
            while(h--) i = i * B + __lg(a[h][i]);
            return i;
         }
         i /= B;
      }
      return -1;
   }
};
```

math

BinaryGCD.hpp

md5: f3ab31

```cpp
u64 ctz(u64 x) { return countr_zero(x); }
u64 binary_gcd(u64 x, u64 y) {
   if(!x || !y) return x | y;
   u64 n = ctz(x), m = ctz(y);
   x >>= n, y >>= m;
   while(x != y) {
      if(x > y) x = (x - y) >> ctz(x - y);
      else y = (y - x) >> ctz(y - x);
   }
   return x << min(n, m);
}
```

ExtGCD.hpp

md5: c3fa9b

```cpp
// returns gcd(a, b) and assign x, y to integers
// s.t. ax + by = gcd(a, b) and |x| + |y| is minimized
ll extgcd(ll a, ll b, ll& x, ll& y) {
   // assert(a >= 0 && b >= 0);
   if(!b) return x = 1, y = 0, a;
   ll d = extgcd(b, a % b, y, x);
   y -= a / b * x;
   return d;
}
```

modint

BarrettReduction.hpp

md5: 2ca7f3

```cpp
// using u64 = uint64_t;
struct Barrett {  // mod < 2^32
   u64 m, im;
   Barrett(u64 mod) : m(mod), im(-1ULL / m + 1) {}
   // input: a * b < 2^64, output: a * b % mod
   u64 mul(u64 a, u64 b) const {
      a *= b;
      u64 x = ((__uint128_t)a * im) >> 64;
      a -= x * m;
      if((ll)a < 0) a += m;
      return a;
   }
};
```

modint.hpp

md5: 81b530

```cpp
const ll mod = 998244353;
struct mm {
   ll x;
   mm(ll x_ = 0) : x(x_ % mod) {
      if(x < 0) x += mod;
   }
   friend mm operator+(mm a, mm b) { return a.x + b.x; }
   friend mm operator-(mm a, mm b) { return a.x - b.x; }
   friend mm operator*(mm a, mm b) { return a.x * b.x; }
   friend mm operator/(mm a, mm b) { return a * b.inv(); }
   // 4 行コピペ  Alt + Shift + クリックで複数カーソル
   friend mm& operator+=(mm& a, mm b) { return a = a.x + b.x; }
   friend mm& operator-=(mm& a, mm b) { return a = a.x - b.x; }
   friend mm& operator*=(mm& a, mm b) { return a = a.x * b.x; }
   friend mm& operator/=(mm& a, mm b) { return a = a * b.inv();
}
   mm inv() const { return pow(mod - 2); }
   mm pow(ll b) const {
      mm a = *this, c = 1;
      while(b) {
         if(b & 1) c *= a;
         a *= a;
         b >>= 1;
      }
      return c;
   }
};
```

FPS

FFT.hpp

md5: 3138c7

```cpp
// {998244353, 3}, {1811939329, 13}, {2013265921, 31}
mm g = 3;  // 原始根
void fft(vector<mm>& a) {
   ll n = sz(a), lg = __lg(n);
   assert((1 << lg) == n);
   vector<mm> b(n);
   rep(l, 1, lg + 1) {
      ll w = n >> l;
      mm s = 1, r = g.pow(mod >> l);
      for(ll u = 0; u < n / 2; u += w) {
         rep(d, 0, w) {
            mm x = a[u << 1 | d], y = a[u << 1 | w | d] * s;
            b[u | d] = x + y;
            b[n >> 1 | u | d] = x - y;
         }
         s *= r;
      }
      swap(a, b);
   }
}
vector<mm> conv(vector<mm> a, vector<mm> b) {
   if(a.empty() || b.empty()) return {};
   size_t s = sz(a) + sz(b) - 1, n = bit_ceil(s);
   // if(min(sz(a), sz(b)) <= 60) 愚直に掛け算
   a.resize(n);
   b.resize(n);
   fft(a);
   fft(b);
   mm inv = mm(n).inv();
   rep(i, 0, n) a[i] *= b[i] * inv;
   reverse(1 + all(a));
   fft(a);
   a.resize(s);
   return a;
}
```

FFT_fast.hpp

md5: c8c567

```cpp
// modint を u32 にして加減算を真面目にやると速い
mm g = 3;  // 原始根
void fft(vector<mm>& a) {
   ll n = sz(a), lg = __lg(n);
   static auto z = [] {
      vector<mm> z(30);
      mm s = 1;
      rep(i, 2, 32) {
         z[i - 2] = s * g.pow(mod >> i);
         s *= g.inv().pow(mod >> i);
      }
      return z;
   }();
   rep(l, 0, lg) {
      ll w = 1 << (lg - l - 1);
      mm s = 1;
      rep(k, 0, 1 << l) {
         ll o = k << (lg - l);
         rep(i, o, o + w) {
            mm x = a[i], y = a[i + w] * s;
            a[i] = x + y;
            a[i + w] = x - y;
         }
         s *= z[countr_zero<uint64_t>(~k)];
      }
   }
}
// コピペ
void ifft(vector<mm>& a) {
   ll n = sz(a), lg = __lg(n);
   static auto z = [] {
      vector<mm> z(30);
      mm s = 1;
      rep(i, 2, 32) {  // g を逆数に
         z[i - 2] = s * g.inv().pow(mod >> i);
         s *= g.pow(mod >> i);
      }
      return z;
   }();
   for(ll l = lg; l--;) {  // 逆順に
      ll w = 1 << (lg - l - 1);
      mm s = 1;
      rep(k, 0, 1 << l) {
         ll o = k << (lg - l);
         rep(i, o, o + w) {
            mm x = a[i], y = a[i + w];  // *s を下に移動
            a[i] = x + y;
            a[i + w] = (x - y) * s;
         }
         s *= z[countr_zero<uint64_t>(~k)];
      }
   }
}
vector<mm> conv(vector<mm> a, vector<mm> b) {
   if(a.empty() || b.empty()) return {};
   size_t s = sz(a) + sz(b) - 1, n = bit_ceil(s);
   // if(min(sz(a), sz(b)) <= 60) 愚直に掛け算
   a.resize(n);
   b.resize(n);
   fft(a);
   fft(b);
   mm inv = mm(n).inv();
   rep(i, 0, n) a[i] *= b[i] * inv;
   ifft(a);
   a.resize(s);
   return a;
}
```

graph

graph/tree

flow

燃やす埋める.md

変形前の制約	変形後の制約
x が 0 のとき z 失う	(x, T, z)
x が 0 のとき z 得る	無条件で z 得る; (S, x, z)
x が 1 のとき z 失う	(S, x, z)
x が 1 のとき z 得る	無条件で z 得る; (x, T, z)
$x, y, \ldots$ がすべて 0 のとき z 得る	無条件で z 得る; $(S, w, z), (w, x, \infty), (w, y, \infty)$
$x, y, \ldots$ がすべて 1 のとき z 得る	無条件で z 得る; $(w, T, z), (x, w, \infty), (y, w, \infty)$

string

KMP.hpp

md5: 886c63

```cpp
// kmp[i] := max{ l ≤ i | s[:l] == s[(i+1)-l:i+1] }
// abacaba -> 0010123
auto KMP(string s) {
   vector<ll> p(sz(s));
   rep(i, 1, sz(s)) {
      ll g = p[i - 1];
      while(g && s[i] != s[g]) g = p[g - 1];
      p[i] = g + (s[i] == s[g]);
   }
   return p;
}
```

Manacher.hpp

md5: 5882fb

```cpp
// 各位置での回文半径を求める
// aaabaaa -> 1214121
// 偶数長の回文を含めて直径を知るには, N+1 個の $ を挿入して 1 を引く
// $a$a$a$b$a$a$a$ -> 123432181234321
auto manacher(string s) {
   ll n = sz(s), i = 0, j = 0;
   vector<ll> r(n);
```

```
   while(i < n) {
      while(i >= j && i + j < n && s[i - j] == s[i + j]) j++;
      r[i] = j;
      ll k = 1;
      while(i >= k && i + k < n && k + r[i - k] < j) {
         r[i + k] = r[i - k];
         k++;
      }
      i += k, j -= k;
   }
   return r;
}
```

RollingHash.hpp

md5: adb8d3

```
// using u64 = uint64_t;
const u64 mod = INF;
u64 add(u64 a, u64 b) {
   a += b;
   if(a >= mod) a -= mod;
   return a;
}
u64 mul(u64 a, u64 b) {
   auto c = (__uint128_t)a * b;
   return add(c >> 61, c & mod);
}
random_device rnd;
const u64 r = ((u64)rnd() << 32 | rnd()) % mod;
struct RH {
   ll n;
   vector<u64> hs, pw;
   RH(string s) : n(sz(s)), hs(n + 1), pw(n + 1, 1) {
      rep(i, 0, n) {
         pw[i + 1] = mul(pw[i], r);
         hs[i + 1] = add(mul(hs[i], r), s[i]);
      }
   }
   u64 get(ll l, ll r) const { return add(hs[r], mod -
mul(hs[l], pw[r - l])); }
};
```

SuffixArray.hpp

md5: 1d70ce

```
// returns pair{sa, lcp}
// sa 長さ n : s[sa[0]:] < s[sa[1]:] < … < s[sa[n-1]:]
// lcp 長さ n-1 : lcp[i] = LCP(s[sa[i]:], s[sa[i+1]:])
auto SA(string s) {
   ll n = sz(s) + 1, lim = 256;
   // assert(lim > ranges::max(s));
   vector<ll> sa(n), lcp(n), x(all(s) + 1), y(n), ws(max(n,
lim)), rk(n);
   iota(all(sa), 0);
   for(ll j = 0, p = 0; p < n; j = max(1LL, j * 2), lim = p) {
      p = j;
      iota(all(y), n - j);
      rep(i, 0, n) if(sa[i] >= j) y[p++] = sa[i] - j;
      fill(all(ws), 0);
      rep(i, 0, n) ws[x[i]]++;
      rep(i, 1, lim) ws[i] += ws[i - 1];
      for(ll i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
      swap(x, y);
      p = 1;
      x[sa[0]] = 0;
      rep(i, 1, n) {
         ll a = sa[i - 1], b = sa[i];
         x[b] = (y[a] == y[b] && y[a + j] == y[b + j]) ? p - 1
: p++;
      }
   }
   rep(i, 1, n) rk[sa[i]] = i;
   for(ll i = 0, k = 0; i < n - 1; lcp[rk[i++]] = k) {
      if(k) k--;
      while(s[i + k] == s[sa[rk[i] - 1] + k]) k++;
   }
   sa.erase(begin(sa));
   lcp.erase(begin(lcp));
   return pair{sa, lcp};
}
```

Zalgorithm.hpp

md5: b20b04

```
// Z[i] := LCP(s, s[i:])
// abacaba -> 7010301
auto Z(string s) {
   ll n = sz(s), l = -1, r = -1;
   vector<ll> z(n, n);
   rep(i, 1, n) {
      ll& x = z[i] = i < r ? min(r - i, z[i - l]) : 0;
      while(i + x < n && s[i + x] == s[x]) x++;
      if(i + x > r) l = i, r = i + x;
   }
   return z;
}
```

algorithm

geometry

memo

Primes.md

素数の個数

n	10^2	10^3	10^4	10^5	10^6	10^7	10^8	10^9	10^{10}
$\pi(n)$	25	168	1229	9592	78498	664579	5.76e+6	5.08e+7	4.55e+8

高度合成数

$\leq n$	10^3	10^4	10^5	10^6	10^7	10^8	10^9
x	840	7560	83160	720720	8648640	73513440	735134400
$d^0(x)$	32	64	128	240	448	768	1344

$\leq n$	10^{10}	10^{11}	10^{12}	10^{13}	10^{14}	10^{15}	10^{16}	10^{17}	10^{18}
$d^0(x)$	2304	4032	6720	10752	17280	26880	41472	64512	103680

素数階乗

n	2	3	5	7	11	13	17	19	23	29
$n\#$	2	6	30	210	2310	30030	510510	9.70e+6	2.23e+8	6.47e+9

階乗

4!	5!	6!	7!	8!	9!	10!	11!	12!	13!
24	120	720	5040	40320	362880	3.63e+6	3.99e+7	4.79e+8	6.23e+9