

DB Context

Implement a class called `database_context_manager` that acts as a context manager for database connections.

The context manager should:

- Create a database connection when entering the context by calling the `__init_db()` method (already defined in the `Database` class).
- Close the connection when exiting the context by calling the `__close_db()` method (also defined in the `Database` class).

Given a string `username` consisting of lowercase English letters, define and complete the `database_context_manager` class. For a successful simulation:

- The input string `username` must be passed to `__init_db()` as an argument.
- The connection string returned from `__init_db()` must be passed to `__close_db()` as an argument to close the connection.

Example

Given input `username = "Sam"`, if the connection string returned by `__init_db()` is `"abc"`:

- `"Sam"` must be passed as an argument to `__init_db()`.
- `"abc"` must be passed to `__close_db()`.

Function Description

Complete the class `database_context_manager` in the editor below.

`database_context_manager`'s `__init__()` method has the following parameter(s):

- `string username`: the string to pass to `__init_db()`

Constraints

- $1 \leq |\text{username}| \leq 10^5$
- `username` consists of lowercase English letters

Input Format For Custom Testing

The first line and the only line of the test case contains a string, `username`.

Sample Case 0

Sample Input For Custom Testing

STDIN	Function
-----	-----
Robin	username = "Robin"

Sample Output

```
Username matched, database connection initialized
Database running...
Connection string matched, database connection closed
```

Explanation

Given, `username = "Robin"`, the steps processed are:

- Implement the class `database\_context\_manager`.
- Call the `\_init\_db()` method with the correct parameter. Output received is "Username matched, database connection initialized".
- The output received is "Database running..." to signal that the database is currently in a running state.
- Call the `\_close\_db()` method with the correct parameter. The output received is "Connection string matched, database connection closed".

Sample Case 1

Sample Input For Custom Testing

STDIN	Function
-----	-----
Sam	username = "Sam"

Sample Output

```
Username matched, database connection initialized
Database running...
Connection string matched, database connection closed
```

Explanation

Given, `username = "Sam"`, the steps processed are identical to Sample Case 0.