

Composition-based Data Analytics Hub

Modern software engineering principles advocate for "Composition over Inheritance" to create flexible and decoupled system architectures. By delegating specialized logic to independent components, developers can assemble complex managers that are easier to test, extend, and maintain compared to rigid, deep-inheritance hierarchies.

Implement a modular analytics engine that utilizes **Composition** to process numeric datasets. The system consists of a `DataProcessor` utility component and an `AnalyticsManager` that hosts it. The manager must leverage the processor to calculate aggregate statistics and provide high-level performance flags based on statistical benchmarks.

Example 1 Input:

```
ADD 10 ADD 20 STATS
```

Output:

```
Sum: 30.0, Avg: 15.0
```

Explanation: Two records are added to the manager's internal state. The manager delegates the sum and average calculations to its **composed** `DataProcessor` instance and returns the results.

Example 2 Input:

```
ADD 50 PERF 40
```

Output:

```
High Performance
```

Explanation: The manager uses its processor to find the average (50.0). Since this value exceeds the provided threshold (40), it returns the "High Performance" classification.

Function Parameter:

- processor (`DataProcessor`): The utility component for mathematical operations.

- value (float): A numeric record to process.
- threshold (float): The target average for performance flagging.

Returns

- dict: A statistics summary `{'sum': float, 'avg': float}`.
- str: A performance classification label.

Constraints

- `AnalyticsManager` must NOT inherit from `DataProcessor`; it must hold an instance of it (Composition).
- Handle empty datasets by returning `0.0` for all average calculations.
- All numeric outputs should be formatted with at least one decimal place.

Input Format for Custom Testing Input from stdin contains commands: `ADD <value>`, `STATS`, or `PERF <threshold>`.

Sample Case 0 Sample Input

```
ADD 100 STATS
```

Sample Output

```
Sum: 100.0, Avg: 100.0
```

Explanation A single record is added and its statistics are generated via the composed processor.