

# COMP 545: Advanced topics in optimization

## From simple to complex ML systems

Lecture 9

# Overview

$\min_x$

s.t.

$$f(x)$$
$$x \in C$$

- Different objective classes
- Different strategies within each problem
- Different approaches based on computational capabilities
- Different approaches based on constraints

And, always having in mind applications in machine learning,  
AI and signal processing

About what we have talked so far

$$\min_x f(x)$$

$$\text{s.t. } x \in \mathcal{C}$$

About what we have talked so far

$$\min_x f(x)$$

s.t.  ~~$x \in C$~~   Unconstrained

About what we have talked so far

$$\min_x \quad f(x) := \frac{1}{n} \sum_{i=1}^n f_i(x)$$

s.t.  ~~$x \in C$~~  

Unconstrained

About what we have talked so far

$$\min_x \quad f(x) := \frac{1}{n} \sum_{i=1}^n f_i(x)$$

Convex

s.t.  ~~$x \in C$~~  Unconstrained

About what we have talked so far

Huge!

$$\min_x f(x) := \frac{1}{n} \sum_{i=1}^n f_i(x)$$

*Convex*

s.t.  ~~$x \in C$~~  *Unconstrained*

About what we have talked so far

Huge!

$$\min_x f(x) := \frac{1}{n} \sum_{i=1}^n f_i(x)$$

*Convex*

~~s.t.~~  $x \in C$  *Unconstrained*

- There is a lot of work on such settings (mostly in the convex domain)  
*(Early stage of modern ML, but out of scope of this course)*

About what we have talked so far

Huge!

$$\min_x \underbrace{f(x)}_{\text{Convex}} := \frac{1}{n} \sum_{i=1}^n f_i(x)$$

s.t.  ~~$x \in C$~~   $x \in C$  Unconstrained

- There is a lot of work on such settings (mostly in the convex domain)  
*(Early stage of modern ML, but out of scope of this course)*
- We focused though on complex ways to deal with such problems: **asynchrony**  
*(We proved convergence under standard conditions and staleness conditions)*

The focus of this lecture

$$\min_x \quad f(x) := \frac{1}{n} \sum_{i=1}^n f_i(x)$$

$$\text{s.t.} \quad x \in \mathcal{C}$$

Huge!

The focus of this lecture

$$\min_x f(x) := \frac{1}{n} \sum_{i=1}^n f_i(x)$$

s.t.  ~~$x \in C$~~

Huge!

Unconstrained

The focus of this lecture

Huge!

$$\min_x f(x) := \frac{1}{n} \sum_{i=1}^n f_i(x)$$

Non-convex!

Unconstrained

s.t.  ~~$x \in C$~~

# Overview

- In this lecture, we will:
  - Go back to the initial discussion of non-convex optimization

# Overview

- In this lecture, we will:
  - Go back to the initial discussion of non-convex optimization
  - We will provide generic convergence results for stochastic methods  
*(More general case than whatever non-convex problem we considered so far)*

# Overview

- In this lecture, we will:
  - Go back to the initial discussion of non-convex optimization
  - We will provide generic convergence results for stochastic methods  
*(More general case than whatever non-convex problem we considered so far)*
  - Inspired by modern ML (neural networks), we will describe alternatives to SGD:
    - Accelerated SGD
    - AdaGrad
    - RMSProp
    - Adam

# Overview

- In this lecture, we will:
  - Go back to the initial discussion of non-convex optimization
  - We will provide generic convergence results for stochastic methods  
*(More general case than whatever non-convex problem we considered so far)*
  - Inspired by modern ML (neural networks), we will describe alternatives to SGD:
    - Accelerated SGD
    - AdaGrad
    - RMSProp
    - Adam
  - Bonus discussion: The marginal value of adaptive methods

# Recall: Stochastic gradient descent

- SGD is used **almost everywhere**: training classical ML tasks (linear prediction, linear classification), training modern ML tasks (non-linear classification, neural networks)

# Recall: Stochastic gradient descent

- SGD is used **almost everywhere**: training classical ML tasks (linear prediction, linear classification), training modern ML tasks (non-linear classification, neural networks)
- In simple math, it satisfies:

$$x_{t+1} = x_t - \eta \nabla f_{i_t}(x_t)$$

based on the objective:  $\min_x f(x) := \frac{1}{n} \sum_{i=1}^n f_i(x)$

Non-convex!

# Recall: Stochastic gradient descent

- SGD is used **almost everywhere**: training classical ML tasks (linear prediction, linear classification), training modern ML tasks (non-linear classification, neural networks)
- In simple math, it satisfies:

$$x_{t+1} = x_t - \eta \nabla f_{i_t}(x_t)$$

based on the objective:  $\min_x f(x) := \frac{1}{n} \sum_{i=1}^n f_i(x)$

**Non-convex!**

- Why SGD is preferable over full-batch GD?

# Recall: Stochastic gradient descent

- SGD is used **almost everywhere**: training classical ML tasks (linear prediction, linear classification), training modern ML tasks (non-linear classification, neural networks)
- In simple math, it satisfies:

$$x_{t+1} = x_t - \eta \nabla f_{i_t}(x_t)$$

based on the objective:  $\min_x f(x) := \frac{1}{n} \sum_{i=1}^n f_i(x)$

**Non-convex!**

- Why SGD is preferable over full-batch GD?
  - Full-batch GD performs **redundant computations** for large datasets

# Recall: Stochastic gradient descent

- SGD is used **almost everywhere**: training classical ML tasks (linear prediction, linear classification), training modern ML tasks (non-linear classification, neural networks)
- In simple math, it satisfies:

$$x_{t+1} = x_t - \eta \nabla f_{i_t}(x_t)$$

based on the objective:  $\min_x f(x) := \frac{1}{n} \sum_{i=1}^n f_i(x)$

**Non-convex!**

- Why SGD is preferable over full-batch GD?
  - Full-batch GD performs **redundant computations** for large datasets
  - SGD's fluctuations enables it to **jump to potentially better local minima**

# Recall: Stochastic gradient descent

- SGD is used **almost everywhere**: training classical ML tasks (linear prediction, linear classification), training modern ML tasks (non-linear classification, neural networks)
- In simple math, it satisfies:

$$x_{t+1} = x_t - \eta \nabla f_{i_t}(x_t)$$

based on the objective:  $\min_x f(x) := \frac{1}{n} \sum_{i=1}^n f_i(x)$

**Non-convex!**

- Why SGD is preferable over full-batch GD?
  - Full-batch GD performs **redundant computations** for large datasets
  - SGD's fluctuations enables it to **jump to potentially better local minima**
- However, SGD's proof for non-convex settings is more **complicated + weaker**

SGD convergence result in non-convex scenario

Whiteboard

# SGD convergence result in non-convex scenario

## Whiteboard

- Key observations:
  - For convergence, this theory assumes a small step size  $O\left(\frac{1}{\sqrt{T}}\right)$
  - In a sense, we need to know a priori the number of iterations to achieve  $\varepsilon$ -approximation
  - Step size can be bad at the beginning – other step sizes used in practice

# SGD convergence result in non-convex scenario

## Whiteboard

- Key observations:
  - For convergence, this theory assumes a small step size  $O\left(\frac{1}{\sqrt{T}}\right)$
  - In a sense, we need to know a priori the number of iterations to achieve  $\varepsilon$ -approximation
  - Step size can be bad at the beginning – other step sizes used in practice
- Nevertheless, in practice SGD performs favorably compared to full-batch GD.

# SGD convergence result in non-convex scenario

## Whiteboard

- Key observations:
  - For convergence, this theory assumes a small step size  $O\left(\frac{1}{\sqrt{T}}\right)$
  - In a sense, we need to know a priori the number of iterations to achieve  $\varepsilon$ -approximation
  - Step size can be bad at the beginning – other step sizes used in practice
- Nevertheless, in practice SGD performs favorably compared to full-batch GD.
- Assuming more structure (e.g., PL condition), one can achieve better rates with constant step sizes (independent on the number of iterations)

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

- Recall:

GD

vs

Acc. GD

Strongly  
Convex

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

- Recall:

GD

vs

Acc. GD

$$O\left(\kappa \log \frac{f(x_0) - f^*}{\varepsilon}\right)$$

Strongly  
Convex

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

- Recall:

Strongly  
Convex

GD

vs

Acc. GD

$$O\left(\kappa \log \frac{f(x_0) - f^*}{\varepsilon}\right)$$

$$O\left(\sqrt{\kappa} \log \frac{f(x_0) - f^*}{\varepsilon}\right)$$

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

- Recall:

Strongly  
Convex

GD

vs

Acc. GD

$$O\left(\boxed{\kappa} \log \frac{f(x_0) - f^*}{\varepsilon}\right)$$

$$O\left(\boxed{\sqrt{\kappa}} \log \frac{f(x_0) - f^*}{\varepsilon}\right)$$

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

- Recall:

Strongly Convex

GD

vs

Acc. GD

$$O\left(\boxed{\kappa} \log \frac{f(x_0) - f^*}{\varepsilon}\right)$$

$$O\left(\boxed{\sqrt{\kappa}} \log \frac{f(x_0) - f^*}{\varepsilon}\right)$$

Non Convex

GD

vs

Acc. GD

(To get to a point such that  $\|\nabla f(\cdot)\|_2 \leq \varepsilon$ )

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

- Recall:

Strongly Convex

GD

vs

Acc. GD

$$O\left(\boxed{\kappa} \log \frac{f(x_0) - f^*}{\varepsilon}\right)$$

$$O\left(\boxed{\sqrt{\kappa}} \log \frac{f(x_0) - f^*}{\varepsilon}\right)$$

Non Convex

GD

vs

Acc. GD

$$O\left(\frac{1}{\varepsilon^2}\right)$$

(To get to a point such that  $\|\nabla f(\cdot)\|_2 \leq \varepsilon$ )

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

- Recall:

Strongly Convex

GD

vs

Acc. GD

$$O\left(\boxed{\kappa} \log \frac{f(x_0) - f^*}{\varepsilon}\right)$$

$$O\left(\boxed{\sqrt{\kappa}} \log \frac{f(x_0) - f^*}{\varepsilon}\right)$$

Non Convex

GD

vs

Acc. GD

$$O\left(\frac{1}{\varepsilon^2}\right)$$

$$O\left(\frac{1}{\varepsilon^{7/4}} \cdot \log(1/\varepsilon)\right)$$

(To get to a point such that  $\|\nabla f(\cdot)\|_2 \leq \varepsilon$ )

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

- Recall:

Strongly Convex

GD

vs

Acc. GD

$$O\left(\boxed{\kappa} \log \frac{f(x_0) - f^*}{\varepsilon}\right)$$

$$O\left(\boxed{\sqrt{\kappa}} \log \frac{f(x_0) - f^*}{\varepsilon}\right)$$

Non Convex

GD

vs

Acc. GD

$$O\left(\frac{1}{\varepsilon^2}\right)$$

$$O\left(\frac{1}{\varepsilon^{7/4}} \cdot \log(1/\varepsilon)\right)$$

Acceleration:  
“get better than  
 $\varepsilon^{-2}$ ”

(To get to a point such that  $\|\nabla f(\cdot)\|_2 \leq \varepsilon$ )

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

- Recall:

SGD

vs

Acc. SGD

Strongly  
Convex

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings  
is not straightforward in most cases

- Recall:

# SGD

VS

# Acc. SGD

# Strongly Convex

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

- Recall:

SGD

vs

Acc. SGD

$$O\left(\frac{1}{\varepsilon}\right)$$

(Results for specific cases –  
Still an open question  
in its most generality)

Strongly  
Convex

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

- Recall:

SGD

vs

Acc. SGD

$$O\left(\frac{1}{\varepsilon}\right)$$

(Results for specific cases –  
Still an open question  
in its most generality)

- 

SGD

vs

Acc. SGD

Strongly  
Convex

Non  
Convex

(To get to a point such that  $\|\nabla f(\cdot)\|_2 \leq \varepsilon$ )

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

- Recall:

SGD

vs

Acc. SGD

$$O\left(\frac{1}{\varepsilon}\right)$$

(Results for specific cases –  
Still an open question  
in its most generality)

- 

SGD

vs

Acc. SGD

$$O\left(\frac{1}{\varepsilon^2}\right)$$

(To get to a point such that  $\|\nabla f(\cdot)\|_2 \leq \varepsilon$ )

Strongly  
Convex

Non  
Convex

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

- Recall:

Strongly  
Convex

SGD

vs

Acc. SGD

$$O\left(\frac{1}{\varepsilon}\right)$$

(Results for specific cases –  
Still an open question  
in its most generality)

- 

Non  
Convex

SGD

vs

Acc. SGD

$$O\left(\frac{1}{\varepsilon^2}\right)$$

(Results for specific cases –  
Still an open question  
in its most generality)

(To get to a point such that  $\|\nabla f(\cdot)\|_2 \leq \varepsilon$ )

# Acceleration in SGD in non-convex scenario

- General observation: moving results from convex to non-convex settings is not straightforward in most cases

- Recall:

Strongly Convex

SGD

vs

Acc. SGD

$$O\left(\frac{1}{\varepsilon}\right)$$

(Results for specific cases –  
Still an open question  
in its most generality)

Non Convex

SGD

vs

Acc. SGD

$$O\left(\frac{1}{\varepsilon^2}\right)$$

(Results for specific cases –  
Still an open question  
in its most generality)

(To get to a point such that  $\|\nabla f(\cdot)\|_2 \leq \varepsilon$ )


(We assume no variance reduction variants)

# Acceleration in SGD in non-convex scenarios


Nevertheless, this does not prevent us from using acceleration in non-convex scenarios

**[https://www.tensorflow.org/api\\_docs/python/tf/train/MomentumOptimizer](https://www.tensorflow.org/api_docs/python/tf/train/MomentumOptimizer)**

# Recall: Momentum acceleration



# Recall: Momentum acceleration



# Recall: Momentum acceleration

- Heavy ball method

$$x_{t+1} = x_t - \eta \nabla f(x_t) + \beta(x_t - x_{t-1})$$

# Recall: Momentum acceleration

- Heavy ball method

$$x_{t+1} = x_t - \eta \nabla f(x_t) + \beta(x_t - x_{t-1})$$



Standard gradient step

# Recall: Momentum acceleration

- Heavy ball method

$$x_{t+1} = x_t - \eta \nabla f(x_t) + \beta(x_t - x_{t-1})$$



Standard gradient step



Momentum step

# Recall: Momentum acceleration

- Heavy ball method

$$x_{t+1} = x_t - \eta \nabla f(x_t) + \beta(x_t - x_{t-1})$$



Standard gradient step



Momentum step

$x_{t-1}$

# Recall: Momentum acceleration


- Heavy ball method

$$x_{t+1} = x_t - \eta \nabla f(x_t) + \beta(x_t - x_{t-1})$$




Standard gradient step

Momentum step




# Recall: Momentum acceleration

- Heavy ball method




# Recall: Momentum acceleration

- Heavy ball method




# Recall: Momentum acceleration

- Heavy ball method




# Recall: Momentum acceleration

- Heavy ball method




# Recall: Momentum acceleration

- Heavy ball method



# Recall: Momentum acceleration

- Heavy ball method



- If current gradient step is in same direction as previous step, then move a little further in that direction

# Guarantees of Heavy Ball method

$$\min_{x \in \mathbb{R}^p} f(x)$$

*“Assume the objective is has Lipschitz continuous gradients, and it is strongly convex. Then:*

$$x_{t+1} = x_t - \eta \nabla f(x_t) + \beta(x_t - x_{t-1})$$

for  $\eta = \frac{4}{\sqrt{L} + \sqrt{\mu}}$  and  $\beta = \max\{|1 - \sqrt{\eta\mu}|, |1 - \sqrt{\eta L}|\}^2$

*converges linearly according to:*

$$\|x_{t+1} - x^*\|_2 \leq \left( \frac{\sqrt{\kappa} - 1}{\sqrt{\kappa} + 1} \right)^t \|x_0 - x^*\|_2 \quad “$$

# Guarantees of Heavy Ball method

Non-convex!

$$\min_{x \in \mathbb{R}^p} f(x)$$

“Assume the objective is has Lipschitz continuous gradients, and it is strongly convex. Then:

$$x_{t+1} = \dots - \eta \nabla f(x_t) + \beta(x_t - x_{t-1})$$

for  $\eta = \frac{4}{\sqrt{L} + \sqrt{\mu}}$  and  $\rho = \max\{|1 - \sqrt{\eta\mu}|, |1 - \sqrt{\eta L}|\}^2$

converges linearly according to:

$$\|x_{t+1} - x^*\|_2 \leq \left( \frac{\sqrt{\kappa} - 1}{\sqrt{\kappa} + 1} \right)^t \|x_0 - x^*\|_2$$

# Recall: Momentum acceleration


- Nesterov's work: a collection of acceleration methods

$$x_{t+1} = x_t - \eta \nabla f(x_t) + \beta(x_t - x_{t-1})$$

# Recall: Momentum acceleration

- Nesterov's work: a collection of acceleration methods

$$x_{t+1} = x_t - \eta \nabla f(x_t) + \beta(x_t - x_{t-1})$$



$$\tilde{x} = x_t - \eta \nabla f(x_t)$$

$$x_{t+1} = \tilde{x} + \beta(x_t - x_{t-1})$$

# Recall: Momentum acceleration

- Nesterov's work: a collection of acceleration methods

$$x_{t+1} = x_t - \eta \nabla f(x_t) + \beta(x_t - x_{t-1})$$

$$\begin{array}{c} \downarrow \\ \widetilde{x} = x_t - \eta \nabla f(x_t) \end{array}$$


Evaluate gradient at  
current point

$$x_{t+1} = \widetilde{x} + \beta(x_t - x_{t-1})$$

# Recall: Momentum acceleration

- Nesterov's work: a collection of acceleration methods


$$x_{t+1} = x_t - \eta \nabla f(x_t) + \beta(x_t - x_{t-1})$$



Evaluate gradient at  
current point

$$\tilde{x} = x_t - \eta \nabla f(x_t)$$

$$x_{t+1} = \tilde{x} + \beta(x_t - x_{t-1})$$



$$\tilde{x} = x_t - \eta \nabla f(x_t + \beta(x_t - x_{t-1}))$$


$$x_{t+1} = \tilde{x} + \beta(x_t - x_{t-1})$$

What if we evaluate the  
gradient at the point we  
end up?

# Recall: Momentum acceleration

- Nesterov's work: a collection of acceleration methods


$$x_{t+1} = x_t - \eta \nabla f(x_t) + \beta(x_t - x_{t-1})$$



Evaluate gradient at  
current point

$$\tilde{x} = x_t - \eta \nabla f(x_t)$$

$$x_{t+1} = \tilde{x} + \beta(x_t - x_{t-1})$$



What if we evaluate the  
gradient at the point we  
end up?

Nesterov's acceleration (1/2)

$$\tilde{x} = x_t - \eta \nabla f(x_t + \beta(x_t - x_{t-1}))$$

$$x_{t+1} = \tilde{x} + \beta(x_t - x_{t-1})$$

# Recall: Momentum acceleration

- Nesterov's work: most famous version

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$

# Recall: Momentum acceleration

- Nesterov's work: most famous version

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$


  
 $x_{t-1}$

# Recall: Momentum acceleration

- Nesterov's work: most famous version

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$




# Recall: Momentum acceleration

- Nesterov's work: most famous version

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$




# Recall: Momentum acceleration

- Nesterov's work: most famous version

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$




# Recall: Momentum acceleration

- Nesterov's work: most famous version

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$




# Recall: Momentum acceleration

- Nesterov's work: most famous version

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$




# Recall: Momentum acceleration

- Nesterov's work: most famous version

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$




# Recall: Momentum acceleration

- Nesterov's work: most famous version

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$




# Recall: Momentum acceleration

- Nesterov's work: most famous version

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$




- Main difference: the point that we are calculating the gradient at.

# Recall: Momentum acceleration

- Nesterov's work: most famous version

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$



- Main difference: the point that we are calculating the gradient at.
- Heavy ball can fail converging in cases where Nesterov's scheme still succeeds

# Recall: Momentum acceleration

- Nesterov's work: how do we set up the momentum parameter?

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$

# Recall: Momentum acceleration

- Nesterov's work: how do we set up the momentum parameter?

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$

$$1. \quad \beta = \frac{\theta_t - 1}{\theta_{t+1}} \quad \text{where} \quad \theta_0 = 1, \quad \theta_{t+1} = \frac{1 + \sqrt{1 + 4\theta_t^2}}{2}$$

# Recall: Momentum acceleration

- Nesterov's work: how do we set up the momentum parameter?

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$

$$1. \beta = \frac{\theta_t - 1}{\theta_{t+1}} \text{ where } \theta_0 = 1, \quad \theta_{t+1} = \frac{1 + \sqrt{1 + 4\theta_t^2}}{2}$$

$$2. \beta = \frac{t}{t+3}$$

# Recall: Momentum acceleration

- Nesterov's work: how do we set up the momentum parameter?

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$

$$1. \beta = \frac{\theta_t - 1}{\theta_{t+1}} \text{ where } \theta_0 = 1, \quad \theta_{t+1} = \frac{1 + \sqrt{1 + 4\theta_t^2}}{2}$$

$$2. \beta = \frac{t}{t+3}$$

$$3. \beta = 0.9$$

# Recall: Momentum acceleration

- Nesterov's work: how do we set up the momentum parameter?

$$x_{t+1} = y_t - \eta \nabla f(y_t)$$

$$y_{t+1} = x_{t+1} + \beta(x_{t+1} - x_t)$$

$$1. \beta = \frac{\theta_t - 1}{\theta_{t+1}} \quad \text{where } \theta_0 = 1, \quad \theta_{t+1} = \frac{1 + \sqrt{1 + 4\theta_t^2}}{2}$$

$$2. \beta = \frac{t}{t+3}$$

$$3. \beta = 0.9$$



One of the mysteries of  
optimization..

# AdaGrad algorithm

(A Google algorithm that found application to  
“Large-scale distributed deep networks” paper)

- Algorithms so far assume a common (and often fixed) step size for all components of  $x_t$

# AdaGrad algorithm

(A Google algorithm that found application to  
“Large-scale distributed deep networks” paper)

- Algorithms so far assume a common (and often fixed) step size for all components of  $x_t$
- AdaGrad adapts the initial step size for each of the components:
  - Associates small step sizes to frequently occurring features
  - Associates large step sizes to rare occurring features

# AdaGrad algorithm

(A Google algorithm that found application to  
“Large-scale distributed deep networks” paper)

- Algorithms so far assume a common (and often fixed) step size for all components of  $x_t$
- AdaGrad adapts the initial step size for each of the components:
  - Associates small step sizes to frequently occurring features
  - Associates large step sizes to rare occurring features
- What is the main idea? Consider  $x_{t+1,i} = x_{t,i} - \eta \nabla f(x_t)_i$   
Entrywise representation of GD

# AdaGrad algorithm

(A Google algorithm that found application to  
“Large-scale distributed deep networks” paper)

- Algorithms so far assume a common (and often fixed) step size for all components of  $x_t$
- AdaGrad adapts the initial step size for each of the components:
  - Associates small step sizes to frequently occurring features
  - Associates large step sizes to rare occurring features
- What is the main idea? Consider  $x_{t+1,i} = x_{t,i} - \eta \nabla f(x_t)_i$   
Entrywise representation of GD

Then, practical version of AdaGrad does:  $x_{t+1,i} = x_{t,i} - \frac{\eta}{\sqrt{B_{t,ii} + \epsilon}} \cdot \nabla f_{i_t}(x_t)_i$

# AdaGrad algorithm

(A Google algorithm that found application to  
“Large-scale distributed deep networks” paper)

- Algorithms so far assume a common (and often fixed) step size for all components of  $x_t$
- AdaGrad adapts the initial step size for each of the components:
  - Associates small step sizes to frequently occurring features
  - Associates large step sizes to rare occurring features
- What is the main idea? Consider  $x_{t+1,i} = x_{t,i} - \eta \nabla f(x_t)_i$   
Entrywise representation of GD

Then, practical version of AdaGrad does:  $x_{t+1,i} = x_{t,i} - \frac{\eta}{\sqrt{B_{t,ii} + \epsilon}} \cdot \nabla f_{i_t}(x_t)_i$

What is this quantity?

# AdaGrad algorithm

# AdaGrad algorithm

- AdaGrad is just another preconditioning algorithm:

$$x_{t+1} = x_t - \eta B_t^{-1} \nabla f(x_t)$$

Recall: Preconditioning algorithms (BFGS, SR1) in lecture 3

# AdaGrad algorithm

- AdaGrad is just another preconditioning algorithm:

$$x_{t+1} = x_t - \eta B_t^{-1} \nabla f(x_t)$$

where

$$B_t = \left( \sum_{j=1}^t \nabla f_{i_j}(x_j) \cdot \nabla f_{i_j}(x_j)^\top \right)^{1/2}$$

Recall: Preconditioning algorithms (BFGS, SR1) in lecture 3

“Square root of the sum of gradient outer products, till current iteration”

# AdaGrad algorithm

- AdaGrad is just another preconditioning algorithm:

$$x_{t+1} = x_t - \eta B_t^{-1} \nabla f(x_t)$$

where

$$B_t = \left( \sum_{j=1}^t \nabla f_{i_j}(x_j) \cdot \nabla f_{i_j}(x_j)^\top \right)^{1/2}$$

Recall: Preconditioning algorithms (BFGS, SR1) in lecture 3

“Square root of the sum of gradient outer products, till current iteration”



Full matrix AdaGrad

# AdaGrad algorithm

- AdaGrad is just another preconditioning algorithm:

$$x_{t+1} = x_t - \eta B_t^{-1} \nabla f(x_t)$$

where

$$B_t = \left( \sum_{j=1}^t \nabla f_{i_j}(x_j) \cdot \nabla f_{i_j}(x_j)^\top \right)^{1/2}$$

Recall: Preconditioning algorithms (BFGS, SR1) in lecture 3

“Square root of the sum of gradient outer products, till current iteration”

- Compare this to the simpler (and practical version)

$$x_{t+1,i} = x_{t,i} - \frac{\eta}{\sqrt{B_{t,ii} + \epsilon}} \cdot \nabla f_{i_t}(x_t)_i$$

Full matrix AdaGrad

# AdaGrad algorithm

- AdaGrad is just another preconditioning algorithm:

$$x_{t+1} = x_t - \eta B_t^{-1} \nabla f(x_t)$$

where

$$B_t = \left( \sum_{j=1}^t \nabla f_{i_j}(x_j) \cdot \nabla f_{i_j}(x_j)^\top \right)^{1/2}$$

Recall: Preconditioning algorithms (BFGS, SR1) in lecture 3

“Square root of the sum of gradient outer products, till current iteration”

- Compare this to the simpler (and practical version)

$$x_{t+1,i} = x_{t,i} - \frac{\eta}{\sqrt{B_{t,ii} + \epsilon}} \cdot \nabla f_{i_t}(x_t)_i$$

Full matrix AdaGrad

Avoids division with zero

# AdaGrad algorithm

- "What is the intuition behind the form of  $B_t$ ?"

$$B_t = \left( \sum_{j=1}^t \nabla f_{i_j}(x_j) \cdot \nabla f_{i_j}(x_j)^\top \right)^{1/2}$$

Relates to the **Fisher Information matrix** (which is related to the expected Hessian) – outside our scope

# AdaGrad algorithm

- "What is the intuition behind the form of  $B_t$ ?"

$$B_t = \left( \sum_{j=1}^t \nabla f_{i_j}(x_j) \cdot \nabla f_{i_j}(x_j)^\top \right)^{1/2}$$

Relates to the **Fisher Information matrix** (which is related to the expected Hessian) – outside our scope

- "What is the connection between full and diagonal preconditioner?"

Whiteboard

# AdaGrad algorithm

- "What is the intuition behind the form of  $B_t$ ?"

$$B_t = \left( \sum_{j=1}^t \nabla f_{i_j}(x_j) \cdot \nabla f_{i_j}(x_j)^\top \right)^{1/2}$$

Relates to the **Fisher Information matrix** (which is related to the expected Hessian) – outside our scope

- "What is the connection between full and diagonal preconditioner?"

## Whiteboard

- "What are some properties of AdaGrad?"

1. Step size is automatically set – default values for initial step size is  $\eta = 0.01$
2. The original version keeps accumulating squared gradients, which makes resulting step sizes really small.

# AdaGrad algorithm

- "What is the intuition behind the form of  $B_t$ ?"

$$B_t = \left( \sum_{j=1}^t \nabla f_{i_j}(x_j) \cdot \nabla f_{i_j}(x_j)^\top \right)^{1/2}$$

Relates to the **Fisher Information matrix** (which is related to the expected Hessian) – outside our scope

- "What is the connection between full and diagonal preconditioner?"

## Whiteboard

- "What are some properties of AdaGrad?"
  1. Step size is automatically set – default values for initial step size is  $\eta = 0.01$
  2. The original version keeps accumulating squared gradients, which makes resulting step sizes really small.
- "Are there guarantees for AdaGrad?"
- Yes, in the convex case, using regret bounds – see Literature section

# AdaGrad pseudocode

**while** stopping criterion not met **do**

    Sample a minibatch of  $m$  examples from the training set  $\{\mathbf{x}^{(1)}, \dots, \mathbf{x}^{(m)}\}$  with corresponding targets  $\mathbf{y}^{(i)}$ .

    Compute gradient:  $\mathbf{g} \leftarrow \frac{1}{m} \nabla_{\boldsymbol{\theta}} \sum_i L(f(\mathbf{x}^{(i)}; \boldsymbol{\theta}), \mathbf{y}^{(i)})$

    Accumulate squared gradient:  $\mathbf{r} \leftarrow \mathbf{r} + \mathbf{g} \odot \mathbf{g}$

    Compute update:  $\Delta \boldsymbol{\theta} \leftarrow -\frac{\epsilon}{\delta + \sqrt{\mathbf{r}}} \odot \mathbf{g}$ .   (Division and square root applied element-wise)




    Apply update:  $\boldsymbol{\theta} \leftarrow \boldsymbol{\theta} + \Delta \boldsymbol{\theta}$

**end while**

# AdaGrad in practice




# AdaGrad in practice

Well-conditioned  
linear regression






# AdaGrad in practice

Well-conditioned linear regression




Ill-conditioned linear regression




# AdaGrad in practice


Well-conditioned linear regression



$$\eta = \frac{1}{L}$$




$$\eta = 0.1$$




$\eta$  carefully selected


Ill-conditioned linear regression



$$\eta = \frac{1}{L}$$




$$\eta = 0.1$$




$\eta$  carefully selected

(Similar performance in logistic regression)

# AdaGrad in practice



# AdaGrad in practice



# Removing extended gradient accumulation: **RMSprop** algorithm

- Idea: keep AdaGrad as it is; except, use a weighted moving average for gradient accumulation

# Removing extended gradient accumulation: **RMSprop** algorithm

- Idea: keep AdaGrad as it is; except, use a weighted moving average for gradient accumulation
  - + Diagonal AdaGrad rule:  $\text{diag}(B_t) = \text{diag}(B_{t-1}) + \text{diag}(\nabla f_{i_t}(x_t) \circ \nabla f_{i_t}(x_t))$

# Removing extended gradient accumulation: **RMSprop** algorithm

- Idea: keep AdaGrad as it is; except, use a weighted moving average for gradient accumulation
  - + Diagonal AdaGrad rule:  $\text{diag}(B_t) = \text{diag}(B_{t-1}) + \text{diag}(\nabla f_{i_t}(x_t) \circ \nabla f_{i_t}(x_t))$

The diagram shows a horizontal line with four open circles representing points on a timeline. Below the first circle is the label  $E[g^2]_t$ , below the second circle is  $E[g^2]_{t-1}$ , and below the third circle is  $g_t^2$ . This visualizes how the current gradient squared ( $g_t^2$ ) is being combined with the previous gradient squared ( $E[g^2]_{t-1}$ ) to update the moving average ( $E[g^2]_t$ ).

# Removing extended gradient accumulation: RMSPROP algorithm

- Idea: keep AdaGrad as it is; except, use a weighted moving average for gradient accumulation
  - + Diagonal AdaGrad rule:  $\text{diag}(B_t) = \text{diag}(B_{t-1}) + \text{diag}(\nabla f_{i_t}(x_t) \circ \nabla f_{i_t}(x_t))$

$$E[g^2]_t \quad E[g^2]_{t-1} \quad g_t^2$$

- + RMSPROP rule:  $E[g^2]_t = \frac{9}{10} \cdot E[g^2]_{t-1} + \frac{1}{10} \cdot g_t^2$

“We always give weight 0.1 to the new information”

# Removing extended gradient accumulation: RMSPROP algorithm

- Idea: keep AdaGrad as it is; except, use a weighted moving average for gradient accumulation
  - + Diagonal AdaGrad rule:  $\text{diag}(B_t) = \text{diag}(B_{t-1}) + \text{diag}(\nabla f_{i_t}(x_t) \circ \nabla f_{i_t}(x_t))$


$$E[g^2]_t \quad E[g^2]_{t-1} \quad g_t^2$$

- + RMSPROP rule:  $E[g^2]_t = \frac{9}{10} \cdot E[g^2]_{t-1} + \frac{1}{10} \cdot g_t^2$

“We always give weight 0.1 to the new information”

- Algorithm:
$$E[g^2]_t = \frac{9}{10} \cdot E[g^2]_{t-1} + \frac{1}{10} \cdot g_t^2$$
$$x_{t+1} = x_t - \frac{\eta}{\sqrt{E[g^2]_t + \epsilon}} \nabla f_{i_t}(x_t)$$

# Introducing exponentially weighted averages


(Adapted from Ng's lectures)

- Toy example: temperature values over a year

# Introducing exponentially weighted averages

(Adapted from Ng's lectures)


- Toy example: temperature values over a year



# Introducing exponentially weighted averages

(Adapted from Ng's lectures)

- Toy example: temperature values over a year
  - Computing trends: local averages and how they evolve



$$V_0 = 0$$

$$V_1 = 0.9V_0 + 0.1\theta_1$$

$$V_2 = 0.9V_1 + 0.1\theta_2$$

⋮

$$V_t = 0.9V_{t-1} + 0.1\theta_t$$

# Introducing exponentially weighted averages

(Adapted from Ng's lectures)


- Toy example: temperature values over a year

- General formula:

$$V_t = \beta V_{t-1} + (1 - \beta)\theta_t$$

- Intuition:  $V_t$  approximates temperature over


$$\approx \frac{1}{1 - \beta} \text{ days}$$



# Introducing exponentially weighted averages

(Adapted from Ng's lectures)

- Toy example: temperature values over a year




- Examples:

$$\left\{ \begin{array}{l} \beta = 0.9 \rightarrow \approx 10 \text{ days} \\ \beta = 0.98 \rightarrow \approx 50 \text{ days} \\ \beta = 0.5 \rightarrow \approx 2 \text{ days} \end{array} \right.$$

# Introducing exponentially weighted averages

(Adapted from Ng's lectures)

- Toy example: temperature values over a year



- Examples:

$$\beta = 0.9 \rightarrow \approx 10 \text{ days}$$

$$\beta = 0.98 \rightarrow \approx 50 \text{ days}$$

$$\beta = 0.5 \rightarrow \approx 2 \text{ days}$$

# Going beyond RMSprop: Adam algorithm

- Idea: Use weighted moving average in gradient also:

# Going beyond RMSprop: Adam algorithm

- Idea: Use weighted moving average in gradient also:
  - + RMSprop rule:  $E[g^2]_t = \frac{9}{10} \cdot E[g^2]_{t-1} + \frac{1}{10} \cdot g_t^2$

# Going beyond RMSprop: Adam algorithm

- Idea: Use weighted moving average in gradient also:

- + RMSprop rule:  $E[g^2]_t = \frac{9}{10} \cdot E[g^2]_{t-1} + \frac{1}{10} \cdot g_t^2$

- + Adam rule:  $E[g^2]_t = \beta_2 \cdot E[g^2]_{t-1} + (1 - \beta_2) \cdot g_t^2$

and

$$m_t = \beta_1 \cdot m_{t-1} + (1 - \beta_1) \cdot \nabla f_{i_t}(x_t)$$

“Moving averages are essentially about averaging many previous values in order to become independent of local fluctuations and focus on the overall trend”

# Going beyond RMSprop: Adam algorithm

- Idea: Use weighted moving average in gradient also:

- + RMSprop rule:  $E[g^2]_t = \frac{9}{10} \cdot E[g^2]_{t-1} + \frac{1}{10} \cdot g_t^2$

- + Adam rule:  $E[g^2]_t = \beta_2 \cdot E[g^2]_{t-1} + (1 - \beta_2) \cdot g_t^2$

and

$$m_t = \beta_1 \cdot m_{t-1} + (1 - \beta_1) \cdot \nabla f_{i_t}(x_t)$$

“Moving averages are essentially about averaging many previous values in order to become independent of local fluctuations and focus on the overall trend”

Further:

$$\hat{m}_t = \frac{m_t}{1 - \beta_1^t}, \quad \hat{v}_t = \frac{E[g^2]_t}{1 - \beta_2^t}$$

# Going beyond RMSprop: Adam algorithm

- Idea: Use weighted moving average in gradient also:

- + RMSprop rule:  $E[g^2]_t = \frac{9}{10} \cdot E[g^2]_{t-1} + \frac{1}{10} \cdot g_t^2$

- + Adam rule:  $E[g^2]_t = \beta_2 \cdot E[g^2]_{t-1} + (1 - \beta_2) \cdot g_t^2$

and

$$m_t = \beta_1 \cdot m_{t-1} + (1 - \beta_1) \cdot \nabla f_{i_t}(x_t)$$

“Moving averages are essentially about averaging many previous values in order to become independent of local fluctuations and focus on the overall trend”

Further:

$$\hat{m}_t = \frac{m_t}{1 - \beta_1^t}, \quad \hat{v}_t = \frac{E[g^2]_t}{1 - \beta_2^t}$$

- Algorithm:  $x_{t+1} = x_t - \frac{\eta}{\sqrt{\hat{v}_t} + \epsilon} \cdot \hat{m}_t$

$$\beta_1 = 0.9, \quad \beta_2 = 0.999$$

# Bias correction in weighted averages

(Adapted from Ng's lectures)


- How to explain these “weird” denominators?

# Bias correction in weighted averages

(Adapted from Ng's lectures)

- How to explain these “weird” denominators?

$$V_t = \beta V_{t-1} + (1 - \beta) \theta_t$$




# Bias correction in weighted averages

(Adapted from Ng's lectures)

- How to explain these “weird” denominators?

$$V_t = \beta V_{t-1} + (1 - \beta) \theta_t$$







# Other algorithms and sources


- Not a complete list: AdaMax, Nadam, AMSGrad, ..
- A nice blog post on the matter:


**<http://ruder.io/optimizing-gradient-descent/>**

- Choosing the right algorithm: there is no consensus about it (see next slides)
- A visualization of their performance in toy examples:









# Other algorithms and sources

- Not a complete list: AdaMax, Nadam, AMSGrad, ..
- A nice blog post on the matter:  
**<http://ruder.io/optimizing-gradient-descent/>**
- Choosing the right algorithm: there is no consensus about it (see next slides)
- A visualization of their performance in toy examples:
- Bonus discussion: The marginal value of adaptive methods

# Other algorithms and sources

- Not a complete list: AdaMax, Nadam, AMSGrad, ..
- A nice blog post on the matter:

**<http://ruder.io/optimizing-gradient-descent/>**

- Choosing the right algorithm: there is no consensus about it (see next slides)
- A visualization of their performance in toy examples:
- Bonus discussion: **The marginal value of adaptive methods**

(Switch presentations)

# Conclusion

- There are various algorithms for modern machine learning
- The most successful of them are gradient based; however, there are variations that make difference in practice (acceleration helps, adaptive learning rates work for most applications, etc).
- Which algorithm to use depends on the problem and the resources at hand
- These topics are highly attractive (research-wise): the idea is to devise new algorithms that achieve practical acceleration (with minimal tuning effort)