

Tonal Languages

Ali Taqi

2023-04-28

```
# Transform
humid_df <- humid_df %>% mutate(perc = (8 + 4*(f/0.001))/100)
# Bounds
bounds <- range(humid_df$f, na.rm = T)
bounds

## [1] 0.00001 0.02089

bounds <- range(humid_df$perc, na.rm = T)
bounds

## [1] 0.0804 0.9156

if(F){
  # Plot
  humid_df %>%
    filter() %>%
    ggplot(mapping = aes(x = x, y = y)) +
    geom_point(mapping = aes(color = f, alpha = perc)) +
    scale_colour_distiller(palette = "YlOrRd")+
    geom_point(data = tonal_df, mapping = aes(x = longitude, y = latitude, color = complex_tonal), alpha = )
}

# Get ggplot coords
world_coordinates <- map_data("world")
# Plot
humid_df %>%
  ggplot() +
  geom_map(data = world_coordinates, map = world_coordinates,
    aes(long, lat, map_id = region)) +
  geom_point(aes(x = x, y = y, alpha = perc), color = "gold") +
  geom_point(data = tonal_df, mapping = aes(x = longitude, y = latitude, color = complex_tonal), alpha = )

## Warning in geom_map(data = world_coordinates, map = world_coordinates,
## aes(long, : Ignoring unknown aesthetics: x and y
```

