

asn1_read_tag(3)

asn1_read_tag(3) libtasn1 asn1_read_tag(3)

NAME

asn1_read_tag - API function

SYNOPSIS

```
#include <libtasn1.h>
```

```
int asn1_read_tag(asn1_noderoot, const char *name, int *tagValue,  
int *classValue);
```

ARGUMENTS

asn1_node root pointer to a structure

const char * name the name of the element inside a structure.

int * tagValue variable that will contain the TAG value.

int * classValue variable that will specify the TAG type.

DESCRIPTION

Returns the TAG and the CLASS of one element inside a structure. CLASS can have one of these constants: **ASN1_CLASS_APPLICATION**,

ASN1_CLASS_UNIVERSAL, **ASN1_CLASS_PRIVATE** or
ASN1_CLASS_CONTEXT_SPECIFIC.

RETURNS

ASN1_SUCCESS if successful, **ASN1_ELEMENT_NOT_FOUND** if
name is not a valid element.

COPYRIGHT

Copyright © 2006-2013 Free Software Foundation, Inc..

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **libtasn1** is maintained as a Texinfo manual. If the **info** and **libtasn1** programs are properly installed at your site, the command

info libtasn1

should give you access to the complete manual. As an alternative you may obtain the manual from:

<http://www.gnu.org/software/libtasn1/manual/>