

# asn1\_\_octet\_\_der(3)

---

asn1__octet__der(3)	libtasn1	asn1__octet__der(3)
---------------------	----------	---------------------

---

## NAME

asn1\_\_octet\_\_der - API function

## SYNOPSIS

```
#include <libtasn1.h>
```

```
void asn1__octet__der(const unsigned char *str, int str_len, unsigned  
char *der, int *der_len);
```

## ARGUMENTS

**const unsigned char \* str** the input data.

**int str\_len** STR length (str[0]..str[\*str\_len-1]).

**unsigned char \* der** encoded string returned.

**int \* der\_len** number of meaningful bytes of DER (der[0]..der[der\_len-1]).

## DESCRIPTION

Creates a length-value DER encoding for the input data. The DER encoding of the input data will be placed in the der variable.

Note that the OCTET STRING tag is not included in the output.

This function does not return any value because it is expected that `der_len` will contain enough bytes to store the string plus the DER encoding. The DER encoding size can be obtained using `asn1_length_der()`.

## COPYRIGHT

Copyright © 2006-2013 Free Software Foundation, Inc..

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **libtasn1** is maintained as a Texinfo manual. If the **info** and **libtasn1** programs are properly installed at your site, the command

**info libtasn1**

should give you access to the complete manual. As an alternative you may obtain the manual from:

**<http://www.gnu.org/software/libtasn1/manual/>**