iOS Device Build Guide

Noodle monorepo: Store, Customer and Rider apps on a physical iPhone

1. Commands

Run everything from the repo root:

```
cd ~/dev/enatega/Noodle
```

Store app

```
scripts/ios-device.sh store
```

Customer app

```
scripts/ios-device.sh app
```

Rider app

```
scripts/ios-device.sh rider --pods
```

Rider: keep `--pods` for its first build, because its Podfile fix hasn't been applied yet. After that you can leave it off.

Each command builds a Release copy of the app and installs it on the iPhone. Release builds include their own JavaScript, so they run without your Mac.

2. Before you build

- Keep the iPhone unlocked and connected, by cable or on the same Wi-Fi.
- Build one app at a time and let each finish before starting the next. Builds running in parallel have corrupted Xcode's build data before.

3. When to add `--pods`

Add `--pods` (runs `pod install` first) when:

- you added or upgraded a package that has native code
- `pnpm install` changed something native
- after a fresh clone, or the build complains about Pods

Otherwise leave it off. It's slower and not needed when only JS or TS code changed.

4. After installing

- If iOS blocks an app the first time you open it: Settings → General → VPN & Device Management, then trust your developer certificate.
- Code changes don't appear live. Rerun the command to pick them up.

5. If something fails

Symptom	What to do
`** BUILD FAILED **` with no error shown	The real error is in Xcode's build log under `apps/<app>/ios/build/dd/Logs/Build`. Ask Claude to read it.

Symptom	What to do
App opens and closes straight away, and the phone has **no** crash report	**Missing UIScene support (iOS 27).** Apps built with Xcode 27 must use Apple's scene life cycle or iOS refuses to launch them; the app just exits with code 0. Each app's `AppDelegate.swift` now has a `SceneDelegate` class and its `Info.plist` has a `UIApplicationSceneManifest` entry. If either is missing (for example after expo prebuild), ask Claude to add them back. To confirm, launch with `xcrun devicectl device process launch --console ...` and look for "UIScene life cycle is required".
App opens and closes straight away (with a crash report)	Sentry saves a crash report on the phone with the actual JS error (see section 6). Ask Claude to pull it.
`npx expo run:ios` fails with "Can't determine id of Simulator app"	Expected on this Mac's Xcode 27 (Simulator.app is missing). Use the script instead.
Deployment target errors ("set to 12.0 ... supported 15.0 to 27.0")	Run with `--pods`. The Podfile raises old pods to iOS 15.1.
Sentry "Auth token is required"	Already handled by the script (`SENTRY_DISABLE_AUTO_UPLOAD=true`).
Log shows expo-updates "HTTP response error 400: channel-name"	Harmless. Local builds have no update channel, so the app runs the JavaScript it was built with.

6. Pulling a crash report off the phone

Example for the store app. Swap in the bundle ID of the app that crashed:

```
xcrun devicectl device copy from \
  --device 00008110-00021061222A401E \
  --domain-type appDataContainer \
  --domain-identifier multivendor.enatega.restaurant.dev \
  --source Library/Caches --destination ~/Desktop/crash
```

Open `~/Desktop/crash/SentryCrash/*/Reports/*.json` and search for `Unhandled JS Exception`.

7. Other things to know

- Different iPhone: `IOS_DEVICE_ID=<udid> scripts/ios-device.sh store`. To find the UDID, run `xcrun devicectl list devices`.
- Customer app after expo prebuild: its `ios/` folder isn't in git, so the Xcode 27 Podfile fix (raising pods to iOS 15.1) **and the UIScene fix** (SceneDelegate in `AppDelegate.swift` + `UIApplicationSceneManifest` in `Info.plist`) would have to be added again. The rider and store versions are in git and can be copied.
- Running `expo prebuild --clean` on rider or store also regenerates their `ios/` folders and drops the UIScene fix. Restore it from git afterwards.
- Duplicate packages: each app's `metro.config.js` pins core packages (react-native, expo, reanimated, safe-area, etc.) to a single copy. Without that, Release builds crash on launch. If you add a new core native package and see a startup crash, it may need adding to that list.

App reference

App	Bundle ID	Workspace
Store	multivendor.enatega.restaurant.dev	EnategaStore
Customer	com.enatega.multivendor.alaadev	EnategaMulti
Rider	multivendor.enatega.rider.dev	EnategaMultivendorRider