

CSV Tables in Markdown — Pandoc Filter for CSV Tables

May 20, 2019

Contents

Contents	i
1 <code>pantable</code>	1
2 <code>pantable2csv</code>	3
3 Related Filters	4

The pantable package comes with 2 pandoc filters, `pantable.py` and `pantable2csv.py`. `pantable` is the main filter, introducing a syntax to include CSV table in markdown source. `pantable2csv` complements `pantable`, is the inverse of `pantable`, which convert native pandoc tables into the CSV table format defined by `pantable`.

Some example uses are:

1. You already have tables in CSV format.
2. You feel that directly editing markdown table is troublesome. You want a spreadsheet interface to edit, but want to convert it to native pandoc table for higher readability. And this process might go back and forth.
3. You want lower-level control on the table and column widths.
4. You want to use all table features supported by the pandoc's internal AST table format, which is not possible in markdown for pandoc ≤ 1.18 .¹

1 pantable

This allows CSV tables, optionally containing markdown syntax (disabled by default), to be put in markdown as a fenced code blocks.

1.1 Example

Also see the README in [GitHub Pages](#). There's a [LaTeX output](#) too.

```
```table

caption: '*Awesome* **Markdown** Table'
alignment: RC
table-width: 2/3
markdown: True

First row,defaulted to be header row,can be disabled
1,cell can contain **markdown**,"It can be aribrary block element:

- following standard markdown syntax
- like this"
2,"Any markdown syntax, e.g.", $E = mc^2$
```
```

becomes

¹In pandoc 1.19, grid-tables is improved to support all features available to the AST too.

Table 1: *Awesome* **Markdown** Table

| First
row | defaulted to be header
row | can be disabled |
|--------------|-------------------------------------|---|
| 1 | cell can contain
markdown | It can be arbitrary block
element: <ul style="list-style-type: none"> • following standard
markdown syntax • like this |
| 2 | Any markdown syntax,
e.g. | $E = mc^2$ |

(The equation might not work if you view this on PyPI.)

1.2 Install and Use

Install:

```
pip install -U pantable
```

Use:

```
pandoc -F pantable -o README.html README.md
```

1.3 Syntax

Fenced code blocks is used, with a class **table**. See [Example](#).

Optionally, YAML metadata block can be used within the fenced code block, following standard pandoc YAML metadata block syntax. 7 metadata keys are recognized:

caption the caption of the table. If omitted, no caption will be inserted. Default: disabled.

alignment a string of characters among L,R,C,D, case-insensitive, corresponds to Left-aligned, Right-aligned, Center-aligned, Default-aligned respectively. e.g. LCRD for a table with 4 columns. Default: DDD...

width a list of relative width corresponding to the width of each columns. e.g.

```
- width
  - 0.1
  - 0.2
  - 0.3
  - 0.4
```

Default: auto calculated from the length of each line in table cells.

table-width the relative width of the table (e.g. relative to `\linewidth`). default: 1.0

header If it has a header row or not. True/False/yes/NO are accepted, case-insensitive. default: True

markdown If CSV table cell contains markdown syntax or not. Same as above. Default: False

include the path to an CSV file, can be relative/absolute. If non-empty, override the CSV in the CodeBlock. default: None

include-encoding if specified, the file from **include** will be decoded according to this encoding, else assumed to be UTF-8.

csv-kwargs If specified, should be a dictionary passed to `csv.reader` as options. e.g.

```
---
csv-kwargs:
  dialect: unix
  key: value...
...
```

pipe_tables If True, a pipe table will be constructed directly in markdown syntax instead of via AST. **markdown** is implied to be True. This trades correctness for speed. It won't be correct if any of the cell is multiline for example, resulting in an invalid pipe table. However, it is much faster comparing to previous **markdown: True** case because previously per cell a subprocess to execute pandoc the parse the markdown to AST is needed.

raw_markdown If True, force output the table as a pipe table (which is tab-delimited.) This is sometimes useful if pandoc is very stubborn to not emit a pipe table even if **markdown-grid_tables...** is used. Note that this should only be used if the output format is markdown.

When the metadata keys is invalid, the default will be used instead. Note that width and table-width accept fractions as well.

2 pantable2csv

This one is the inverse of **pantable**, a panflute filter to convert any native pandoc tables into the CSV table format used by pantable.

Effectively, **pantable** forms a “CSV Reader”, and **pantable2csv** forms a “CSV Writer”. It allows you to convert back and forth between these 2 formats.

For example, in the markdown source:

```
+-----+-----+-----+
| First | defaulted to be | can be disabled |
| row   | header row      |                   |
+=====+=====+=====+
```

| | | | |
|---------------------------|------------------|---------------------------|--|
| 1 | cell can contain | It can be arbitrary block | |
| | markdown | element: | |
| | | | |
| | | - following standard | |
| | | markdown syntax | |
| | | - like this | |
| +-----+-----+-----+-----+ | | | |
| 2 | Any markdown | $E = mc^2$ | |
| | syntax, e.g. | | |
| +-----+-----+-----+-----+ | | | |

: **Awesome** **Markdown** Table

running `pandoc -F pantable2csv -o output.md input.md`, it becomes

```

``` {.table}

alignment: DDD
caption: 'Awesome Markdown Table'
header: true
markdown: true
table-width: 0.8055555555555556
width: [0.125, 0.3055555555555556, 0.375]

First row, defaulted to be header row, can be disabled
1, cell can contain markdown, "It can be arbitrary block element:

- following standard markdown syntax
- like this
"
2, "Any markdown syntax, e.g.", $E = mc^2$
```

```

3 Related Filters

The followings are pandoc filters written in Haskell that provide similar functionality. This filter is born after testing with theirs.

- [baig/pandoc-csv2table](#): A Pandoc filter that renders CSV as Pandoc Markdown Tables.
- [mb21/pandoc-placetable](#): Pandoc filter to include CSV data (from file or URL)
- [sergiocorreia/panflute/csv-tables.py](#)

| | pandoc-csv2table | pandoc-placetable | panflute example | pantable |
|---------|------------------|-------------------|------------------|----------|
| caption | caption | caption | title | caption |

| | pandoc-csv2table | pandoc-placetable | panflute example | pantable |
|-------------|---|---|--------------------------|---|
| aligns | aligns = LRCD | aligns = LRCD | | aligns = LRCD |
| width | | widths = "0.5 0.2 0.3" | | width: [0.5, 0.2, 0.3] |
| table-width | | | | table-width: 1.0 |
| header | header = yes no | header = yes no | has_header: True False | header: True False yes NO |
| markdown | | inlinemarkdown | | markdown: True False yes NO |
| source | source | file | source | include |
| others | type = simple multiline grid pipe | delimiter
quotechar
id (wrapped by div) | | |
| Notes | | | | width are auto-calculated when width is not specified |