

SQL NULL Functions

[< Previous](#)[Next >](#)

SQL IFNULL(), ISNULL(), COALESCE(), and NVL()

Functions

Look at the following "Products" table:

P_Id	ProductName	UnitPrice	UnitsInStock	UnitsOnOrder
1	Jarlsberg	10.45	16	15
2	Mascarpone	32.56	23	
3	Gorgonzola	15.67	9	20

Suppose that the "UnitsOnOrder" column is optional, and may contain NULL values.

Look at the following SELECT statement:

```
SELECT ProductName, UnitPrice * (UnitsInStock + UnitsOnOrder)
FROM Products;
```

In the example above, if any of the "UnitsOnOrder" values are NULL, the result will be NULL.

Solutions

MySQL

The **MySQL IFNULL()** function lets you return an alternative value if an expression is NULL:

```
SELECT ProductName, UnitPrice * (UnitsInStock + IFNULL(UnitsOnOrder, 0))  
FROM Products;
```

or we can use the **COALESCE()** function, like this:

```
SELECT ProductName, UnitPrice * (UnitsInStock + COALESCE(UnitsOnOrder, 0))  
FROM Products;
```

SQL Server

The SQL Server **ISNULL()** function lets you return an alternative value when an expression is NULL:

```
SELECT ProductName, UnitPrice * (UnitsInStock + ISNULL(UnitsOnOrder, 0))  
FROM Products;
```

or we can use the **COALESCE()** function, like this:

```
SELECT ProductName, UnitPrice * (UnitsInStock + COALESCE(UnitsOnOrder, 0))  
FROM Products;
```

MS Access

The MS Access `IsNull()` function returns TRUE (-1) if the expression is a null value, otherwise FALSE (0):

```
SELECT ProductName, UnitPrice * (UnitsInStock + IIF(IsNull(UnitsOnOrder), 0, UnitsOnOrder))  
FROM Products;
```

Oracle

The Oracle `NVL()` function achieves the same result:

```
SELECT ProductName, UnitPrice * (UnitsInStock + NVL(UnitsOnOrder, 0))  
FROM Products;
```

or we can use the `COALESCE()` function, like this:

```
SELECT ProductName, UnitPrice * (UnitsInStock + COALESCE(UnitsOnOrder, 0))  
FROM Products;
```

[< Previous](#)[Next >](#)

