

[JAVA TUTORIAL](#)[#INDEX POSTS](#)[#INTERVIEW QUESTIONS](#)[RESOURCES](#)[HIRE ME](#)[DOWNLOAD ANDROID APP](#)[CONTRIBUTE](#)[HOME](#) » [INTERVIEW QUESTIONS](#) » JDBC INTERVIEW QUESTIONS AND ANSWERS

JDBC Interview Questions and Answers

APRIL 2, 2018 BY [PANKAJ](#) — [34 COMMENTS](#)

Welcome to JDBC Interview Questions and Answers. JDBC API is used to connect to relational databases and run SQL queries from Java Programs. In last few articles, we learned about JDBC API and it's important features. This article is aimed to provide some of the important JDBC Interview Questions with Answers to help you in [Java interview](#).

JDBC Interview Questions



1. What is JDBC API and when do we use it?
2. What are different types of JDBC Drivers?
3. How does JDBC API helps us in achieving loose coupling between Java Program and JDBC Drivers API?
4. What is JDBC Connection? Explain steps to get Database connection in a simple java program.
5. What is the use of JDBC DriverManager class?
6. How to get the Database server details in java program?
7. What is JDBC Statement?
8. What is the difference between execute, executeQuery, executeUpdate?
9. What is JDBC PreparedStatement?
10. How to set NULL values in JDBC PreparedStatement?
11. What is the use of getGeneratedKeys() method in Statement?
12. What are the benefits of PreparedStatement over Statement?
13. What is the limitation of PreparedStatement and how to overcome it?
14. What is JDBC ResultSet?

15. What are different types of ResultSet?
16. What is the use of setFetchSize() and setMaxRows() methods in Statement?
17. How to use JDBC API to call Stored Procedures?
18. What is JDBC Batch Processing and what are its benefits?
19. What is JDBC Transaction Management and why do we need it?
20. How to rollback a JDBC transaction?
21. What is JDBC Savepoint? How to use it?
22. What is JDBC DataSource and what are its benefits?
23. How to achieve JDBC Connection Pooling using JDBC DataSource and JNDI in Apache Tomcat Server?
24. What is Apache DBCP API?
25. What is JDBC Connection isolation levels?
26. What is JDBC RowSet? What are different types of RowSet?
27. What is the difference between ResultSet and RowSet?
28. What are common JDBC Exceptions?
29. What is CLOB and BLOB datatypes in JDBC?
30. What is "dirty read" in JDBC? Which isolation level prevents dirty read?
31. What is 2 phase commit?
32. What are the different types of locking in JDBC?
33. What do you understand by DDL and DML statements?
34. What is difference between java.util.Date and java.sql.Date?
35. How to insert an image or raw data into database?
36. What is phantom read and which isolation level prevents it?
37. What is SQL Warning? How to retrieve SQL warnings in the JDBC program?
38. How to invoke Oracle Stored Procedure with Database Objects as IN/OUT?
39. When do we get java.sql.SQLException: No suitable driver found?
40. What are JDBC Best Practices?

JDBC Interview Questions and Answers


1. What is JDBC API and when do we use it?

Java DataBase Connectivity API allows us to work with relational databases. JDBC API interfaces and classes are part of `java.sql` and `javax.sql` package. We can use JDBC API to get the database connection, run SQL queries and stored procedures in the database server and process the results.

JDBC API is written in a way to allow loose coupling between our Java program and actual JDBC drivers that makes our life easier in switching from one database to another database servers easily.

2. What are different types of JDBC Drivers?

There are four types of JDBC drivers. Any java program that works with database has two parts, first part is the JDBC API and second part is the driver that does the actual work.



1. **JDBC-ODBC Bridge plus ODBC Driver (Type 1):** It uses ODBC driver to connect to database. We should have ODBC drivers installed to connect to database, that's why this driver is almost obsolete.
2. **Native API partly Java technology-enabled driver (Type 2):** This driver converts JDBC class to the client API for the database servers. We should have database client API installed. Because of extra dependency on database client API drivers, this is also not preferred driver.
3. **Pure Java Driver for Database Middleware (Type 3):** This driver sends the JDBC calls to a middleware server that can connect to different type of databases. We should have a middleware server installed to work with this driver. This adds to extra network calls and slow performance and that's why not widely used JDBC driver.
4. **Direct-to-Database Pure Java Driver (Type 4):** This driver converts the JDBC calls to the network protocol understood by the database server. This solution is simple and suitable for database connectivity over the network. However for this solution, we should use database specific drivers, for example OJDBC jars by Oracle for Oracle DB and MySQL Connector/J for MySQL databases.

3. **How does JDBC API helps us in achieving loose coupling between Java Program and JDBC Drivers API?**

JDBC API uses **Java Reflection API** to achieve loose coupling between java programs and JDBC Drivers. If you look at a simple JDBC example, you will notice that all the programming is done in terms of JDBC API and Driver comes in picture only when it's loaded through reflection using `Class.forName()` method.

I think this is one of the best example of using Reflection in core java classes to make sure that our application doesn't work directly with Drivers API and that makes it very easy to move from one database to another. Please read more at [JDBC Example](#).

4. What is JDBC Connection? Explain steps to get Database connection in a simple java program.

JDBC Connection is like a Session created with the database server. You can also think Connection is like a **Socket connection** from the database server.

Creating a JDBC Connection is very easy and requires two steps:

1. Register and Load the Driver: Using `Class.forName()`, Driver class is registered to the DriverManager and loaded in the memory.
2. Use DriverManager to get the Connection object: We get connection object from `DriverManager.getConnection()` by passing Database URL String, username and password as argument.

```
Connection con = null;
try{
    // load the Driver Class
    Class.forName("com.mysql.jdbc.Driver");

    // create the connection now
    con = DriverManager.getConnection("jdbc:mysql://localhost:3306/UserDB",
                                     "pankaj",
                                     "pankaj123");
}catch (SQLException e) {
    System.out.println("Check database is UP and configs are
```

```
correct");  
                e.printStackTrace();  
            }catch (ClassNotFoundException e) {  
                System.out.println("Please include JDBC MySQL jar in  
classpath");  
                e.printStackTrace();  
            }  
        }  
    }  
}
```

5. What is the use of JDBC DriverManager class?

JDBC `DriverManager` is the factory class through which we get the Database Connection object. When we load the JDBC Driver class, it registers itself to the `DriverManager`, you can look up the JDBC Driver classes source code to check this.

Then when we call `DriverManager.getConnection()` method by passing the database configuration details, `DriverManager` uses the registered drivers to get the `Connection` and return it to the caller program.

6. How to get the Database server details in java program?

We can use `DatabaseMetaData` object to get the database server details. When the database connection is created successfully, we can get the meta data object by calling `getMetaData()` method. There are so many methods in `DatabaseMetaData` that we can use to get the database product name, its version and configuration details.

```
DatabaseMetaData metaData = con.getMetaData();  
String dbProduct = metaData.getDatabaseProductName();
```

7. What is JDBC Statement?

JDBC API **Statement** is used to execute SQL queries in the database. We can create the Statement object by calling Connection `createStatement()` method. We can use Statement to execute static SQL queries by passing query through different execute methods such as `execute()`, `executeQuery()`, `executeUpdate()` etc.

Since the query is generated in the java program, if the user input is not properly validated it can lead to SQL injection issue, more details can be found at [SQL Injection Example](#).

By default, only one ResultSet object per Statement object can be open at the same time. Therefore, if we want to work with multiple ResultSet objects, then each must have been generated by different Statement objects. All `execute()` methods in the Statement interface implicitly close a statment's current ResultSet object if an open one exists.

8. What is the difference between execute, executeQuery, executeUpdate?

Statement `execute(String query)` is used to execute any SQL query and it returns TRUE if the result is an ResultSet such as running Select queries. The output is FALSE when there is no ResultSet object such as running Insert or Update queries. We can use `getResultSet()` to get the ResultSet and `getUpdateCount()` method to retrieve the update count.

Statement `executeQuery(String query)` is used to execute Select queries and returns the ResultSet. ResultSet returned is never null even if there are no records matching the query. When executing select queries we should use `executeQuery` method so that if someone tries to execute insert/update statement it will throw `java.sql.SQLException` with message "executeQuery method can not be used for update".

Statement `executeUpdate(String query)` is used to execute Insert/Update/Delete (DML) statements or DDL statements that returns nothing. The output is int and equals to the row count for SQL Data Manipulation Language (DML) statements. For DDL statements, the output is 0.

You should use `execute()` method only when you are not sure about the type of statement else use `executeQuery` or `executeUpdate` method.

9. **What is JDBC PreparedStatement?**

JDBC `PreparedStatement` object represents a precompiled SQL statement. We can use its setter method to set the variables for the query.

Since `PreparedStatement` is precompiled, it can then be used to efficiently execute this statement multiple times. `PreparedStatement` is better choice than `Statement` because it automatically escapes the special characters and avoid SQL injection attacks.

10. **How to set NULL values in JDBC PreparedStatement?**

We can use `PreparedStatement setNull()` method to bind the null variable to a parameter. The `setNull` method takes index and SQL Types as argument, for example

```
ps.setNull(10, java.sql.Types.INTEGER);
```

11. **What is the use of getGeneratedKeys() method in Statement?**

Sometimes a table can have auto generated keys used to insert the unique column value for primary key. We can use `Statement getGeneratedKeys()` method to get the value of this auto generated key.

12. **What are the benefits of PreparedStatement over Statement?**

Some of the benefits of PreparedStatement over Statement are:

- PreparedStatement helps us in preventing SQL injection attacks because it automatically escapes the special characters.
- PreparedStatement allows us to execute dynamic queries with parameter inputs.
- PreparedStatement is faster than Statement. It becomes more visible when we reuse the PreparedStatement or use its batch processing methods for executing multiple queries.
- PreparedStatement helps us in writing object Oriented code with setter methods whereas with Statement we have to use String Concatenation to create the query. If there are multiple parameters to set, writing Query using String concatenation looks very ugly and error prone.

13. **What is the limitation of PreparedStatement and how to overcome it?**

One of the limitation of PreparedStatement is that we can't use it directly with IN clause statements. Some of the alternative approaches to use PreparedStatement with IN clause are;

1. **Execute Single Queries** – very slow performance and not recommended
2. **Using Stored Procedure** – Database specific and hence not suitable for multiple database applications.
3. **Creating PreparedStatement Query dynamically** – Good approach but loses the benefit of cached PreparedStatement.
4. **Using NULL in PreparedStatement Query** – A good approach when you know the maximum number of variables inputs, can be extended to allow unlimited parameters by executing in parts.

A more detailed analysis can be found at [JDBC PreparedStatement IN clause alternatives](#).

14. **What is JDBC ResultSet?**

JDBC **ResultSet** is like a table of data representing a database result set, which is usually generated by executing a statement that queries the database.

ResultSet object maintains a cursor pointing to its current row of data. Initially the cursor is positioned before the first row. The `next()` method moves the cursor to the next row. If there are no more rows, `next()` method returns false and it can be used in a while loop to iterate through the result set.

A default ResultSet object is not updatable and has a cursor that moves forward only. Thus, you can iterate through it only once and only from the first row to the last row. It is possible to produce ResultSet objects that are scrollable and/or updatable using below syntax.

```
Statement stmt = con.createStatement(ResultSet.TYPE_SCROLL_INSENSITIVE,  
                                     ResultSet.CONCUR_UPDATABLE);
```

A ResultSet object is automatically closed when the Statement object that generated it is closed, re-executed, or used to retrieve the next result from a sequence of multiple results.

We can use ResultSet getter method with column name or index number starting from 1 to retrieve the column data.

15. What are different types of ResultSet?

There are different types of ResultSet objects that we can get based on the user input while creating the Statement. If you will look into the Connection methods, you will see that `createStatement()` and `prepareStatement()` method are overloaded to provide ResultSet type and **concurrency** as input argument.

There are three types of ResultSet object.

1. **ResultSet.TYPE_FORWARD_ONLY**: This is the default type and cursor can only move forward in the result set.
 2. **ResultSet.TYPE_SCROLL_INSENSITIVE**: The cursor can move forward and backward, and the result set is not sensitive to changes made by others to the database after the result set was created.
 3. **ResultSet.TYPE_SCROLL_SENSITIVE**: The cursor can move forward and backward, and the result set is sensitive to changes made by others to the database after the result set was created.
- Based on the concurrency there are two types of ResultSet object.

1. **ResultSet.CONCUR_READ_ONLY**: The result set is read only, this is the default concurrency type.
2. **ResultSet.CONCUR_UPDATABLE**: We can use ResultSet update method to update the rows data.

16. What is the use of `setFetchSize()` and `setMaxRows()` methods in Statement?

We can use `setMaxRows(int i)` method to limit the number of rows that the database returns from the query. You can achieve the same thing using SQL query itself. For example in MySQL we can use LIMIT clause to set the max rows that will be returned by the query.

Understanding **fetchSize** can be tricky, for that you should know how Statement and ResultSet works. When we execute a query in the database, the result is obtained and maintained in the database cache and ResultSet is returned. ResultSet is the cursor that has the reference to the result in the database.

Let's say we have a query that returns 100 rows and we have set fetchSize to 10, so in every database trip JDBC driver will fetch only 10 rows and hence there will be 10 trips to fetch all the rows. Setting optimal fetchSize is helpful when you need a lot of processing time for each row and number of rows in the result is huge.

We can set fetchSize through Statement object but it can be overridden through ResultSet object setFetchSize() method.

17. How to use JDBC API to call Stored Procedures?

Stored Procedures are group of SQL queries that are compiled in the database and can be executed from JDBC API. JDBC `CallableStatement` can be used to execute stored procedures in the database. The syntax to initialize CallableStatement is;

```
CallableStatement stmt = con.prepareCall("{call insertEmployee(?,?,?,?,?,?)}");
stmt.setInt(1, id);
stmt.setString(2, name);
stmt.setString(3, role);
stmt.setString(4, city);
stmt.setString(5, country);

//register the OUT parameter before calling the stored procedure
stmt.registerOutParameter(6, java.sql.Types.VARCHAR);

stmt.executeUpdate();
```

We need to register the OUT parameters before executing the CallableStatement. More details about this can be found at [JDBC CallableStatement Example](#).

18. What is JDBC Batch Processing and what are its benefits?

Sometimes we need to run bulk queries of similar kind for a database, for example loading data from CSV files to relational database tables. As we know that we have option to use Statement or

PreparedStatement to execute queries. Apart from that JDBC API provides Batch Processing feature through which we can execute bulk of queries in one go for a database.

JDBC API supports batch processing through Statement and PreparedStatement `addBatch()` and `executeBatch()` methods.

Batch Processing is faster than executing one statement at a time because the number of database calls are less, read more at [JDBC Batch Processing Example](#).

19. What is JDBC Transaction Management and why do we need it?

By default when we create a database connection, it runs in auto-commit mode. It means that whenever we execute a query and it's completed, the commit is fired automatically. So every SQL query we fire is a transaction and if we are running some DML or DDL queries, the changes are getting saved into database after every SQL statement finishes.

Sometimes we want a group of SQL queries to be part of a transaction so that we can commit them when all the queries runs fine and if we get any exception, we have a choice of rollback all the queries executed as part of the transaction.

JDBC API provide method `setAutoCommit(boolean flag)` through which we can disable the auto commit feature of the connection. We should disable auto commit only when it's required because the transaction will not be committed unless we call the `commit()` method on connection. Database servers uses table locks to achieve transaction management and it's resource intensive process. So we should commit the transaction as soon as we are done with it. Read more with example program at [JDBC Transaction Management Example](#).

20. How to rollback a JDBC transaction?

We can use Connection object `rollback()` method to rollback the transaction. It will rollback all the changes made by the transaction and release any database locks currently held by this Connection object.

21. **What is JDBC Savepoint? How to use it?**

Sometimes a transaction can be group of multiple statements and we would like to rollback to a particular point in the transaction. JDBC Savepoint helps us in creating checkpoints in a transaction and we can rollback to that particular checkpoint.

Any savepoint created for a transaction is automatically released and become invalid when the transaction is committed, or when the entire transaction is rolled back. Rolling a transaction back to a savepoint automatically releases and makes invalid any other savepoints that were created after the savepoint in question. Read more at [JDBC Savepoint Example](#).

22. **What is JDBC DataSource and what are it's benefits?**

JDBC DataSource is the interface defined in `javax.sql` package and it is more powerful than DriverManager for database connections. We can use DataSource to create the database connection and Driver implementation classes does the actual work for getting connection. Apart from getting Database connection, DataSource provides some additional features such as:

- Caching of PreparedStatement for faster processing
- Connection timeout settings
- Logging features
- ResultSet maximum size threshold
- Connection Pooling in servlet container using JNDI support

Read more about DataSource at [JDBC DataSource Example](#).

23. How to achieve JDBC Connection Pooling using JDBC DataSource and JNDI in Apache Tomcat Server?

For web applications deployed in a servlet container, creating JDBC connection pool is very easy and involve only few steps.

1. Creating JDBC JNDI resource in the container configuration files, usually server.xml or context.xml. For example

server.xml

```
<Resource name="jdbc/MyDB"
    global="jdbc/MyDB"
    auth="Container"
    type="javax.sql.DataSource"
    driverClassName="com.mysql.jdbc.Driver"
    url="jdbc:mysql://localhost:3306/UserDB"
    username="pankaj"
    password="pankaj123"

    maxActive="100"
    maxIdle="20"
    minIdle="5"
    maxWait="10000"/>
```

context.xml


```
<ResourceLink name="jdbc/MyLocalDB"
              global="jdbc/MyDB"
              auth="Container"
              type="javax.sql.DataSource" />
```

2. In web application, using InitialContext to look up the JNDI resource configured in the first step and then get the connection.

```
Context ctx = new InitialContext();
DataSource ds = (DataSource) ctx.lookup("java:/comp/env/jdbc/MyLocalDB");
```

For a complete example, read [Tomcat DataSource JNDI Example](#).

24. What is Apache DBCP API?

If you use `DataSource` to get the Database connection, usually the code to get the connection is tightly coupled with the Driver specific `DataSource` implementation. Also most of the code is boiler-plate code except the choice of the `DataSource` implementation class.

Apache DBCP helps us in getting rid of these issues by providing `DataSource` implementation that works as an abstraction layer between our program and different JDBC drivers. Apache DBCP library depends on Commons Pool library, so make sure they both are in the build path.

For a complete example, read [Apache DBCP Example](#).

25. What is JDBC Connection isolation levels?

When we use JDBC Transactions for data integrity, DBMS uses locks to block access by others to the data being accessed by the transaction. DBMS uses locks to prevent Dirty Read, Non-Repeatable Reads and Phantom-Read issue.

JDBC transaction isolation level is used by DBMS to use the locking mechanism, we can get the isolation level information through Connection `getTransactionIsolation()` method and set it with `setTransactionIsolation()` method.

ISOLATION LEVEL	TRANSACTION	DIRTY READ	NON-REPEATABLE READ	PHANTOM READ
TRANSACTION_NONE	Not Supported	Not Applicable	Not Applicable	Not Applicable
TRANSACTION_READ_COMMITTED	Supported	Prevented	Allowed	Allowed
TRANSACTION_READ_UNCOMMITTED	Supported	Allowed	Allowed	Allowed
TRANSACTION_REPEATABLE_READ	Supported	Prevented	Prevented	Allowed
TRANSACTION_SERIALIZABLE	Supported	Prevented	Prevented	Prevented

26. What is JDBC RowSet? What are different types of RowSet?

JDBC **RowSet** holds tabular data in more flexible ways than **ResultSet**. All **RowSet** objects are derived from **ResultSet**, so they have all the capabilities of **ResultSet** with some additional features. **RowSet** interface is defined in `javax.sql` package.

Some additional features provided by RowSet are:

- Functions as Java Beans with properties and their getter-setter methods. RowSet uses JavaBeans event model and they can send notifications to any registered component for events such as cursor movement, update/insert/delete of a row and change to RowSet contents.
- RowSet objects are scrollable and updatable by default, so if DBMS doesn't support scrollable or updatable ResultSet, we can use RowSet to get these features.

RowSet are broadly divided into two types:

1. **Connected RowSet Objects** – These objects are connected to database and are most similar to ResultSet object. JDBC API provides only one connected RowSet object `javax.sql.rowset.JdbcRowSet` and its standard implementation class is `com.sun.rowset.JdbcRowSetImpl`
2. **Disconnected RowSet Objects** – These RowSet objects are not required to connected to a database, so they are more lightweight and serializable. They are suitable for sending data over a network. There are four types of disconnected RowSet implementations.
 - **CachedRowSet** – They can get the connection and execute a query and read the ResultSet data to populate the RowSet data. We can manipulate and update data while it is disconnected and reconnect to database and write the changes.
 - **WebRowSet** derived from **CachedRowSet** – They can read and write XML document.
 - **JoinRowSet** derived from **WebRowSet** – They can form SQL JOIN without having to connect to a data source.
 - **FilteredRowSet** derived from **WebRowSet** – We can apply filtering criteria so that only selected data is visible.

27. What is the different between ResultSet and RowSet?

RowSet objects are derived from ResultSet, so they have all the features of ResultSet with some additional features. One of the huge benefit of RowSet is that they can be disconnected and that makes it lightweight and easy to transfer over a network.

Whether to use ResultSet or RowSet depends on your requirements but if you are planning to use ResultSet for longer duration, then a disconnected RowSet is better choice to free database resources.

28. **What are common JDBC Exceptions?**

Some of the common JDBC Exceptions are:

1. java.sql.SQLException – This is the base exception class for JDBC exceptions.
2. java.sql.BatchUpdateException – This exception is thrown when Batch operation fails, but it depends on the JDBC driver whether they throw this exception or the base SQLException.
3. java.sql.SQLWarning – For warning messages in SQL operations.
4. java.sql.DataTruncation – when a data values is unexpectedly truncated for reasons other than its having exceeded MaxFieldSize.

29. **What is CLOB and BLOB datatypes in JDBC?**

Character Large Objects (CLOBs) are character string made up of single-byte characters with an associated code page. This data type is appropriate for storing text-oriented information where the amount of information can grow beyond the limits of a regular VARCHAR data type (upper limit of 32K bytes).

Binary Large Objects (BLOBs) are binary string made up of bytes with no associated code page. This data type can store binary data larger than VARBINARY (32K limit). This data type is good for storing image, voice, graphical, and other types of business or application-specific data.

30. **What is “dirty read” in JDBC? Which isolation level prevents dirty read?**

When we work with transactions, there is a chance that a row is updated and at the same time other query can read the updated value. This results in a dirty read because the updated value is not permanent yet, the transaction that has updated the row can rollback to previous value resulting in invalid data.

Dirty Read is prevented by isolation levels TRANSACTION_READ_COMMITTED, TRANSACTION_REPEATABLE_READ and TRANSACTION_SERIALIZABLE.

31. **What is 2 phase commit?**

When we work in distributed systems where multiple databases are involved, we are required to use 2 phase commit protocol. 2 phase commit protocol is an atomic commitment protocol for distributed systems. In the first phase, transaction manager sends commit-request to all the transaction resources. If all the transaction resources are OK, then transaction manager commits the transaction changes for all the resources. If any of the transaction resource responds as Abort, then the transaction manager can rollback all the transaction changes.

32. **What are the different types of locking in JDBC?**

On a broad level, there are two types of locking mechanism to prevent data corruption because of more than one user working with the same data.

1. Optimistic Locking – This locking is achieved with code. A extra column is introduced in the table to keep count of updates. When you select the row, you read this column too, say 'version'. Now when you are trying to update/delete the row, you pass this 'version' in the where clause. So if there are updates from other threads performed in between, the update will fail. It's a good way

to avoid data corruption but it can be error prone if someone missed to update the 'version' in their update statement. The update query looks something like below in this way of locking.

```
mysql> update emp SET name = 'David', version = 5 WHERE id = 10 and version = 4;
```

2. Pessimistic Locking – Locking the record from the select to read, update and commit phase. This is usually done by database vendor software and triggered by use of **SELECT FOR UPDATE** query. This way of locking the row can lead to slow performance and dead lock if threads are handling the lock for longer time.

Apart from that some DBMS systems provide locking mechanism to lock single row, table or database.

33. **What do you understand by DDL and DML statements?**

Data Definition Language (DDL) statements are used to define the database schema. Create, Alter, Drop, Truncate, Rename statements comes under DDL statements and usually they don't return any result.

Data Manipulation Language (DML) statements are used to manipulate data in the database schema. Select, Insert, Update, Delete, Call etc are example of DML statements.

34. **What is difference between java.util.Date and java.sql.Date?**

java.util.Date contains information about the date and time whereas java.sql.Date contains information only about the date, it doesn't have time information. So if you have to keep time information in the database, it is advisable to use Timestamp or DateTime fields.

35. **How to insert an image or raw data into database?**

We can use BLOB to insert image or raw binary data into database.

36. **What is phantom read and which isolation level prevents it?**

A phantom read is the situation where a transaction executes a query multiple times and get different data. Suppose a transaction is executing a query to get data based on a condition and then another transaction inserts a row that matches the condition. Now when same transaction will execute the query again, a new row will be part of the result set. This new row is referred as Phantom Row and this situation is termed as Phantom Read.

Phantom read can be prevented only with TRANSACTION_SERIALIZABLE isolation level.

37. **What is SQL Warning? How to retrieve SQL warnings in the JDBC program?**

SQLWarning is the subclass of SQLException and we can retrieve it by calling getWarnings() method on Connection, Statement, and ResultSet objects. SQL Warnings doesn't stops the execution of the script but alerts the user about the warning.

38. **How to invoke Oracle Stored Procedure with Database Objects as IN/OUT?**

If Oracle Stored Procedure has IN/OUT parameters as DB Objects then we need to create an Object array of the same size in the program and then use it to create Oracle STRUCT object. Then we can set this STRUCT object for the database object by calling setSTRUCT() method and work with it.

39. **When do we get java.sql.SQLException: No suitable driver found?**

You get No suitable driver found exception when the SQL URL String is not properly formatted. You can get this exception in both simple java application using DriverManager or with JNDI resource using DataSource. The exception stack trace looks like below.

```
org.apache.tomcat.dbcp.dbcp.SQLNestedException: Cannot create JDBC driver of class
'com.mysql.jdbc.Driver' for connect URL 'jdbc:mysql://localhost:3306/UserDB'
    at
org.apache.tomcat.dbcp.dbcp.BasicDataSource.createConnectionFactory(BasicDataSource.

    at
org.apache.tomcat.dbcp.dbcp.BasicDataSource.createDataSource(BasicDataSource.java:13

    at
org.apache.tomcat.dbcp.dbcp.BasicDataSource.getConnection(BasicDataSource.java:1044)

java.sql.SQLException: No suitable driver found for
'jdbc:mysql://localhost:3306/UserDB'
    at java.sql.DriverManager.getConnection(DriverManager.java:604)
    at java.sql.DriverManager.getConnection(DriverManager.java:221)
    at com.journaldev.jdbc.DBConnection.getConnection(DBConnection.java:24)
    at com.journaldev.jdbc.DBConnectionTest.main(DBConnectionTest.java:15)
Exception in thread "main" java.lang.NullPointerException
    at com.journaldev.jdbc.DBConnectionTest.main(DBConnectionTest.java:16)
```

While debugging this exception, just check the URL getting printed in the logs, as in above logs the URL String is 'jdbc:mysql://localhost:3306/UserDB' whereas it should be 'jdbc:mysql://localhost:3306/UserDB'.

40. What are JDBC Best Practices?

Some of the JDBC Best Practices are:

- Database resources are heavy, so make sure you close it as soon as you are done with it. Connection, Statement, ResultSet and all other JDBC objects have close() method defined to close them.
- Always close the result set, statement and connection explicitly in the code, because if you are working in connection pooling environment, the connection might be returned to the pool leaving open result sets and statement objects resulting in resource leak.
- Close the resources in the finally block to make sure they are closed even in case of exception scenarios.
- Use batch processing for bulk operations of similar kind.
- Always use PreparedStatement over Statement to avoid SQL Injection and get pre-compilation and caching benefits of PreparedStatement.
- If you are retrieving bulk data into result set, setting an optimal value for fetchSize helps in getting good performance.
- The database server might not support all isolation levels, so check it before assuming.
- More strict isolation levels result in slow performance, so make sure you have optimal isolation level set for your database connections.
- If you are creating database connections in a web application, try to use JDBC DataSource resources using JNDI context for re-using the connections.
- Try to use disconnected RowSet when you need to work with ResultSet for a long time.

Thats all for JDBC interview questions and answers, I hope it will help you in JDBC interviews. Let me know if I have missed any important question and I will add it to the list.

FILED UNDER: [DATABASE](#), [INTERVIEW QUESTIONS](#), [JAVA](#)

About Pankaj

If you have come this far, it means that you liked what you are reading. Why not reach little more and connect with me directly on [Google Plus](#), [Facebook](#) or [Twitter](#). I would love to hear your thoughts and opinions on my articles directly.

Recently I started creating video tutorials too, so do check out my videos on [Youtube](#).

[« Java PreparedStatement IN clause alternatives](#)[JavaMail Example – Send Mail in Java using SMTP »](#)

Comments

mayur says

NOVEMBER 13, 2017 AT 10:30 PM

Great post! I think really these are frequently asked JDBC interview questions and answers which are simply helpful and important for freshers along with experienced Java developers. Thanks for sharing such a great list here!

[Reply](#)**NEERAJ SHARMA says**

SEPTEMBER 17, 2017 AT 7:38 PM

Question 7 needs correction : `getStatement()` should be changed to `createStatement()`;
Question 32 : Optimistic Locking does not lock the record .instead it provides version number and timestamp to see if record is required to have change or not ...please correct the answer...

[Reply](#)**Pankaj says**

SEPTEMBER 17, 2017 AT 8:01 PM

I really appreciate the time you took in reading and the comment. Both the points mentioned has been corrected with additional details provided for locking mechanism. Thanks again!

[Reply](#)

rahul says

SEPTEMBER 14, 2017 AT 1:49 PM

Sir Seriously ! you are Sir ! __/__ thanks .

[Reply](#)**Anurag Singh says**

JULY 24, 2017 AT 3:06 AM

this is really very informative article for me.

nice work.

really i like this..

[Reply](#)**Shalini says**

OCTOBER 24, 2016 AT 9:02 AM

Thank you very much. Your article helped me get a job!!

[Reply](#)**Pankaj says**

OCTOBER 24, 2016 AT 11:20 AM

Wow, I am really happy for you.

[Reply](#)

Reshma says

OCTOBER 16, 2016 AT 12:18 PM

Thank you for he effort. This article gives a good overview of the JDBC api.

[Reply](#)

Sahaj says

AUGUST 25, 2015 AT 11:26 AM

Thank you very much.

Please add

1.Which design pattern has been used by JDBC.

[Reply](#)

rohit says

SEPTEMBER 2, 2015 AT 5:01 PM

please give the answer?

[Reply](#)

Anand Loni says

MAY 13, 2016 AT 8:28 AM

JDBC uses Bridge design pattern

[Reply](#)

Nandhini says

MAY 20, 2015 AT 2:14 AM

A good collection of JDBC keypoints

[Reply](#)

dinesh says

MARCH 24, 2015 AT 5:32 AM

hi pankaj ,

i want to ask one thing if result set is interface where is the implementation of next() method

[Reply](#)

dinesh says

MARCH 24, 2015 AT 5:29 AM

the best one

[Reply](#)

Mallikarjun says

NOVEMBER 21, 2014 AT 3:06 AM

Is JDBC is an acronym of Java DataBase Connectivity

[Reply](#)

rohit says

AUGUST 3, 2017 AT 7:40 PM

yes, obviously

[Reply](#)

Ravindra Nehra says

OCTOBER 21, 2014 AT 8:13 AM

Hi, Pankaj u posted very good questions which i have recently faced in my interview, i want a simple insurance project developed using java, Spring, Hibernate so can u suggest me from wher can i get it with code.

Thanks.

[Reply](#)

Abhinav Jayaram says

JULY 23, 2014 AT 9:51 AM

Good post helped a lot

[Reply](#)

Sc says

JULY 7, 2014 AT 1:43 AM

Hi, I am unable to unlock the remaining questions in JDBC section

Thanks

[Reply](#)

Pankaj says

JULY 7, 2014 AT 4:15 AM

I just tested it out for facebook and google plus and its working.

[Reply](#)

Unknown says

JULY 17, 2014 AT 3:33 AM

nice questions also put new question from java 8 and some other question from ee 7 beacuse there is some missing questions in servlets so please put typical questions in servlets and jsp quesions thank u

[Reply](#)

Allwyn says

JULY 4, 2014 AT 11:41 AM

Hey Panjaj,

Please let me know how to unlock the questions. I am following you on Twitter.

[Reply](#)

HIMANSU NAYAK says

JUNE 2, 2014 AT 6:22 AM

What is the use of JDBC DriverManager class?

Driver Manager can be also used to register and de-register driver manually instead of static block registering.

[Reply](#)

HIMANSU NAYAK says

JUNE 2, 2014 AT 5:53 AM

Hi Pankaj,

I have used Type1 and Type4 in my previous projects.

Type1: using ODBC driver to connect to access database from a java application

Type4. almost all my project.

Can you please tell me in which all real time scenario we can use Type 2 and Type 3 ?

Thank you

[Reply](#)

jaihind saini says

MAY 21, 2014 AT 11:54 AM

Its good article for JDBC interview preparation

[Reply](#)

varma says

MAY 15, 2014 AT 2:03 AM

Its Good Article

[Reply](#)

Vinoth says

FEBRUARY 20, 2014 AT 6:03 AM

Hi ,

First of all thank for this post. If you add examples for types of JDBC Drivers, it would be fine.

[Reply](#)

Rishi Raj says

FEBRUARY 18, 2014 AT 5:13 AM

Hi Pankaj,

Thanks for questionnaire.

In second JDBC best practice "Always close the result set, statement and connection implicitly in the code, ...", do you mean to say "explicitly" instead of "implicitly"?

Please confirm.

Reply

Pankaj says

FEBRUARY 18, 2014 AT 11:19 PM

Yes, we should close it explicitly. Thanks for pointing out the error, corrected.

Reply

Siddu says

FEBRUARY 5, 2014 AT 4:48 AM

Could you post about build tool like ant/maven tool.

Reply

Siddu says

FEBRUARY 5, 2014 AT 4:46 AM

I would like to add few more questions in jdbc.

These are the question asked in interview.

Could you please explain.

- 1) How to get the connection object by using third type of jdbc driver.
- 2) How resultset works, I mean selected records how it will store at java app side?
- 3) How to load java class at oracle database or how can i can call java methods from oracle?
- 4) What is mock objects?
- 5) Say suppose I have implemented connection pooling with size is 10 connections limited, How it will hanlde when there more than 10 users start using connection.

Reply

Pankaj says

FEBRUARY 5, 2014 AT 4:52 AM

Thanks for providing some more questions, I will try to add these to the list in sometime.

Reply

Siddu says

FEBRUARY 6, 2014 AT 8:56 AM

Thank U.

Reply

Ate says

OCTOBER 30, 2017 AT 5:23 AM

Kindly provide the answers for the above questions

Reply

Leave a Reply

Your email address will not be published. Required fields are marked *

Comment

Name *

Email *

☐

Save my name, email, and website in this browser for the next time I comment.

POST COMMENT

DOWNLOAD ANDROID APP



CORE JAVA TUTORIAL

Java 10 Tutorials Java 9 Tutorials
Java 8 Tutorials Java 7 Tutorials Core
Java Basics OOPS Concepts Data
Types and Operators String Manipulation
Java Arrays Annotation and Enum
Java Collections Java IO Operations
Java Exception Handling
MultiThreading and Concurrency
Regular Expressions Advanced Java
Concepts

IMPORTANT INTERVIEW QUESTIONS

Java Interview Questions

- > [Core Java Interview Questions](#)
- > [String Interview Questions](#)
- > [Multithreading Interview Questions](#)
- > [Collections Interview Questions](#)
- > [Exception Interview Questions](#)
- > [Java Programming Interview Questions](#)
- > [Java 8 Interview Questions Part 1](#)
- > [Java 8 Interview Questions Part 2](#)
- > [Servlet Interview Questions](#)
- > [JSP Interview Questions](#)
- > [Struts 2 Interview Questions](#)
- > [JDBC Interview Questions](#)
- > [Spring Interview Questions](#)
- > [Hibernate Interview Questions](#)
- > [JSF Interview Questions](#)
- > [Web Services Interview Questions](#)
- > [Scala Basic Interview Questions](#)
- > [Scala Intermediate Interview Questions](#)
- > [Scala Advanced Interview Questions](#)
- > [Scala Interview Questions Summary](#)
- > [Common Job Interview Questions](#)

Miscellaneous

- > [Java ClassLoader](#)
- > [String StringBuffer StringBuilder](#)
- > [Java is Pass By Value](#)

- > [Java Heap vs Stack Memory](#)

RECOMMENDED TUTORIALS

Java Tutorials

- > [Java IO](#)
- > [Java Regular Expressions](#)
- > [Multithreading in Java](#)
- > [Java Logging](#)
- > [Java Annotations](#)
- > [Java XML](#)
- > [Collections in Java](#)
- > [Java Generics](#)
- > [Exception Handling in Java](#)
- > [Java Reflection](#)
- > [Java Design Patterns](#)
- > [JDBC Tutorial](#)

Java EE Tutorials

- > [Servlet JSP Tutorial](#)
- > [Struts2 Tutorial](#)
- > [Spring Tutorial](#)
- > [Hibernate Tutorial](#)
- > [Primefaces Tutorial](#)
- > [Apache Axis 2](#)
- > [JAX-RS](#)
- > [Memcached Tutorial](#)

Database Integration

SQL Server Database

ASP Database

SQL Server 2018

Database Programs

Client Database

Java Software

Java Programming

