

[JAVA TUTORIAL](#)[#INDEX POSTS](#)[#INTERVIEW QUESTIONS](#)[RESOURCES](#)[HIRE ME](#)[DOWNLOAD ANDROID APP](#)[CONTRIBUTE](#)**Subscribe to Download Java Design Patterns eBook****DOWNLOAD NOW**[HOME](#) » [HIBERNATE](#) » HIBERNATE SESSION GET() VS LOAD() DIFFERENCE WITH EXAMPLES

Hibernate Session get() vs load() difference with examples

APRIL 2, 2018 BY [PANKAJ](#) — [23 COMMENTS](#)

Hibernate Session provide different methods to fetch data from database. Two of them are – **get()** and **load()**. There are also a lot of overloaded methods for these, that we can use in different circumstances.

At first look both `get()` and `load()` seems similar because both of them fetch the data from database, however there are few differences between them, let's look at them with a simple example.

```
package com.journaldev.hibernate.main;

import org.hibernate.Session;
import org.hibernate.SessionFactory;
import org.hibernate.Transaction;

import com.journaldev.hibernate.model.Employee;
import com.journaldev.hibernate.util.HibernateUtil;
```

```

public class HibernateGetVsLoad {

    public static void main(String[] args) {

        //Prep Work
        SessionFactory sessionFactory = HibernateUtil.getSessionFactory();
        Session session = sessionFactory.openSession();
        Transaction tx = session.beginTransaction();

        //Get Example
        Employee emp = (Employee) session.get(Employee.class, new Long(2));
        System.out.println("Employee get called");
        System.out.println("Employee ID= "+emp.getId());
    }
}

```

When I execute above code, it produces following output.

```

Hibernate: select employee0_.emp_id as emp_id1_1_0_, employee0_.emp_name as
emp_name2_1_0_, employee0_.emp_salary as emp_sala3_1_0_, address1_.emp_id as
emp_id1_0_1_, address1_.address_line1 as address_2_0_1_, address1_.city as city3_0_1_,
address1_.zipcode as zipcode4_0_1_ from EMPLOYEE employee0_ left outer join ADDRESS
address1_ on employee0_.emp_id=address1_.emp_id where employee0_.emp_id=?

```

Employee **get** called

Employee ID= 2

Employee **Get** Details:: Id= 2, Name= David, Salary= 200.0, {Address= AddressLine1= Arques Ave, City=Santa Clara, Zipcode=95051}

Employee **load** called

Employee ID= 1

```

Hibernate: select employee0_.emp_id as emp_id1_1_0_, employee0_.emp_name as
emp_name2_1_0_, employee0_.emp_salary as emp_sala3_1_0_, address1_.emp_id as
emp_id1_0_1_, address1_.address_line1 as address_2_0_1_, address1_.city as city3_0_1_,
address1_.zipcode as zipcode4_0_1_ from EMPLOYEE employee0_ left outer join ADDRESS
address1_ on employee0_.emp_id=address1_.emp_id where employee0_.emp_id=?

```

Employee **load** Details:: Id= 1, Name= Pankaj, Salary= 100.0, {Address= AddressLine1= Albany Dr, City=San Jose, Zipcode=95129}

From the output it's clear that `get()` returns the object by fetching it from database or from **hibernate cache** whereas `load()` just returns the reference of an object that might not actually exists, it loads the data from database or cache only when you access other properties of the object.

Now let's try to fetch data that doesn't exists in the database.

```
//Get Example
try{
Employee emp = (Employee) session.get(Employee.class, new Long(200));
System.out.println("Employee get called");
if(emp != null){
System.out.println("Employee GET ID= "+emp.getId());
System.out.println("Employee Get Details:: "+emp+"\n");
}
}catch(Exception e){
e.printStackTrace();
}

//load Example
try{
Employee emp1 = (Employee) session.load(Employee.class, new Long(100));
System.out.println("Employee load called");
System.out.println("Employee LOAD ID= "+emp1.getId());
System.out.println("Employee load Details:: "+emp1+"\n");
}catch(Exception e){
e.printStackTrace();
}
```

Above code produces following output.

```
Hibernate: select employee0_.emp_id as emp_id1_1_0_, employee0_.emp_name as
emp_name2_1_0_, employee0_.emp_salary as emp_sala3_1_0_, address1_.emp_id as
emp_id1_0_1_, address1_.address_line1 as address_2_0_1_, address1_.city as
city3_0_1_, address1_.zipcode as zipcode4_0_1_ from EMPLOYEE employee0_ left outer
join ADDRESS address1_ on employee0_.emp_id=address1_.emp_id where
employee0_.emp_id=?
Employee get called
Employee load called
Employee LOAD ID= 100
Hibernate: select employee0_.emp_id as emp_id1_1_0_, employee0_.emp_name as
emp_name2_1_0_, employee0_.emp_salary as emp_sala3_1_0_, address1_.emp_id as
emp_id1_0_1_, address1_.address_line1 as address_2_0_1_, address1_.city as
city3_0_1_, address1_.zipcode as zipcode4_0_1_ from EMPLOYEE employee0_ left outer
join ADDRESS address1_ on employee0_.emp_id=address1_.emp_id where
employee0_.emp_id=?
org.hibernate.ObjectNotFoundException: No row with the given identifier exists:
[com.journaldev.hibernate.model.Employee#100]
at
```

```
org.hibernate.internal.SessionFactoryImpl$1$1.handleEntityNotFound(SessionFactoryImpl.j
```

```
at
```

Look at the output closely, when we use `get()` to retrieve data that doesn't exist, it returns **null**. That makes sense because it tries to load the data as soon as it's called.

With `load()`, we are able to print the id but as soon as we try to access other fields, it fires database query and throws `org.hibernate.ObjectNotFoundException` if there is no record found with the given identifier. It's hibernate specific **RuntimeException**, so we don't need to catch it explicitly.

Let's look at some of the overloaded methods too. Above **get()** and **load()** methods could have been written as below too.

```
Employee emp = (Employee) session.get("com.journaldev.hibernate.model.Employee", new  
Long(2));
```

```
Employee emp1 = (Employee) session.load("com.journaldev.hibernate.model.Employee", new  
Long(1));
```

```
Employee emp2 = new Employee();  
session.load(emp1, new Long(1));
```

There are other methods with `LockOptions` argument but I haven't used them. Notice that we need to pass full class name as argument.

Based on the above explanations we have following differences between **get()** vs **load()**:

1. `get()` loads the data as soon as it's called whereas `load()` returns a proxy object and loads data only when it's actually required, so `load()` is better because it supports lazy loading.
2. Since `load()` throws exception when data is not found, we should use it only when we know data exists.
3. We should use `get()` when we want to make sure data exists in the database.

That's all for hibernate get and load methods, I hope it will clear some doubts and help you in deciding which one to use in different scenarios.

**« PREVIOUS**[Hibernate Named Query Example – @NamedQuery](#)**NEXT »**[\[Solved\] org.hibernate.AnnotationException: No identifier specified for entity Class](#)**About Pankaj**

If you have come this far, it means that you liked what you are reading. Why not reach little more and connect with me directly on [Google Plus](#), [Facebook](#) or [Twitter](#). I would love to hear your thoughts and opinions on my articles directly.

Recently I started creating video tutorials too, so do check out my videos on [Youtube](#).

FILED UNDER: [HIBERNATE](#)

Comments**venky says**[MAY 7, 2018 AT 11:14 PM](#)

```
try{
Employee emp1 = (Employee) session.load(Employee.class, new Long(100));
System.out.println("Employee load called");
if(null!=emp1){
System.out.println("Employee LOAD ID= "+emp1.getId());
System.out.println("Employee load Details:: "+emp1+"\n");
}
}catch(Exception e){
e.printStackTrace();
}
above load method will throw error or not?
```

[Reply](#)

yashwanth potu says

APRIL 1, 2017 AT 5:13 PM

Thanks pankaj,It's precise and very explanatory

[Reply](#)

aman verma says

JANUARY 6, 2017 AT 11:36 AM

any other differences for load() and get() ?

[Reply](#)

Vinod Kumar says

OCTOBER 21, 2016 AT 8:31 AM

As Toral says that even we get the ID then it check for database. But In your explanation the query not hitting on getting ID. When I check in my system when I get ID is hitting database first after printing Id. Why is this please let me know

[Reply](#)

Rakshit says

AUGUST 4, 2016 AT 1:32 AM

well explained

[Reply](#)

Sreekanth says

JULY 5, 2016 AT 10:46 PM

Good Explanation ..

[Reply](#)**preeti chauhan says**

MAY 25, 2016 AT 5:49 PM

ya, i m very much staisfy with the above explanation.

[Reply](#)**NikhiJini says**

FEBRUARY 14, 2016 AT 8:53 PM

thanks

[Reply](#)**Vijay Jetti says**

APRIL 29, 2016 AT 12:01 AM

Thanks dude

[Reply](#)**Aakash Deep Sharma says**

NOVEMBER 22, 2015 AT 7:45 AM

best explanation for this topic

[Reply](#)**kriti sinha says**

SEPTEMBER 12, 2015 AT 12:28 AM

Best explanation i ever got for this concept.

[Reply](#)

Sudeshna says

AUGUST 13, 2015 AT 8:34 AM

Very clear and concise. Thank you.

[Reply](#)**Annu Upadhuaya says**

JULY 17, 2015 AT 4:50 AM

Hi Pankaj,

Thank you so much for explaining it so perfectly. It helped me a lot.

[Reply](#)**Ravi says**

JUNE 10, 2015 AT 5:25 AM

it's very good explanation

[Reply](#)**Dorel says**

MAY 28, 2015 AT 8:21 PM

Well, quite bad explained, read more about get and load.

I will ask you: why not use ONLY .get() since it will retrieve the object or return null and forget about .load()?

[Reply](#)**RW says**

FEBRUARY 17, 2015 AT 6:32 AM

Very well explained. Have a look at <http://www.aurorasolutions.io/get-and-load-methods-in-hibernate-2/> . It's also one of the good ones.

[Reply](#)**Sumit Chauhan says**

JANUARY 15, 2015 AT 3:51 AM

Good Explanation. Such an good example cleared the doubts.

[Reply](#)**Suresh Kumar Pandey says**

DECEMBER 10, 2014 AT 1:12 AM

I used the same example and i am seeing there is no difference between the load and get apart from that

load() returns ObjectNotFoundException() and get() returns null pointer exception.

[Reply](#)**Suresh Kumar Pandey says**

DECEMBER 10, 2014 AT 1:20 AM

Sorry for the comment above. I had missed the if else part. Thanks for the nice explanation.

[Reply](#)**Harman says**

DECEMBER 15, 2014 AT 8:48 AM

Thanks for explanation

[Reply](#)**Gurdeep Singh says**

NOVEMBER 10, 2014 AT 7:42 PM

Good Example...thanks for sharing

[Reply](#)**Toral says**

SEPTEMBER 24, 2014 AT 11:38 AM

That's a great example. Clears the concept well. However, even in case of load, we cannot retrieve the Id. I understand that to fetch any of the attributes including Id, a check is made in the database and the data retrieved. So, if the required record is not available, it will throw Object not found exception.

Please correct me if the understanding is wrong.

[Reply](#)

Vimal Kumar says

SEPTEMBER 22, 2014 AT 4:46 AM

Great!!! Seriously cleared my concept. Great Explanation with practical proofs

[Reply](#)

Leave a Reply

Your email address will not be published. Required fields are marked *

Comment

Name *

Email *

☐

Save my name, email, and website in this browser for the next time I comment.

POST COMMENT

[DOWNLOAD ANDROID APP](#)



HIBERNATE FRAMEWORK

Hibernate Tutorial

- > [Hibernate Example](#)
- > [Hibernate SessionFactory](#)
- > [Hibernate Session get load](#)
- > [Hibernate Session save](#)
- > [HQL Example](#)
- > [Hibernate Criteria](#)
- > [Hibernate SQL](#)
- > [Hibernate Named Query](#)
- > [Hibernate Log4J](#)
- > [Hibernate Validator](#)
- > [Hibernate Tomcat DataSource](#)

Hibernate Mapping

- > [Hibernate One to One Mapping](#)
- > [Hibernate One to Many Mapping](#)
- > [Hibernate Many to Many Join Tables](#)

Hibernate Caching

- > [Hibernate Cache](#)
- > [Hibernate EHCACHE](#)

Hibernate Integrations

- > [Hibernate Spring](#)
- > [Hibernate Spring MVC](#)
- > [Hibernate Struts 2](#)
- > [Hibernate Primefaces](#)
- > [Hibernate Primefaces Spring](#)
- > [Hibernate SpringRoo Primefaces](#)
- > [Hibernate JSF Spring](#)

Miscellaneous

- > [Hibernate Tools Eclipse Plugin](#)
- > [Hibernate Configuration Offline](#)
- > [\[Solved\] No identifier specified](#)
- > [Hibernate Program Not Terminating](#)

- > [Access to DialectResolutionInfo](#)
- > [get is not valid](#)
- > [No CurrentSessionContext configured](#)
- > [Hibernate Interview Questions](#)

RECOMMENDED TUTORIALS

Java Tutorials

- > [Java IO](#)
- > [Java Regular Expressions](#)
- > [Multithreading in Java](#)
- > [Java Logging](#)
- > [Java Annotations](#)
- > [Java XML](#)
- > [Collections in Java](#)
- > [Java Generics](#)
- > [Exception Handling in Java](#)
- > [Java Reflection](#)
- > [Java Design Patterns](#)
- > [JDBC Tutorial](#)

Java EE Tutorials

- > [Servlet JSP Tutorial](#)
- > [Struts2 Tutorial](#)
- > [Spring Tutorial](#)
- > [Hibernate Tutorial](#)
- > [Primefaces Tutorial](#)
- > [Apache Axis 2](#)
- > [JAX-RS](#)
- > [Memcached Tutorial](#)

Employee Vacation Tracking

Onboarding New Employees

Employee Communication Apps

How to Retain Employees

Hiring Good Employees

Employee Engagement Activities

Employee Engagement Surveys

Employee Benefits Information



© 2018 · Privacy Policy · Don't copy, it's Bad Karma · P