

JAVA TUTORIAL	#INDEX POSTS	#INTERVIEW QUESTIONS	RESOURCES	HIRE ME	DOWNLOAD ANDROID APP	CONTRIBUTE	
---------------	--------------	----------------------	-----------	---------	----------------------	------------	--

Subscribe to Download Java Design Patterns eBook

Full name

name@example.com

DOWNLOAD NOW

HOME » SPRING » SPRING VALIDATION EXAMPLE – SPRING MVC FORM VALIDATOR

# Spring Validation Example – Spring MVC Form Validator


APRIL 2, 2018 BY PANKAJ — 53 COMMENTS

When we accept user inputs in any web application, it become necessary to validate them. We can validate the user input at client side using JavaScript but it's also necessary to validate them at server side to make sure we are processing valid data incase user has javascript disabled.

Table of Contents [\[hide\]](#)

- 1 Spring Validation
- 2 Spring MVC Form Validator
  - 2.1 Deployment Descriptor
  - 2.2 Spring Bean Configuration File
  - 2.3 Model Classes
  - 2.4 Custom Validator Implementations
  - 2.5 Controller Classes
  - 2.6 Form Validation Error Messages Resource Bundle
  - 2.7 View Pages with Form and Errors
  - 2.8 Test the Spring MVC Form Validation Application


## Spring Validation



**Spring MVC Framework** supports JSR-303 specs by default and all we need is to add JSR-303 and its implementation dependencies in Spring MVC application. Spring also provides `@Validator` annotation and `BindingResult` class through which we can get the errors raised by Validator implementation in the controller request handler method.

We can create our custom validator implementations by two ways – first one is to create an annotation that confirms to the JSR-303 specs and implement its Validator class. Second approach is to implement the `org.springframework.validation.Validator` interface and add set it as validator in the Controller class using `@InitBinder` annotation.

Let's create a simple Spring MVC project in Spring Tool Suite where we will use JSR-303 specs with its implementation artifact **hibernate-validator**. We will use annotation based form validation and create our own custom validator based on JSR-303 specs standards. We will also create our own custom validator class by implementing `Validator` interface and use it in one of the controller handler methods. Our final project looks like below image.



Let's look at each of the components one by one.

## Spring MVC Form Validator

Our final pom.xml file looks like below. Apart from standard Spring MVC artifacts, we have validation-api and hibernate-validator dependencies in the project.

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
  http://maven.apache.org/maven-v4_0_0.xsd">
  <modelVersion>4.0.0</modelVersion>
  <groupId>com.journaldev</groupId>
  <artifactId>spring</artifactId>
  <name>SpringFormValidation</name>
  <packaging>war</packaging>
  <version>1.0.0-BUILD-SNAPSHOT</version>
  <properties>
    <java-version>1.7</java-version>
```

```

<org.springframework-version>4.0.2.RELEASE</org.springframework-
version>

<org.aspectj-version>1.7.4</org.aspectj-version>
<org.slf4j-version>1.7.5</org.slf4j-version>
</properties>
<dependencies>
<!-- Form Validation using Annotations -->
<dependency>
<groupId>javax.validation</groupId>

```

## Deployment Descriptor

When you create Spring MVC project from STS, it creates two context configuration files. I have cleaned it up a bit and have only one spring bean configuration file. My final web.xml file looks like below.

```

<?xml version="1.0" encoding="UTF-8"?>
<web-app version="2.5" xmlns="http://java.sun.com/xml/ns/javaee"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://java.sun.com/xml/ns/javaee
http://java.sun.com/xml/ns/javaee/web-app_2_5.xsd">

  <!-- Processes application requests -->
  <servlet>
    <servlet-name>appServlet</servlet-name>
    <servlet-
class>org.springframework.web.servlet.DispatcherServlet</servlet-class>
    <init-param>
      <param-name>contextConfigLocation</param-name>
      <param-value>/WEB-INF/spring/spring.xml</param-value>
    </init-param>
    <load-on-startup>1</load-on-startup>
  </servlet>

  <servlet-mapping>
    <servlet-name>appServlet</servlet-name>
    <url-pattern>/</url-pattern>
  </servlet-mapping>

```

## Spring Bean Configuration File

Usually we look into spring wirings at the last, but this time we don't have much configurations in the spring bean configuration file. Our final spring.xml file looks like below.

```

<?xml version="1.0" encoding="UTF-8"?>
<beans:beans xmlns="http://www.springframework.org/schema/mvc"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:beans="http://www.springframework.org/schema/beans"
  xmlns:context="http://www.springframework.org/schema/context"
  xsi:schemaLocation="http://www.springframework.org/schema/mvc
http://www.springframework.org/schema/mvc/spring-mvc.xsd
  http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans.xsd
  http://www.springframework.org/schema/context
http://www.springframework.org/schema/context/spring-context.xsd">

  <!-- DispatcherServlet Context: defines this servlet's request-processing

```

```

infrastructure -->

<!-- Enables the Spring MVC @Controller programming model -->
<annotation-driven />

<!-- Handles HTTP GET requests for /resources/** by efficiently serving up
static resources in the ${webappRoot}/resources directory -->
<resources mapping="/resources/**" location="/resources/" />

```

The only important point to note are `employeeValidator` bean that we will inject into one of the controller and `messageSource` bean to read the localized data from resource bundles. Rest of the part is to support annotations, view resolvers and providing package to scan for Controller classes and other components.

## Model Classes

We have two model classes in this project – first one where we will use JSR-303 annotation and our custom annotation based validator and second one where we will use only our Validator implementation.

Customer.java code:

```

package com.journaldev.spring.form.model;

import java.util.Date;

import javax.validation.constraints.Max;
import javax.validation.constraints.Min;
import javax.validation.constraints.NotNull;
import javax.validation.constraints.Past;
import javax.validation.constraints.Size;

import org.hibernate.validator.constraints.Email;
import org.hibernate.validator.constraints.NotEmpty;
import org.springframework.format.annotation.DateTimeFormat;

import com.journaldev.spring.form.validator.Phone;

public class Customer {

    @Size(min=2, max=30)
    private String name;

    @NotEmpty @Email

```

Notice that we are using `@Email`, `@NotEmpty` and `@DateTimeFormat` annotations that are additional to JSR-303 and provided by hibernate validator implementation. Some of the JSR-303 annotations that we are using are `@Size`, `@NotNull` etc.

`@Phone` annotation used is our custom implementation based on JSR-303 specs, we will look into it in next section.

Employee.java code:

```
package com.journaldev.spring.form.model;

public class Employee {

    private int id;
    private String name;
    private String role;

    public int getId() {
        return id;
    }
    public void setId(int id) {
        this.id = id;
    }
    public String getName() {
        return name;
    }
    public void setName(String name) {
        this.name = name;
    }
    public String getRole() {
        return role;
    }
}
```

Employee is a standard java bean and we will use our custom Validator implementation to validate the form with Employee bean.

## Custom Validator Implementations

Phone.java code:

```
package com.journaldev.spring.form.validator;

import java.lang.annotation.Documented;
import java.lang.annotation.Retention;
import java.lang.annotation.Target;
import java.lang.annotation.ElementType;
import java.lang.annotation.RetentionPolicy;

import javax.validation.Constraint;
import javax.validation.Payload;

@Documented
@Constraint(validatedBy = PhoneValidator.class)
@Target( { ElementType.METHOD, ElementType.FIELD })
@Retention(RetentionPolicy.RUNTIME)
public @interface Phone {

    String message() default "{Phone}";

    Class<?>[] groups() default {};
}
```

Most of the part is boiler-plate code to confirm with JSR-303 specs. The most important part is @Constraint annotation where we provide the class that will be used for validation i.e PhoneValidator.

PhoneValidator.java code:

```
package com.journaldev.spring.form.validator;

import javax.validation.ConstraintValidator;
import javax.validation.ConstraintValidatorContext;

public class PhoneValidator implements ConstraintValidator<Phone, String> {

    @Override
    public void initialize(Phone paramA) {
    }

    @Override
    public boolean isValid(String phoneNo, ConstraintValidatorContext ctx) {
        if(phoneNo == null){
            return false;
        }
        //validate phone numbers of format "1234567890"
        if (phoneNo.matches("\\d{10}")) return true;
        //validating phone number with -, . or spaces
        else if(phoneNo.matches("\\d{3}[-\\.\\s]\\d{3}[-\\.\\s]\\d{4}")) return true;
        //validating phone number with extension length from 3 to 5
        else if(phoneNo.matches("\\d{3}-\\d{3}-\\d{4}\\s(x|(ext))\\d{3,5}")) return
```

Our JSR-303 specs validator implementation should implement `javax.validation.ConstraintValidator` interface. If we are using some resource such as `DataSource`, we can initialize them in the `initialize()` method. The validation method is `isValid` and it returns true if data is valid else it should return false.

If you are new to regular expressions, you can read more about it at [Java Regular Expressions Tutorial](#).

EmployeeFormValidator.java class code:

```
package com.journaldev.spring.form.validator;

import org.springframework.validation.Errors;
import org.springframework.validation.ValidationUtils;
import org.springframework.validation.Validator;

import com.journaldev.spring.form.model.Employee;

public class EmployeeFormValidator implements Validator {

    //which objects can be validated by this validator
    @Override
    public boolean supports(Class<?> paramClass) {
        return Employee.class.equals(paramClass);
    }

    @Override
    public void validate(Object obj, Errors errors) {
        ValidationUtils.rejectIfEmptyOrWhitespace(errors, "id",
            "id.required");
    }
}
```

EmployeeFormValidator is the validator implementation that is specific to [Spring Framework](#). `supports()` method implementation by Spring Framework to know objects on which this validation can be used.

We implement `validate()` method and add errors if any field validation fails. Spring provides `org.springframework.validation.ValidationUtils` utility class for basic validations such as null or empty. Once this method returns, spring framework binds the Errors object to the BindingResult object that we use in our controller handler method.

Notice that `ValidationUtils.rejectIfEmptyOrWhitespace()` last argument takes the key name for message resources. This way we can provide localized error messages to the user. For more information about i18n in Spring, read [Spring i18n Example](#).

## Controller Classes

We have two controller classes, one for annotation based form validation and another for our custom validator.

CustomerController.java class code:

```
package com.journaldev.spring.form.controllers;

import java.util.HashMap;
import java.util.Map;

import javax.validation.Valid;

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.validation.BindingResult;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RequestMethod;

import com.journaldev.spring.form.model.Customer;

@Controller
public class CustomerController {

    private static final Logger logger = LoggerFactory
        .getLogger(CustomerController.class);
```

When we use annotation based form validation, we just need to make little changes in our controller handler method implementation to get it working.

First we need to annotate model object that we want to validate with `@Valid` annotation. Then we need to have BindingResult argument in the method, spring takes care of populating it with error messages. The handler method logic is very simple, if there are any errors we are responding with the same page or else we are redirecting user to the success page.

Another important point to note is that we are adding "customer" attribute to the model, this is necessary to let Spring framework know which model object to use in the form page. If we won't do it, object binding to form data will not take place and our form validation will not work.

EmployeeController.java class code:

```

package com.journaldev.spring.form.controllers;

import java.util.HashMap;
import java.util.Map;

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.beans.factory.annotation.Qualifier;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.validation.BindingResult;
import org.springframework.validation.Validator;
import org.springframework.validation.annotation.Validated;
import org.springframework.web.bind.WebDataBinder;
import org.springframework.web.bind.annotation.InitBinder;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RequestMethod;

import com.journaldev.spring.form.model.Employee;

```

For using custom validator, first we need to inject it in the controller class. We are using **spring bean auto wiring** to achieve this using `@Autowired` and `@Qualifier` annotations.

Next we need to have a method that will take `WebDataBinder` as argument and we set our custom validator to be used. This method should be annotated with `@InitBinder` annotation.

Using `@ModelAttribute` is another way to add our bean object to the Model. Rest of the code is similar to customer controller implementation.

## Form Validation Error Messages Resource Bundle

It's time to look at our resource bundle where we have different types of messages to be used for validation errors.

message\_en.properties file:

```

#application defined error messages
id.required=Employee ID is required
name.required=Employee Name is required
role.required=Employee Role is required
negativeValue={0} can't be negative or zero

#Spring framework error messages to be used when conversion from form data to bean fails
typeMismatch.int={0} Value must be an integer
typeMismatch.java.lang.Integer={0} must be an integer
typeMismatch={0} is of invalid format

#application messages for annotations, {ValidationClass}.{modelName}.{field}
#the {0} is field name, other fields are in alphabetical order, max and then min
Size.customer.name=Customer {0} should be between {2} and {1} characters long
NotEmpty.customer.email=Email is a required field

```



```
NotNull.customer.age=Customer {0} should be in years
```

```
#Generic annotation class messages
Email=Email address is not valid
NotNull=This is a required field
NotEmpty=This is a required field
```

I have provided message key details in the comment itself, so I will skip them here. The only important point to note here is the way messages will be looked up, first key name [ValidationClass].[modelName].[fieldName] is looked up and if that is not found then [ValidationClass].[modelName] is looked up. If that is missing, then finally [ValidationClass] key is looked up. If nothing is found then the default message provided will be returned.

Read more about resource messages at [Spring Localization Example](#).

## View Pages with Form and Errors

Since we are using Spring framework validation implementation, we will have to use Spring Form tags to get the errors and set the form bean and variable names.

Our custSave.jsp file code is given below.

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>
<!DOCTYPE html PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
<%@ taglib uri="http://www.springframework.org/tags/form"
    prefix="springForm"%>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>Customer Save Page</title>
<style>
.error {
    color: #ff0000;
    font-style: italic;
    font-weight: bold;
}
</style>
</head>
<body>

    <springForm:form method="POST" commandName="customer"
        action="save.do">
```

commandName="customer" is used to set the name of the model attribute under which form object is exposed. Its default value is "command" by default, hence we should set it to the model attribute name we are using in our controller classes.

springForm:errors is used to render the errors, if any, found when the page is rendered. path attribute is used to define the object property to be used for data binding. Rest of the code is standard HTML with some CSS for error messages styling.

Our custSaveSuccess.jsp file is given below.

```

<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>
<%@ taglib prefix="fmt" uri="http://java.sun.com/jsp/jstl/fmt" %>

<%@ page session="false" %>
<html>
<head>
    <title>Customer Saved Successfully</title>
</head>
<body>
<h3>
    Customer Saved Successfully.
</h3>

<strong>Customer Name:${customer.name}</strong><br>
<strong>Customer Email:${customer.email}</strong><br>
<strong>Customer Age:${customer.age}</strong><br>
<strong>Customer Gender:${customer.gender}</strong><br>
<strong>Customer Birthday:<fmt:formatDate value="${customer.birthday}" type="date" />
</strong><br>

</body>
</html>

```

Simple JSP page showing the customer values if there are no validation errors and this page is returned as response. It's name is empSave.jsp.

```

<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>
<!DOCTYPE html PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
<%@ taglib uri="http://www.springframework.org/tags/form"
    prefix="springForm"%>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>Employee Save Page</title>
<style>
.error {
    color: #ff0000;
    font-style: italic;
    font-weight: bold;
}
</style>
</head>
<body>

    <springForm:form method="POST" commandName="employee"
        action="save.do">

```

empSaveSuccess.jsp file:

```

<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>
<%@ page session="false" %>
<html>

```

```

<head>
    <title>Employee Saved Successfully</title>
</head>
<body>
<h3>
    Employee Saved Successfully.
</h3>

<strong>Employee ID:${emp.id}</strong><br>
<strong>Employee Name:${emp.name}</strong><br>
<strong>Employee Role:${emp.role}</strong><br>

</body>
</html>

```

## Test the Spring MVC Form Validation Application

Our application is ready to deploy and run some tests, deploy it in your favorite servlet container. I am using Apache Tomcat 7 and below images show some of the pages with validation error messages. Based on your input data, you might get different error messages too.

Customer Save Page

localhost:9090/SpringFormValidation/cust/save.do

Apps Java Utility Apple Android Personal JQuery Spring Database

Name:  *Customer name should be between 2 and 30 characters long*

Email:  *Email is a required field*

Age:  *Customer age should be in years*

Gender:  *This is a required field*

Birthday:  *This is a required field*

Phone:  *Invalid format, valid formats are 1234567890, 123-456-7890 x1234*

Customer Save Page

localhost:9090/SpringFormValidation/cust/save.do

Apps Java Utility Apple Android Personal JQuery Spring Database

Name:  *Customer name should be between 2 and 30 characters long*

Email:  *Email address is not valid*

Age:  *Customer age should be in years*

Gender:  *This is a required field*

Birthday:  *birthday is of invalid format*

Phone:  *Invalid format, valid formats are 1234567890, 123-456-7890 x1234*

Employee Save Page

localhost:9090/SpringFormValidation/emp/save.do

Apps Java Utility Apple Android Personal JQuery

Employee ID:  *'id' cant be negative or zero*

Employee Name:  *Employee Name is required*

Employee Role:  *Employee Role is required*

That's all for Spring MVC Form validation with different ways and using resource bundles for localized error messages. You can download the sample project from below link and play around with it to learn more.

[Download Spring Form Validation Project](#)

**« PREVIOUS**

Spring MVC Exception Handling –  
@ControllerAdvice, @ExceptionHandler,  
HandlerExceptionResolver

**NEXT »**

Spring MVC Interceptor  
HandlerInterceptorAdapter, HandlerInterceptor  
Example

**About Pankaj**

If you have come this far, it means that you liked what you are reading. Why not reach little more and connect with me directly on [Google Plus](#), [Facebook](#) or [Twitter](#). I would love to hear your thoughts and opinions on my articles directly.

Recently I started creating video tutorials too, so do check out my videos on [Youtube](#).

FILED UNDER: [SPRING](#)

**Comments****shan says**

DECEMBER 12, 2017 AT 4:43 AM

Hi,

The article is so good , but in real time no body will go for spring validation approach to validate form .  
client side validation is simple and good,  
any body really use spring validator for validation ?

[Reply](#)

**pastor Zion says**

DECEMBER 28, 2017 AT 5:22 AM

Hi Shan,

Client side validation could cause you unexpected troubles.The input field is an access door into the

heart of your app and controlling what gets in is very important. The trouble with doing validation with javascript is that it can be disabled at client side. For this singular reason consider server side validation.

[Reply](#)

**Arun Singh says**

NOVEMBER 26, 2017 AT 12:54 AM

explained in detail

thanks

[Reply](#)

**Manas Kumar says**

NOVEMBER 21, 2017 AT 10:45 AM

Cannot find class [com.journaldev.spring.form.validator.EmployeeFormValidator] for bean with name 'employeeValidator' defined in ServletContext resource [/WEB-INF/spring/spring.xml]; nested exception is java.lang.ClassNotFoundException: com.journaldev.spring.form.validator.EmployeeFormValidator  
I am getting this error while running. I have checked all possibilities but unable to resolve. Could you please help me??

[Reply](#)

**Ankit kumar gupta says**

FEBRUARY 27, 2017 AT 2:37 AM

please help me out in one problem related to validation

how to validate the Path Variable in spring application? if possible then please provide me example also.

[Reply](#)

**Aatif says**

NOVEMBER 30, 2016 AT 5:13 AM

localhost:8080/SpringFormValidation/emp/save.do showing HTTP 404 error. Not getting the form page.

!!A

[Reply](#)

**Praveen says**

DECEMBER 20, 2016 AT 10:30 PM

Aatif please try the below URL.

localhost:8080/spring/emp/save.do

[Reply](#)

**Farhan says**

OCTOBER 25, 2016 AT 11:33 PM

Hi Pankaj,

Thanks, example is good. I have two question regarding Spring MVC validation. I want to know how to register more than one validators for single command object by using @IntBinder annotated method so that I need not to call them explicitly in my controller method for validation. My second question is I want to use JSR 303 validation annotation such as @NotBlank as well as my own custom designed validation annotation for example @Phone ( which you have shown in this example) but these two validation are annotations are different then how can I use them without losing other one? Can I use @Valid @Validated to command argument of request handling method of controller or there is some other way. Wanting for your reply

[Reply](#)

**Stephane Eybert says**

JANUARY 25, 2017 AT 12:21 AM

You can have multiple @IntBinder("EntityNameMatchingTheOneToBeValidated") annotated methods with method names of your liking, and adding in each method the validator you need, that will be used for the entity type specified in the annotation attribute.

[Reply](#)

**IMRAN AHMAD says**

AUGUST 11, 2016 AT 4:56 AM

How to validation int array in server side in java spring

[Reply](#)

**kunal says**

JUNE 15, 2016 AT 8:45 PM

Hi,

Your articles are very useful.

I have tried to built the application and deploy it on JBOSS.

But I got an error " ERROR [org.apache.catalina.core.ContainerBase.[jboss.web].[defaultHost].[/spring-1.0.0-BUILD-SNAPSHOT]] (ServerService Thread Pool — 57) JBWEB00028g: Servlet spring threw load() exception: java.io.FileNotFoundException:

Could not open ServletContext resource [/WEB-INF/spring/spring.xml]" .

Could you please help me to resolve the same.

Thank you

[Reply](#)

**Pankaj says**

JUNE 16, 2016 AT 2:50 AM

It clearly says file not found, you need to see where is spring.xml file and whether it's being packaged in your WAR or not.

[Reply](#)

**David Adkins says**

MAY 18, 2016 AT 3:08 PM

Your tutorials are some of the best I have seen, Thank You

[Reply](#)

**IMRAN AHMAD says**

AUGUST 11, 2016 AT 4:58 AM

Please suggest how to validate int array in server side in java spring

[Reply](#)**koushal says**

APRIL 15, 2016 AT 3:24 AM

Thanks a lot , its very useful.

[Reply](#)**Dinesh Pise says**

NOVEMBER 30, 2015 AT 6:41 AM

Hi Pankaj,

Can we have custom validation and annotation validation together. Say for example in Customer I want to have annotation validation for all field except for age, for age I want to use validator class. Is that possible.

Regards,

Dinesh Pise

[Reply](#)**Zac C says**

SEPTEMBER 25, 2015 AT 2:36 PM

For the save page, when you run save.do, the number 0 is defaulted into the "Employee ID" field. How'd you get that to default to zero? What if I wanted employer name and employee role to default to null.

[Reply](#)**Zac C says**

SEPTEMBER 18, 2015 AT 2:57 PM

"When you create Spring MVC project from STS, it creates two context configuration files. I have cleaned it up a bit and have only one spring bean configuration file. My final web.xml file looks like below."

Where are the original two? I only see the one web.xml

[Reply](#)**Pankaj says**

SEPTEMBER 18, 2015 AT 10:45 PM

web.xml is deployment descriptor, spring.xml is the beans configuration file.

[Reply](#)**Zac C says**

SEPTEMBER 21, 2015 AT 8:16 AM

where is spring.xml?

[Reply](#)

**Zac C says**

SEPTEMBER 21, 2015 AT 8:52 AM

I found "spring.xml" by doing a google search and finding out my question is a common question. Therefore, I suggest you clarify that statement about the two config files. My "spring.xml" file is called "servlet-context.xml".

Reply

**Vinod Paliwal says**

AUGUST 16, 2015 AT 4:50 AM

Hi Pankaj Sir,

I do appreciate you each and every topics explanation as which helped a lot to develop my website. I have deployed the above project and without using pom.xml (means not maven) and facing below error.

Am i missing any jar file ?

Please provide your guide line .

```
org.springframework.beans.factory.BeanCreationException: Error creating bean with name
'org.springframework.web.servlet.mvc.annotation.DefaultAnnotationHandlerMapping#0': Initialization of
bean failed; nested exception is org.springframework.beans.factory.BeanCreationException: Error
creating bean with name 'customerController' defined in file
[D:\WORK\Spring3MVC4Site\metadata\plugins\org.eclipse.wst.server.core\tmp0\wtpwebapps\Spring3MVCFormValidation\WEB-
INF\classes\com\journaldev\spring\form\controllers\CustomerController.class]: Instantiation of bean
failed; nested exception is java.lang.NoClassDefFoundError: Could not initialize class
com.journaldev.spring.form.controllers.CustomerController
org.springframework.beans.factory.support.AbstractAutowireCapableBeanFactory.doCreateBean(AbstractAutowireCapableBeanFactory.java:5
org.springframework.beans.factory.support.AbstractAutowireCapableBeanFactory.createBean(AbstractAutowireCapableBeanFactory.java:450
org.springframework.beans.factory.support.AbstractBeanFactory$1.getObject(AbstractBeanFactory.java:290)
org.springframework.beans.factory.support.DefaultSingletonBeanRegistry.getSingleton(DefaultSingletonBeanRegistry.java:222)
org.springframework.beans.factory.support.AbstractBeanFactory.doGetBean(AbstractBeanFactory.java:287)
org.springframework.beans.factory.support.AbstractBeanFactory.getBean(AbstractBeanFactory.java:189)
org.springframework.beans.factory.support.DefaultListableBeanFactory.preInstantiateSingletons(DefaultListableBeanFactory.java:562)
org.springframework.context.support.AbstractApplicationContext.finishBeanFactoryInitialization(AbstractApplicationContext.java:871)
org.springframework.context.support.AbstractApplicationContext.refresh(AbstractApplicationContext.java:423)
org.springframework.web.servlet.FrameworkServlet.createWebApplicationContext(FrameworkServlet.java:443)
org.springframework.web.servlet.FrameworkServlet.createWebApplicationContext(FrameworkServlet.java:459)
org.springframework.web.servlet.FrameworkServlet.initWebApplicationContext(FrameworkServlet.java:340)
org.springframework.web.servlet.FrameworkServlet.initServletBean(FrameworkServlet.java:307)
org.springframework.web.servlet.HttpServletBean.init(HttpServletBean.java:127)
javax.servlet.GenericServlet.init(GenericServlet.java:160)
org.apache.catalina.authenticator.AuthenticatorBase.invoke(AuthenticatorBase.java:502)
org.apache.catalina.valves.ErrorReportValve.invoke(ErrorReportValve.java:99)
org.apache.catalina.valves.AccessLogValve.invoke(AccessLogValve.java:953)
org.apache.catalina.connector.CoyoteAdapter.service(CoyoteAdapter.java:408)
org.apache.coyote.http11.AbstractHttp11Processor.process(AbstractHttp11Processor.java:1023)
org.apache.coyote.AbstractProtocol$AbstractConnectionHandler.process(AbstractProtocol.java:589)
org.apache.tomcat.util.net.JIoEndpoint$SocketProcessor.run(JIoEndpoint.java:310)
java.util.concurrent.ThreadPoolExecutor$Worker.runTask(Unknown Source)
java.util.concurrent.ThreadPoolExecutor$Worker.run(Unknown Source)
java.lang.Thread.run(Unknown Source)
```

Thanks,

Vinod Paliwal



[Reply](#)**Andy says**

OCTOBER 13, 2015 AT 12:06 AM

update your hibernate-validator version and try again, this is work for me.

org.hibernate

hibernate-validator

5.1.0.Final

[Reply](#)**Hieu says**

AUGUST 11, 2015 AT 3:28 PM

I add new plugins in pom.xml

org.apache.tomcat.maven

tomcat7-maven-plugin

2.2

and

org.eclipse.jetty

jetty-maven-plugin

9.0.6.v20130930

/\${project.artifactId}

When I start tomcat by command : mvn tomcat7:run or mvn jetty-run. I have an error:

Caused by: java.lang.AbstractMethodError:

org.hibernate.validator.engine.ConfigurationImpl.getDefaultParameterNameProvider()Ljava/validation/ParameterNameProvider;

at sun.reflect.NativeMethodAccessorImpl.invoke(Native Method)

at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:57)

at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)

at java.lang.reflect.Method.invoke(Method.java:606)

at org.springframework.util.ReflectionUtils.invokeMethod(ReflectionUtils.java:196)

at org.springframework.util.ReflectionUtils.invokeMethod(ReflectionUtils.java:181)

at

org.springframework.validation.beanvalidation.LocalValidatorFactoryBean.configureParameterNameProviderIfPossible(LocalValidatorFactoryBean.java:245)

at

org.springframework.validation.beanvalidation.LocalValidatorFactoryBean.afterPropertiesSet(LocalValidatorFactoryBean.java:245)

at

org.springframework.validation.beanvalidation.OptionalValidatorFactoryBean.afterPropertiesSet(OptionalValidatorFactoryBean.java:40)

at

org.springframework.beans.factory.support.AbstractAutowireCapableBeanFactory.invokeInitMethods(AbstractAutowireCapableBeanFactory.java:156)

at

org.springframework.beans.factory.support.AbstractAutowireCapableBeanFactory.initializeBean(AbstractAutowireCapableBeanFactory.java:156)

... 66 more

Can you explain my error and how to fix it.

Thanks

[Reply](#)**Hieu says**

AUGUST 11, 2015 AT 3:33 PM

I add new plugins in pom.xml

For tomcat plugin

org.apache.tomcat.maven

tomcat7-maven-plugin

2.2

and for jetty plugin

org.eclipse.jetty

jetty-maven-plugin

9.0.6.v20130930

/\${project.artifactId}

When I start tomcat by command : mvn tomcat7:run or mvn jetty-run. I have an error:

Caused by: java.lang.AbstractMethodError:

org.hibernate.validator.engine.ConfigurationImpl.getDefaultParameterNameProvider()Ljava/lang/validation/ParameterNameP

at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)

at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:57)

at

sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)

at java.lang.reflect.Method.invoke(Method.java:606)

at org.springframework.util.ReflectionUtils.invokeMethod(ReflectionUtils.java:196)

at org.springframework.util.ReflectionUtils.invokeMethod(ReflectionUtils.java:181)

at

org.springframework.validation.beanvalidation.LocalValidatorFactoryBean.configureParameterNameProviderIfPossible(L

at

org.springframework.validation.beanvalidation.LocalValidatorFactoryBean.afterPropertiesSet(LocalValidatorFactoryBe

at

org.springframework.validation.beanvalidation.OptionalValidatorFactoryBean.afterPropertiesSet(OptionalValidatorFac

at

org.springframework.beans.factory.support.AbstractAutowireCapableBeanFactory.invokeInitMethods(AbstractAutowireCap

at

org.springframework.beans.factory.support.AbstractAutowireCapableBeanFactory.initializeBean(AbstractAutowireCapabl

... 66 more

Can you explain my error and how to fix it.

Thanks

[Reply](#)

### Vijay G says

AUGUST 10, 2015 AT 7:31 AM

Hi,

Please give me one solution in spring frame work for the below scenario,

1. If I click or submit any action in jsp, that action name should be configured against the controller in the spring config xml.
2. Once the flow has gone to Controller, ModelAndView will return success, failure or any constant string.
3. Based on that string, view will be redirected based on the configuration in the same config.
4. Different method name will be used in the same controller.

Problem should be addressed::

1. We have to identify the method name in the controller by action name and go to that method and come back to the spring config xml and redirect the view based on the string returned from the controller.

I am waiting for your response..

Thank You...

Vijay G

.

[Reply](#)

**Rajasekhar Balusupati says**

AUGUST 6, 2015 AT 10:52 AM

Very nice explanation, Pankaj!!

I have a situation to validate the date for Future and today!! We have @Future annotation. Can you please help me to validate today's date?

Appreciate your help. Thanks in advance!!

[Reply](#)**NHP says**

JUNE 17, 2015 AT 3:02 AM

Tomcat Server showing blank page when started from eclipse : 'Your Project is not working'

WARN : org.springframework.web.servlet.PageNotFound - No mapping found for HTTP request with URI [/spring/custSave] in DispatcherServlet with name 'appServlet'

[Reply](#)**bindu says**

MARCH 9, 2015 AT 3:10 AM

hi pankaj,well explained.

I am facing problem while running this project.My tomcat is going blank after running this project on eclipse usin tomcat:run in configuration.

Kindly let me know the reason this.

Outside of eclipse tomcat is running perfectly

[Reply](#)**Pankaj says**

MARCH 9, 2015 AT 3:17 AM

Hi Bindu,

If application is running fine when tomcat is not launched from Eclipse, it means everything is fine. I would suggest you to add a fresh server to Eclipse and try again, some issues with the current configured server might be causing this. Also check the URL in browser when app is launched in Eclipse.

[Reply](#)**abdul says**

DECEMBER 17, 2014 AT 11:52 PM

Thanks alot very helpful.

[Reply](#)**Max says**

DECEMBER 12, 2014 AT 9:03 AM

Hello, Pankaj!

Please, change the Hibernate version in dependency from 5 to 4:

org.hibernate

hibernate-validator

4.1.0.Final

[Reply](#)**Pankaj says**

DECEMBER 12, 2014 AT 9:57 AM

Thanks, corrected the typo error.

[Reply](#)**Kanika says**

DECEMBER 12, 2014 AT 3:14 AM

Could you include a snippet to give errors in a json result and include Ajax Request?

[Reply](#)**Adarsh says**

DECEMBER 27, 2016 AT 4:55 AM

Hi Kanika

The JSON request bind with JsonRequest of controller context

```
public override object BindModel(ControllerContext controllerContext,
    ModelBindingContext bindingContext)
```

```
{
    if (!IsJsonRequest(controllerContext))
```

```
{
    return base.BindModel(controllerContext, bindingContext);
}
```

pls see above code for manipulate the JSON Request

[Reply](#)**Sandeep says**

NOVEMBER 21, 2014 AT 10:57 PM

Thanks for the post, it is really helpful.

I was wondering how validation can be done in case we have @OneToMany mapping (say Employee class has Set of Address and none of the address field is inputted by the user from frontend, thus returning NULL to Spring MVC)?

Thanks in advance,

[Reply](#)**Adarsh says**

DECEMBER 27, 2016 AT 4:51 AM

Hi Sandeep,

@OneToMany mapping is totally depends on @Request Mapping of URL  
and NULL value is coming only on that case

Regards

Adarsh

[Reply](#)

**Ashirwad Kumar says**

OCTOBER 7, 2014 AT 2:10 AM

Not able to download the zip even after following on Twitter.

[Reply](#)**Rahul says**

OCTOBER 2, 2014 AT 8:56 PM

I see that you have defined a messageSource bean in your Spring bean configuration file. Where does this bean get used? I don't see a place where it gets auto wired. Can you please explain how Spring internally works to get messages from this bean. Is the bean name "messageSource" special to Spring MVC? Does this bean need to be named with that name?

[Reply](#)**Pankaj says**

OCTOBER 2, 2014 AT 9:59 PM

It's to load messages property files, it's used for localization, read more at

<https://www.journaldev.com/2610/spring-mvc-internationalization-i18n-and-localization-l10n-example>

You can keep any other name, but in that case you will have to bind it manually, with this name it's autowired.

[Reply](#)**Rahul says**

OCTOBER 4, 2014 AT 8:49 PM

Pankaj, thanks for the quick feedback. You are right. I just tried this. Yes I need to name the Message Source bean as "messageSource" for it to be picked up.

[Reply](#)**Dmytro says**

SEPTEMBER 16, 2014 AT 11:44 AM

Thank you for this useful tutorial!

Please add message.properties file to src/main/resources folder. Spring cannot resolve bound if there is no default properties file and client uses another locale. For example, for my locale "\_ru" I've got default text message or exception stack trace instead of text from message\_en.properties.

[Reply](#)**Pankaj says**

SEPTEMBER 16, 2014 AT 1:26 PM

Thanks for the suggestion.

[Reply](#)**Vlad says**

APRIL 17, 2018 AT 5:19 AM

I have default message from stack trace as well. What's wrong? I've added message.properties file to resources folder

[Reply](#)**kumar says**

JULY 29, 2014 AT 7:41 AM

hi pankaj very nice explanation ...

could you post webservice example.wre webservices r useful in real time?

[Reply](#)**dev says**

JULY 22, 2014 AT 10:54 PM

such nice deep concept.....

[Reply](#)**Tanuja says**

JULY 17, 2014 AT 4:31 AM

Really great concepts of validation thanks a lot.....

[Reply](#)**santhosh says**

JULY 16, 2014 AT 12:13 AM

Your site is really good with the examples provided for java and spring framework.

Could you post an article on Spring AOP concepts using annotations

[Reply](#)**Pankaj says**

JULY 16, 2014 AT 2:52 AM

Its already posted, check the Spring category articles.

[Reply](#)**Anil says**

JULY 6, 2014 AT 5:12 AM

{Phone} validation is not showing the value from resource bundle

Adjacent to the phone it is showing key instead of value

{Phone}

[Reply](#)**Rajesh Antony says**

JUNE 15, 2014 AT 3:13 PM

Hi Pankaj, the article has been very useful for me to pickup the basics. Thank you very much

[Reply](#)

**eduardo says**

JUNE 11, 2014 AT 9:59 AM

hi, could you upload again the zip file. thanks

[Reply](#)

**Pankaj says**

JUNE 11, 2014 AT 10:33 AM

it was an issue with the plugin I use for managing downloads, solved it. Please try now.

[Reply](#)

## Leave a Reply

Your email address will not be published. Required fields are marked \*

Comment

Name \*

Email \*

☐

Save my name, email, and website in this browser for the next time I comment.

DOWNLOAD ANDROID APP



## SPRING FRAMEWORK

## Spring Tutorial

### Spring Core

- > [Spring Framework](#)
- > [Spring Dependency Injection](#)
- > [Spring IoC and Bean](#)
- > [Spring Bean Life Cycle](#)
- > [Spring REST](#)
- > [Spring REST XML](#)
- > [Spring RestTemplate](#)
- > [Spring AOP](#)
- > [Spring AOP Method Profiling](#)
- > [Spring Annotations](#)
- > [Spring @Autowired](#)
- > [Spring @RequestMapping](#)

### Spring MVC

- > [Spring MVC Example](#)
- > [Spring MVC Tutorial](#)
- > [Spring MVC Exception Handling](#)
- > [Spring MVC Validator](#)
- > [Spring MVC Interceptor](#)
- > [Spring MVC File Upload](#)
- > [Spring MVC i18n](#)
- > [Spring MVC Hibernate MqSQL](#)

### Spring ORM

- > [Spring ORM](#)
- > [Spring ORM JPA](#)
- > [Spring Data JPA](#)
- > [Spring Transaction](#)
- > [Spring JdbcTemplate](#)

### Spring Security

- > [Spring Security Overview](#)
- > [Spring Security Example Tutorial](#)
- > [Spring Security UserDetailsService](#)
- > [Spring MVC Login Logout](#)
- > [Spring Security Roles](#)

### Spring Boot

- > [Spring Boot Tutorial](#)
- > [Spring Boot Components](#)
- > [Spring Boot CLI Hello World](#)
- > [Spring Boot Initializr Web](#)
- > [Spring Boot Initializr IDE](#)
- > [Spring Boot Initializr CLI](#)
- > [Spring Boot Initializr Tools](#)
- > [Spring Boot MongoDB](#)
- > [Spring Boot Redis Cache](#)
- > [Spring Boot Interview Questions](#)

### Spring Batch

- > [Spring Batch](#)
- > [Spring Batch Example](#)

### Spring AMQP

- > [Spring AMQP](#)
- > [Spring RabbitMQ](#)
- > [Spring AMQP RabbitMQ](#)
- > [Apache ActiveMQ](#)



- > [Spring ActiveMQ Tutorial](#)
- > [Spring ActiveMQ Example](#)

## Spring Integrations

- > [Spring JDBC](#)
- > [Spring DataSource JNDI](#)
- > [Spring Hibernate](#)
- > [Spring Primefaces JPA](#)
- > [Spring Primefaces MongoDB](#)
- > [Spring Primefaces Hibernate](#)
- > [SpringRoo Primefaces Hibernate](#)
- > [Spring JSF](#)
- > [Spring JDF Hibernate](#)

## Miscellaneous

- > [Spring Data MongoDB](#)
- > [Spring Interview Questions](#)

---

### RECOMMENDED TUTORIALS

## Java Tutorials

- > [Java IO](#)
- > [Java Regular Expressions](#)
- > [Multithreading in Java](#)
- > [Java Logging](#)
- > [Java Annotations](#)
- > [Java XML](#)
- > [Collections in Java](#)
- > [Java Generics](#)
- > [Exception Handling in Java](#)
- > [Java Reflection](#)
- > [Java Design Patterns](#)
- > [JDBC Tutorial](#)

## Java EE Tutorials

- > [Servlet JSP Tutorial](#)
- > [Struts2 Tutorial](#)
- > [Spring Tutorial](#)
- > [Hibernate Tutorial](#)
- > [Primefaces Tutorial](#)
- > [Apache Axis 2](#)
- > [JAX-RS](#)
- > [Memcached Tutorial](#)

## Interior Design Software

