Every model of the project, in the order it was tried

1 Development: graph proposal (CMx7-MM)

Temporal CNN
EEGNet
Fixed-graph GCN
Static learnable graph
Dynamic graph
Graph + graph consistency
Graph + subject adversary
Graph + plain task GRL
Graph + TCAI (flatten head)
Full model v1 (seed ensemble)
Full model v2 (subject_zscore)
Full model v2 (subject_euclid)
EEGNet + plain GRL
EEGNet + TCAI

2 FINAL run (both datasets)

EEGNet
EEGNet + TCAI
IG-TCAI (EEGNet)
EEGNet + EA + AdaBN · seed 0
v3 (earlier version) · seed 0
ShallowConvNet
EEG-Conformer
CBraMod, linear probe
CBraMod, fine-tuned
EEGNet + EA + AdaBN · 3-seed
v3 (earlier version) · 3-seed
EEGNet + plain task GRL
Graph A (+consistency, +subject adversary)
Graph B (+plain task GRL)
Graph C (+TCAI)
Graph model v2 (earlier proposal)

3 Final model: APNet

EEGNet + EA + AdaBN [SWA] · 3-seed
★ APNet (proposed) · seed 0
★ APNet (proposed) · 3-seed

4 Challengers to APNet

Riemann TS-LR
Riemann RC-TS-LR
APNet + Riemannian fusion
APNet + test-time IM
APNet + augmentation [SWA]
APNet + augmentation + test-time IM + Riemannian fusion

chance

CMx7-MM
COG-BCI
graph models (original proposal)
alignment pipelines
recent models
Riemannian
APNet (final)

0.3
0.4
0.5
0.6
0.7
0.8

fold-mean balanced accuracy (task-only lookup without EEG: CMx7-MM 0.771, COG-BCI 0.333)