	"						Chine	se   German	man   Korean	
Maydon k	erk					SEARCH			GO	
									Admin	
PRECISION MOTION CONTROL			Home	About Us	News	Events	Contact	Support	FAQs	
LINEAR ACTUATORS	A									
LEAD SCREWS & NUTS	PART NUMBER CONSTRUCTION									
LINEAR RAILS, GUIDES & SPLINES	Hybrid Stepper Motor Linear Actuators									
	For Haydon Kerk Motor Series <u>21000</u> , <u>28000</u> , <u>28000 Double Stack</u> , <u>35000</u> , <u>35000 Double Stack</u> , <u>43000</u> , <u>43000 Double Stack</u> , <u>87000</u> , <u>57000 Double Stack</u> , <u>87000</u>									
DRIVES	Example Part Number: E43H4N-05-900									
	(Hover n	(Hover mouse over Part Number segments to get definition.)								
ROTARY MOTORS	E	43 H	4 N	-	05 -	900				
SEALED SWITCHES	PART N	UMBER DESIGNATION	ONS FOR H	YBRID STEPF	PER MOTOR	LINEAR ACTU	ATORS			
PITTMAN BRUSH AND BRUSHLESS DC MOTORS	F	Prefix +rqd #khq#kvlgj## E @ #External			42	Series Number Designat 21 ⊚ #21000	ion			
RESOURCES	E	P ⊕ #Proximity Sensor S ⊕ #Home Switch T ⊕ #High Temp		43	28 @ #28000 35 @ #55000 43 @ #13000 57 @ #57000 87 @ #87000					
PART NUMBER CONSTRUCTION Please Select  NEWSLETTER SIGN UP Name	н	Style F = 1.8° Non-captiv H = 1.8° Captive (u J = 0.9° Non-captiv (u J = 0.9° Captive (u L = 1.8° Double St M = 1.8° Double St M = 1.8° Double St "External")	4	Coils 4 ⊚ #Bipolar (4 wire) 6 ⊚ #Unipolar (6 Wire) G ⊚ #Integrated Programmable Drive						
Submit  Questions? Call 800-243-2715 Site Map   Catalog   RSS	N	Code ID* Resolution T H{\$\dp \sdn#\ N = travels .00012- >> Single Stack: F >> Double Stack: F	05	Voltage  H{dp sdnv= 05 ⊚ #5 VDC 12 ⊚ #12 VDC Custom V Available						
Windjammer.	900	Suffix Stroke** 910 @#.0-in								
<b>ROTRON®</b>		900 @ External Linear with Grease Flanged Nut XXX @ Special Custom***								
Nautilair	* Refer to Travel/Step chart on motor series product page by clicking product number above									
		**Refer to Stroke chart on Captive motor series product page								
AMETEK®		*** Special part numbers for custom screw lengths and design options will require an issued 3 digit suffix number. Please contact our sales or applications engineering department for assistance								

EXAMPLES

**E43H4N-05-900** = External linear actuator, 43000 series, 1.8 degree, Bipolar coils, .00012-in travel per step, 5 volt DC. **43H4N-05-910** ⊚ #43000 series, 1.8 degree captive linear actuator, Bipolar, .00012-in travel per step, 5 volt DC, 1.0-in stroke.