

Sales & Support: 1.800.377.6329

[Print This Page](#)

DMC-40x0 Part Number Generator

Choose Number of Axes

 8-Axis Stand-Alone Controller

Communication Board (required)

 C012: 100BaseT Ethernet, 32 Extended I/O, LCD, RS-422

Interconnect for Axes 1-4 (required)

 I200: ICM with 26 pin High Density D-type connectors

Interconnect for Axes 5-8 (required)

 I200: ICM with 26 pin High Density D-type connectors

Amplifier for Axes 1-4 (optional)

 D4040: Four 1.4A (max) Stepper Drives- Full,Half,1/4,1/16 step

Amplifier for axes 5-8 (optional)

 D4040: Four 1.4A (max) Stepper Drives- Full,Half,1/4,1/16 step

Shunt Regulator (optional)

Notes (optional)

Notes (optional)

Part # **DMC-4080(ISCNTL)-C012(P422)-I200(SS,STEP)-I200(SS,STEP)-D4040-D4040**

Unit Price (USD) \$ 3835

[Printable Version](#)

Although we work to ensure all pricing online is as accurate as possible, prices must be confirmed by Galil upon order entry.

NOTE: MouseOver Options for Full Description

Controller Board Options

- ☐ DIN ☐ TRES
☐ 12V ☐ ETL
☐ -16bit ☐ MO
☒ ISCNTL

Communication Board Options

- ☐ 5V
☐ RS-232 on Both (Default)
☐ RS-422 on Main (P1)
☐ RS-422 on Aux (P2)
☒ RS-422 on Both

Axis 1-4 ICM Options

- ☒ SSI ☐ BiSS
☐ DIFF
☒ STEP

Axis 1-4 AmpEnable

Axis 5-8 ICM Options

- ☒ SSI ☐ BiSS
☐ DIFF
☒ STEP

Axis 5-8 AmpEnable

Amp1 Options

- ☐ 100mA
☐ SSR
☐ HALLF

Amp2 Options

- ☐ 100mA ☐ HALLF
☐ SSR
☐ ISAMP

5V, 12V, and 24V Amp Enable option is field configurable with a jumper. Default setting is 5V, HAEN, Sinking.