

Assignment 1 Design Document

Alan Caro
CruzID: alcaro

CSE130, Fall 2019

1 Goal

The goal of this program is to implement a single-threaded HTTP server. The server will be capable of handling GET and PUT request sent by a client.

2 Assumptions

I am assuming the user will only send one request at a time and that the user will only use the curl command. No directories will be sent by the client or requested. When no Content-Length is passed the client will have to exit the process by himself/herself. Also, I am assuming the user will send request with this format:

PUT:

```
curl -T localfile http://localhost:8080 --request-target filename_27_character
```

GET:

```
curl http://localhost:8080 --request-target filename_27_character
```

3 Design

The general approach I am taking is to check what request and file name the user passed. Then, if the request and file name is valid, I open a socket then process the GET or PUT command accordingly. If there is any errors like an invalid file or request I send the appropriate error code.

4 Pseudocode

This is the core pseudocode for the program. Note that it's pseudocode, not C (or Java or Python) code.

```

procedure main
    Declare string hostname
    Declare string port

    if argc > 1
        hostname = argv[1]
        if argv[2] != NULL
            strcpy(port, argv[2])
        else
            strcpy(port, "80")

        Declare struct addrinfo addrs, hints
        hints.ai_family = AF_INET
        hints.ai_socktype = SOCK_STREAM
        getaddrinfo(hostname, port, &hints, &addrs)
        main_socket = socket(addrs.ai_family, addrs.ai_socktype, addrs.ai_protocol)
        enable ← 1
        setsockopt(main_socket, SOL_SOCKET, SO_REUSEADDR, &enable,
sizeof(enable))
        bind(main_socket, addrs.ai_addr, addrs.ai_addrlen)
        listen(main_socket, 16)

        Declare a client_socket

        loop
            Declare buffer
            memset(buffer, 0, 1024);
            Declare request
            Declare fileName

            client_socket = accept(main_socket, NULL, NULL);
            recv(client_socket, buffer, 1024, 0);

            sscanf(buffer, "%s %s", request, fileName);
            processOneRequest(fileName, request, client_socket, buffer);

        else
            fprintf(stderr, "usage: ./httpserver localhost port")
            return 1
    return 0

procedure processOnerequest

```

```

    if fileName[0] == '/'
        memmove(fileName, fileName + 1, strlen(fileName))
    if isValidName(fileName) == -1
        send(socket, "HTTP/1.1 400 Bad Request", strlen("HTTP/1.1 400 Bad
Request"),0)
        return
    if strcmp(request, "GET") == 0
        processGet(fileName, socket)
    else if strcmp(request, "PUT") == 0
        line ← strtok(buffer, "\r\n")
        array[7]
        word[20]
        i ← 0
        j ← 0

        loop
            array[i++] = line
            line = strtok(NULL, "\r\n")

        loop
            if strstr(array[j], "Content-Length: ") != NULL
                break

            if array[j] != NULL
                sscanf(array[j], "%*s, %s", word)
                i = atoi(word)
            else
                i = -1
            processPut(fileName, socket, i)
        else
            send(socket, "HTTP/1.1 400 Bad Request", strlen("HTTP/1.1 400 Bad

```

```

procedure isValidName
    Declare variable j
    Declare struct path_stat
    loop
        j+= 1
    if j != 27
        return -1
    loop
        c ← fileName[i]
        if isalpha(c)
            continue
        if isdigit(c)

```

```

        continue
    if c == '-'
        continue
    if c == '_'
        continue
    return -1

return 0

procedure processGet
    fd ← open(fileName, O_RDONLY)
    buffer[32]

    if fd == -1
        if access(fileName, F_OK) == -1
            send(socket, "404 Not Found" strlen("404 Not Found"),0)
        else
            send(socket, "403 Forbidden" strlen("403 Forbidden"),0)
        return

    Declare struct of type stat st

    if stat(fileName, &st) == 1)
        send(socket, "500 Internal Server Error" strlen("500 Internal Server Error"),0)

    size ← st.st_size
    Declare char array str[1024]
    sprintf(str, "HTTP/1.1 200 OK \r\nContent-Length: %d\r\n\r\n", size);
    send(socket, str, strlen(str), 0);

    loop read(fd,buffer,1)
        send(socket, buffer, 1, 0)

    close(fd)

procedure processPut
    fd ← open(fileName, O_CREAT | O_RDWR | O_TRUNC, 0644)

    if fd == -1
        send(socket, "403 Forbidden" strlen("403 Forbidden"),0)
        return
    i ← 0

```

```
loop
    read (socket, buffer, 1)
    write(fd, buffer, 1)
    i+=1
    send(socket, "HTTP/1.1 201 Created \r\nContent-Length: 0\r\n\r\n",
strlen("HTTP/1.1 201 Created \r\nContent-Length: 0\r\n\r\n"), 0);

close(fd);
```