

Test Specification

Test Project: TaskFlow
Test Suite: TaskFlow - E - Rasan soran - Storage navigation and accessibility

Printed by TestLink on 27/10/2026

2026 Group TaskFlow - Project 1 Test Case Design

Table Of Contents

1.E - Rasan soran - Storage navigation and accessibility

1.1.TS-E1 - Storage loading and recovery

TF-166: TC-E-001 - Missing task key loads quietly

TF-167: TC-E-002 - Persist task through ordinary reload

TF-168: TC-E-003 - Malformed JSON copied byte-for-byte

TF-169: TC-E-004 - Parsed object rejected as non-array

TF-170: TC-E-005 - Valid stored task loads normalized

TF-171: TC-E-006 - Missing id skipped with singular warning

TF-172: TC-E-007 - Empty id skipped

TF-173: TC-E-008 - Duplicate id keeps first valid record

TF-174: TC-E-009 - Plural invalid count grammar

TF-175: TC-E-010 - Reject bad priority in storage

TF-176: TC-E-011 - Reject bad status in storage

TF-177: TC-E-012 - Reject invalid date and missing creation time

TF-178: TC-E-013 - Missing updatedAt falls back to createdAt

TF-179: TC-E-014 - Malformed updatedAt falls back

TF-180: TC-E-015 - Valid siblings retained around rejected row

1.2.TS-E2 - Storage failures warnings and navigation

TF-181: TC-E-016 - Read exception returns unavailable warning

TF-182: TC-E-017 - Blocked backup write does not throw

TF-183: TC-E-018 - Failed creation save reports error but stays optimistic

TF-184: TC-E-019 - Failed status save is optimistic

TF-185: TC-E-020 - Reset removes primary and retains backup

TF-186: TC-E-021 - Repeated reset remains safe

TF-187: TC-E-022 - Dismiss warning changes no storage

TF-188: TC-E-023 - Warning role and dismissal name

TF-189: TC-E-024 - Dashboard and All Tasks show all statuses

TF-190: TC-E-025 - Each status navigation sets title and active state

TF-191: TC-E-026 - Desktop sidebar collapse toggles labels

TF-192: TC-E-027 - Responsive behavior at 767px

TF-193: TC-E-028 - Responsive behavior at 768px and README discrepancy

TF-194: TC-E-029 - Responsive behavior at 769px

TF-195: TC-E-030 - Close drawer via close control and navigation

TF-196: TC-E-031 - Backdrop closes drawer but inside click does not

TF-197: TC-E-032 - Mobile navigation updates page title

1.3.TS-E3 - Dialog focus and toast accessibility

TF-198: TC-E-033 - Dialog name and modal accessibility properties

TF-199: TC-E-034 - Dialog autofocuses marked control

TF-200: TC-E-035 - Dialog close restores opener focus

TF-201: TC-E-036 - Success toast uses status and dismiss control

TF-202: TC-E-037 - Error toast uses alert and dismiss control

TF-203: TC-E-038 - Toast automatic duration tolerance

Scope

TaskFlow - single-user React/Vite task manager. SECJ3343 Project 1 local preparation environment. Import exports into the lecturer's existing project.

1.Test Suite : E - Rasan soran - Storage navigation and accessibility

Tester: Rasan soran (Member 5, E). SECJ3343 Project 1, TaskFlow main@5133a6c. Scope: reload persistence; storage recovery/failure; warning behavior; navigation/title; responsive sidebar; dialog focus/name; toast timing/semantics. A owns creation/text limits/draft cancellation, B editing/deletion, C enums/dates/status/counts, D querying. Shared actions are setup only.

Basis: README.md Storage, Requirements traceability, Behaviour notes and Exact messages, plus implementing functions cited by each code-derived requirement. Cases are designs, initially Not Run; no execution or peer review claimed.

Use a disposable Chrome profile at http://localhost:5173. Only seed/remove taskflow_tasks and taskflow_tasks_backup in that profile. Never clear personal browser data. For storage functions inaccessible through normal UI, cases marked UNIT HARNESS use DevTools Console on Vite, dynamically import /src/utils/storage.js, replace window.localStorage with a stub, and call loadTasks/saveTasks/resetStorage directly. This is a unit harness, not browser-level fault injection. To simulate failed UI writes without reload, patch Storage.prototype.setItem to throw a QuotaExceededError before the action; use the disposable profile. For storage fixtures define const validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}); const seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a));. To inspect normalized loader objects use const m=await import("/src/utils/storage.js"); console.log(m.loadTasks().tasks). For read faults use UNIT HARNESS: const m=await import("/src/utils/storage.js"); Object.defineProperty(window,"localStorage", {configurable:true,value:{getItem(){throw Error("blocked")},setItem(){throw Error("blocked")},removeItem(){throw Error("blocked")}}}); console.log(m.loadTasks());. For write fault on live UI: Storage.prototype.setItem=function() {throw new DOMException("blocked","QuotaExceededError")}. Restore only by closing the disposable profile. Toast target is 3000ms; accept manual timing from 2700 through 3800ms.

1.1.Test Suite : TS-E1 - Storage loading and recovery

Reload persistence; missing/corrupt/non-array data; validation/duplicate skips; timestamps and normalization.

Test Case TF-166: TC-E-001 - Missing task key loads quietly [Version : 1]		
Author:	rasan	
Summary:		
TC-E-001 - Missing task key loads quietly. **Test design technique:** EP - missing key **Requirements:** REQ-E-002		
Preconditions:		
Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Remove only taskflow_tasks and taskflow_tasks_backup in the disposable profile; reload.	No tasks yet; no warning; primary key remains absent until a mutation.
2	Inspect backup key.	Backup is absent.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	High	
Requirements	REQ-E-002: Missing and corrupt storage [Version : 1]	
Keywords:	None	

Test Case TF-167: TC-E-002 - Persist task through ordinary reload [Version : 1]		
Author:	rasan	
Summary: TC-E-002 - Persist task through ordinary reload. **Test design technique:** Use Case - save and restart **Requirements:** REQ-E-001		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Create one valid task titled Reload proof (creation is setup only).	Reload proof card appears.
2	Inspect saved JSON, then reload.	One JSON array entry has id, title, description, priority, status, dueDate, createdAt, updatedAt; same id and card values remain.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	High	
Requirements	REQ-E-001: Reload persistence [Version : 1]	
Keywords:	None	

Test Case TF-168: TC-E-003 - Malformed JSON copied byte-for-byte [Version : 1]		
Author:	rasan	
Summary: TC-E-003 - Malformed JSON copied byte-for-byte. **Test design technique:** EP - malformed JSON **Requirements:** REQ-E-002		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set taskflow_tasks to exact string { "unclosed": including spaces; reload.	Empty list and alert Saved task data was corrupted and could not be loaded. A backup was kept. with Reset storage.
2	Inspect taskflow_tasks_backup.	Exact original raw string { "unclosed": is retained.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	High	
Requirements	REQ-E-002: Missing and corrupt storage [Version : 1]	
Keywords:	None	

Test Case TF-169: TC-E-004 - Parsed object rejected as non-array [Version : 1]		
Author:	rasan	
Summary:		
TC-E-004 - Parsed object rejected as non-array. **Test design technique:** EP - non-array JSON **Requirements:** REQ-E-002		
Preconditions:		
Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set taskflow_tasks to exact string {"tasks":[]} and reload.	No tasks load; exact corruption alert and Reset storage appear.
2	Inspect backup.	Backup equals exact original string {"tasks":[]}.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-002: Missing and corrupt storage [Version : 1]	
Keywords:	None	

Test Case TF-170: TC-E-005 - Valid stored task loads normalized [Version : 1]		
Author:	rasan	
Summary:		
TC-E-005 - Valid stored task loads normalized. **Test design technique:** EP - valid saved-entry partition **Requirements:** REQ-E-003, REQ-E-004		
Preconditions:		
Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set taskflow_tasks to JSON.stringify([validTask("ok-1",{title:" Stored task ",description:" note "})]); reload.	One card appears titled Stored task; description is note; no warning.
2	Inspect original localStorage string.	Primary value stays as seeded until a later mutation; loader normalizes in memory only.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-003: Invalid entries and duplicate ids [Version : 1] REQ-E-004: Updated timestamp fallback and normalization [Version : 1]	
Keywords:	None	

Test Case TF-171: TC-E-006 - Missing id skipped with singular warning [Version : 1]		
Author:	rasan	
Summary: TC-E-006 - Missing id skipped with singular warning. **Test design technique:** EP - invalid identity **Requirements:** REQ-E-003		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set primary to exact JSON string [{"title":"No id","description":"","priority":"Medium","status":"To Do","dueDate":"","createdAt":"2026-01-02T03:04:05.000Z","updatedAt":"2026-01-02T03:04:05.000Z"}]; reload.	No card; alert is exactly 1 saved entry was invalid and skipped. A backup was kept.; Reset storage absent.
2	Inspect backup.	Full original JSON array is retained byte-for-byte.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	High	
Requirements	REQ-E-003: Invalid entries and duplicate ids [Version : 1]	
Keywords:	None	

Test Case TF-172: TC-E-007 - Empty id skipped [Version : 1]		
Author:	rasan	
Summary: TC-E-007 - Empty id skipped. **Test design technique:** EP - empty identity **Requirements:** REQ-E-003		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	For each id value "", 42 and null, independently set taskflow_tasks to JSON.stringify([validTask(id, {title:"Invalid id"})]); reload after each value.	Each identity partition is skipped. Exact alert: "1 saved entry was invalid and skipped. A backup was kept." No Reset storage button; backup equals the raw array for that run.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-003: Invalid entries and duplicate ids [Version : 1]	
Keywords:	None	

Test Case TF-173: TC-E-008 - Duplicate id keeps first valid record [Version : 1]		
Author:	rasan	
Summary:		
TC-E-008 - Duplicate id keeps first valid record. **Test design technique:** Error Guessing - duplicate identity **Requirements:** REQ-E-003		
Preconditions:		
Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set primary to JSON.stringify([validTask("dup-7",{title:"First"}),validTask("dup-7",{title:"Second"})]); reload.	Only First card loads; warning counts one skipped entry.
2	Inspect backup.	Full original two-item JSON remains byte-for-byte as backup.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	High	
Requirements	REQ-E-003: Invalid entries and duplicate ids [Version : 1]	
Keywords:	None	

Test Case TF-174: TC-E-009 - Plural invalid count grammar [Version : 1]		
Author:	rasan	
Summary: TC-E-009 - Plural invalid count grammar. **Test design technique:** EP - multiple invalid saved-entry partition and plural count **Requirements:** REQ-E-003		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set primary to exact JSON string [null, {"id":"bad","title":"x","description":"","priority":"Medium","status":"To Do","dueDate":"","createdAt":"2026-01-02T03:04:05.000Z","updatedAt":"2026-01-02T03:04:05.000Z"}] and reload.	No rows load; alert exactly 2 saved entries were invalid and skipped. A backup was kept.
2	Inspect Reset storage and backup.	No Reset button; backup retains complete original array string.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-003: Invalid entries and duplicate ids [Version : 1]	
Keywords:	None	

Test Case TF-175: TC-E-010 - Reject bad priority in storage [Version : 1]		
Author:	rasan	
Summary: TC-E-010 - Reject bad priority in storage. **Test design technique:** EP - invalid saved enum **Requirements:** REQ-E-003		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set primary to JSON.stringify([validTask("p1", {priority:"Urgent"})]); reload.	Row is skipped; exact alert "1 saved entry was invalid and skipped. A backup was kept." Backup equals the original raw JSON; no Reset storage button.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-003: Invalid entries and duplicate ids [Version : 1]	
Keywords:	None	

Test Case TF-176: TC-E-011 - Reject bad status in storage [Version : 1]		
Author:	rasan	
Summary: TC-E-011 - Reject bad status in storage. **Test design technique:** EP - invalid saved enum **Requirements:** REQ-E-003		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set primary to JSON.stringify([validTask("s1", {status:"Done"})]); reload.	Row is skipped; exact alert "1 saved entry was invalid and skipped. A backup was kept." Backup equals the original raw JSON; no Reset storage button.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-003: Invalid entries and duplicate ids [Version : 1]	
Keywords:	None	

Test Case TF-177: TC-E-012 - Reject invalid date and missing creation time [Version : 1]		
Author:	rasan	
Summary: TC-E-012 - Reject invalid date and missing creation time. **Test design technique:** EP - invalid saved fields **Requirements:** REQ-E-003		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set primary to JSON.stringify([validTask("d1", {dueDate:"2026-02-30"})]); reload.	Row is skipped, count one, backup is exact original primary string.
2	Set primary to JSON.stringify([validTask("d2", {dueDate:"2026-02-28",createdAt:undefined})]); reload.	JSON serialization omits undefined createdAt; row is skipped, count one because createdAt is required.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-003: Invalid entries and duplicate ids [Version : 1]	
Keywords:	None	

Test Case TF-178: TC-E-013 - Missing updatedAt falls back to createdAt [Version : 1]		
Author:	rasan	
Summary: TC-E-013 - Missing updatedAt falls back to createdAt. **Test design technique:** EP - omitted optional timestamp **Requirements:** REQ-E-004		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set primary to JSON.stringify([validTask("u1", {updatedAt:undefined})]); reload.	Task loads without warning.
2	In DevTools run const m=await import("/src/utils/storage.js"); console.log(m.loadTasks().tasks[0]).	updatedAt equals exactly 2026-01-02T03:04:05.000Z.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-004: Updated timestamp fallback and normalization [Version : 1]	
Keywords:	None	

Test Case TF-179: TC-E-014 - Malformed updatedAt falls back [Version : 1]		
Author:	rasan	
Summary:		
TC-E-014 - Malformed updatedAt falls back. **Test design technique:** EP - invalid optional timestamp **Requirements:** REQ-E-004		
Preconditions:		
Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set primary to JSON.stringify([validTask("u2", {updatedAt:"not-a-date"})]); reload.	Task is retained; invalid updatedAt alone does not skip entry.
2	In DevTools run const m=await import("/src/utils/storage.js"); console.log(m.loadTasks().tasks[0]).	updatedAt equals createdAt exactly.
3	UNIT HARNESS: load a valid entry with description:undefined and dueDate:undefined; inspect loadTasks().tasks[0].	Both normalized description and dueDate are empty strings; no warning.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-004: Updated timestamp fallback and normalization [Version : 1]	
Keywords:	None	

Test Case TF-180: TC-E-015 - Valid siblings retained around rejected row [Version : 1]		
Author:	rasan	
Summary: TC-E-015 - Valid siblings retained around rejected row. **Test design technique:** EP - mixed valid and invalid saved-entry partitions **Requirements:** REQ-E-003		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set primary to JSON.stringify([validTask("A",{title:"Task A"}),null,validTask("B",{title:"Task B"})]); reload.	Task A and Task B load in source order (their creation times are equal); exact alert "1 saved entry was invalid and skipped. A backup was kept." Backup equals the full raw array.
2	Dismiss warning then reload without changing storage.	The warning returns and both valid tasks remain.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-003: Invalid entries and duplicate ids [Version : 1]	
Keywords:	None	

1.2.Test Suite : TS-E2 - Storage failures warnings and navigation

Blocked storage, optimistic failed writes, reset/backup, warning dismissal, page navigation and responsive sidebar.

Test Case TF-181: TC-E-016 - Read exception returns unavailable warning [Version : 1]		
Author:	rasan	
Summary: TC-E-016 - Read exception returns unavailable warning. **Test design technique:** Error Guessing - blocked read **Requirements:** REQ-E-005		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	UNIT HARNESS: dynamic-import /src/utils/storage.js after replacing window.localStorage with stub whose getItem throws; call loadTasks.	No exception; result tasks=[] and warning message Browser storage is unavailable, so tasks cannot be loaded or saved. with canReset false.
2	Inspect stub calls.	No reset control can be offered; loadTasks does not attempt backup.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-005: Storage read failure [Version : 1]	
Keywords:	None	

Test Case TF-182: TC-E-017 - Blocked backup write does not throw [Version : 1]		
Author:	rasan	
Summary: TC-E-017 - Blocked backup write does not throw. **Test design technique:** Error Guessing - backup write failure **Requirements:** REQ-E-002		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	UNIT HARNESS: const m=await import("/src/utils/storage.js"); Object.defineProperty(window,"localStorage", {configurable:true,value:{getItem(){return "garbage"},setItem(k,v){throw Error("blocked")},removeItem(){}}}); console.log(m.loadTasks()).	Returns empty tasks and corruption warning with canReset true; no exception escapes.
2	Inspect stub behavior.	Backup write was attempted using taskflow_tasks_backup and exact raw string garbage.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-002: Missing and corrupt storage [Version : 1]	
Keywords:	None	

Test Case TF-183: TC-E-018 - Failed creation save reports error but stays optimistic [Version : 1]		
Author:	rasan	
Summary: TC-E-018 - Failed creation save reports error but stays optimistic. **Test design technique:** Error Guessing - quota failure **Requirements:** REQ-E-007		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	On clean UI patch Storage.prototype.setItem to throw QuotaExceededError, then create valid task Unsaved optimistic.	Dialog closes, card appears in current in-memory UI; toast is Could not save tasks to browser storage. with error semantics.
2	Reload disposable profile after restoring storage.	Task is absent because write did not persist.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	High	
Requirements	REQ-E-007: Failed write remains optimistic [Version : 1]	
Keywords:	None	

Test Case TF-184: TC-E-019 - Failed status save is optimistic [Version : 1]		
Author:	rasan	
Summary: TC-E-019 - Failed status save is optimistic. **Test design technique:** Error Guessing - failed mutation write **Requirements:** REQ-E-007		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Seed a To Do task, load app, patch setItem to throw, change status to In Progress.	Card changes immediately and error toast appears.
2	Restore storage and reload.	Persisted status remains To Do.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-007: Failed write remains optimistic [Version : 1]	
Keywords:	None	

Test Case TF-185: TC-E-020 - Reset removes primary and retains backup [Version : 1]		
Author:	rasan	
Summary: TC-E-020 - Reset removes primary and retains backup. **Test design technique:** Use Case - storage reset **Requirements:** REQ-E-002, REQ-E-006		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set taskflow_tasks to "not-json" and taskflow_tasks_backup to "older-backup"; reload.	The exact corruption warning appears; loading replaces the old backup with "not-json".
2	Click Reset storage, inspect keys, then reload.	Warning clears; "No tasks yet" appears. Primary key is absent and backup still equals "not-json". No warning on reload.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	High	
Requirements	REQ-E-002: Missing and corrupt storage [Version : 1] REQ-E-006: Reset and backup retention [Version : 1]	
Keywords:	None	

Test Case TF-186: TC-E-021 - Repeated reset remains safe [Version : 1]		
Author:	rasan	
Summary:		
TC-E-021 - Repeated reset remains safe. **Test design technique:** Error Guessing - repeated reset **Requirements:** REQ-E-006		
Preconditions:		
Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Trigger corruption warning and click Reset storage. Trigger corruption again using malformed primary and repeat.	Both attempts clear warning and tasks; no runtime error.
2	Inspect backup.	Backup retained unchanged by reset.
3	UNIT HARNESS: import /src/utils/storage.js; replace localStorage with a stub whose removeItem throws; call resetStorage().	resetStorage returns without throwing; it never removes taskflow_tasks_backup.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-006: Reset and backup retention [Version : 1]	
Keywords:	None	

Test Case TF-187: TC-E-022 - Dismiss warning changes no storage [Version : 1]		
Author:	rasan	
Summary: TC-E-022 - Dismiss warning changes no storage. **Test design technique:** State Transition - warning visible to dismissed **Requirements:** REQ-E-008		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Load malformed data, record primary and backup, click Dismiss warning.	Alert disappears.
2	Compare keys and reload.	Both strings unchanged; warning appears again on reload.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-008: Warning announcement and dismissal [Version : 1]	
Keywords:	None	

Test Case TF-188: TC-E-023 - Warning role and dismissal name [Version : 1]		
Author:	rasan	
Summary: TC-E-023 - Warning role and dismissal name. **Test design technique:** Use Case - accessible warning announcement and dismissal **Requirements:** REQ-E-008		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Trigger invalid-entry warning and inspect DOM/accessibility tree.	Warning has role alert and Dismiss warning button accessible name.
2	Activate dismissal.	Banner disappears; primary and backup are unchanged.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-008: Warning announcement and dismissal [Version : 1]	
Keywords:	None	

Test Case TF-189: TC-E-024 - Dashboard and All Tasks show all statuses [Version : 1]		
Author:	rasan	
Summary:		
TC-E-024 - Dashboard and All Tasks show all statuses. **Test design technique:** State Transition - all-status navigation **Requirements:** REQ-E-009		
Preconditions:		
Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Seed one task of each status; select Dashboard.	Dashboard aria-current=page; h1 Dashboard; status filter All.
2	Select All Tasks.	All Tasks active, h1 All Tasks; status filter All.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-009: Navigation and page title [Version : 1]	
Keywords:	None	

Test Case TF-190: TC-E-025 - Each status navigation sets title and active state [Version : 1]		
Author:	rasan	
Summary:		
TC-E-025 - Each status navigation sets title and active state. **Test design technique:** State Transition - status navigation **Requirements:** REQ-E-009		
Preconditions:		
Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Select To Do, In Progress, then Completed.	After each click, matching nav item alone has aria-current=page, h1 matches label and status filter matches.
2	Select Dashboard.	Dashboard active; h1 Dashboard; filter returns All.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	High	
Requirements	REQ-E-009: Navigation and page title [Version : 1]	
Keywords:	None	

Test Case TF-191: TC-E-026 - Desktop sidebar collapse toggles labels [Version : 1]		
Author:	rasan	
Summary: TC-E-026 - Desktop sidebar collapse toggles labels. **Test design technique:** State Transition - expanded/collapsed **Requirements:** REQ-E-010		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	At viewport 1024px inspect expanded sidebar; click Collapse sidebar.	Width transitions 248px to 72px; brand/nav/profile labels hide; aria-expanded=false and control name Expand sidebar.
2	Click Expand sidebar.	Width returns 248px; labels show; aria-expanded=true.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-010: Responsive sidebar breakpoint [Version : 1]	
Keywords:	None	

Test Case TF-192: TC-E-027 - Responsive behavior at 767px [Version : 1]		
Author:	rasan	
Summary: TC-E-027 - Responsive behavior at 767px. **Test design technique:** BVA - breakpoint below 768 **Requirements:** REQ-E-010		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set viewport exactly 767px and reload.	Mobile media rules apply: closed sidebar off-canvas/hidden; hamburger shown; collapse hidden.
2	Click Open menu.	272px drawer opens and overlay appears.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-010: Responsive sidebar breakpoint [Version : 1]	
Keywords:	None	

Test Case TF-193: TC-E-028 - Responsive behavior at 768px and README discrepancy [Version : 1]		
Author:	rasan	
Summary: TC-E-028 - Responsive behavior at 768px and README discrepancy. **Test design technique:** BVA - exact breakpoint **Requirements:** REQ-E-010		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set viewport exactly 768px and reload.	App.css max-width:768px applies mobile drawer rules at this width.
2	Compare README Behaviour notes.	README says under 768px, excluding 768; code includes 768. Record discrepancy; CSS determines implemented behavior.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	High	
Requirements	REQ-E-010: Responsive sidebar breakpoint [Version : 1]	
Keywords:	None	

Test Case TF-194: TC-E-029 - Responsive behavior at 769px [Version : 1]		
Author:	rasan	
Summary: TC-E-029 - Responsive behavior at 769px. **Test design technique:** BVA - breakpoint above 768 **Requirements:** REQ-E-010		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Set viewport exactly 769px and reload.	Mobile rules no longer apply; desktop sidebar 248px; hamburger/close hidden; collapse shown.
2	Collapse sidebar.	Width becomes 72px and labels hide.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-010: Responsive sidebar breakpoint [Version : 1]	
Keywords:	None	

Test Case TF-195: TC-E-030 - Close drawer via close control and navigation [Version : 1]		
Author:	rasan	
Summary:		
TC-E-030 - Close drawer via close control and navigation. **Test design technique:** State Transition - drawer close paths **Requirements:** REQ-E-011		
Preconditions:		
Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	At 767px open menu, click Close menu.	Drawer and overlay disappear.
2	Reopen and select Completed.	Drawer closes; Completed filter/title/active state updates.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-011: Drawer close paths [Version : 1]	
Keywords:	None	

Test Case TF-196: TC-E-031 - Backdrop closes drawer but inside click does not [Version : 1]		
Author:	rasan	
Summary: TC-E-031 - Backdrop closes drawer but inside click does not. **Test design technique:** Error Guessing - overlay target **Requirements:** REQ-E-011		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	At 767px open menu and click overlay outside drawer.	Drawer closes and overlay disappears.
2	Reopen; click inside drawer without selecting item.	Drawer remains open.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-011: Drawer close paths [Version : 1]	
Keywords:	None	

Test Case TF-197: TC-E-032 - Mobile navigation updates page title [Version : 1]		
Author:	rasan	
Summary: TC-E-032 - Mobile navigation updates page title. **Test design technique:** Use Case - drawer navigation **Requirements:** REQ-E-009, REQ-E-011		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	At 767px open menu and select Completed.	Drawer closes; Completed is aria-current=page; h1 Completed; status filter Completed.
2	Reopen and select Dashboard.	Drawer closes; h1 Dashboard; filter All.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-009: Navigation and page title [Version : 1] REQ-E-011: Drawer close paths [Version : 1]	
Keywords:	None	

1.3.Test Suite : TS-E3 - Dialog focus and toast accessibility

Implemented dialog semantics, autofocus and opener restoration; success/error toast roles, dismissal and timeout.

Test Case TF-198: TC-E-033 - Dialog name and modal accessibility properties [Version : 1]		
Author:	rasan	
Summary: TC-E-033 - Dialog name and modal accessibility properties. **Test design technique:** Use Case - modal accessible name and semantics **Requirements:** REQ-E-012		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Open New Task and inspect dialog DOM/accessibility tree.	role dialog, aria-modal true, aria-labelledby points to visible h2 named New Task.
2	Close using Cancel.	Dialog is removed; no focus trap is asserted because implementation has none.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	High	
Requirements	REQ-E-012: Dialog name, focus and opener restoration [Version : 1]	
Keywords:	None	

Test Case TF-199: TC-E-034 - Dialog autofocuses marked control [Version : 1]		
Author:	rasan	
Summary: TC-E-034 - Dialog autofocuses marked control. **Test design technique:** Use Case - modal entry focus **Requirements:** REQ-E-012		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open. Seed validTask("focus") and reload before opening any dialog.		
#:	Step actions:	Expected Results:
1	Open New Task and inspect document.activeElement.	Task Title receives focus via data-autofocus.
2	Click Cancel, then Delete on Task focus and inspect document.activeElement.	Delete Task opens and its Cancel button receives focus via data-autofocus.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-012: Dialog name, focus and opener restoration [Version : 1]	
Keywords:	None	

Test Case TF-200: TC-E-035 - Dialog close restores opener focus [Version : 1]		
Author:	rasan	
Summary: TC-E-035 - Dialog close restores opener focus. **Test design technique:** State Transition - focus return **Requirements:** REQ-E-012		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Focus + New Task and activate it; click Cancel.	Focus returns to same + New Task opener after unmount.
2	Remove the primary/backup keys and reload to the empty state. Focus Create your first task, activate it, then press Escape.	New Task closes and focus returns to the still-mounted Create your first task opener.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-012: Dialog name, focus and opener restoration [Version : 1]	
Keywords:	None	

Test Case TF-201: TC-E-036 - Success toast uses status and dismiss control [Version : 1]		
Author:	rasan	
Summary: TC-E-036 - Success toast uses status and dismiss control. **Test design technique:** EP - success announcement **Requirements:** REQ-E-013		
Preconditions: Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Create one task titled Toast success with valid defaults, then inspect the toast immediately.	Exact message "Task created successfully."; role=status; accessible button "Dismiss notification".
2	Dismiss before timeout.	Toast disappears immediately.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-013: Toast timing and semantics [Version : 1]	
Keywords:	None	

Test Case TF-202: TC-E-037 - Error toast uses alert and dismiss control [Version : 1]		
Author:	rasan	
Summary:		
TC-E-037 - Error toast uses alert and dismiss control. **Test design technique:** EP - error announcement **Requirements:** REQ-E-007, REQ-E-013		
Preconditions:		
Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Patch setItem to throw, then perform valid mutation.	role alert and exact Could not save tasks to browser storage. message; Dismiss notification button.
2	Dismiss notification.	Toast disappears immediately; optimistic state remains until reload.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-007: Failed write remains optimistic [Version : 1] REQ-E-013: Toast timing and semantics [Version : 1]	
Keywords:	None	

Test Case TF-203: TC-E-038 - Toast automatic duration tolerance [Version : 1]		
Author:	rasan	
Summary:		
TC-E-038 - Toast automatic duration tolerance. **Test design technique:** State Transition - visible toast to timed automatic dismissal at 3000ms **Requirements:** REQ-E-013		
Preconditions:		
Independent reset: in this disposable profile restore any patched storage by reloading; remove only taskflow_tasks and taskflow_tasks_backup, then reload again. Disposable Chrome profile; app main@5133a6c at http://localhost:5173; use DevTools only on this profile. Storage-fixture helper: define validTask=(id,o={})=>({id,title:"Task "+id,description:"",priority:"Medium",status:"To Do",dueDate:"",createdAt:"2026-01-02T03:04:05.000Z",updatedAt:"2026-01-02T03:04:05.000Z",...o}) and seedTasks=a=>localStorage.setItem("taskflow_tasks",JSON.stringify(a)); use seedTasks([validTask("x")]) for an exact valid baseline. Unless specified start Dashboard with no drawer/dialog open.		
#:	Step actions:	Expected Results:
1	Trigger success toast and time from visible onset to removal.	Initial toast visible; measure duration.
2	Repeat for an error toast.	Each auto-closes between 2700 and 3800ms; outside range is a defect.
Execution type:	Manual	
Estimated exec. duration (min):		
Importance:	Medium	
Requirements	REQ-E-013: Toast timing and semantics [Version : 1]	
Keywords:	None	