

```

1  SET @OLD_UNIQUE_CHECKS=@@UNIQUE_CHECKS, UNIQUE_CHECKS=0;
2  SET @OLD_FOREIGN_KEY_CHECKS=@@FOREIGN_KEY_CHECKS, FOREIGN_KEY_CHECKS=0;
3  SET @OLD_SQL_MODE=@@SQL_MODE, SQL_MODE='TRADITIONAL,ALLOW_INVALID_DATES';
4  DROP SCHEMA IF EXISTS `northwind` ;
5  CREATE SCHEMA IF NOT EXISTS `northwind` DEFAULT CHARACTER SET latin1 ;
6  USE `northwind` ;
7  -- -----
8  -- Table `northwind`.`customers`
9  -----
10 CREATE TABLE IF NOT EXISTS `northwind`.`customers` (
11   `id` INT(11) NOT NULL AUTO_INCREMENT,
12   `company` VARCHAR(50) NULL DEFAULT NULL,
13   `last_name` VARCHAR(50) NULL DEFAULT NULL,
14   `first_name` VARCHAR(50) NULL DEFAULT NULL,
15   `email_address` VARCHAR(50) NULL DEFAULT NULL,
16   `job_title` VARCHAR(50) NULL DEFAULT NULL,
17   `business_phone` VARCHAR(25) NULL DEFAULT NULL,
18   `home_phone` VARCHAR(25) NULL DEFAULT NULL,
19   `mobile_phone` VARCHAR(25) NULL DEFAULT NULL,
20   `fax_number` VARCHAR(25) NULL DEFAULT NULL,
21   `address` LONGTEXT NULL DEFAULT NULL,
22   `city` VARCHAR(50) NULL DEFAULT NULL,
23   `state_province` VARCHAR(50) NULL DEFAULT NULL,
24   `zip_postal_code` VARCHAR(15) NULL DEFAULT NULL,
25   `country_region` VARCHAR(50) NULL DEFAULT NULL,
26   `web_page` LONGTEXT NULL DEFAULT NULL,
27   `notes` LONGTEXT NULL DEFAULT NULL,
28   `attachments` LONGBLOB NULL DEFAULT NULL,
29   PRIMARY KEY (`id`),
30   INDEX `city` (`city` ASC),
31   INDEX `company` (`company` ASC),
32   INDEX `first_name` (`first_name` ASC),
33   INDEX `last_name` (`last_name` ASC),
34   INDEX `zip_postal_code` (`zip_postal_code` ASC),
35   INDEX `state_province` (`state_province` ASC))
36   ENGINE = InnoDB
37   DEFAULT CHARACTER SET = utf8;
38  -- -----
39  -- Table `northwind`.`employees`
40  -----
41 CREATE TABLE IF NOT EXISTS `northwind`.`employees` (
42   `id` INT(11) NOT NULL AUTO_INCREMENT,
43   `company` VARCHAR(50) NULL DEFAULT NULL,
44   `last_name` VARCHAR(50) NULL DEFAULT NULL,
45   `first_name` VARCHAR(50) NULL DEFAULT NULL,
46   `email_address` VARCHAR(50) NULL DEFAULT NULL,
47   `job_title` VARCHAR(50) NULL DEFAULT NULL,
48   `business_phone` VARCHAR(25) NULL DEFAULT NULL,
49   `home_phone` VARCHAR(25) NULL DEFAULT NULL,
50   `mobile_phone` VARCHAR(25) NULL DEFAULT NULL,
51   `fax_number` VARCHAR(25) NULL DEFAULT NULL,
52   `address` LONGTEXT NULL DEFAULT NULL,
53   `city` VARCHAR(50) NULL DEFAULT NULL,
54   `state_province` VARCHAR(50) NULL DEFAULT NULL,
55   `zip_postal_code` VARCHAR(15) NULL DEFAULT NULL,
56   `country_region` VARCHAR(50) NULL DEFAULT NULL,
57   `web_page` LONGTEXT NULL DEFAULT NULL,
58   `notes` LONGTEXT NULL DEFAULT NULL,
59   `attachments` LONGBLOB NULL DEFAULT NULL,
60   PRIMARY KEY (`id`),
61   INDEX `city` (`city` ASC),
62   INDEX `company` (`company` ASC),
63   INDEX `first_name` (`first_name` ASC),
64   INDEX `last_name` (`last_name` ASC),
65   INDEX `zip_postal_code` (`zip_postal_code` ASC),
66   INDEX `state_province` (`state_province` ASC))
67   ENGINE = InnoDB
68   DEFAULT CHARACTER SET = utf8;
69  -- -----

```

```

70  -- Table `northwind`.`privileges`
71  -----
72  CREATE TABLE IF NOT EXISTS `northwind`.`privileges` (
73    `id` INT(11) NOT NULL AUTO_INCREMENT,
74    `privilege_name` VARCHAR(50) NULL DEFAULT NULL,
75    PRIMARY KEY (`id`))
76    ENGINE = InnoDB
77    DEFAULT CHARACTER SET = utf8;
78  -----
79  -- Table `northwind`.`employee_privileges`
80  -----
81  CREATE TABLE IF NOT EXISTS `northwind`.`employee_privileges` (
82    `employee_id` INT(11) NOT NULL,
83    `privilege_id` INT(11) NOT NULL,
84    PRIMARY KEY (`employee_id`, `privilege_id`),
85    INDEX `employee_id` (`employee_id` ASC),
86    INDEX `privilege_id` (`privilege_id` ASC),
87    INDEX `privilege_id_2` (`privilege_id` ASC),
88    CONSTRAINT `fk_employee_privileges_employees1`
89    FOREIGN KEY (`employee_id`)
90    REFERENCES `northwind`.`employees` (`id`)
91    ON DELETE NO ACTION
92    ON UPDATE NO ACTION,
93    CONSTRAINT `fk_employee_privileges_privileges1`
94    FOREIGN KEY (`privilege_id`)
95    REFERENCES `northwind`.`privileges` (`id`)
96    ON DELETE NO ACTION
97    ON UPDATE NO ACTION)
98    ENGINE = InnoDB
99    DEFAULT CHARACTER SET = utf8;
100 -----
101 -- Table `northwind`.`inventory_transaction_types`
102 -----
103 CREATE TABLE IF NOT EXISTS `northwind`.`inventory_transaction_types` (
104   `id` TINYINT(4) NOT NULL,
105   `type_name` VARCHAR(50) NOT NULL,
106   PRIMARY KEY (`id`))
107   ENGINE = InnoDB
108   DEFAULT CHARACTER SET = utf8;
109 -----
110 -- Table `northwind`.`shippers`
111 -----
112 CREATE TABLE IF NOT EXISTS `northwind`.`shippers` (
113   `id` INT(11) NOT NULL AUTO_INCREMENT,
114   `company` VARCHAR(50) NULL DEFAULT NULL,
115   `last_name` VARCHAR(50) NULL DEFAULT NULL,
116   `first_name` VARCHAR(50) NULL DEFAULT NULL,
117   `email_address` VARCHAR(50) NULL DEFAULT NULL,
118   `job_title` VARCHAR(50) NULL DEFAULT NULL,
119   `business_phone` VARCHAR(25) NULL DEFAULT NULL,
120   `home_phone` VARCHAR(25) NULL DEFAULT NULL,
121   `mobile_phone` VARCHAR(25) NULL DEFAULT NULL,
122   `fax_number` VARCHAR(25) NULL DEFAULT NULL,
123   `address` LONGTEXT NULL DEFAULT NULL,
124   `city` VARCHAR(50) NULL DEFAULT NULL,
125   `state_province` VARCHAR(50) NULL DEFAULT NULL,
126   `zip_postal_code` VARCHAR(15) NULL DEFAULT NULL,
127   `country_region` VARCHAR(50) NULL DEFAULT NULL,
128   `web_page` LONGTEXT NULL DEFAULT NULL,
129   `notes` LONGTEXT NULL DEFAULT NULL,
130   `attachments` LONGBLOB NULL DEFAULT NULL,
131   PRIMARY KEY (`id`),
132   INDEX `city` (`city` ASC),
133   INDEX `company` (`company` ASC),
134   INDEX `first_name` (`first_name` ASC),
135   INDEX `last_name` (`last_name` ASC),
136   INDEX `zip_postal_code` (`zip_postal_code` ASC),
137   INDEX `state_province` (`state_province` ASC))
138   ENGINE = InnoDB

```

```

139 DEFAULT CHARACTER SET = utf8;
140 -- -----
141 -- Table `northwind`.`orders_tax_status`
142 -- -----
143 CREATE TABLE IF NOT EXISTS `northwind`.`orders_tax_status` (
144   `id` TINYINT(4) NOT NULL,
145   `tax_status_name` VARCHAR(50) NOT NULL,
146   PRIMARY KEY (`id`))
147 ENGINE = InnoDB
148 DEFAULT CHARACTER SET = utf8;
149 -- -----
150 -- Table `northwind`.`orders_status`
151 -- -----
152 CREATE TABLE IF NOT EXISTS `northwind`.`orders_status` (
153   `id` TINYINT(4) NOT NULL,
154   `status_name` VARCHAR(50) NOT NULL,
155   PRIMARY KEY (`id`))
156 ENGINE = InnoDB
157 DEFAULT CHARACTER SET = utf8;
158 -- -----
159 -- Table `northwind`.`orders`
160 -- -----
161 CREATE TABLE IF NOT EXISTS `northwind`.`orders` (
162   `id` INT(11) NOT NULL AUTO_INCREMENT,
163   `employee_id` INT(11) NULL DEFAULT NULL,
164   `customer_id` INT(11) NULL DEFAULT NULL,
165   `order_date` DATETIME NULL DEFAULT NULL,
166   `shipped_date` DATETIME NULL DEFAULT NULL,
167   `shipper_id` INT(11) NULL DEFAULT NULL,
168   `ship_name` VARCHAR(50) NULL DEFAULT NULL,
169   `ship_address` LONGTEXT NULL DEFAULT NULL,
170   `ship_city` VARCHAR(50) NULL DEFAULT NULL,
171   `ship_state_province` VARCHAR(50) NULL DEFAULT NULL,
172   `ship_zip_postal_code` VARCHAR(50) NULL DEFAULT NULL,
173   `ship_country_region` VARCHAR(50) NULL DEFAULT NULL,
174   `shipping_fee` DECIMAL(19,4) NULL DEFAULT '0.0000',
175   `taxes` DECIMAL(19,4) NULL DEFAULT '0.0000',
176   `payment_type` VARCHAR(50) NULL DEFAULT NULL,
177   `paid_date` DATETIME NULL DEFAULT NULL,
178   `notes` LONGTEXT NULL DEFAULT NULL,
179   `tax_rate` DOUBLE NULL DEFAULT '0',
180   `tax_status_id` TINYINT(4) NULL DEFAULT NULL,
181   `status_id` TINYINT(4) NULL DEFAULT '0',
182   PRIMARY KEY (`id`),
183   INDEX `customer_id` (`customer_id` ASC),
184   INDEX `customer_id_2` (`customer_id` ASC),
185   INDEX `employee_id` (`employee_id` ASC),
186   INDEX `employee_id_2` (`employee_id` ASC),
187   INDEX `id` (`id` ASC),
188   INDEX `id_2` (`id` ASC),
189   INDEX `shipper_id` (`shipper_id` ASC),
190   INDEX `shipper_id_2` (`shipper_id` ASC),
191   INDEX `id_3` (`id` ASC),
192   INDEX `tax_status` (`tax_status_id` ASC),
193   INDEX `ship_zip_postal_code` (`ship_zip_postal_code` ASC),
194   CONSTRAINT `fk_orders_customers`
195     FOREIGN KEY (`customer_id`)
196     REFERENCES `northwind`.`customers` (`id`)
197     ON DELETE NO ACTION
198     ON UPDATE NO ACTION,
199   CONSTRAINT `fk_orders_employees1`
200     FOREIGN KEY (`employee_id`)
201     REFERENCES `northwind`.`employees` (`id`)
202     ON DELETE NO ACTION
203     ON UPDATE NO ACTION,
204   CONSTRAINT `fk_orders_shippers1`
205     FOREIGN KEY (`shipper_id`)
206     REFERENCES `northwind`.`shippers` (`id`)
207     ON DELETE NO ACTION

```

```

208 ON UPDATE NO ACTION,
209 CONSTRAINT `fk_orders_orders_tax_status1`
210 FOREIGN KEY (`tax_status_id`)
211 REFERENCES `northwind`.`orders_tax_status` (`id`)
212 ON DELETE NO ACTION
213 ON UPDATE NO ACTION,
214 CONSTRAINT `fk_orders_orders_status1`
215 FOREIGN KEY (`status_id`)
216 REFERENCES `northwind`.`orders_status` (`id`)
217 ON DELETE NO ACTION
218 ON UPDATE NO ACTION)
219 ENGINE = InnoDB
220 DEFAULT CHARACTER SET = utf8;
221 -- -----
222 -- Table `northwind`.`products`
223 -- -----
224 CREATE TABLE IF NOT EXISTS `northwind`.`products` (
225   `supplier_ids` LONGTEXT NULL DEFAULT NULL,
226   `id` INT(11) NOT NULL AUTO_INCREMENT,
227   `product_code` VARCHAR(25) NULL DEFAULT NULL,
228   `product_name` VARCHAR(50) NULL DEFAULT NULL,
229   `description` LONGTEXT NULL DEFAULT NULL,
230   `standard_cost` DECIMAL(19,4) NULL DEFAULT '0.0000',
231   `list_price` DECIMAL(19,4) NOT NULL DEFAULT '0.0000',
232   `reorder_level` INT(11) NULL DEFAULT NULL,
233   `target_level` INT(11) NULL DEFAULT NULL,
234   `quantity_per_unit` VARCHAR(50) NULL DEFAULT NULL,
235   `discontinued` TINYINT(1) NOT NULL DEFAULT '0',
236   `minimum_reorder_quantity` INT(11) NULL DEFAULT NULL,
237   `category` VARCHAR(50) NULL DEFAULT NULL,
238   `attachments` LONGBLOB NULL DEFAULT NULL,
239   PRIMARY KEY (`id`),
240   INDEX `product_code` (`product_code` ASC))
241 ENGINE = InnoDB
242 DEFAULT CHARACTER SET = utf8;
243 -- -----
244 -- Table `northwind`.`purchase_order_status`
245 -- -----
246 CREATE TABLE IF NOT EXISTS `northwind`.`purchase_order_status` (
247   `id` INT(11) NOT NULL,
248   `status` VARCHAR(50) NULL DEFAULT NULL,
249   PRIMARY KEY (`id`))
250 ENGINE = InnoDB
251 DEFAULT CHARACTER SET = utf8;
252 -- -----
253 -- Table `northwind`.`suppliers`
254 -- -----
255 CREATE TABLE IF NOT EXISTS `northwind`.`suppliers` (
256   `id` INT(11) NOT NULL AUTO_INCREMENT,
257   `company` VARCHAR(50) NULL DEFAULT NULL,
258   `last_name` VARCHAR(50) NULL DEFAULT NULL,
259   `first_name` VARCHAR(50) NULL DEFAULT NULL,
260   `email_address` VARCHAR(50) NULL DEFAULT NULL,
261   `job_title` VARCHAR(50) NULL DEFAULT NULL,
262   `business_phone` VARCHAR(25) NULL DEFAULT NULL,
263   `home_phone` VARCHAR(25) NULL DEFAULT NULL,
264   `mobile_phone` VARCHAR(25) NULL DEFAULT NULL,
265   `fax_number` VARCHAR(25) NULL DEFAULT NULL,
266   `address` LONGTEXT NULL DEFAULT NULL,
267   `city` VARCHAR(50) NULL DEFAULT NULL,
268   `state_province` VARCHAR(50) NULL DEFAULT NULL,
269   `zip_postal_code` VARCHAR(15) NULL DEFAULT NULL,
270   `country_region` VARCHAR(50) NULL DEFAULT NULL,
271   `web_page` LONGTEXT NULL DEFAULT NULL,
272   `notes` LONGTEXT NULL DEFAULT NULL,
273   `attachments` LONGBLOB NULL DEFAULT NULL,
274   PRIMARY KEY (`id`),
275   INDEX `city` (`city` ASC),
276   INDEX `company` (`company` ASC),

```

```

277 INDEX `first_name` (`first_name` ASC),
278 INDEX `last_name` (`last_name` ASC),
279 INDEX `zip_postal_code` (`zip_postal_code` ASC),
280 INDEX `state_province` (`state_province` ASC))
281 ENGINE = InnoDB
282 DEFAULT CHARACTER SET = utf8;
283 -----
284 -- Table `northwind`.`purchase_orders`
285 -----
286 CREATE TABLE IF NOT EXISTS `northwind`.`purchase_orders` (
287   `id` INT(11) NOT NULL AUTO_INCREMENT,
288   `supplier_id` INT(11) NULL DEFAULT NULL,
289   `created_by` INT(11) NULL DEFAULT NULL,
290   `submitted_date` DATETIME NULL DEFAULT NULL,
291   `creation_date` DATETIME NULL DEFAULT NULL,
292   `status_id` INT(11) NULL DEFAULT '0',
293   `expected_date` DATETIME NULL DEFAULT NULL,
294   `shipping_fee` DECIMAL(19,4) NOT NULL DEFAULT '0.0000',
295   `taxes` DECIMAL(19,4) NOT NULL DEFAULT '0.0000',
296   `payment_date` DATETIME NULL DEFAULT NULL,
297   `payment_amount` DECIMAL(19,4) NULL DEFAULT '0.0000',
298   `payment_method` VARCHAR(50) NULL DEFAULT NULL,
299   `notes` LONGTEXT NULL DEFAULT NULL,
300   `approved_by` INT(11) NULL DEFAULT NULL,
301   `approved_date` DATETIME NULL DEFAULT NULL,
302   `submitted_by` INT(11) NULL DEFAULT NULL,
303   PRIMARY KEY (`id`),
304   UNIQUE INDEX `id` (`id` ASC),
305   INDEX `created_by` (`created_by` ASC),
306   INDEX `status_id` (`status_id` ASC),
307   INDEX `id_2` (`id` ASC),
308   INDEX `supplier_id` (`supplier_id` ASC),
309   INDEX `supplier_id_2` (`supplier_id` ASC),
310   CONSTRAINT `fk_purchase_orders_employees1`
311   FOREIGN KEY (`created_by`)
312   REFERENCES `northwind`.`employees` (`id`)
313   ON DELETE NO ACTION
314   ON UPDATE NO ACTION,
315   CONSTRAINT `fk_purchase_orders_purchase_order_status1`
316   FOREIGN KEY (`status_id`)
317   REFERENCES `northwind`.`purchase_order_status` (`id`)
318   ON DELETE NO ACTION
319   ON UPDATE NO ACTION,
320   CONSTRAINT `fk_purchase_orders_suppliers1`
321   FOREIGN KEY (`supplier_id`)
322   REFERENCES `northwind`.`suppliers` (`id`)
323   ON DELETE NO ACTION
324   ON UPDATE NO ACTION)
325 ENGINE = InnoDB
326 DEFAULT CHARACTER SET = utf8;
327 -----
328 -- Table `northwind`.`inventory_transactions`
329 -----
330 CREATE TABLE IF NOT EXISTS `northwind`.`inventory_transactions` (
331   `id` INT(11) NOT NULL AUTO_INCREMENT,
332   `transaction_type` TINYINT(4) NOT NULL,
333   `transaction_created_date` DATETIME NULL DEFAULT NULL,
334   `transaction_modified_date` DATETIME NULL DEFAULT NULL,
335   `product_id` INT(11) NOT NULL,
336   `quantity` INT(11) NOT NULL,
337   `purchase_order_id` INT(11) NULL DEFAULT NULL,
338   `customer_order_id` INT(11) NULL DEFAULT NULL,
339   `comments` VARCHAR(255) NULL DEFAULT NULL,
340   PRIMARY KEY (`id`),
341   INDEX `customer_order_id` (`customer_order_id` ASC),
342   INDEX `customer_order_id_2` (`customer_order_id` ASC),
343   INDEX `product_id` (`product_id` ASC),
344   INDEX `product_id_2` (`product_id` ASC),
345   INDEX `purchase_order_id` (`purchase_order_id` ASC),

```

```

346 INDEX `purchase_order_id_2` (`purchase_order_id` ASC),
347 INDEX `transaction_type` (`transaction_type` ASC),
348 CONSTRAINT `fk_inventory_transactions_orders1`
349 FOREIGN KEY (`customer_order_id`)
350 REFERENCES `northwind`.`orders` (`id`)
351 ON DELETE NO ACTION
352 ON UPDATE NO ACTION,
353 CONSTRAINT `fk_inventory_transactions_products1`
354 FOREIGN KEY (`product_id`)
355 REFERENCES `northwind`.`products` (`id`)
356 ON DELETE NO ACTION
357 ON UPDATE NO ACTION,
358 CONSTRAINT `fk_inventory_transactions_purchase_orders1`
359 FOREIGN KEY (`purchase_order_id`)
360 REFERENCES `northwind`.`purchase_orders` (`id`)
361 ON DELETE NO ACTION
362 ON UPDATE NO ACTION,
363 CONSTRAINT `fk_inventory_transactions_inventory_transaction_types1`
364 FOREIGN KEY (`transaction_type`)
365 REFERENCES `northwind`.`inventory_transaction_types` (`id`)
366 ON DELETE NO ACTION
367 ON UPDATE NO ACTION)
368 ENGINE = InnoDB
369 DEFAULT CHARACTER SET = utf8;
370 -----
371 -- Table `northwind`.`invoices`
372 -----
373 CREATE TABLE IF NOT EXISTS `northwind`.`invoices` (
374   `id` INT(11) NOT NULL AUTO_INCREMENT,
375   `order_id` INT(11) NULL DEFAULT NULL,
376   `invoice_date` DATETIME NULL DEFAULT NULL,
377   `due_date` DATETIME NULL DEFAULT NULL,
378   `tax` DECIMAL(19,4) NULL DEFAULT '0.0000',
379   `shipping` DECIMAL(19,4) NULL DEFAULT '0.0000',
380   `amount_due` DECIMAL(19,4) NULL DEFAULT '0.0000',
381   PRIMARY KEY (`id`),
382   INDEX `id` (`id` ASC),
383   INDEX `id_2` (`id` ASC),
384   INDEX `fk_invoices_orders1_idx` (`order_id` ASC),
385   CONSTRAINT `fk_invoices_orders1`
386   FOREIGN KEY (`order_id`)
387   REFERENCES `northwind`.`orders` (`id`)
388   ON DELETE NO ACTION
389   ON UPDATE NO ACTION)
390   ENGINE = InnoDB
391   DEFAULT CHARACTER SET = utf8;
392 -----
393 -- Table `northwind`.`order_details_status`
394 -----
395 CREATE TABLE IF NOT EXISTS `northwind`.`order_details_status` (
396   `id` INT(11) NOT NULL,
397   `status_name` VARCHAR(50) NOT NULL,
398   PRIMARY KEY (`id`))
399   ENGINE = InnoDB
400   DEFAULT CHARACTER SET = utf8;
401 -----
402 -- Table `northwind`.`order_details`
403 -----
404 CREATE TABLE IF NOT EXISTS `northwind`.`order_details` (
405   `id` INT(11) NOT NULL AUTO_INCREMENT,
406   `order_id` INT(11) NOT NULL,
407   `product_id` INT(11) NULL DEFAULT NULL,
408   `quantity` DECIMAL(18,4) NOT NULL DEFAULT '0.0000',
409   `unit_price` DECIMAL(19,4) NULL DEFAULT '0.0000',
410   `discount` DOUBLE NOT NULL DEFAULT '0',
411   `status_id` INT(11) NULL DEFAULT NULL,
412   `date_allocated` DATETIME NULL DEFAULT NULL,
413   `purchase_order_id` INT(11) NULL DEFAULT NULL,
414   `inventory_id` INT(11) NULL DEFAULT NULL,

```

```

415 PRIMARY KEY (`id`),
416 INDEX `id` (`id` ASC),
417 INDEX `inventory_id` (`inventory_id` ASC),
418 INDEX `id_2` (`id` ASC),
419 INDEX `id_3` (`id` ASC),
420 INDEX `id_4` (`id` ASC),
421 INDEX `product_id` (`product_id` ASC),
422 INDEX `product_id_2` (`product_id` ASC),
423 INDEX `purchase_order_id` (`purchase_order_id` ASC),
424 INDEX `id_5` (`id` ASC),
425 INDEX `fk_order_details_orders1_idx` (`order_id` ASC),
426 INDEX `fk_order_details_order_details_status1_idx` (`status_id` ASC),
427 CONSTRAINT `fk_order_details_orders1`
428 FOREIGN KEY (`order_id`)
429 REFERENCES `northwind`.`orders` (`id`)
430 ON DELETE NO ACTION
431 ON UPDATE NO ACTION,
432 CONSTRAINT `fk_order_details_products1`
433 FOREIGN KEY (`product_id`)
434 REFERENCES `northwind`.`products` (`id`)
435 ON DELETE NO ACTION
436 ON UPDATE NO ACTION,
437 CONSTRAINT `fk_order_details_order_details_status1`
438 FOREIGN KEY (`status_id`)
439 REFERENCES `northwind`.`order_details_status` (`id`)
440 ON DELETE NO ACTION
441 ON UPDATE NO ACTION)
442 ENGINE = InnoDB
443 DEFAULT CHARACTER SET = utf8;
444 -----
445 -- Table `northwind`.`purchase_order_details`
446 -----
447 CREATE TABLE IF NOT EXISTS `northwind`.`purchase_order_details` (
448   `id` INT(11) NOT NULL AUTO_INCREMENT,
449   `purchase_order_id` INT(11) NOT NULL,
450   `product_id` INT(11) NULL DEFAULT NULL,
451   `quantity` DECIMAL(18,4) NOT NULL,
452   `unit_cost` DECIMAL(19,4) NOT NULL,
453   `date_received` DATETIME NULL DEFAULT NULL,
454   `posted_to_inventory` TINYINT(1) NOT NULL DEFAULT '0',
455   `inventory_id` INT(11) NULL DEFAULT NULL,
456   PRIMARY KEY (`id`),
457   INDEX `id` (`id` ASC),
458   INDEX `inventory_id` (`inventory_id` ASC),
459   INDEX `inventory_id_2` (`inventory_id` ASC),
460   INDEX `purchase_order_id` (`purchase_order_id` ASC),
461   INDEX `product_id` (`product_id` ASC),
462   INDEX `product_id_2` (`product_id` ASC),
463   INDEX `purchase_order_id_2` (`purchase_order_id` ASC),
464   CONSTRAINT `fk_purchase_order_details_inventory_transactions1`
465   FOREIGN KEY (`inventory_id`)
466   REFERENCES `northwind`.`inventory_transactions` (`id`)
467   ON DELETE NO ACTION
468   ON UPDATE NO ACTION,
469   CONSTRAINT `fk_purchase_order_details_products1`
470   FOREIGN KEY (`product_id`)
471   REFERENCES `northwind`.`products` (`id`)
472   ON DELETE NO ACTION
473   ON UPDATE NO ACTION,
474   CONSTRAINT `fk_purchase_order_details_purchase_orders1`
475   FOREIGN KEY (`purchase_order_id`)
476   REFERENCES `northwind`.`purchase_orders` (`id`)
477   ON DELETE NO ACTION
478   ON UPDATE NO ACTION)
479   ENGINE = InnoDB
480   DEFAULT CHARACTER SET = utf8;
481 -----
482 -- Table `northwind`.`sales_reports`
483 -----

```

```

484 CREATE TABLE IF NOT EXISTS `northwind`.`sales_reports` (
485   `group_by` VARCHAR(50) NOT NULL,
486   `display` VARCHAR(50) NULL DEFAULT NULL,
487   `title` VARCHAR(50) NULL DEFAULT NULL,
488   `filter_row_source` LONGTEXT NULL DEFAULT NULL,
489   `default` TINYINT(1) NOT NULL DEFAULT '0',
490   PRIMARY KEY (`group_by`))
491   ENGINE = InnoDB
492   DEFAULT CHARACTER SET = utf8;
493   -- -----
494   -- Table `northwind`.`strings`
495   -- -----
496   CREATE TABLE IF NOT EXISTS `northwind`.`strings` (
497     `string_id` INT(11) NOT NULL AUTO_INCREMENT,
498     `string_data` VARCHAR(255) NULL DEFAULT NULL,
499     PRIMARY KEY (`string_id`))
500     ENGINE = InnoDB
501     DEFAULT CHARACTER SET = utf8;
502     SET SQL_MODE=@OLD_SQL_MODE;
503     SET FOREIGN_KEY_CHECKS=@OLD_FOREIGN_KEY_CHECKS;
504     SET UNIQUE_CHECKS=@OLD_UNIQUE_CHECKS;

```