


Glitch Filter

2.0

Features

- Eliminates unwanted “glitch” pulses on digital input lines
- Programmable filtering length and bypass option



General Description

Glitch filtering is the process of removing unwanted pulses from a digital input signal that is usually high or low. Glitches frequently occur on lines carrying signals from sources such as RF receivers. Electrical or in some cases even mechanical interference can trigger an unwanted glitch pulse from the receiver.

This design outputs a ‘1’ only when the current and previous N samples are ‘1’, and a ‘0’ only when the current and previous N samples are ‘0’. Otherwise the output is unchanged from its current value.

For more details on glitch filtering please see application note AN60024.

When to Use a Glitch Filter

A Glitch Filter component can be used with any digital input; it is typically associated with noise interference on a line that is connected to an input pin. Since it does a lot of work that could otherwise be done by firmware, it can be used when a firmware-based glitch filter solution is not practical.

Input/Output Connections

This section describes the input and output connections for the Glitch Filter component.

d – Input

The input that is sampled. It is usually connected to an input Pin component.

reset – Input

Active high synchronous reset that requires at least one rising edge of the clock. The reset input may be left floating with no external connection. If nothing is connected to the reset line, the component will assign it a constant logic 0.

clock – Input


Clock used to sample the 'd' input. Its frequency depends on anticipated glitch pulse width and delay through the filter.

q – Output

This output is set to logic '1' when the current and previous N samples are logic '1', and logic '0' when the current and previous N samples are '0'. Otherwise the output is unchanged from its current value.

Component Parameters

Drag a Glitch Filter component onto your design and double-click it to open the **Configure** dialog.



Signal Width

This parameter configures the signal width that will be filtered. This value can be set between 1 and 24. The default setting is **1 bit**.

Glitch Length

Determines the number of samples for which input has to be stable before being propagated to the output. This value can be set between 1 and 256 clock cycles. The default setting is **3**.

Bypass Filter

Specifies the logic level that will be propagated to the output immediately. The Bypass Filter **Logic zero** option makes the Glitch Filter output logic '0' on the next clock cycle the 'd' input is at logic '0'. Similarly, there is an option for Bypass Filter **Logic one**. The default setting is **None**.

Clock Selection

There is no internal clock in this component. You must attach a clock source. This component operates from a single clock connected to the component.

Sample Firmware Source Code

PSoC Creator provides many example projects that include schematics and example code in the Find Example Project dialog. For component-specific examples, open the dialog from the Component Catalog or an instance of the component in a schematic. For general examples, open the dialog from the Start Page or **File** menu. As needed, use the **Filter Options** in the dialog to narrow the list of projects available to select.

Refer to the “Find Example Project” topic in the PSoC Creator Help for more information..

Functional Description



The glitch filter component outputs a '1' only when the current and previous N samples are '1', and a '0' only when the current and previous N samples are '0'. Otherwise, the output is unchanged from its current value.

For more details on glitch filtering please see application note AN60024

Block Diagram and Configuration

The Glitch Filter component implementation depends on programmable filter length parameter. If the parameter value is ≤ 8 the implementation uses the PLD portion of one or more of the UDBs. If the filter length is between 9 and 256 samples, the component is implemented on datapath elements of the UDB Array. [Figure 1](#) shows this implementation.



Figure 1. Block Diagram**Glitch length ≤ 8**  **$8 < \text{Glitch length} \leq 256$** 

Resources

The Glitch Filter component is placed throughout the UDB array. The component utilizes the following resources.

Configuration	Resource Type					
	Datapath Cells	Macrocells	Status Cells	Control Cells	DMA Channels	Interrupts
Glitch Length ≤ 8	—	$N * (L + 1)$ ^[1]	—	—	—	—
$8 < \text{Glitch Length} \leq 256$	N	N	—	—	—	—

1. N – Signal width; L – Filtering length.

DC and AC Electrical Characteristics

Specifications are valid for $-40\text{ }^{\circ}\text{C} \leq T_A \leq 85\text{ }^{\circ}\text{C}$ and $T_J \leq 100\text{ }^{\circ}\text{C}$, except where noted.
Specifications are valid for 1.71 V to 5.5 V, except where noted.

AC Characteristics

Parameter	Description	Min	Typ	Max	Unit
f_{CLOCK}	Component clock frequency				
	Glitch Length ≤ 8	–	–	67	MHz
	$8 < \text{Glitch Length} \leq 256$	–	–	40	MHz

Component Changes

This section lists the major changes in the component from the previous version.

Version	Description of Changes	Reason for Changes / Impact
2.0	Complete redesign. Glitch Filter v2.0 is NOT AT ALL backwards compatible with previous versions.	Updated for compatibility with PSoC Creator v2.1 to be included as standard library component. Added 'Signal width', 'Glitch Length' and 'Bypass Filter' parameter to allow configuring of the component.
1.30	Updated for compatibility with PSoC Creator v2.0, to be used as a concept component included in PSoC Creator.	
1.2	Updated for compatibility with PSoC Creator v1.0.	
1.1	Updated for compatibility with PSoC Creator beta5. Updated data sheet format.	
1.0	Initial design.	

© Cypress Semiconductor Corporation, 2012. The information contained herein is subject to change without notice. Cypress Semiconductor Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in a Cypress product. Nor does it convey or imply any license under patent or other rights. Cypress products are not warranted nor intended to be used for medical, life support, life saving, critical control or safety applications, unless pursuant to an express written agreement with Cypress. Furthermore, Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress products in life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

PSoC® is a registered trademark, and PSoC Creator™ and Programmable System-on-Chip™ are trademarks of Cypress Semiconductor Corp. All other trademarks or registered trademarks referenced herein are property of the respective corporations.

Any Source Code (software and/or firmware) is owned by Cypress Semiconductor Corporation (Cypress) and is protected by and subject to worldwide patent protection (United States and foreign), United States copyright laws and international treaty provisions. Cypress hereby grants to licensee a personal, non-exclusive, non-transferable license to copy, use, modify, create derivative works of, and compile the Cypress Source Code and derivative works for the sole purpose of creating custom software and or firmware in support of licensee product to be used only in conjunction with a Cypress integrated circuit as specified in the applicable agreement. Any reproduction, modification, translation, compilation, or representation of this Source Code except as specified above is prohibited without the express written permission of Cypress.

Disclaimer: CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Cypress reserves the right to make changes without further notice to the materials described herein. Cypress does not assume any liability arising out of the application or use of any product or circuit described herein. Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress' product in a life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Use may be limited by and subject to the applicable Cypress software license agreement.

