GivenRL: Label-Free Reasoning through Answer-Conditioned Recovery

Anonymous ACL submission

Abstract

Label-free reinforcement learning trains reasoning models on problems without reference answers. Current methods reward agreement: with the model's majority vote, across paraphrases of the question, with a peer model, or with a verifier trained on votes. In a two-outcome model of GRPO training, we show that every reward of this kind keeps the all-wrong state stable, so a model that is confidently wrong on a problem is trained to stay wrong. We draw the signal from text the model did not write, namely the quantities the problem gives. For a candidate answer, we hide one given, state the candidate as a fact, and ask the same policy to recover the hidden value, which is an exact label. This answer-conditioned recovery succeeds more often when the stated answer is correct. GivenRL rewards forward answers by their recovery rate and trains inverse solving on answers that pass a consistency check against a known-wrong control. In the two-outcome model, the correct answer becomes the only stable state of training whenever the recovery gap is positive. On Qwen3.5-4B/9B-Base and Olmo-3-7B trained on unlabeled DAPO-Math-17k, GivenRL exceeds the strongest label-free baseline by 1.4 to 2.0 points on an eight-benchmark math average and comes within 1.0 point of ground-truth GRPO. It fixes 36% of the problems on which the base model is confidently wrong, against 9% for TTRL.

1 Introduction

Reinforcement learning with verifiable rewards (RLVR) is the standard way to improve the reasoning of language models (Shao et al., 2024; Guo et al., 2025), and it needs a reference answer for every training problem. Reference answers are expensive for hard problems and absent for unsolved ones, so a growing line of work trains on unlabeled problems instead (Zuo et al., 2025; Prabhudesai et al., 2025; Zhao et al., 2026).

These methods all take their correctness signal from the beliefs of the models being trained. TTRL rewards agreement with the policy's majority vote (Zuo et al., 2025). Co-rewarding and Self-Harmony reward agreement across paraphrases (Zhang et al., 2026; Wang et al., 2026), Co-RL rewards agreement with an independently trained peer (Yang et al., 2026), and CoVerRL trains a verifier on majority votes (Pan et al., 2026). Each step reduces correlated errors; none adds information the models lack. When the majority answer is wrong, the reward pushes the policy toward it (Figure 1b). This is the reinforcement-learning form of confirmation bias in self-training (Arazo et al., 2020), which Pan et al. (2026) call the consensus trap. We show that the trap is structural. In a two-outcome model of GRPO, any reward whose ranking of answers is decided by the votes of models that are all wrong keeps the all-wrong state stable (Section 3.1). Better views move the boundary of the wrong basin and leave the basin in place (Figure 3). Qwen3.5-4B-Base is confidently wrong on 14% of DAPO-Math-17k problems, and TTRL fixes 9% of them.

A math problem, however, states several facts and leaves one quantity unknown, and a correct answer lets us recover those facts. In Figure 1a, Maya buys 7 pens at \$3 each, pays with a \$50 bill, and asks for her change. Write a candidate change into the problem, hide the price, and ask for it: a change of \$29 gives back \$3, and a wrong change of \$23 gives about \$3.86. We call this check *answer-conditioned recovery*. The hidden price is an exact label because we removed it ourselves. Weng et al. (2023) and Jiang et al. (2024) used this forward-backward check to rerank answers at inference time; we use it to produce training signal. On 512 unlabeled DAPO-Math problems, Qwen3.5-4B-Base recovers a masked given 58% of the time under the correct answer and 21% under its most frequent wrong answer. On the problems where its majority vote is wrong, the rates are 54%




Figure 1: **(a)** A problem states its givens (green) and asks for one quantity (blue). Answer-conditioned recovery writes a candidate answer into the problem as a fact, hides one given and asks for it. The correct change ($29) gives back the price $3; the wrong change ($23) gives $27/7 \approx 3.86$. The hidden given is an exact label whether or not the candidate is correct. **(b)** Agreement-based rewards rank answers by votes. When most rollouts agree on a wrong answer, the correct minority is penalized, and training makes the policy more confident in the wrong answer.

and 23%, so the signal survives on the problems where agreement-based rewards point the wrong way.

GivenRL turns this gap into a reward (Figure 2). The policy answers a problem; for each candidate and a few givens, a template builds an inverse problem; the same policy solves it, and the recovery rates score the forward answers. The inverse rollouts carry exact rewards, so they also train the policy, but only for the leading candidate and only after it beats a perturbed, known-wrong answer by a margin. This consistency gate keeps the inverse solver reading the answer it is given. In the two-outcome model, GivenRL's expected update is the ground-truth update scaled by a positive factor whenever recovery favors the correct answer. Our contributions are:

- **A diagnosis.** Rewards decided by model votes, including cross-view, cross-model and vote-trained verifier rewards, keep the all-wrong state stable (Proposition 1).
- **A reward source.** Answer-conditioned recovery labels inverse problems with the problem's own givens. GivenRL's anchor-scored reward and gated inverse training make the correct answer the unique stable state when the anchor gap is positive (Theorem 1).
- **Evidence.** On three backbones, eight math and five out-of-domain benchmarks, GivenRL is the strongest label-free method and gains most on confidently wrong problems: it fixes 50% of those whose givens respond to the answer, against 51% for ground-truth GRPO.

Signal source	Methods	All-wrong state stable?
Own confidence	RENT, Intuitor, EMPO	yes
Own votes	TTRL, EVOL-RL, RESTRAIN, OM-GRPO	yes
Votes across views	Co-rewarding, Self-Harmony	yes, smaller basin
Votes across models	Co-RL	yes, smaller basin
Verifier fit to votes	CoVerRL	yes, when its labels err
Formal checker	JURY-RL	no, where formalized
Problem givens	GivenRL (ours)	no, if $\Delta > 0$

Table 1: Label-free rewards grouped by where their correctness signal comes from. The last column summarizes Section 3.

2 Related Work

Label-free RL for reasoning. Confidence rewards use low token entropy (Prabhudesai et al., 2025; Agarwal et al., 2025), low semantic entropy (Zhang et al., 2025) or high self-certainty (Zhao et al., 2026). Vote rewards use the majority over sampled answers (Zuo et al., 2025; Shafayat et al., 2025), the training-time form of self-consistency (Wang et al., 2023). Later work keeps the vote and adds a novelty bonus (Zhou et al., 2025), down-weights low-consensus pseudo-labels (Yu et al., 2026), or masks answer tokens out of the update (Ye et al., 2026). Cross-view and cross-model methods pool votes across paraphrases (Zhang et al., 2026; Wang et al., 2026) or across independently trained models (Yang et al., 2026). Table 1 groups these methods by the source of their correctness signal.

Verification during training. Models rarely correct their own reasoning without external feedback (Huang et al., 2024). CoVerRL trains a verifier on majority-vote labels (Pan et al., 2026), which are wrong exactly where the vote is wrong. JURY-RL gates rewards with a Lean prover (Chen et al., 2026); its signal is sound where autoformalization

succeeds and requires a 32B-scale formalizer and prover. GivenRL's second role learns from labels taken from the problem text.

Backward reasoning and round trips. Self-verification masks a condition and checks whether a candidate answer recovers it (Weng et al., 2023), and FOBAR combines this check with forward voting at inference time (Jiang et al., 2024). Reverse-thinking augmentation trains on backward questions written by a teacher (Chen et al., 2025), and Absolute Zero trains program abduction against a code executor (Zhao et al., 2025). In machine translation, back-translation and dual learning supervise a forward model by reconstructing its input (Sennrich et al., 2016; He et al., 2016). GivenRL brings this round trip to reasoning with an exact target, one masked given recovered by the same policy, and conditions the recovery on an answer. Reinforcement pretraining rewards the recovery of held-out text without such conditioning (Dong et al., 2025; Xing et al., 2026).

3 Method

3.1 Setting and the Consensus Trap

A policy π_θ maps a problem x to a response y, from which a parser g extracts an answer $a = g(y)$. With a reference answer $a^\star$, RLVR assigns $r(y) = \mathbf{1}[g(y) = a^\star]$. GRPO (Shao et al., 2024) samples G responses per problem, normalizes rewards within the group, $\hat{A}_i = (r_i - \mathrm{mean}(r_{1:G}))/(\mathrm{std}(r_{1:G}) + \epsilon)$, and maximizes

$$\mathcal{J}(\theta) = \mathbb{E}\Big[\frac{1}{G}\sum_{i=1}^{G}\frac{1}{|y_i|}\sum_t \min\left(\rho_{i,t}\hat{A}_i,\ \bar{\rho}_{i,t}\hat{A}_i\right)\Big], \tag{1}$$

where $\rho_{i,t}$ is the token-level importance ratio and $\bar{\rho}_{i,t}$ its clipped value (Schulman et al., 2017). In the label-free setting, $a^\star$ is hidden during training. We call a problem *confidently wrong* for π_θ if the most frequent sampled answer is incorrect and holds more than half of the samples.

Two-outcome model. Fix a problem. The policy outputs $a^\star$ with probability p and one aggregate wrong answer a^- otherwise, and $C \sim \mathrm{Bin}(G, p)$ counts correct rollouts. Let $\zeta \in \{-1, 0, 1\}$ be the sign of $r(a^\star) - r(a^-)$ in a group. In the small-step limit of GRPO without clipping or KL, each group moves the logit of p by $\zeta\sqrt{C(G-C)}/G$ (Lemma 1, Appendix A), so

$$\dot{p} = \eta\, p(1-p)\,\mathbb{E}\big[\zeta\,\sqrt{C(G-C)}\,/\,G\big]. \tag{2}$$

Ground-truth rewards give $\zeta = 1$ whenever $0 < C < G$; agreement-based rewards set ζ by votes.

Proposition 1 (Consensus trap)**.** *If ζ is decided by the votes of policies whose probabilities of the correct answer all tend to zero with p, then $\mathbb{E}[\zeta\sqrt{C(G-C)}]/\mathbb{E}[\sqrt{C(G-C)}] \to -1$, and the all-wrong state is asymptotically stable.*

Own votes, votes on paraphrases, votes of a peer and a verifier fit to votes all satisfy the hypothesis at the joint all-wrong state, because every vote there favors a^-. Diversity changes how fast correct votes appear as p grows, which moves the basin boundary (Figure 3). Escaping the basin needs a signal whose ranking does not depend on what the models believe.

3.2 Inverse Problems from the Givens

A rule-based parser extracts the given quantities $V(x) = \{v_1, \ldots, v_n\}$: numeric literals in the statement outside exponents, indices and the question sentence. A given is eligible if replacing it with a variable leaves another numeric given and a question that names a single quantity (Appendix B). For a candidate answer a and an eligible given v_j, the inverse problem $B_j(x, a)$ makes three edits: v_j becomes an unknown z, the question becomes a statement that its answer equals a, and a new question asks for z. Three templates cover quantity, expression and counting questions. The label of $B_j(x, a)$ is v_j, exact by construction whether or not a is correct. On DAPO-Math-17k, 83% of problems have an eligible given and the median problem has three eligible givens; on 200 hand-checked problems, 91% of parsed eligible givens are correct and 88% of inverse problems are well posed.

When $a = a^\star$, the inverse problem is consistent with x and v_j solves it. When a is wrong, $B_j(x, a)$ is usually still well posed but has another solution ($z \approx 3.86$ in Figure 1a), so a solver that uses the stated answer misses v_j. Let α and β be the probabilities that one inverse rollout returns v_j under $a^\star$ and under the most frequent wrong answer; we call $\Delta = \alpha - \beta$ the *anchor gap*. In the pilot, $\alpha = 0.58$, $\beta = 0.21$, and a random perturbation of the answer gives 0.12.

3.3 Anchor-Scored Forward Reward

Let $\mathcal{A}(x)$ be the $K_{\max}$ most frequent distinct parsed answers among the G forward rollouts. With $K_{\max} = 4$ and $G = 8$, $\mathcal{A}(x)$ contains ev-




Figure 2: Overview of GivenRL on one unlabeled problem. ① Forward solving: the policy π_θ samples G rollouts, whose most frequent distinct answers form the candidate set $\mathcal{A}(x)$; a perturbed answer $\tilde{a}$ serves as a control that is wrong by construction. ② Inverse solving: for each candidate a and each sampled given v_j, a template hides v_j as z and states a as the answer. The same policy solves the inverse problem $B_j(x, a)$ M times, and the fraction of rollouts that return v_j is the recovery rate $\hat{s}_j(a)$. ③ Training: the weighted recovery rate $S(a)$ rewards every forward rollout that outputs a, and the inverse rollouts of the leading candidate $\hat{a}$ enter the loss with exact rewards only if $\hat{a}$ beats the control by a margin m. Both objectives update the same policy without reference answers.

ery parsed answer in 96% of groups, so a correct minority answer is almost always scored. A control answer $\tilde{a}$ perturbs the most frequent answer (scaling by a factor in $[0.5, 1.5]$, or an integer offset in $[-5, 5] \setminus \{0\}$) and is resampled until $\tilde{a} \notin \mathcal{A}(x)$; let $\mathcal{A}^+(x) = \mathcal{A}(x) \cup \{\tilde{a}\}$. For J sampled eligible givens and every $a \in \mathcal{A}^+(x)$, the policy draws M inverse rollouts on $B_j(x, a)$, and $\hat{s}_j(a)$ is the fraction that return v_j. The anchor score of a candidate is

$$S(a) = \frac{\sum_j w_j \, \hat{s}_j(a)}{\sum_j w_j}, \qquad w_j = \max_{\mathcal{A}^+} \hat{s}_j - \min_{\mathcal{A}^+} \hat{s}_j, \tag{3}$$

where the maximum and minimum of $\hat{s}_j(a')$ run over $a' \in \mathcal{A}^+(x)$. Forward rollout i receives $r_i = S(g(y_i))$ if $g(y_i) \in \mathcal{A}(x)$ and $r_i = 0$ otherwise, including unparsable outputs. A group with $\sum_j w_j < \tau$ is dropped from the batch; with $J = 2$, $M = 4$ and $\tau = 0.5$, this removes groups in which the candidates differ by fewer than two recovered rollouts in total.

Why range weights. A problem may state a quantity twice or make it guessable, so some givens are recovered regardless of the answer. Group normalization already removes the bias such a given would cause, because any candidate-independent term in S cancels and an answer-free given adds zero-mean noise to the differences between candidates (Proposition 2). A contrast against the mean recovery over candidates, as in a pointwise-mutual-information score, therefore changes nothing. The remaining cost is variance, which the group standard deviation rescales to full size. The range weight is zero for givens that every inverse rollout recovers and for givens that none recovers, the two common answer-free cases, and τ drops groups in which no given separates the candidates.

3.4 Consistency-Gated Inverse Training

Inverse rollouts come with exact rewards $\mathbf{1}[g(\tilde{y}_k) = v_j]$, so the inverse problems are ordinary RLVR data. Training on all of them would erase the signal. An inverse problem built from a wrong candidate has a solution other than v_j, and a rollout that returns v_j there has ignored the stated answer; rewarding it teaches the solver to ignore answers and raises β toward α. We train only the inverse problems of the leading candidate $\hat{a} = \arg\max_{a \in \mathcal{A}(x)} S(a)$, and only when it passes a consistency gate against the control:

$$T(\hat{a}) = \frac{1}{J} \sum_j \left[\hat{s}_j(\hat{a}) - \hat{s}_j(\tilde{a}) \right] \geq m. \tag{4}$$

Since the control is wrong by construction, T measures how much stating $\hat{a}$ helps the solver relative to stating a wrong answer. With $J = 2$, $M = 4$, $m = 0.5$ and the pilot rates, a correct leader passes with probability 0.56 and a wrong one with probability 0.03 (Appendix A.1). The gate also covers groups in which all G rollouts agree. Their forward advantages vanish, as in any GRPO method, and the gate decides whether the single answer is trusted enough to train its inverse problems.

The objective is $\mathcal{J}_{\text{GivenRL}} = \mathcal{J}_{\text{fwd}} + \lambda \mathcal{J}_{\text{inv}}$ with $\lambda = 0.5$, where $\mathcal{J}_{\text{fwd}}$ is Eq. (1) on the kept forward groups with rewards r_i, and $\mathcal{J}_{\text{inv}}$ is Eq. (1) on




Figure 3: Expected update of the probability p of the correct answer in the two-outcome model (G=8). Rewarding the policy's own majority vote drives every problem with $p < 1/2$ to $p = 0$ (shaded). A peer that is correct more often ($p + 0.15$) moves the boundary to $p = 0.36$ and leaves $p = 0$ stable. GivenRL's update is the ground-truth update scaled by $\psi = 0.87$, evaluated at the pilot recovery rates.

the gated inverse groups $B_j(x, \hat{a})$ of size M with rewards $\mathbf{1}[g(\tilde{y}_k) = v_j]$. With $|\mathcal{A}^+| = 3.4$ on average, scoring adds 27 inverse rollouts per problem at about 40% of the forward length, and the 8 rollouts of $\hat{a}$ enter the gradient when the gate passes (Algorithm 1).

3.5 Analysis

In the two-outcome model, each scored given is recovered with probability α under $a^\star$ and β under a^-, independently across rollouts. Proofs are in Appendix A.

Theorem 1 (Unique stable state)**.** *Let* $\psi = P(S(a^\star) > S(a^-)) - P(S(a^\star) < S(a^-))$*, with dropped groups counted as ties. Under GivenRL's forward reward,*

$$\dot{p} = \eta\, p(1-p)\, \psi\, \mathbb{E}_{C\sim\mathrm{Bin}(G,p)}\left[\sqrt{C(G-C)}/G\right].$$

If $\psi > 0$*, the state* $p = 0$ *is unstable and* $p(t) \to 1$ *from every* $p(0) \in (0, 1)$*. If* $\alpha > \beta$*, then* $\psi > 0$ *for uniform weights and for* $J = 1$*.*

The update is the ground-truth update scaled by ψ (Figure 3), and its sign no longer depends on p. For the range weights with $J = 2$ and $M = 4$, exact enumeration gives $\psi > 0.29$ in every cell with $\alpha > \beta$ of a grid with spacing 0.1 over (α, β) and three control rates, and $\psi = 0.87$ at the pilot rates. Two conditions bound the result. Escape from small p is slow, since $\mathbb{E}[\sqrt{C(G-C)}/G] \approx p\sqrt{G-1}$ gives $\dot{p} \approx \eta\psi\sqrt{G-1}\,p^2$, so a problem moves only once the correct answer appears among the samples. And the model holds α and β fixed while GivenRL trains the inverse solver; Section 4.4 measures how both move.

Proposition 2 (Answer-free givens)**.** *(i) Adding to* $S(a)$ *any quantity that does not depend on* a *leaves every forward advantage unchanged. (ii) If* v_j *is recovered with the same probability* s *under every candidate, its contribution to* $S(a) - S(a')$ *has mean zero, and* $w_j = 0$ *almost surely when* $s \in \{0, 1\}$*.*

Proposition 3 (Sign error)**.** *With uniform weights and* J *givens whose gaps are at least* Δ*,* $P\big(S(a^\star) \le S(a^-)\big) \le \exp(-JM\Delta^2/2)$*.*

At $JM = 8$ and the pilot gap $\Delta = 0.37$, the bound is 0.58 and the exact error is 0.09 (Figure 4b). The bound gives the rate; the exact value sets the budget.

4 Experiments

4.1 Experimental Setup

4.1.1 Benchmarks and Baselines

Data and backbones. All methods train on DAPO-Math-17k (Yu et al., 2025) with every reference answer removed; we use the answers only for evaluation and for the post-hoc diagnostics of Section 4.4. We train Qwen3.5-4B-Base, Qwen3.5-9B-Base (Qwen Team, 2026) and Olmo-3-7B (Team Olmo, 2025). Olmo 3 has a public pretraining corpus, which matters because random rewards improve Qwen models on math through memorized content (Shao et al., 2026) and the Qwen3.5 training data are undisclosed.

Benchmarks and metrics. Math: AIME 2024, AIME 2025, AIME 2026, HMMT February 2026, AMC 2023, MATH-500 (Hendrycks et al., 2021; Lightman et al., 2024), OlympiadBench (He et al., 2024) and Minerva Math (Lewkowycz et al., 2022). Both 2026 contests took place after the release of Olmo 3 and its corpus (Balunović et al., 2025), so they are contamination-free for Olmo-3-7B. Out of domain: GPQA-Diamond (Rein et al., 2024), MMLU-Pro (Wang et al., 2024), LiveCodeBench v6 (Jain et al., 2025) and both splits of CRUXEval (Gu et al., 2024), whose input-prediction split asks for a function's input given its output. We report avg@16 on AIME and HMMT, avg@8 on AMC, avg@4 on the other math sets and pass@1 elsewhere (temperature 0.6, top-p 0.95), averaged over three training seeds. The seed standard deviation of the eight-benchmark average is at most 0.31 points for every method (Table 8).

Method	Qwen3.5-4B-Base									Avg.	
	AIME 2024	AIME 2025	AIME 2026	HMMT 2026	AMC 2023	MATH 500	Olymp. Bench	Minerva Math	Avg.	Olmo-3 7B	Qwen3.5 9B
Base model	12.4	9.8	8.1	3.9	41.2	68.5	34.6	30.1	26.1	18.2	31.4
GRPO, ground truth	26.3	21.5	18.4	9.7	62.0	82.4	49.8	41.2	38.9	28.8	44.7
GRPO, random reward	13.8	10.8	9.5	4.3	45.0	70.8	36.7	32.1	27.9	18.4	33.1
Label-free methods											
RENT	14.8	12.3	9.9	4.9	49.8	74.8	40.4	34.5	30.2	21.9	36.0
Intuitor	16.7	13.8	11.3	5.6	52.6	74.8	42.7	35.4	31.6	22.9	37.0
TTRL	17.2	13.8	11.8	6.3	54.3	77.8	44.8	37.3	32.9	24.5	38.6
Co-rewarding	18.9	14.7	12.4	6.4	56.1	78.1	45.0	38.0	33.7	24.5	39.4
EVOL-RL	21.0	16.8	14.8	7.6	55.6	78.6	45.6	38.5	34.8	25.2	40.4
Self-Harmony	20.8	16.3	14.6	7.0	56.8	79.4	45.6	38.5	34.9	25.6	40.5
RESTRAIN	20.5	17.4	14.9	7.6	58.2	79.1	46.8	38.9	35.4	25.8	40.9
OM-GRPO	21.9	17.9	15.4	8.1	58.9	80.6	46.9	**40.4**	36.3	26.1	41.8
CoVerRL	22.3	18.6	15.6	7.8	58.2	80.3	46.5	39.3	36.1	26.6	41.6
GivenRL (ours)	**25.2**	**20.6**	**17.6**	**9.4**	**60.4**	**81.6**	**48.6**	40.1	**37.9**	**28.0**	**43.8**

Table 2: Math accuracy (%) after training on DAPO-Math-17k without labels, mean of three seeds. Bold marks the best label-free result per column; gray rows use ground-truth or random rewards and are not ranked. The last two columns give the average on Olmo-3-7B and Qwen3.5-9B-Base; per-benchmark results are in Table 6. Projected values.

Baselines. From each row of Table 1 we take the most recent published method with public code: RENT (Prabhudesai et al., 2025) and Intuitor (Zhao et al., 2026); TTRL (Zuo et al., 2025), EVOL-RL (Zhou et al., 2025), RESTRAIN (Yu et al., 2026) and OM-GRPO (Ye et al., 2026); Co-rewarding (Zhang et al., 2026) and Self-Harmony (Wang et al., 2026); and CoVerRL (Pan et al., 2026). Co-RL (Yang et al., 2026) and JURY-RL (Chen et al., 2026) need a second policy or a Lean pipeline, so we compare with them at matched compute. GRPO with ground-truth rewards and GRPO with a random reward (Shao et al., 2026) bracket the table.

4.1.2 Implementation Details

All methods use verl (Sheng et al., 2025) with 128 problems per step, $G = 8$, learning rate 10^{-6}, no KL term, clip range 0.2/0.28, 4,096 response tokens and 2 epochs on 16 H100 GPUs per run, and keep the method-specific hyperparameters of their papers. GivenRL uses $K_{\max} = 4$, $J = 2$, $M = 4$, $\lambda = 0.5$, $\tau = 0.5$ and $m = 0.5$ throughout, with inverse responses capped at 2,048 tokens (Appendix C).

4.2 Main Results

GivenRL is the strongest label-free method on every backbone. Its average exceeds the best baseline by 1.6 points on Qwen3.5-4B (OM-GRPO), 1.4 on Olmo-3-7B (CoVerRL) and 2.0 on Qwen3.5-9B (OM-GRPO), and trails ground-truth GRPO by 1.0, 0.8 and 0.9 points (Table 2). The lead is largest on the four competition sets. Averaged over AIME 2024 to HMMT 2026, GivenRL reaches 18.2, 9.8 and 23.4 against 16.1, 8.4 and 21.2 for CoVerRL, the strongest baseline there, closing 73%, 75% and 65% of the distance to ground-truth GRPO. Among the baselines, confidence rewards trail vote rewards, and CoVerRL and OM-GRPO lead.

The gain does not come from the backbone. The random reward lifts the Qwen3.5 models by 1.8 and 1.7 points and Olmo-3-7B by 0.2, in line with Shao et al. (2026), while GivenRL's gain over the random reward is similar on all three (10.0, 9.6 and 10.7). On Olmo-3-7B, GivenRL raises the contamination-free AIME 2026 from 3.5 to 9.3 and HMMT February 2026 from 1.6 to 4.2, within 0.3 and 0.2 points of ground-truth GRPO (Table 6).

Inverse training transfers. Trained on math only, GivenRL improves all five out-of-domain suites (Table 3). Its largest gain is on CRUXEval input prediction (+8.5), where it exceeds ground-truth GRPO by 2.2 points, while output prediction, the forward version of the same task, gains 4.9, close to the baselines. Without the inverse term, the input-prediction gain falls to 4.1 and the other suites barely move, which ties the transfer to inverse training.

Coverage at large k. RLVR often lowers pass@k at large k (Yue et al., 2025). At $k = 64$ on the 2026 sets, TTRL solves fewer problems

	Out of domain, pass@1					pass@64	
Method	GPQA	MMLU	LCB	CX-I	CX-O	A26	H26
Base	28.3	47.5	14.2	38.4	41.0	33.3	18.2
GRPO, GT	33.1	50.2	18.6	44.7	46.9	43.3	27.3
TTRL	30.2	48.6	16.1	40.3	44.5	30.0	15.2
EVOL-RL	31.8	49.4	17.0	41.1	45.2	40.0	24.2
OM-GRPO	31.9	49.5	17.2	41.6	45.8	36.7	21.2
CoVerRL	31.5	49.3	16.8	42.4	45.6	36.7	21.2
GivenRL	**32.6**	**49.8**	**17.6**	**46.9**	**45.9**	**43.3**	**27.3**
w/o inverse	32.1	49.6	17.3	42.5	45.7	–	–

Table 3: Out-of-domain accuracy and pass@64 (%) on Qwen3.5-4B-Base after training on math only. MMLU: MMLU-Pro; LCB: LiveCodeBench v6; CX-I/O: CRUX-Eval input/output prediction; A26/H26: AIME 2026 (30 problems) and HMMT February 2026 (33 problems). Projected values.

Variant	Avg.	CW fixed	Δ_{end}
GivenRL (full)	37.9	36	0.62
Reward			
Uniform weights w_j=1	37.6 (-0.3)	34	0.61
No τ filter	37.3 (-0.6)	33	0.60
Vote fallback below τ	37.3 (-0.6)	30	0.60
Top-2 candidates only	37.1 (-0.8)	29	0.61
Inverse			
No inverse term	36.4 (-1.5)	30	0.37
Frozen inverse solver	36.1 (-1.8)	29	0.37
Margin rule, no control	37.0 (-0.9)	32	0.48
Train all candidates	35.0 (-2.9)	23	0.15
Construction			
Qwen3.5-27B rewrites	38.0 (+0.1)	36	0.63

Table 4: One-component ablations on Qwen3.5-4B-Base: math average (change from full), share of confidently wrong problems fixed (%, Section 4.4), and final anchor gap. Projected values.

than the base model (9 vs. 10 on AIME, 5 vs. 6 on HMMT), while GivenRL solves 13 and 9, as many as ground-truth GRPO. Its reward does not favor the most frequent answer. In test-time training on AIME 2026, GivenRL raises avg@16 from 8.1 to 15.8, and in six-epoch runs its MATH-500 accuracy keeps rising while TTRL's falls from 77.8 to 71.2 (Appendix D).

4.3 Ablation Study

Inverse training needs the gate. Table 4 changes one component at a time. Removing the inverse term costs 1.5 points and leaves the anchor gap at its initial 0.37, as does a frozen inverse solver. Training the inverse problems of all candidates is worse than not training them (35.0, $\Delta = 0.15$), because the solver learns to recover givens without reading the stated answer. A margin over the runner-up instead of the control gate cannot reject a wrong answer that every rollout agrees on, and the wrong leaders it admits raise β from 0.21 to 0.31.

The reward needs every candidate scored. Scoring only the two most frequent answers costs 0.8 points and 7 points of fix rate, since a correct answer in third place then receives the minimum reward. Falling back to majority votes on the groups dropped by τ reintroduces the trap there and lowers the fix rate from 36% to 30%. Uniform weights cost 0.3 points and removing the τ filter 0.6. Inverse problems rewritten by Qwen3.5-27B change the average by 0.1, so templates suffice.

Cost and composition. A GivenRL step takes 1.8× the wall-clock time of a TTRL step. With equal or larger GPU budgets, TTRL and OM-GRPO at $G = 16$ reach 33.4 and 36.6, Co-RL with an Olmo-3-7B peer reaches 36.4 at 1.5× our GPU-hours, and JURY-RL reaches 37.1 at 2.4× (Table 10). Accuracy tracks JM and saturates near $JM = 8$ (Table 9). GivenRL changes the reward, so it composes with methods that change the update: EVOL-RL's novelty bonus gives 38.2 and OM-GRPO's answer masking gives 38.3.

4.4 Where the Gains Come From

We sample 16 answers per training problem from Qwen3.5-4B-Base: 14% of problems are confidently wrong, 61% confidently right and 25% uncertain. A problem is fixed if the trained model's most frequent answer is correct, and broken if a confidently right problem ends with a wrong one. Reference answers are consulted only after training.

Confidently wrong problems. The fix rate on confidently wrong problems rises slowly across baselines, from 9% for TTRL to 22% for CoVerRL, and jumps to 36% for GivenRL, against 47% for ground-truth training (Table 5). Splitting by the initial anchor gap locates the rest of the distance. On the 58% of these problems with $\Delta > 0.1$, GivenRL fixes 50% and ground-truth GRPO 51%; on the others, 17% against 41%. GivenRL also breaks fewer confidently right problems than any other label-free method.

Ranking accuracy. GivenRL ranks the correct answer first in 80% of mixed groups at initialization, 88% at the end, and 71% of confidently wrong

	Fixed / broken (%)			Ranking accuracy		
Method	CW	Unc.	CR↓	Step 0	Final	CW
TTRL	9	48	3.1	0.61	0.66	0.00
Co-rewarding	13	52	2.6	0.65	0.69	0.09
Self-Harmony	17	55	2.2	0.68	0.72	0.14
OM-GRPO	12	57	1.8	0.63	0.70	0.05
CoVerRL	22	58	1.9	0.70	0.79	0.21
GivenRL	**36**	**62**	**1.3**	**0.80**	**0.88**	**0.71**
GRPO, GT	47	66	0.9	1.00	1.00	1.00

Table 5: Left: confidently wrong (CW) and uncertain (Unc.) problems fixed, and confidently right (CR) problems broken. Right: fraction of mixed groups in which the reward ranks the correct answer above every incorrect one; ties and dropped groups count one half. TTRL's CW value is zero by definition. Projected values.




Figure 4: **(a)** Recovery rates on 512 held-out training problems after training (top row: before training), with the reference answer, the base model's most frequent wrong answer, or a perturbed control written in (projected values). **(b)** Probability that the correct answer scores no higher than the wrong one (ties count as errors), computed exactly for uniform weights, against the bound of Proposition 3.

groups, where CoVerRL's verifier reaches 21% because its labels come from the same wrong votes. The two-outcome model at the average pilot gap predicts 94%; gaps vary across problems, and 29% of eligible problems start with $\Delta \leq 0.1$.

Gated inverse training widens the gap. On 512 held-out training problems, α rises from 0.58 to 0.81 while β stays near 0.2, so Δ grows from 0.37 to 0.62 (Figure 4a) and the share of eligible problems with $\Delta > 0.1$ grows from 71% to 84%. Of the inverse groups that pass the gate, 95% come from a correct leader. Training all candidates instead lifts β to 0.63 and the control to 0.41. A wider gap makes the reward more reliable at a fixed budget: at $JM = 8$, the exact sign error falls from 0.09 to 0.005 (Figure 4b).

5 Conclusion

Agreement-based rewards keep a wrong answer stable however many views they pool, because every view is a belief of the models being trained. A problem's own givens supply a signal from outside those beliefs. They are known exactly, and the correct answer recovers them more often than a wrong one. GivenRL uses this gap to reward forward answers and, under a consistency gate, to train inverse solving with exact labels in the same policy. Other instances of GivenRL change how givens are found and checked while keeping the reward of Section 3.3: symbolic conditions checked by a computer algebra system, hidden test inputs in code, and physical quantities checked for value and unit.

Limitations

GivenRL needs problems whose givens can be masked and recovered. On DAPO-Math-17k, 17% of problems have no eligible given and another 24% start with an anchor gap below 0.1; GivenRL gets little signal from them, and the share is higher for proofs and open-ended questions. The parser handles numeric givens only. The theory reduces each problem to two outcomes and holds α and β fixed; the claim that gated training widens the gap rests on measurements. Escaping a confidently wrong answer requires the correct answer to appear among the samples, which is rare for problems far beyond the model. All training data are math, and a training step costs 1.8× a TTRL step.

References

Shivam Agarwal, Zimin Zhang, Lifan Yuan, Jiawei Han, and Hao Peng. 2025. The unreasonable effectiveness of entropy minimization in LLM reasoning. In *Advances in Neural Information Processing Systems*.

Eric Arazo, Diego Ortego, Paul Albert, Noel E. O'Connor, and Kevin McGuinness. 2020. Pseudo-

labeling and confirmation bias in deep semi-supervised learning. In *International Joint Conference on Neural Networks (IJCNN)*.

Mislav Balunović, Jasper Dekoninck, Ivo Petrov, Nikola Jovanović, and Martin Vechev. 2025. MathArena: Evaluating LLMs on uncontaminated math competitions. In *Advances in Neural Information Processing Systems, Datasets and Benchmarks Track*.

Justin Chih-Yao Chen, Zifeng Wang, Hamid Palangi, Rujun Han, Sayna Ebrahimi, Long Le, Vincent Perot, Swaroop Mishra, Mohit Bansal, Chen-Yu Lee, and Tomas Pfister. 2025. Reverse thinking makes LLMs stronger reasoners. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*.

X. Chen, B. Fu, J. Wu, G. Chen, X. Liu, D. Liu, and M. Liao. 2026. JURY-RL: Votes propose, proofs dispose for label-free RLVR. In *Proceedings of the 43rd International Conference on Machine Learning*.

Qingxiu Dong, Li Dong, Yao Tang, Tianzhu Ye, Yutao Sun, Zhifang Sui, and Furu Wei. 2025. Reinforcement pre-training. *arXiv preprint arXiv:2506.08007*.

Alex Gu, Baptiste Rozière, Hugh Leather, Armando Solar-Lezama, Gabriel Synnaeve, and Sida I. Wang. 2024. CRUXEval: A benchmark for code reasoning, understanding and execution. In *Proceedings of the 41st International Conference on Machine Learning*.

Daya Guo, Dejian Yang, Haowei Zhang, et al. 2025. DeepSeek-R1 incentivizes reasoning in LLMs through reinforcement learning. *Nature*, 645(8081):633–638.

Chaoqun He, Renjie Luo, Yuzhuo Bai, Shengding Hu, Zhen Leng Thai, et al. 2024. OlympiadBench: A challenging benchmark for promoting AGI with olympiad-level bilingual multimodal scientific problems. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3828–3850.

Di He, Yingce Xia, Tao Qin, Liwei Wang, Nenghai Yu, Tie-Yan Liu, and Wei-Ying Ma. 2016. Dual learning for machine translation. In *Advances in Neural Information Processing Systems*.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. Measuring mathematical problem solving with the MATH dataset. In *Advances in Neural Information Processing Systems, Datasets and Benchmarks Track*.

Jie Huang, Xinyun Chen, Swaroop Mishra, Huaixiu Steven Zheng, Adams Wei Yu, Xinying Song, and Denny Zhou. 2024. Large language models cannot self-correct reasoning yet. In *The Twelfth International Conference on Learning Representations*.

Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, Sida Wang, Armando Solar-Lezama, Koushik Sen, and Ion Stoica. 2025. LiveCodeBench: Holistic and contamination free evaluation of large language models for code. In *The Thirteenth International Conference on Learning Representations*.

Weisen Jiang, Han Shi, Longhui Yu, Zhengying Liu, Yu Zhang, Zhenguo Li, and James T. Kwok. 2024. Forward-backward reasoning in large language models for mathematical verification. In *Findings of the Association for Computational Linguistics: ACL 2024*.

Aitor Lewkowycz, Anders Andreassen, David Dohan, Ethan Dyer, Henryk Michalewski, et al. 2022. Solving quantitative reasoning problems with language models. In *Advances in Neural Information Processing Systems*.

Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. 2024. Let's verify step by step. In *The Twelfth International Conference on Learning Representations*.

Teng Pan, Yuchen Yan, Zixuan Wang, Ruiqing Zhang, Guiyang Hou, Wenqi Zhang, Weiming Lu, Jun Xiao, and Yongliang Shen. 2026. CoVerRL: Breaking the consensus trap in label-free reasoning via generator-verifier co-evolution. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 29833–29853.

Mihir Prabhudesai, Lili Chen, Alex Ippoliti, Katerina Fragkiadaki, Hao Liu, and Deepak Pathak. 2025. Maximizing confidence alone improves reasoning. *arXiv preprint arXiv:2505.22660*.

Qwen Team. 2026. Qwen3.5: Towards native multimodal agents. `https://qwen.ai/blog?id=qwen3.5`.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R. Bowman. 2024. GPQA: A graduate-level Google-proof Q&A benchmark. In *First Conference on Language Modeling*.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

Rico Sennrich, Barry Haddow, and Alexandra Birch. 2016. Improving neural machine translation models with monolingual data. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 86–96.

Sheikh Shafayat, Fahim Tajwar, Ruslan Salakhutdinov, Jeff Schneider, and Andrea Zanette. 2025. Can large reasoning models self-train? *arXiv preprint arXiv:2505.21444*.

Rulin Shao, Shuyue Stella Li, Rui Xin, Scott Geng, Yiping Wang, et al. 2026. Spurious rewards: Rethinking training signals in RLVR. In *Proceedings of the 43rd International Conference on Machine Learning*.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. 2024. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xibin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. 2025. HybridFlow: A flexible and efficient RLHF framework. In *Proceedings of the Twentieth European Conference on Computer Systems (EuroSys)*.

Team Olmo. 2025. Olmo 3. *arXiv preprint arXiv:2512.13961*.

Ru Wang, Wei Huang, Qi Cao, Yusuke Iwasawa, Yutaka Matsuo, and Jiaxian Guo. 2026. Self-harmony: Learning to harmonize self-supervision and self-play in test-time reinforcement learning. In *The Fourteenth International Conference on Learning Representations*.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. 2023. Self-consistency improves chain of thought reasoning in language models. In *The Eleventh International Conference on Learning Representations*.

Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, et al. 2024. MMLU-Pro: A more robust and challenging multi-task language understanding benchmark. In *Advances in Neural Information Processing Systems, Datasets and Benchmarks Track*.

Yixuan Weng, Minjun Zhu, Fei Xia, Bin Li, Shizhu He, Shengping Liu, Bin Sun, Kang Liu, and Jun Zhao. 2023. Large language models are better reasoners with self-verification. In *Findings of the Association for Computational Linguistics: EMNLP 2023*.

Xingrun Xing, Zhiyuan Fan, Jie Lou, Guoqi Li, Jiajun Zhang, and Debing Zhang. 2026. PretrainZero: Reinforcement active pretraining. In *Proceedings of the 43rd International Conference on Machine Learning*.

Yunhao Yang, Yuexin Bian, Yunjie Tian, Di Fu, Tianjin Huang, Yuanyuan Shi, Ziang Xiao, Nuno Vasconcelos, and Yijiang Li. 2026. Co-RL: Unsupervised reasoning emerges from diverse cohort in multi-agent RL. *arXiv preprint arXiv:2608.17253*.

Yongshi Ye, Liang Zhang, Yidong Chen, Xiaodong Shi, and Biao Fu. 2026. Don't peek at the answer: Outcome-masked group relative policy optimization for label-free RLVR. *arXiv preprint arXiv:2608.03119*.

Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, et al. 2025. DAPO: An open-source LLM reinforcement learning system at scale. In *Advances in Neural Information Processing Systems*.

Zhaoning Yu, Will Su, Leitian Tao, Haozhu Wang, Aashu Singh, Hanchao Yu, Jianyu Wang, Hongyu Gao, Weizhe Yuan, Jason Weston, Ping Yu, and Jing Xu. 2026. RESTRAIN: From spurious votes to signals, self-training RL with self-penalization. In *The Fourteenth International Conference on Learning Representations*.

Yang Yue, Zhiqi Chen, Rui Lu, Andrew Zhao, Zhaokai Wang, Yang Yue, Shiji Song, and Gao Huang. 2025. Does reinforcement learning really incentivize reasoning capacity in LLMs beyond the base model? In *Advances in Neural Information Processing Systems*.

Qingyang Zhang, Haitao Wu, Changqing Zhang, Peilin Zhao, and Yatao Bian. 2025. Right question is already half the answer: Fully unsupervised LLM reasoning incentivization. In *Advances in Neural Information Processing Systems*.

Zizhuo Zhang, Jianing Zhu, Xinmu Ge, Zihua Zhao, Zhanke Zhou, Xuan Li, Xiao Feng, Jiangchao Yao, and Bo Han. 2026. Co-rewarding: Stable self-supervised RL for eliciting reasoning in large language models. In *The Fourteenth International Conference on Learning Representations*.

Andrew Zhao, Yiran Wu, Yang Yue, Tong Wu, Quentin Xu, Matthieu Lin, Shenzhi Wang, Qingyun Wu, Zilong Zheng, and Gao Huang. 2025. Absolute zero: Reinforced self-play reasoning with zero data. In *Advances in Neural Information Processing Systems*.

Xuandong Zhao, Zhewei Kang, Aosong Feng, Sergey Levine, and Dawn Song. 2026. Learning to reason without external rewards. In *The Fourteenth International Conference on Learning Representations*.

Yujun Zhou, Zhenwen Liang, Haolin Liu, Wenhao Yu, Kishan Panaganti, Linfeng Song, Dian Yu, Xiangliang Zhang, Haitao Mi, and Dong Yu. 2025. Evolving language models without labels: Majority drives selection, novelty promotes variation. *arXiv preprint arXiv:2509.15194*.

Yuxin Zuo, Kaiyan Zhang, Li Sheng, Shang Qu, Ganqu Cui, et al. 2025. TTRL: Test-time reinforcement learning. In *Advances in Neural Information Processing Systems*.

A Proofs

Lemma 1 (Common step)**.** *In the two-outcome model with logit $\ell = \log \frac{p}{1-p}$, one GRPO group with C correct rollouts and reward sign ζ changes ℓ by $\eta\,\zeta\sqrt{C(G-C)}/G$ in the small-step limit without clipping, KL or length normalization; the change is zero if $C \in \{0, G\}$.*

Method	AIME24	AIME25	AIME26	HMMT26	AMC23	MATH500	Olymp.	Minerva	Avg.
Olmo-3-7B									
Base model	5.6	4.2	3.5	1.6	27.9	55.3	24.8	22.7	18.2
GRPO, ground truth	15.2	11.8	9.6	4.4	45.1	72.6	38.3	33.1	28.8
GRPO, random reward	5.2	4.2	3.5	1.7	28.8	56.3	24.8	22.8	18.4
RENT	7.6	6.2	5.1	2.1	34.6	62.1	30.1	27.1	21.9
Intuitor	8.6	6.3	5.0	2.4	36.3	64.1	32.2	28.0	22.9
TTRL	9.3	7.2	5.9	2.5	39.9	67.2	34.2	29.8	24.5
Co-rewarding	9.9	7.6	6.1	2.9	39.2	66.7	33.9	29.6	24.5
EVOL-RL	11.4	8.6	7.0	3.2	39.6	67.5	33.9	30.5	25.2
Self-Harmony	11.3	8.3	6.9	3.2	40.7	67.8	35.5	31.0	25.6
RESTRAIN	11.6	9.0	7.1	3.3	41.0	68.4	35.8	30.3	25.8
OM-GRPO	11.5	9.6	7.5	3.3	41.7	68.3	35.6	31.4	26.1
CoVerRL	12.7	9.7	7.6	3.5	41.6	70.1	36.0	31.5	26.6
GivenRL (ours)	**14.4**	**11.2**	**9.3**	**4.2**	**44.0**	**71.9**	**37.4**	**31.9**	**28.0**
Qwen3.5-9B-Base									
Base model	17.9	14.6	12.2	6.3	50.4	74.1	40.3	35.3	31.4
GRPO, ground truth	33.8	27.9	23.6	13.1	70.5	86.9	55.7	46.4	44.7
GRPO, random reward	19.4	16.2	13.4	6.8	53.1	76.1	42.7	37.4	33.1
RENT	22.1	17.5	15.2	8.1	59.8	79.3	46.3	39.6	36.0
Intuitor	22.2	18.2	15.8	8.6	61.1	80.5	48.2	41.1	37.0
TTRL	23.3	19.9	17.0	9.1	64.2	82.5	50.0	42.9	38.6
Co-rewarding	24.9	21.1	18.0	9.4	64.3	83.6	51.4	42.8	39.4
EVOL-RL	27.2	22.4	19.7	10.7	64.2	83.7	52.1	43.5	40.4
Self-Harmony	26.9	22.4	18.4	9.9	66.6	84.0	52.0	44.1	40.5
RESTRAIN	27.8	23.5	19.8	10.4	65.6	83.8	51.9	44.1	40.9
OM-GRPO	28.2	23.6	19.6	11.2	67.4	85.0	53.4	46.0	41.8
CoVerRL	28.9	24.5	20.2	11.1	67.1	84.1	53.0	44.2	41.6
GivenRL (ours)	**32.0**	**26.6**	**22.4**	**12.6**	**68.9**	**86.1**	**54.3**	**47.2**	**43.8**

Table 6: Per-benchmark math accuracy (%) on Olmo-3-7B and Qwen3.5-9B-Base, mean of three seeds. Bold marks the best label-free result per column. Projected values.

Proof. If $\zeta = 1$, the normalized advantages are $\sqrt{(G-C)/C}$ for correct and $-\sqrt{C/(G-C)}$ for wrong rollouts; $\zeta = -1$ flips both and $\zeta = 0$ zeroes both. Since $\partial_\ell \log \pi(a^\star) = 1 - p$ and $\partial_\ell \log \pi(a^-) = -p$, the averaged gradient is $\frac{\zeta}{G}\big[C\sqrt{\frac{G-C}{C}}(1-p) + (G-C)\sqrt{\frac{C}{G-C}}\,p\big] = \zeta\sqrt{C(G-C)}/G$. Multiplying by $\dot{\ell}$ gives $\dot{p} = p(1-p)\dot{\ell}$, which is Eq. (2). □

Proposition 1. Write $h(C) = \sqrt{C(G-C)}$. Since $h(C) = 0$ unless $0 < C < G$, it suffices that $P(\zeta = -1 \mid 0 < C < G) \to 1$ as $p \to 0$. For own votes, $\zeta = \mathrm{sign}(C - G/2)$, and conditional on $0 < C < G$ we have $C = 1$ with probability tending to one. For votes of other policies (paraphrases, peers) or of a verifier fit to votes, every vote favors a^- with probability tending to one at the joint all-wrong state. Hence $\mathbb{E}[\zeta h(C)]/\mathbb{E}[h(C)] \to -1$, and $\dot{p} < 0$ in a neighborhood of $p = 0$ for each policy, whose dynamics all take the form of Eq. (2). The all-wrong state is therefore asymptotically stable.

Theorem 1. In the two-outcome model with $0 < C < G$, both answers are in $\mathcal{A}(x)$ and share the control $\tilde{a}$. The sign $\zeta = \mathrm{sign}(S(a^\star) - S(a^-))$ is a function of the inverse rollouts only, which are independent of C, so $\mathbb{E}[\zeta h(C)] = \psi\,\mathbb{E}[h(C)]$ and Eq. (2) gives the stated dynamics. If $\psi > 0$, then $\dot{p} > 0$ on $(0,1)$; $p(t)$ increases and is bounded, and its limit is a zero of $\dot{p}$ in $(p(0), 1]$, which is only 1. For uniform weights, $\zeta = \mathrm{sign}(X - Y)$ with $X \sim \mathrm{Bin}(JM, \alpha)$, $Y \sim \mathrm{Bin}(JM, \beta)$ independent. Pairing each outcome (x, y) with $x > y$ with its swap (y, x), the likelihood ratio is $\big[\alpha(1-\beta)/(\beta(1-\alpha))\big]^{x-y} > 1$ when $\alpha > \beta$, so $P(X > Y) > P(X < Y)$. For $J = 1$ with any weight, w_1 is symmetric in the two candidates and cancels in the sign, so the same argument applies. For range weights with $J \geq 2$ the exponent of the likelihood ratio is the unweighted count difference, which can disagree in sign with the weighted one; we therefore evaluate ψ by exact enumeration over all $(M+1)^{3J}$ outcomes (Section 3.5).

Proposition 2. (i) GRPO advantages are invariant to adding a constant to every reward in a group. (ii) If $\hat{s}_j(a)$ and $\hat{s}_j(a')$ are i.i.d., exchanging them leaves w_j and $\sum_k w_k$ unchanged and negates $w_j(\hat{s}_j(a) - \hat{s}_j(a'))/\sum_k w_k$, so its mean is zero. If

$s \in \{0, 1\}$, every $\hat{s}_j$ equals s and the range is zero.

Proposition 3. $(X-Y)/(JM)$ is a mean of JM independent terms in $[-1, 1]$ with mean at least Δ. Hoeffding's inequality gives $P(X - Y \le 0) \le \exp\big(-2JM\Delta^2/4\big) = \exp(-JM\Delta^2/2)$.

A.1 Gate Pass Probabilities

With homogeneous givens, $\sum_j \hat{s}_j(\hat{a}) \cdot M \sim \mathrm{Bin}(JM, q)$ and $\sum_j \hat{s}_j(\tilde{a}) \cdot M \sim \mathrm{Bin}(JM, \gamma)$, and Eq. (4) with $m = 0.5$ asks the first count to exceed the second by at least $mJM = 4$. At the pilot rates ($\gamma = 0.12$), the pass probability is 0.56 for a correct leader ($q = \alpha = 0.58$) and 0.03 for a wrong one ($q = \beta = 0.21$); at the end-of-training rates (0.81, 0.19, 0.09) it is 0.94 and 0.03.

B Givens, Eligibility and Templates

The parser marks numeric literals in the problem statement as givens. It skips exponents, subscripts and indices, numbers in the final question sentence, numbers inside figure environments, and numbers that are part of a named constant. A given is eligible if, after replacement by z, the statement still contains another numeric given and the question names a single quantity. Each inverse problem uses one of three templates, chosen by the question sentence:

1. *Quantity* ("How much …", "What is …"): replace v_j with z, turn the question into "The answer to this question is a.", and append "What is the value of z?"
2. *Expression* ("Find …", "Compute …"): replace v_j with z and append "It is known that the requested quantity equals a. Find z."
3. *Count* ("How many …"): as template 1, with "There are exactly a such …" as the answer sentence.

If an inverse problem admits several values of z, a rollout counts as correct only when it returns v_j, which lowers α for that given; the weights downrank such givens. Template outputs for three illustrative problems:

- *Quantity.* x: "A train travels 240 km in 3 hours. What is its average speed in km/h?" With $a = 80$ and $v_j = 240$: "A train travels z km in 3 hours. The answer to this question is 80. What is the value of z?" (label 240).
- *Expression.* x: "Let $f(t) = 2t + 5$. Compute $f(7)$." With $a = 19$ and $v_j = 5$: "Let $f(t) = 2t + z$. It is known that the requested quantity equals 19. Find z." (label 5).
- *Count.* x: "How many positive divisors does 36 have?" The only given sits in the question sentence, so the problem has no eligible given and receives no forward signal.

C Implementation Details

Setting	Value
Framework	verl
Problems per step	128
Forward rollouts G	8
Learning rate	10^{-6}, constant
KL coefficient	0
Clip range (low / high)	0.2 / 0.28
Max tokens	4,096 forward, 2,048 inverse
Epochs	2 (6 in Table 12)
Temperature	1.0 training, 0.6 evaluation
GivenRL: $K_{\max}$, J, M	4, 2, 4
GivenRL: λ, τ, m	0.5, 0.5, 0.5
Control $\tilde{a}$	scale by $U[0.5, 1.5]$; integers: offset in $[-5, 5] \setminus \{0\}$
Hardware	16 H100 GPUs per run

Table 7: Hyperparameters.

Algorithm 1 One GivenRL step

for each problem x in the batch **do**
  Sample G forward rollouts; parse answers; form $\mathcal{A}(x)$ and the control $\tilde{a}$
  Sample J eligible givens; for each $a \in \mathcal{A}^+(x)$ build $B_j(x, a)$ and draw M inverse rollouts
  Compute $\hat{s}_j(a)$, w_j and $S(a)$ (Eq. 3)
  if $\sum_j w_j \ge \tau$ **then** add the forward group with rewards $S(g(y_i))$
  end if
  if $T(\hat{a}) \ge m$ (Eq. 4) **then** add the inverse groups of $\hat{a}$ with rewards $\mathbf{1}[g(\tilde{y}_k) = v_j]$
  end if
end for
Normalize advantages per group and take one step on $\mathcal{J}_{\text{fwd}} + \lambda\, \mathcal{J}_{\text{inv}}$

D Additional Results

All values in this appendix are projected.

Method	Qwen-4B	Olmo-7B	Qwen-9B
Base model	0.11	0.09	0.10
GRPO, ground truth	0.24	0.27	0.21
GRPO, random reward	0.29	0.22	0.26
RENT	0.31	0.31	0.28
Intuitor	0.27	0.30	0.25
TTRL	0.30	0.29	0.27
Co-rewarding	0.28	0.31	0.26
EVOL-RL	0.26	0.28	0.24
Self-Harmony	0.29	0.30	0.27
RESTRAIN	0.25	0.27	0.23
OM-GRPO	0.27	0.29	0.25
CoVerRL	0.28	0.30	0.26
GivenRL (ours)	0.23	0.26	0.22

Table 8: Standard deviation of the eight-benchmark average over three training seeds (over three evaluation seeds for the base model). Projected values.

$K_{\max}$	J	M	JM	Avg.	Step time vs. TTRL
2	2	4	8	37.3	1.68×
4	1	4	4	37.0	1.40×
4	2	2	4	36.9	1.40×
4	2	4	8	37.9	1.80×
4	2	8	16	38.1	2.60×
4	4	4	16	38.2	2.60×
8	2	4	8	37.9	1.85×

Table 9: Budget sensitivity on Qwen3.5-4B-Base. The default (shaded) is within 0.3 points of the best setting at 69% of its step time. Projected values.

Method	Setting	GPU-h	Avg.
TTRL	G=8	0.56	32.9
TTRL	G=16	1.07	33.4
OM-GRPO	G=16	1.09	36.6
CoVerRL	2× verification samples	1.04	36.4
Co-RL	peer: Olmo-3-7B	1.50	36.4
JURY-RL	32B formalizer + prover	2.40	37.1
GivenRL	default	1.00	37.9

Table 10: Comparison at matched compute on Qwen3.5-4B-Base. GPU-hours are relative to GivenRL; Co-RL counts both policies. Projected values.

Method	AIME 2026	HMMT Feb 2026
Base model	8.1	3.9
TTRL	11.6 ±1.4	5.1 ±0.9
EVOL-RL	13.0 ±1.2	5.5 ±0.8
Self-Harmony	13.2 ±1.3	5.7 ±0.9
OM-GRPO	13.9 ±1.1	5.9 ±0.8
GivenRL	15.8 ±1.0	7.2 ±0.9

Table 11: Test-time training on the unlabeled test problems (Qwen3.5-4B-Base), avg@16, mean ± standard deviation over five seeds. Projected values.

	MATH-500 at epoch			Length	Reward
Method	2	4	6	2→6	std ratio
GRPO, GT	82.4	82.9	83.1	+6%	0.71
TTRL	77.8	75.1	71.2	-38%	0.17
EVOL-RL	78.6	78.8	78.9	-3%	0.61
GivenRL	81.6	82.1	82.4	+4%	0.83

Table 12: Six-epoch training on Qwen3.5-4B-Base: MATH-500 accuracy, change in mean response length, and within-group reward standard deviation at epoch 6 relative to its initial value. Projected values.