

11. 表單

1. 表單樣式

form-control, form-label, form-text

```
<div class="demo">
  <form>
    <div class="mb-3">
      <label class="form-label" for="username">Username</label>
      <input type="text" id="username" class="form-control">
      <div class="form-text">不會記憶任何資訊!</div>
    </div>
  </form>
</div>
```


for, id 需要一致, 選取label也可同時選取input



type="button" form表單無反應

type="submit" form表單內容送出並清空

```
<form>
  <div class="mb-3">
    <label class="form-label" for="username">Username</label>
    <input type="text" id="username" class="form-control">
    <div class="form-text">不會記憶任何資訊!</div>
  </div>
  <div class="mb-3">
    <label class="form-label" for="tel">電話</label>
    <input type="tel" id="tel" class="form-control">
    <div class="form-text">不會記憶任何資訊!</div>
  </div>
  <button type="button" class="btn btn-primary">確認</button>
  <button type="submit" class="btn btn-primary">確認</button>
</form>
```



利用align-items-center 搭配 form-text 讓文字垂直置中

```
<div class="demo">
  <div class="row align-items-center">
    <div class="col-auto">
      <label class="form-label" for="username">Username</label>
    </div>
    <div class="col-auto">
      <input type="text" id="username" class="form-control">
    </div>
    <div class="col-auto">
      <div class="form-text">不會記憶任何資訊!</div>
    </div>
  </div>
</div>
```



disabled

```

<div class="demo">
  <form>
    <div class="row align-items-center">
      <div class="col-auto">
        <label class="form-label" for="username">Username</label>
      </div>
      <div class="col-auto">
        <input disabled type="text" id="username" class="form-control">
      </div>
      <div class="col-auto">
        <div class="form-text">不會記憶任何資訊!</div>
      </div>
    </div>
  </form>
</div>

```

2. Form controls

```

<div class="demo">
  <input class="form-control form-control-lg mb-2" type="text" placeholder=".form-control-lg"
    aria-label=".form-control-lg example">
  <input class="form-control mb-2" type="text" placeholder="Default input" aria-label="default input
    example">
  <input class="form-control form-control-sm mb-2" type="text" placeholder=".form-control-sm"
    aria-label=".form-control-sm example">
</div>

```

File input

```

<div class="demo">
  <div class="mb-3">
    <label for="formFile" class="form-label">Default file input example</label>
    <input class="form-control" type="file" id="formFile">
  </div>
  <div class="mb-3">
    <label for="formFileMultiple" class="form-label">Multiple files input example</label>
    <input class="form-control" type="file" id="formFileMultiple" multiple>
  </div>
  <div class="mb-3">
    <label for="formFileDisabled" class="form-label">Disabled file input example</label>
    <input class="form-control" type="file" id="formFileDisabled" disabled>
  </div>
  <div class="mb-3">
    <label for="formFileSm" class="form-label">Small file input example</label>
    <input class="form-control form-control-sm" id="formFileSm" type="file">
  </div>
  <div>
    <label for="formFileLg" class="form-label">Large file input example</label>
    <input class="form-control form-control-lg" id="formFileLg" type="file">
  </div>
</div>

```

Default file input example

選擇檔案 未選擇任何檔案

Multiple files input example

選擇檔案 未選擇任何檔案

Disabled file input example

選擇檔案 未選擇任何檔案

Small file input example

選擇檔案 未選擇任何檔案

Large file input example

選擇檔案 未選擇任何檔案

Datalists

```

<div class="demo">
  <label for="exampleDataList" class="form-label">我的美食紀錄</label>
  <input class="form-control" list="datalistOptions" id="exampleDataList" placeholder="Type to search...">
  <datalist id="datalistOptions">
    <option value="牛肉麵">
    <option value="麥當勞">
    <option value="肯德基">
    <option value="必勝客">
    <option value="春水堂">
  </datalist>
</div>

```

我的美食紀錄

Type to search...

3. Select

```
<div class="demo">
  <select class="form-select" aria-label="Default select example">
    <option selected>Open this select menu</option>
    <option value="1">One</option>
    <option value="2">Two</option>
    <option value="3">Three</option>
  </select>
</div>
```

Open this select menu

Open this select menu

One

Two

Three

Multiple, form-select-lg

```
<div class="demo">
  <select class="form-select mb-2" multiple aria-label="Default select example">
    <option selected>Open this select menu</option>
    <option value="1">One</option>
    <option value="2">Two</option>
    <option value="3">Three</option>
  </select>
  <select class="form-select form-select-lg" aria-label="Default select example">
    <option selected>Open this select menu</option>
    <option value="1">One</option>
    <option value="2">Two</option>
    <option value="3">Three</option>
  </select>
</div>
```

Open this select menu

One

Two

Three

Open this select menu

Size 表達可以顯示幾筆資料

```
<select class="form-select mb-2" size="4" multiple aria-label="Default select example">
  <option selected>Open this select menu</option>
  <option value="1">One</option>
  <option value="2">Two</option>
  <option value="3">Three</option>
  <option value="4">Four</option>
</select>
```

4. Checks and radios form-check, form-check-input, form-check-label, checked

```
<div class="demo">
  <div class="form-check">
    <input class="form-check-input" type="checkbox" value="" id="flexCheckDefault">
    <label class="form-check-label" for="flexCheckDefault">
      Default checkbox
    </label>
  </div>
  <div class="form-check">
    <input class="form-check-input" type="checkbox" value="" id="flexCheckChecked" checked>
    <label class="form-check-label" for="flexCheckChecked">
      Checked checkbox
    </label>
  </div>
</div>
```

- ☐ Default checkbox
☒ Checked checkbox

Radio: name 必須一致!

```
<div class="demo">
  <div class="form-check">
    <input class="form-check-input" type="radio" name="sameDefault" id="flexRadioDefault1">
    <label class="form-check-label" for="flexRadioDefault1">
      Default radio
    </label>
  </div>
  <div class="form-check">
    <input class="form-check-input" type="radio" name="sameDefault" id="flexRadioDefault2" checked>
    <label class="form-check-label" for="flexRadioDefault2">
      Default checked radio
    </label>
  </div>
</div>
```

- ☐ Default radio
☒ Default checked radio

Switches (.form-switch, role="switch")

```
<div class="demo">
  <div class="form-check form-switch">
    <input class="form-check-input" type="checkbox" role="switch" id="flexSwitchCheckDefault">
    <label class="form-check-label" for="flexSwitchCheckDefault">Default switch checkbox input</
    label>
  </div>
  <div class="form-check form-switch">
    <input class="form-check-input" type="checkbox" role="switch" id="flexSwitchCheckChecked"
    checked>
    <label class="form-check-label" for="flexSwitchCheckChecked">Checked switch checkbox input</
    label>
  </div>
  <div class="form-check form-switch">
    <input class="form-check-input" type="checkbox" role="switch" id="flexSwitchCheckDisabled"
    disabled>
    <label class="form-check-label" for="flexSwitchCheckDisabled">Disabled switch checkbox input</
    label>
  </div>
  <div class="form-check form-switch">
    <input class="form-check-input" type="checkbox" role="switch"
    id="flexSwitchCheckCheckedDisabled" checked disabled>
    <label class="form-check-label" for="flexSwitchCheckCheckedDisabled">Disabled checked switch
    checkbox
    input</label>
  </div>
</div>
```

- ☐ Default switch checkbox input
- ☒ Checked switch checkbox input
- ☐ Disabled switch checkbox input
- ☒ Disabled checked switch checkbox input

Inline

```
<div class="demo">
  <div class="form-check form-check-inline">
    <input class="form-check-input" type="checkbox" id="inlineCheckbox1" value="option1">
    <label class="form-check-label" for="inlineCheckbox1">1</label>
  </div>
  <div class="form-check form-check-inline">
    <input class="form-check-input" type="checkbox" id="inlineCheckbox2" value="option2">
    <label class="form-check-label" for="inlineCheckbox2">2</label>
  </div>
  <div class="form-check form-check-inline">
    <input class="form-check-input" type="checkbox" id="inlineCheckbox3" value="option3" disabled>
    <label class="form-check-label" for="inlineCheckbox3">3 (disabled)</label>
  </div>
</div>
```

- ☒ 1
- ☒ 2
- ☐ 3 (disabled)

```

<div class="demo">
  <div class="form-check form-check-inline">
    <input class="form-check-input" type="radio" name="inlineRadioOptions" id="inlineRadio1"
    value="option1">
    <label class="form-check-label" for="inlineRadio1">1</label>
  </div>
  <div class="form-check form-check-inline">
    <input class="form-check-input" type="radio" name="inlineRadioOptions" id="inlineRadio2"
    value="option2">
    <label class="form-check-label" for="inlineRadio2">2</label>
  </div>
  <div class="form-check form-check-inline">
    <input class="form-check-input" type="radio" name="inlineRadioOptions" id="inlineRadio3"
    value="option3"
    disabled>
    <label class="form-check-label" for="inlineRadio3">3 (disabled)</label>
  </div>
</div>

```

☐ 1 ☐ 2 ☐ 3 (disabled)

Checkbox toggle buttons (保留狀態)

```

<div class="demo">
  <input type="checkbox" class="btn-check" id="btn-check" autocomplete="off">
  <label class="btn btn-primary" for="btn-check">Single toggle</label>
</div>
<div class="demo">
  <input type="checkbox" class="btn-check" id="btn-check-2" checked="" autocomplete="off">
  <label class="btn btn-primary" for="btn-check-2">Checked</label>
</div>

```

5. Range

```

<div class="demo">
  <label for="customRange3" class="form-label">Example range</label>
  <input type="range" class="form-range" min="0" max="100" step="1" id="customRange3">
</div>
<div class="demo">
  range的參數為: <span id="demo">0</span>
</div>
<script>
  const range = document.querySelector('#customRange3');
  range.addEventListener('change', (evt) => {
    document.querySelector('#demo').innerHTML = evt.target.value;
  });
</script>

```

6. Input群組

input-group, input-group-text

```

<div class="input-group mb-3">
  <span class="input-group-text" id="basic-addon1">@</span>
  <input type="text" class="form-control" placeholder="Username" aria-label="Username"
  aria-describedby="basic-addon1">
</div>

```

@ Username


```
<div class="input-group mb-3">
  <input type="text" class="form-control" placeholder="Recipient's username"
    aria-label="Recipient's username"
    aria-describedby="basic-addon2">
  <span class="input-group-text" id="basic-addon2">@example.com</span>
</div>
```

```
<label for="basic-url" class="form-label">Your vanity URL</label>
<div class="input-group mb-3">
  <span class="input-group-text" id="basic-addon3">https://example.com/users/</span>
  <input type="text" class="form-control" id="basic-url" aria-describedby="basic-addon3">
</div>

<div class="input-group mb-3">
  <span class="input-group-text">$</span>
  <input type="text" class="form-control" aria-label="Amount (to the nearest dollar)">
  <span class="input-group-text">.00</span>
</div>
```

Your vanity URL

Button addons

```
<div class="demo">
  <div class="input-group mb-3">
    <button class="btn btn-outline-secondary" type="button" id="button-addon1">Button</button>
    <input type="text" class="form-control" placeholder="" aria-label="Example text with button
      addon" aria-describedby="button-addon1">
    </div>

    <div class="input-group mb-3">
      <input type="text" class="form-control" placeholder="Recipient's username"
        aria-label="Recipient's username" aria-describedby="button-addon2">
      <button class="btn btn-outline-secondary" type="button" id="button-addon2">Button</button>
    </div>

    <div class="input-group mb-3">
      <button class="btn btn-outline-secondary" type="button">Button</button>
      <button class="btn btn-outline-secondary" type="button">Button</button>
      <input type="text" class="form-control" placeholder="" aria-label="Example text with two
        button addons">
    </div>

    <div class="input-group">
      <input type="text" class="form-control" placeholder="Recipient's username"
        aria-label="Recipient's username with two button addons">
      <button class="btn btn-outline-secondary" type="button">Button</button>
      <button class="btn btn-outline-secondary" type="button">Button</button>
    </div>
</div>
```

Button

The image shows four examples of Bootstrap form layouts:

- Example 1: A button followed by a text input field.
- Example 2: A text input field followed by a button.
- Example 3: Two buttons followed by a text input field.
- Example 4: A text input field followed by two buttons.

7. 表單驗證

is-valid 呼叫 valid-feedback

is-invalid 呼叫 invalid-feedback

required 表示需要驗證

此驗證功能可以搭配後端並該改 .is-valid or .is-invalid 以顯示相對的警告訊息!


```
<div class="demo">
  <form class="row g-3">
    <div class="col-md-4">
      <label for="validationServer01" class="form-label">First name</label>
      <input type="text" class="form-control is-invalid" id="validationServer01" value="Mark"
        required>
      <div class="valid-feedback"> 輸入正確!</div>
      <div class="invalid-feedback">錯誤輸入錯誤!</div>
    </div>
    <div class="col-md-4">
      <label for="validationServer02" class="form-label">Last name</label>
      <input type="text" class="form-control is-valid" id="validationServer02" value="Otto"
        required>
      <div class="valid-feedback"> 輸入正確!</div>
      <div class="invalid-feedback">錯誤輸入錯誤!</div>
    </div>
    <div class="col-12">
      <div class="form-check">
        <input class="form-check-input is-invalid" type="checkbox" value="" id="invalidCheck3"
          aria-describedby="invalidCheck3Feedback" required>
        <label class="form-check-label" for="invalidCheck3">
          同意條款和條件
        </label>
        <div id="invalidCheck3Feedback" class="invalid-feedback">你必須先同意條款和條件</div>
      </div>
    </div>
    <div class="col-12">
      <button class="btn btn-primary" type="submit">Submit form</button>
    </div>
  </form>
</div>
```

The image shows a Bootstrap form with the following elements:

- First name:** A text input field containing "Mark". It has a red border and a red error icon (a circle with an exclamation mark). Below it, the text "錯誤輸入錯誤!" (Error input error!) is displayed in red.
- Last name:** A text input field containing "Otto". It has a green border and a green checkmark icon. Below it, the text "輸入正確!" (Input correct!) is displayed in green.
- Form Check:** A checkbox labeled "同意條款和條件" (I agree with the terms and conditions). The checkbox is unchecked. Below the label, the text "你必須先同意條款和條件" (You must first agree with the terms and conditions) is displayed in red.
- Submit form:** A blue button with the text "Submit form".


8. Floating labels(浮動標籤)

```
<div class="demo">
  <div class="form-floating mb-3">
    <input type="email" class="form-control" id="floatingInput" placeholder="name@example.com">
    <label for="floatingInput">Email address</label>
  </div>
  <div class="form-floating">
    <input type="password" class="form-control" id="floatingPassword" placeholder="Password">
    <label for="floatingPassword">Password</label>
  </div>
</div>
```



9. 表單排版練習 利用格線排版, 搭配gutter

```
<div class="demo">
  <div class="row mb-3">
    <div class="col-6">
      <input type="text" class="form-control" placeholder="First name">
    </div>
    <div class="col-6">
      <input type="text" class="form-control" placeholder="Last name">
    </div>
  </div>
  <div class="row gx-1">
    <div class="col-6">
      <input type="text" class="form-control" placeholder="First name">
    </div>
    <div class="col-6">
      <input type="text" class="form-control" placeholder="Last name">
    </div>
  </div>
</div>
```



```

<div class="demo">
  <div class="row gx-2 gy-3">
    <div class="col-6">
      <label for="" class="form-text">First name</label>
      <input type="text" class="form-control" placeholder="First name">
    </div>
    <div class="col-6">
      <label for="" class="form-text">Last name</label>
      <input type="text" class="form-control" placeholder="Last name">
    </div>
    <div class="col-12">
      <label for="" class="form-text">email</label>
      <input type="email" class="form-control" placeholder="email">
    </div>
    <div class="col-12">
      <label for="" class="form-text">address</label>
      <input type="text" class="form-control" placeholder="address">
    </div>
  </div>
</div>

```

First name

First name

Last name

Last name

email

email

address

address

label文字垂直置中 col-form-label

```

<div class="demo">
  <div class="row gx-2 gy-3">
    <div class="col-6">
      <div class="row">
        <label for="" class="form-text col-sm-4 col-form-label">First name</label>
        <div class="col-sm-8">
          <input type="text" class="form-control" placeholder="First name">
        </div>
      </div>
    </div>
    <div class="col-6">
      <div class="row">
        <label for="" class="form-text col-sm-4">First name</label>
        <div class="col-sm-8">
          <input type="text" class="form-control" placeholder="First name">
        </div>
      </div>
    </div>
    <div class="col-12">
      <div class="row">
        <label for="" class="form-text col-sm-2 col-form-label">email</label>
        <div class="col-sm-10">
          <input type="email" class="form-control" placeholder="email">
        </div>
      </div>
    </div>
  </div>
</div>

```

First name First name First name

email email

email email