

CSE 130

Programming Languages

Lecture: Polymorphism

Ranjit Jhala
UC San Diego



Example: Calculator Revisited

```
type expr =  
  | Num of int  
  | Div of expr * expr
```

Can you write a function?

```
val eval : expr -> int
```

In Class Exercise

```
type expr =  
  | Num of int  
  | Div of expr * expr
```

Write an Evaluation function

```
val eval : expr -> int option
```

That returns *None* if a div-by-zero occurs

Moral

Failure *is* an Option!

Datatypes with many type variables

```
type ('a, 'b) tree =  
  Leaf  
| Node of 'a * 'b * ('a, 'b) tree * ('a, 'b) tree
```

Datatypes with many type variables

- Multiple type variables

```
type ('a, 'b) tree =  
  Leaf  
| Node of 'a * 'b * ('a, 'b) tree * ('a, 'b) tree
```

- Type is instantiated for each use:

Node("alice", 2, Leaf, Leaf)

Node("charlie", 3, Leaf, Leaf)

*Node("bob", 13,
 , Node("alice", 2, Leaf, Leaf)
 , Node("charlie", 3, Leaf, Leaf))*

Datatypes with many type variables

- Multiple type variables

```
type ('a, 'b) tree =  
  Leaf  
| Node of 'a * 'b * ('a, 'b) tree * ('a, 'b) tree
```

- Type is instantiated for each use:

Node("alice", 2, Leaf, Leaf)

Node("charlie", 3, Leaf, Leaf)

*Node("bob", 13,
 , Node("alice", 2, Leaf, Leaf)
 , Node(3, "charlie", Leaf, Leaf))*


Binary Search Trees

```
type ('a, 'b) tree =  
  Leaf  
| Node of 'a * 'b * ('a, 'b) tree * ('a, 'b) tree
```

Node (key, value, left, right)

BST Property:
keys in left < key < keys in right

BST Property: *keys in left < key < keys in right*



```
Node("bob", 13
    , Node("alice", 2, Leaf, Leaf)
    , Node("charlie", 3, Leaf, Leaf))
```

In-Class Exercise!

BST Property: *keys in left < key < keys in right*

```
type ('a, 'b) tree =
  Leaf
| Node of 'a * 'b * ('a, 'b) tree * ('a, 'b) tree
```

Write a function to lookup keys...

```
val lookup: 'a -> ('a, 'b) tree -> 'b option
```

Polymorphic Data Structures

- **Container** data structures independent of type !
- Appropriate type is **instantiated** at each **use**:

```
'a list
('a , 'b) tree
('a , 'b) hashtable ...
```

- **Static type checking catches errors** early
 - Cannot add **int** key to **string** hashtable
- **Generics**: in Java, C#, VB (borrowed from ML)

Type Inference

How DOES Ocaml figure out all the types ?!

Polymorphic Types

- Polymorphic types are tricky
- Not always obvious from staring at code
- How to ensure correctness ?
- Types (almost) never entered w/ program!

Polymorphic Type Inference

- Every expression accepted by ML must have a valid inferred type
- Can have no idea what a function does, but still know its exact type
- A function may never (or sometimes terminate), but will still have a valid type

Polymorphic Type Inference

- Computing the types of all expressions
 - At **compile** time : **statically Typed**
- Each binding is processed in order
 - Types are computed for each binding
 - For expression and variable bound to
 - Types used for subsequent bindings
- Unlike values (determined at run-time)

Example 1

```
let x = 2 + 3;;  
  
let y = string_of_int x;;
```

Example 2

```
let x = 2 + 3;;  
  
let y = string_of_int x;;  
  
let inc y = x + y;;
```

ML doesn't know what function does,
or even that it finishes only its type!

```
let rec cat xs =  
  match xs with  
  | []      -> ""  
  | x::xs   -> x^(cat xs)
```

```
let rec cat xs =  
  match xs with  
  | []      -> cat []  
  | x::xs   -> x^(cat xs)
```

Example 5

```
let rec cat xs =  
  match xs with  
  | []      -> ""  
  | x::xs   -> x^(cat xs)
```

Example 5

```
let rec map f xs =  
  match xs with  
  | []      -> []  
  | x::xs'  -> (f x)::(map f xs')
```

Example 5

```
let rec map f xs =  
  match xs with  
  | []      -> []  
  | x::xs'  -> (f x)::(map f xs')
```

“Generalize” Unconstrained Vars

$(\text{'a} \rightarrow \text{'b}) \rightarrow \text{'a list} \rightarrow \text{'b list}$

Example 11

```
let foo1 f g x =  
  if f x  
  then x  
  else g x
```

Example 7

```
let rec fold f cur xs =  
  match xs with  
  | []      -> cur  
  | x::xs'  -> fold f (f cur x) xs'
```

Example 12

```
let foo2 f g x =  
  if f x  
  then x  
  else foo2 f g (g x)
```