

**Haynes**  
*shows you how*

**BMW 3-Series and Z4 (99-05) Includes 2006 325ci/330ci Coupe and Convertible models Haynes Online Manual.**

## 23 Body exterior fittings - removal and installation

### Wheel arch liners and body under-panels

1 The various plastic covers fitted to the underside of the vehicle are secured in position by a mixture of screws, nuts and retaining clips, and removal will be fairly obvious on inspection. Work methodically around, removing its retaining screws and releasing its retaining clips until the panel is free and can be removed from the underside of the vehicle. Most clips used on the vehicle are simply pried out of position. Other clips can be released by unscrewing and prying out the center pins and then removing the clip.

2 On installation, replace any retaining clips that may have been broken on removal, and ensure that the panel is securely retained by all the relevant clips and screws.

### Body trim strips and badges

3 The various body trim strips and badges are held in position with a special adhesive tape. Removal requires the trim/badge to be heated, to soften the adhesive, and then cut away from the surface. Due to the high risk of damage to the vehicle's paint during this operation, it is recommended that this task should be entrusted to a BMW dealer or suitably-equipped specialist.

### Rear spoiler (Sport Wagon)

4 This is a complex task requiring specialist body tools, and experience. Any attempt to remove the spoiler without the necessary equipment is very likely to result in damage. Consequently, we recommend that this work is entrusted to a BMW dealer or suitably-equipped specialist.

© 2024 Haynes Manuals, Inc. Contact us