




American Chassis Depot

20/40' SLIDER 12PINS TANDEM CONTAINER CHASSIS




4811 N McCarty St Suite C, Houston, TX 77013




TECHNICAL SPECIFICATIONS

Overall Length	31'-7" (retracted) or 40'-11" (extended)
Overall Width	96"
Fifth Wheel Height	47±1"
Rear Deck Height	48±1"
Kingpin Location	18" (From the rear of the front bolster)
Landing Gear Location	100" (From the kingpin center)
Tandem Location	32" (From rear face of rear bolster to rear axles center when extended)
Axle Spread	109"
Tare Weight	9,350 lbs±2%
Payload	54,500lbs for 20' loaded or 57,000lbs for 40' loaded


This chassis is designed to carry one ISO 20' or 2 x 20' empties or 40' ISO containers
This chassis meets all DOT, AAR, ANSI, TOFC, FMVSS, SAE and TTMA specifications



View N



View P





STEEL FRAME & COMPONENTS

1. Main Beam - 16"x5" fabricated I-beam with high strength flanges and 6-11/32" height for gooseneck rail.

2. Upper Coupler - 5/16" pick up plate with JOST 2" diameter square type kingpin per SAE standard, 380-420 HB, with 2" water drain holes, design to be integrated with main frame through welding.

3. Front Bolster - Fabricated bolster assembly with high strength plates with 89" centers, equipped with none retractable twist locks.

4. Intermediate Bolster - Fabricated with retractable twistlocks with swing down twistlocks.

5. Rear Bolster - Tapered rectangle bolster of the main frame fabricated by 3/8" thick top and bottom plate with 5/16" thick side plates. 6-5/8" height x 4" wide fabricated box beam bolster on slider composed by 1/2" thick top/bottom plates with 5/16" thick side plates with flip up twistlocks.

6. Slider Beam - Fabricated I beam with 3/4"x5" upper and lower flanges and 3/16" web, slider extends or retract on 6" diameter steel rollers.

7. Locking System - Air operated locking pins, activated by 30/30 spring brakes on both sides of the trailer through third gladhand on front sill.

8. Landing Gear - "AXN FW32E00J with 60,000 lbs capacity, 2-speed 17" travel with low "T" shoes. Crank handle is located on the driver's side of the chassis. Pre-painted BLACK color. Landing gear brackets are bolted on the main beam as the layout.

9. Container Locks - TOCA

10. Suspension - AXN 109" axle spread, underslung configuration with high-arch single spring (360-00). Pre-painted BLACK color.

11. Axles - AXN 5" round axles with 22500lb capacity; 71.5" track, Q+16.5"x7" 4707Q brake. Pre-painted BLACK color. 1.5-28 spline, HALDEX 5.5" automatic slack adjusters. Reserved PSI interface; Heat Sensing Labels. Axle Installation orientation - 90 degrees rear, chambers DOWN (1 abs ready front, 1 non abs rear per unit).

12. Wheel End - AXN Hub & Drum Assembly P/N H30-0647BFNTZ/H30-0647BFNZ, STEMCO 358-4009 Integrated Sentinel Grease Hub Cap, STEMCO seals and bearings. Spindle nut: STEMCO Pro-Torq P/N 447-4743. (5-year warranty wheelend).

13. Lubricant - Petro Canada precision synthetic EP 00 semi fluid grease lubricant.

14. Wheels - JINGU 22.5x8.25 10-stud hub-piloted wheels with 5 hand holes and with TR572 valve stem. Pre-painted PMS BLACK C color.

15. Tires - WESTLAKE 255/70R22.5-16PR tubeless type.

16. Brake System - SEALCO 110800 spring brake priority valve system and WABCO 2S/1M ABS system. PHILLIPS glad hand 12-0061 and 12-0081, 3/8" blue air tube for control and 3/8" red for supply. HALDEX Goldseal T30/30, 2.5" stroke brake chamber. FUWA air tanks.

17. Electrical - PHILLIPS mold seal wiring harness, Reserved PSI and GPS connector. (10-year warranty) Optronics LED lights (amp connections for S/T/T lights and .180 bullets for others). The theft proof design used for 4" LED lighting.

18. Electrical Receptacle - PHILLIPS 15-7292 zinc alloy material with solid pins.

19. Document Holder - PHILLIPS 16-802. Installed on roadside near crank handle.

20. Conspicuity Tape - "3M" brand. Installed per federal regulations.

21. Painting - Abrasive blast of all metal surfaces - not less than SA-2.5 to achieve clean bare steel. Surface will be coated with electrophoresis primer and powder topcoat. Color BLACK and at the corner painted YELLOW color. Total thickness not less than 80µm after dry membrane. Coating supplier: PPG (7-year warranty).





American Chassis Depot



American Chassis Depot is a leading provider of high-quality chassis solutions for the transportation and logistics industry. With years of experience in the field, our team is committed to helping you find the perfect chassis solution for your specific needs.

For more information americanchassisdepot.com