



Specifications

Weight	46,440 lbs (21,065 kg)
Weight on 5th Wheel	16,780 lbs (7,611 kg)
Weight on Rear Axles	29,660 lbs (13,453 kg)
Travel Height	159" (404 cm)
Work Height	249" (633 cm)
Travel Width	102" (259 cm)
Work Width	102" (259 cm)
Travel Length	447" (1135 cm)
Work Length	536" (1,363 cm)
Hitch	2" Kingpin Hitch
Axles	Tandem/Air Brakes
Suspension	Spring
Tires	318/80 R22.5
Electric Motor	60 hp
Diesel Engine	82 hp
Fuel Tank Capacity	42 Gallons/159 Liters
Oil Tank Capacity	107 Gallons/405 Liters
Minimum Tire Capacity	20.5R25
Max Tire Capacity	59/80R63
Average Cycle Time	8-10 mins
Average Hourly Production	6-8 Tires/Hour

- Hydraulic Adjusted Die Plate Openings
- Shear To Cut Off Excessive Rubber
- Light Tree Assembly
- Radio Remote
- Alloy Die Plates
- Emergency Stop Buttons
- Crane to Lift Off Beads
- Hydraulic Adjusted Cage



The Eagle OTR Debeader has been built, proven and engineered to complete this specific task of pulling the Bead bundles from OTR tires and is the only machine in the world capable of pulling the bead bundles from all sizes of radial OTR tires. The tires are lifted onto the machine and are completely contained for safety.

Through the development of this machine we have pulled tire sizes from 20.5/25's all of the way up to and including the 59.80R63's. We have pulled the bead bundles from the 20.5/25's up to the 33.00R51's both beads at the same time. When processing the larger tires (57's and 63's) we pull one bead bundle at a time, the first and then the hook extends to grab & pull the second bead.

Crane arm lifts bead off of hook and disposes bead off to the side.



A radio remote is used to operate most of the functions