



Specifications



Weight	50,140lbs (22,743kg)
Tongue Weight	22,400lbs (10,160kg)
Rear Axle Weight	27,740lbs (12,583kg)
Height	118.5" (301.1cm)
Width	96" (244.5 cm)
Length	433" (1099.3 cm)
Hitch	2" King Pin
Axles	Tandam Meritor Axles
Suspension	Leaf Spring Hutch Suspension
Tires	255/70R22.5
Brakes	16 1/2" x 7" Air Brakes
Fuel Tank Cap.	42 Gallons (159 liters)
Oil Tank Cap.	239 Gallons (904 liters)
Hydraulic Tank Spec.	Dextron III or ISO 32
Diesel Engine (opt)	Fiat, FPT N67MNTX, Tier 3
Electric Motor (opt)	125 hp, 3 Phase (91.94 kw)
Blade Size	1" x 4" x 76"
Rotatable Blades	4 Edges
Rec. Max Tire Capacity	Up To and Uncloding 59/8063 (punchfirst) or 40.00157 Whole Tire
Average Production	Cut 24, 288# Pieces of Tires in 30 mins out of the two halves of a 40/57 OTR tire

- 5 Hydraulic Powered Bed Rollers
- 2 Hydraulic Lifted Extension Rollers
- Hydraulic Probe Arm for Positioning Tire
- Operator Control Stand
- Operator Cab
- Tire Positioner to More Accurately Cut Tire To Size

The patented Eagle Titan II is the ultimate tire cutter that we can supply to the Waste Tire Recycling Market. The Titan II has the ability to handle and cut large OTR and mining tires up to 44" across the tread and up to 12' in diameter. We have experience cutting 27.00R49 up through 40.00R57 mining tires with satisfactory results. The H.P. of the diesel engine, special design location of the cylinder mount and the blade design allows equal cutting pressure throughout the total cycling time.. The Titan II is complete with powered extension rollers, bed, and integral trailer. Tires need to be punch cut before they are down-sized

