

# GEN-L



## Technical specification

| Category                                      | Specification                                          | Value                                                                                                                                            |                                           |
|-----------------------------------------------|--------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|
|                                               |                                                        | Imperial                                                                                                                                         | Metric                                    |
| Dimensions                                    | Length                                                 | 112.2"                                                                                                                                           | 2850mm                                    |
|                                               | Width                                                  | 87.8"                                                                                                                                            | 2230mm                                    |
|                                               | Height                                                 | With legs: 103.95"<br>Without legs: 92.1"                                                                                                        | With legs: 2640mm<br>Without legs: 2340mm |
|                                               | Weight                                                 | 4798 pounds                                                                                                                                      | 2630 kg                                   |
| Operation, storage and transportation climate | Operation                                              | ≥59°F<br>≥20%                                                                                                                                    | ≥15°C                                     |
|                                               | Storage and transportation                             | 14°F-167°F                                                                                                                                       | -10°C to 75°C                             |
| Air filters                                   | Filtration method                                      | Multi-barrier air filtration                                                                                                                     |                                           |
| Water production and purification             | pH                                                     | 6.5-8.5                                                                                                                                          |                                           |
|                                               | Purification method                                    | Removing heavy metals, particles filtration, biological treatment, organic compounds (VOC, SVOC) and mineralization by cutting edge technologies |                                           |
|                                               | Production Capacity Per Day                            | 951 gallons (26.6°C/60%RH)                                                                                                                       | 3600 L (26.6°C/60%RH)                     |
|                                               |                                                        | 1585 Gallons (Max)                                                                                                                               | 6000 L (Max)                              |
|                                               | Refrigerant                                            | R410A                                                                                                                                            |                                           |
|                                               | Dispensing options                                     | Ambient                                                                                                                                          |                                           |
| Acoustic                                      | Noise Levels                                           | ≤ 80 dBA                                                                                                                                         |                                           |
| Lifting and transportation platform           | Transportation                                         | Standard cargo                                                                                                                                   |                                           |
|                                               | Lifting                                                | Forklift or crane                                                                                                                                |                                           |
| Electricity                                   | Nominal Operation Voltage                              | EU                                                                                                                                               | 3 phase 400, Vac/50 Hz                    |
|                                               |                                                        | USA                                                                                                                                              | 3 phase 480 Vac/60 Hz                     |
|                                               | Allowed Deviation on individual phases, Self Protected | Voltage ±5%<br>Frequency ±1Hz                                                                                                                    |                                           |
|                                               | Power Consumption                                      | Nominal: 60 kW<br>Peak: Up to 90 kW                                                                                                              |                                           |
|                                               | Energy Efficiency (26.6 C°, 60%RH)                     | 350 Wh/L                                                                                                                                         |                                           |
|                                               | Circuit Breaker Current                                | 400 Vac: 3 x 125 A<br>480 Vac: 3 x 135 A                                                                                                         |                                           |
|                                               | Mains Power connection                                 | 3 phase power cable 5 wires x 35mm <sup>2</sup>                                                                                                  |                                           |
|                                               | Main Power supply                                      | 3 phase sockets per local regulations                                                                                                            |                                           |
| Certifications                                | Electrical safety                                      | CE, CA, CB - IEC 60204-1                                                                                                                         |                                           |
|                                               | Water safety                                           | IS-5452                                                                                                                                          |                                           |