

Technical Data Sheet GENNY+

Category	Specification	Value	
Dimensions			
		Imperial	Metric
	Length	17.32"	44cm
	Width	11.82"	30cm
	Height	45.2"	115cm
	Weight	99 pounds	45kg
Climate			
	Operation climate	≥72°F-35%	≥22°C-≥35%
	Storage and transportation climate	59°F-104°F	15°C- 40°C
Air & water purification			
	Air filtration method	Multi-barrier air filtration	
	Purification method	Removing heavy metals, particles filtration, biologicalEUI treatment, organic compounds (VOC, SVOC) and mineralization by cutting edge technologies	
	pH	6.5-8.5	
Water production & dispensing			
	Production Capacity per Day	5.3 gallon (26.6°C/60%RH)	20 L (26.6°C/60%RH)
		6.6 Gallons (Max)	25 L (Max)
	Refrigerant	R134a	
	Dispensing options	Cold: 42.8°F, Hot: 180°F	Cold: 6°C, Hot: 82°C
	Internal Tank	Cold: 5.28 Gallons, Hot: 0.53 Gallon	Cold: 11 Litters, Hot: 2 liter
Lifting & transportation			
	Transportation platform	Standard cargo	
	Lifting platform	Standard - Forklift	
Electricity			
	Nominal Operation Voltage	EU	1 Phase, 230Vac, 50Hz
		USA	1 Phase, 120Vac, 60Hz
		Japan East	1 Phase, 100Vac, 50Hz
		Japan West	1 Phase, 105Vac, 60Hz
	Allowed Deviation on individual phases, Self Protected	Voltage ±5%	
		Frequency ±1Hz	
	Power Consumption	Nominal: 520W	
		Water Heating: 500W (EU), 500W (USA)	
		Maximum consumption: 1020 (EU), 1020 (USA)	
	Circuit Breaker Current	120VAC - 15A Slow + GFCI	230VAC - 16A Slow + RCD
	Main Power Connectors	USA, Japan - NEMA 5-15	Rest of the world - 1 phase outlet per local regulations
Acoustics			
	Noise Levels	≤ 45 dBA	
Childproof			
	Dedicated button to block hot water		
Certifications			
CE; IEC; (IECEE) CB Scheme; Low Voltage Directive 2014/35/EU; Electromagnetic Compatibility Directive 2014/30/EU; SGS-CSTC Standards; Dubai Central Laboratory Food & Environment Testing; EMC Test Report; Intertek Water Analysis; Water Quality Testing			