

Blueprint: GenAI Data Import

Process summary

A back-office process for safely committing GenAI-generated datasets (e.g., LLM-extracted product attributes, AI-generated catalog updates, AI-classified inventory adjustments) to a system of record. Validation runs unattended; commit is gated by a manager approval delivered via Slack.

Roles

- **Requester** — kicks off a workflow when a GenAI batch is ready. Provides the import payload.
- **Import Managers** (group) — receives approval requests in Slack. Approves or rejects.
- **System** — the Heroku-hosted system of record (`slack-heroku-demo-ars`).

Stages

Stage 1 — Validate (Automation Task)

- Agent: Regrello Agent
- Inputs (form):
 - `import_id` — text, required, external id
 - `source_dataset` — text (e.g. S3 URI), required
 - `requested_by` — email, required
 - `record_count` — number, required
- Steps:
 1. Look up `source_dataset` in the inventory database via SQL.
 2. Verify referential integrity (every SKU must exist; every warehouse must exist).
 3. Verify count matches `record_count` .
- Outputs:
 - `validation_status` — picklist: `PASS` | `FAIL`
 - `validation_notes` — long text (human-readable summary)
 - `row_errors_count` — number
- Branching:
 - `validation_status = FAIL` → end workflow with outcome **Rejected** (don't waste manager time).
 - `validation_status = PASS` → proceed to Stage 2.

Stage 2 — Manager Approval (Approval Task with Slack delivery)

- Approver: group **Import Managers**
- Due: 24 hours after assignment.
- On task assigned, fire Custom HTTP webhook to `heroku_slack_app` :
 - Method: POST
 - Path: `/api/afo/approve-request`
 - Body (JSON):

```
{
  "blueprint": "genai-data-import",
  "workflow_id": "{{workflow.id}}",
  "stage": "manager-approval",
  "task_id": "{{task.id}}",
  "import_id": "{{import.id}}",
  "requested_by": {
    "name": "{{requested_by.name}}",
    "email": "{{requested_by.email}}"
  },
  "action_required": "approve|reject",
  "validation": {
    "status": "{{validation.status}}",
    "row_errors_count": "{{row_errors_count}}",
    "record_count": "{{record_count}}"
  },
  "complete_url": "${REGRELL0_API_BASE}/api/v1/tasks/{{task.id}}/complete",
  "callback_token": "{{task.callback_token}}"
}
```

- The approval task waits open until the Heroku app calls AFO's `complete_url` with the manager's decision (Slack button → Heroku → AFO REST).
- On task complete, fire Custom HTTP webhook to `salesforce_apex_rest` :
 - Method: POST
 - Path: `/afo/import-request`
 - Body:

```
{
  "import_id": "{{import_id}}",
  "status":    "{{decision == 'approve' ? 'Approved' : 'Rejected'}}",
  "decided_by": "{{decided_by.email}}",
  "decided_at": "{{now}}",
  "afo_workflow_id": "{{workflow.id}}",
  "afo_task_id":    "{{task.id}}"
}
```

- Branching:
 - Reject → end workflow with outcome **Rejected**.
 - Approve → proceed to Stage 3.

Stage 3 — Commit (Automation Task)

- Custom HTTP integration: `heroku_slack_app`
- Request:
 - Method: POST
 - Path: `/api/afo/commit-import`
 - Body:

```
{
  "import_id":    "{{import_id}}",
  "source_dataset": "{{source_dataset}}",
  "approved_by":  "{{decided_by.email}}",
  "workflow_id":  "{{workflow.id}}"
}
```

- Outputs (form):
 - `committed_at` — datetime
 - `committed_by` — email
 - `result_summary` — long text
- On task complete, fire Custom HTTP webhook to `salesforce_apex_rest` with `status: Committed`.

Workspace integrations to set up first

1. `heroku_slack_app` (Custom HTTP)
 - Base URL: `https://slack-heroku-demo-ars-185a8cef5ba3.herokuapp.com`
 - Auth: Bearer token (use `AF0_BEARER_TOKEN` you provision on Heroku) or no auth for demo
2. `salesforce_apex_rest` (Custom HTTP)

- Base URL: `https://purple-slack-demo.my.salesforce.com/services/apexrest`
 - Auth: Bearer (Salesforce session token; for production swap to Connected App OAuth)
3. `Import Managers` (User Group)
- Members: yourself for the demo.

Outcomes

- `committed` — happy path
- `rejected` — manager rejected or validation failed
- `failed` — system error (wire to AFO's default failure handling)