



MC1672

TRIPLE 2-INPUT EXCLUSIVE-OR GATE




$V_{CC1} = \text{Pin 1 (5)}$
 $V_{CC2} = \text{Pin 16 (4)}$
 $V_{EE} = \text{Pin 8 (12)}$

$t_{pd} = 1.1 \text{ ns typ (510-ohm load)}$
 $= 1.3 \text{ ns typ (50-ohm load)}$
 $P_D = 220 \text{ mW typ/pkg}$
 Full Load Current, $I_L = -25 \text{ mAdc max}$



L SUFFIX
 CERAMIC PACKAGE
 CASE 620



F SUFFIX
 CERAMIC PACKAGE
 CASE 650

Number at end of terminal denotes pin number for L package.
 Number in parenthesis denotes pin number for F package.

Characteristic	Symbol	-30°C		+25°C		+85°C		Unit
		Min	Max	Min	Max	Min	Max	
Power Supply Drain Current	I_E	—	—	—	55	—	—	mAdc
Input Current								μAdc
A Inputs	I_{inH}	—	—	—	350	—	—	
B Inputs	I_{inH}	—	—	—	270	—	—	
Switching Times								ns
Propagation Delay	A Inputs	t_{++}, t_{-+}	2.0	—	1.8	—	2.3	
		t_{+-}, t_{--}	2.1	—	1.9	—	2.4	
	B Inputs	t_{++}, t_{-+}	2.5	—	2.3	—	2.8	
		t_{+-}, t_{--}	2.5	—	2.3	—	2.8	
Rise Time (10% to 90%)	t_+	—	2.7	—	2.5	—	2.9	ns
Fall Time (10% to 90%)	t_-	—	2.4	—	2.2	—	2.6	ns