


L SUFFIX
CERAMIC PACKAGE
CASE 620

V_{CC1} = Pin 1(5)
 V_{CC2} = Pin 16(4)
 V_{EE} = Pin 8(12)

t_{pd} = 1.1 ns typ (510-ohm load)
= 1.3 ns typ (50-ohm load)
 P_D = 220 mW typ/pkg
Full Load Current, I_L = -25 mAdc max



F SUFFIX
CERAMIC PACKAGE
CASE 650

Number at end of terminal denotes pin number for L package.
Number in parenthesis denotes pin number for F package.

Characteristic	Symbol	-30°C		+25°C		+85°C		Unit
		Min	Max	Min	Max	Min	Max	
Power Supply Drain Current	I _E	—	—	—	55	—	—	mAdc
Input Current								μAdc
A Inputs	I _{inH}	—	—	—	350	—	—	
B Inputs	I _{inH}	—	—	—	270	—	—	
Switching Times								ns
Propagation Delay	A Inputs	t ₊₊ ,t ₋₊	—	2.0	—	1.8	—	2.3
		t ₊₋ ,t ₋₋	—	2.1	—	1.9	—	2.4
	B Inputs	t ₊₊ ,t ₋₊	—	2.5	—	2.3	—	2.8
		t ₊₋ ,t ₋₋	—	2.5	—	2.3	—	2.8
Rise Time (10% to 90%)	t ₊	—	2.7	—	2.5	—	2.9	ns
Fall Time (10% to 90%)	t ₋	—	2.4	—	2.2	—	2.6	ns