

Functional Connectivity

How to study the connectivity in the brain with resting state fMRI

Alessio Borriero
PhD student


Computational application
to cognitive neuroscience



UNIVERSITÀ
DI TORINO


What does Functional Connectivity (FC) mean?

correlation of some kind of neurophysiological signal measured in different brain regions




Van Den Heuvel et al., 2010


A brief timeline of studies about functional connectivity




Correlation of spike trains



PCA-based FC with PET




Seed-based FC with rs-fMRI between motor cortices






Default-mode network in PET data

Default-mode network in fMRI data



Resting-state networks





Collective dynamics of small-world networks

Emergence of scaling in random networks

Organization of complex brain networks


Graph-based analysis of complex brain networks

Network Theory



Different approaches to FC with fMRI

model-dependent
(seed methods)





model-free
(without a priori information)

PCA

ICA




**clustering
methods**

**network-based
analysis**



The idea of a connected brain

has a very long story...




Medler, 1998

...but it was only in the last 3 decades that we managed to observe and analyse the connections inside the brain

Many types of connectivity


Anatomical



<https://www.umimri.com/dti/>

connections between neurons are too “slow” to explain cognitive functions...


Functional



Raichle, 2007

To study the functional connectivity allows to look at the emergent properties of the brain

Effective



Ting, 2014

Models of causal (and directed) relations between brain regions or group of neurons

Granger causality

Whole brain computational modeling (e.g. Hopf model)

Why the resting-state?

Lowe, 2010

The incredible amount of information in the activity at rest of the brain was discovered studying the “physiological noise” of the brain (cardiac and respiratory related signal).


Even removing this kind of noise of the brain, some residual spatio-temporal correlation of the signal remains...

let's try to look together at this correlation between brain regions in the resting-state brain signal

The Default-Mode Network

Since the first experimental observation of the brain in the early 20th century researchers has observed that the amount of activity of the brain at rest is nearly the same as during an active task.


In 1997, Shulman et al. observed the existence of *task-negative network* that seemed to be deactivate during active tasks, like language, motor or visual goal-directed tasks.



The Default-Mode Network

In 2001, Raichle et al. observed the same pattern of activated brain areas in subjects at rest using PET imaging. They coined the term *Default Mode Network* for this particular network.

In 2003, Greicius et al. discover the same network with fMRI resting state data.



The Default-Mode Network


Following this initial works, many studies have addressed the role of the Default Mode Network with respect to representation of the self, thinking about others and remembering the past.

Alteration of the DMN have also been related to clinical disorders such as Alzheimer's disease, autism depression and many others.

The brain region composing the DMN are the medial prefrontal cortex, the posterior cingulate cortex, the precuneus and the angular gyrus.

The Resting State Networks

In 2005, Beckmann et al. Defined a set of resting-state networks performing an ICA analysis over resting-state fMRI data.



Our lectures about functional connectivity


01 - Seed-based FC

02 - Graph analysis applied to resting-state fMRI

03 - Dynamic Functional Connectivity

01 - Seed-based FC

Just choose a seed region of the brain



And then correlate the average time series of the seed with all the voxels of the brain

It's simple :)

02 - Graph analysis applied to resting-state fMRI

Definitions

$G = (V, E) : \textit{Graph}$

$V = \{v_1, \dots, v_n\} : \textit{Set of vertices}$


$E = \{\{v_1, v_2\}, \dots, \{v_n, v_m\}\} : \textit{Set of edges}$

$A = (a_{ij}) : \textit{Adjacency matrix},$

where $a_{ij} = \begin{cases} 0 & \textit{if } \{v_i, v_j\} \in E, \\ 1 & \textit{if } \{v_i, v_j\} \notin E \end{cases}$

02 - Graph analysis applied to resting-state fMRI

Random graphs, scale-free property and small wordness




Boronchelli et al., 2013

	Random	Small-world	Scale-free
Degree distribution	Poisson	Peaked	Power law
Characteristic path length	Scales as $\log(N)$	Scales linearly with N for small p . And for higher p scales as $\log(N)$	Scales as $\log(N)/\log(\log N)$
Clustering coefficient	p (the connection probability)	High, but as $p \rightarrow 1$ behaves like a random graph	$((m-1)/2) * (\log(N)/N)$ where m is the number of edges with which a node enters
Robustness to failures	Similar responses to both random and targeted attacks	Similar response as random networks. This is because it has a degree distribution similar to random networks.	Highly resilient to random failures while being very sensitive to targeted attacks


Thadakamalla et al., 2004

02 - Graph analysis applied to resting-state fMRI


Centrality measures




(A) Degree Centrality




(B) Closeness Centrality



(C) Betweenness Centrality




(D). Jordan Centrality



(E) Eigenvector Centrality


02 - Graph analysis applied to resting-state fMRI

Percolation



Bordier et al., 2013

03 - Dynamic Functional Connectivity



References

Hebb DO. *The organization of Behavior. A Neuropsychological Theory*. Wiley. 1949

Aertsen AM, Gerstein GL, Habib MK, Palm G. *Dynamics of neuronal firing correlation: modulation of "effective connectivity"*. J Neurophysiol. 1989

Friston KJ, Frith CD, Liddle PF, Frackowiak RS. *Functional connectivity: the principal-component analysis of large (PET) data sets*. J Cereb Blood Flow Metab. 1993

Biswal B, Yetkin FZ, Haughton VM, Hyde JS. *Functional connectivity in the motor cortex of resting human brain using echo-planar MRI*. Magn Reson Med. 1995

Shulman GL, Fiez JA, Corbetta M, Buckner RL, Miezin FM, Raichle ME, Petersen SE. *Common Blood Flow Changes across Visual Tasks: 11. Decreases in Cerebral Cortex*. J Cognitive Neuroscience. 1997

Greicius MD, Krasnow B, Reiss AL, Menon V. *Functional connectivity in the resting brain: A network analysis of the default mode hypothesis*. PNAS. 2003

Medler DA. *A Brief history of connectionism*. Neural computing surveys. 1998

Callaway DS et al.. *Network Robustness and Fragility: Percolation on Random Graphs*. Physical Review Letters. 2000

Raichle ME, MacLeod AM, Snyder AZ, Powers WJ, Gusnard DA, Shulman GL. *A default mode of brain function*. Proc Natl Acad Sci U S A. 2001

Greicius MD, Krasnow B, Reiss AL, Menon V. *Functional connectivity in the resting brain: a network analysis of the default mode hypothesis*. Proc Natl Acad Sci U S A. 2003

References

Sporns O, Chialvo DR, Kaiser M, Hilgetag CC. *Organization, development and function of complex brain networks*. Trends Cogn Sci. 2004

Thadakamalla HP, Raghavan UN, Kumara S, Albert R. *Survivability of Multiagent-Based Supply Networks: A Topological Perspective*. IEEE Intelligent Systems. 2004

Sporns O, Chialvo DR, Kaiser M, Hilgetag CC. *Organization, development and function of complex brain networks*. Trends Cogn Sci. 2004

Beckmann CF, DeLuca M, Devlin JT, Smith SM. *Investigations into resting-state connectivity using independent component analysis*. Philos Trans R Soc Lond B Biol Sci. 2005

Borgatti SP, Everett MG. *A Graph-theoretic perspective on centrality*. Social networks. 2006

Raichle ME, Snyder AZ. *A default mode of brain function: A brief history of an evolving idea*. NeuroImage. 2007

Rogers BP, Morgan VL, Newton AT, Gore JC. *Assessing Functional Connectivity in the Human Brain by FMRI*. Magn Reson Imaging. 2007

Bullmore E, Sporns O. *Complex brain networks: graph theoretical analysis of structural and functional systems*. Nat Rev Neurosci. 2009

Van Den Heuvel MP, Hulshoff Pol HE. *Exploring the brain network: a review on resting-state fMRI functional connectivity*. Eur Neuropsychopharmacol. 2010

Lowe MJ. *A historical perspective on the evolution of resting-state functional connectivity with MRI*. Magn Reson Mater Phys. 2010

References

- Baronchelli A, Ferrer-i-Cancho R, Pastor-Satorras R, Chater N, Christiansen MH. *Networks in Cognitive Science*. Trends in Cognitive Sciences. 2013
- Hutchinson M et al.. *Dynamic functional connectivity: Promise, issues, and interpretations*. NeuroImage. 2013
- Bordier C, Nicolini C, Bifone A. *Graph Analysis and Modularity of Brain Functional Connectivity Networks: Searching for the Optimal Threshold*. Frontiers in Neuroscience, 2017
- Ting CM, Seghouane AK, Salleh SH, Noor AM. *Estimating Effective Connectivity from fMRI Data Using Factor-based Subspace Autoregressive Model*. IEEE Signal Processing Letters. 2014
- Smitha KA , Raja KA, Arun KM , Rajesh PG, Thomas B, Kapilamoorthy TR, Kesavadas C. *Resting state fMRI: A review on methods in resting state connectivity analysis and resting state networks*. The Neuroradiology Journal. 2017
- Vidaurre D, Smith SM, Woolrich MW. *Brain network dynamics are hierarchically organized in time*. PNAS. 2017
- Michel CM, Koenig T. *EEG microstates as a tool for studying the temporal dynamics of whole-brain neuronal networks: A review*. NeuroImage. 2018
- Demertzi et al.. *Human consciousness is supported by dynamic complex patterns of brain signal coordination*. Science advances. 2019
- Shelke S, Attar V. *Source detection of rumor in social network – A review*. Online Social Networks and Media. 2019
- Shahhosseini Y, Miranda MF. *Functional Connectivity Methods and Their Applications in fMRI Data*. Entropy. 2022