AudioTwin: Safety-Constrained Preferential Bayesian Optimisation for Query-Efficient Personalised Hearing-Aid Fitting

Alan Vallavaraj[a]

[a]*School of Computer Science and Engineering, University of Westminster, London, United Kingdom*

Abstract

Personalisation problems often require optimisation of an unknown subjective utility function from a small number of user interactions while respecting hard operational constraints. We present *AudioTwin*, a safety-constrained preferential Bayesian optimisation framework evaluated for personalised hearing-aid fitting. AudioTwin represents candidate processing configurations in a six-dimensional latent space controlling gain, spectral tilt, compression, noise reduction, speech enhancement and compression speed. Listener-specific utility is learned from noisy pairwise preferences using a Gaussian-process preference model with Laplace-approximated inference, while candidate configurations are restricted to a deterministic feasible region. Expected utility of the best option (qEUBO) is used to select decision-relevant comparisons. A frozen evaluation was conducted on 128 independent simulated listeners across three listening contexts and three pre-registered preference families. At the pre-specified primary endpoint of 20 preference queries, qEUBO reduced mean normalised regret from 0.3212 for the per-cell best of three strengthened static prescription baselines to 0.2405, a paired difference of -0.0807 (95% listener-level bootstrap CI $[-0.1027, -0.0593]$), corresponding to a 25.1% reduction in mean regret. Improvement was already evident after five queries. Against an otherwise identical preference-GP using random pair selection, qEUBO achieved lower regret at five queries (-0.0495, 95% CI $[-0.0627, -0.0364]$) and ten queries (-0.0371, 95% CI $[-0.0489, -0.0252]$), isolating an acquisition-efficiency benefit. Effects were strongest for comfort-oriented preferences and

Email address: a.vallavaraj@westminster.ac.uk (Alan Vallavaraj)

speech-oriented contexts, while music-intelligibility remained a failure case. AudioTwin provides a reproducible testbed for constrained active preference learning; human-listener validation is required before clinical effectiveness can be inferred.

Keywords: preferential Bayesian optimisation, preference learning, Gaussian process, active learning, personalisation, hearing aid, safe optimisation

---

1. Introduction

Many applied machine-learning systems must optimise outcomes that cannot be measured directly. Instead, the target is a latent human preference revealed through interaction. Recommender systems, interface personalisation, assistive technology and adaptive control are examples in which the objective is subjective, observations are noisy, and querying the user is costly. In such settings, the central learning problem is not merely to estimate a response surface, but to identify a high-utility decision using as few interactions as possible.

Bayesian optimisation (BO) provides a natural framework for sample-efficient optimisation of expensive black-box objectives [1]. When feedback is comparative rather than numerical, preferential Bayesian optimisation (PBO) replaces direct function observations with statements such as "configuration i is preferred to configuration j". Gaussian-process (GP) preference learning provides a probabilistic model for these comparisons [2, 3], while acquisition functions determine which comparisons should be presented next. The resulting problem is especially challenging when candidate queries must also satisfy hard constraints.

Hearing-aid fitting provides a concrete application with all of these properties. Prescriptive procedures such as NAL-NL2 provide a principled initial response based primarily on audiometric information [4], but individual listeners may prefer different trade-offs among audibility, comfort and signal-processing artefacts. User-controlled fitting studies show that listeners can make systematic adjustments [5–8], and pairwise preference approaches have been explored for hearing-aid personalisation [9–12]. However, practical deployment requires more than preference modelling: comparisons should be informative, the search space should remain clinically plausible, and performance should be assessed against strong rather than weak static comparators.

This paper presents *AudioTwin*, a reproducible framework for safety-constrained active preference learning in hearing-aid fitting. AudioTwin maintains a simulated listener with a hidden preference function and exposes the learner only to an imperfect audiometric estimate and pairwise choices. The learner uses a Laplace-approximated GP preference model and selects comparisons using expected utility of the best option (qEUBO) [13]. Every proposed configuration is projected into a deterministic feasible region before it can be queried or recommended.

The term *safety-constrained* is used in a computational sense: known model-based gain, output and transition constraints are enforced by construction. This differs from SafeOpt-style methods that learn an unknown safety function under uncertainty [14]. AudioTwin therefore evaluates active preference optimisation within a known feasible set; it does not claim medical-device safety certification.

The work was designed to address four methodological questions:

(Q1) Can active preference learning outperform a strengthened static prescription comparator under a small interaction budget?

(Q2) Does qEUBO add value beyond fitting the same GP preference model with random comparisons?

(Q3) How does performance vary across preference families and listening contexts?

(Q4) Can the evaluation be structured to reduce leakage between method development and final reporting?

The principal contributions are:

- a continuous six-dimensional, model-constrained personalisation space spanning gain, spectral tilt, compression, noise reduction, speech enhancement and compression speed;
- a matched comparison of qEUBO, BALD and GP-random acquisitions using the same GP model, candidate-generation process and preference-response streams;
- a conservative static comparator defined as the per-cell best of three prescription variants rather than a single default fitting;

- a frozen final evaluation with a reserved seed, pre-specified primary endpoint, listener-level bootstrap inference and an explicit rule for infeasible simulated listeners;
- a public implementation and publication snapshot enabling exact reproduction of the computational experiment.

The final evaluation contains 128 independent simulated listeners. The pre-specified primary hypothesis is that AudioTwin-qEUBO at 20 comparisons will achieve lower normalised regret than the per-cell best static comparator. Secondary analyses assess query efficiency against GP-random, BALD, larger budgets, context/family heterogeneity and a separately labelled post-hoc robustness family.

2. Related work

2.1. Preferential Bayesian optimisation

A pairwise preference $x_i \succ x_j$ can be represented through a latent utility function f with $f(x_i) > f(x_j)$. Chu and Ghahramani [2] introduced a GP framework for learning such latent preference functions from comparison data. A GP prior supplies a smooth probabilistic function model, and a non-Gaussian pairwise likelihood maps utility differences to comparison probabilities. Approximate posterior inference is then required, commonly via Laplace or expectation-propagation methods.

PBO extends this model from prediction to sequential decision making. At each iteration, the learner chooses a pair of alternatives, observes the user's preference, updates the posterior and ultimately recommends a configuration. Selection policies can target uncertainty, information gain or decision quality. BALD is an information-theoretic active-learning strategy based on expected information gain [15]. qEUBO instead chooses a candidate set by its expected utility of the best option and is derived directly from the terminal decision objective [13]. Astudillo et al. showed that qEUBO has a simple computational form and favourable simple-regret behaviour under appropriate assumptions.

Safety-aware BO is a related but distinct literature. SafeOpt, for example, expands a set of points whose unknown safety value is inferred with a GP while maintaining probabilistic safety guarantees [14]. In AudioTwin, the relevant constraints are deterministic functions of the estimated listener state and DSP configuration. The learner therefore searches only over projected feasible settings rather than learning whether a queried point is safe.

2.2. Machine learning for hearing-aid personalisation

Population-derived prescriptions are an important starting point in hearing-aid fitting, but they cannot encode every listener's subjective preference. NAL-NL2 combines audiometric information with models of speech intelligibility and loudness to derive frequency-dependent targets [4]. User-directed adjustment studies nevertheless demonstrate residual individual preference variation. Dreschler et al. [5] reported systematic client-controlled gain adjustments, while the "Goldilocks" studies showed that users can navigate low-dimensional self-fitting controls and obtain plausible gain responses [6, 7]. Sabin et al. [8] further evaluated a self-fitting interface that jointly adjusted gain and compression in real-world use.

Machine-learning approaches attempt to improve the efficiency of this preference elicitation. Birlutiu et al. [9] used multi-task GP preference learning on pairwise sound-quality data, demonstrating that structure shared across users can improve prediction. Vyas et al. [10] reduced a 24-dimensional configuration space to a set of presets and used online learning over pairwise comparisons; their simulation study indicated that the preferred preset could be identified with fewer comparisons than baseline approaches. Ni et al. [11] proposed efficient multi-band Bayesian learning and reported both simulation evidence and a small clinical experiment. More recently, Ignatenko et al. [12] formalised hearing-aid preference learning as sequential Bayesian optimisation with pairwise comparisons.

AudioTwin is complementary to these studies rather than a replacement for them. Its methodological focus is the joint evaluation of (i) continuous latent control across multiple DSP dimensions, (ii) deterministic feasibility constraints, (iii) decision-theoretic active acquisition, (iv) matched acquisition ablations, and (v) a leakage-resistant final protocol. In particular, the qEUBO comparison asks whether an explicit decision-theoretic acquisition policy improves recommendations relative to random querying when all other modelling choices are held fixed.

3. Problem formulation

Let $z \in \mathcal{Z} \subset [-1, 1]^6$ denote a latent hearing-aid configuration and $c \in \mathcal{C}$ denote a listening context. For listener l, an unknown utility function

$$u_l(z, c) : \mathcal{Z} \times \mathcal{C} \to \mathbb{R} \tag{1}$$

encodes preference. Direct utility observations are unavailable. Instead, a query presents two feasible settings (z_A, z_B) and returns a binary preference $y \in \{A, B\}$.

The optimisation objective after T comparisons is to recommend

$$\hat{z}_T(c) = \arg \max_{z \in \mathcal{S}(\hat{a}_l, c)} \mathbb{E}[f_l(z, c) \mid \mathcal{D}_T], \tag{2}$$

where $\hat{a}_l$ is an estimated audiogram, $\mathcal{S}$ is the deterministic feasible set, f_l is the learned latent preference model, and $\mathcal{D}_T$ is the set of observed pairwise choices.

For evaluation only, a hidden oracle utility u_l^* is available. Let $u_{l,c,F}^*$ be the feasible optimum for listener l, context c and preference family F, and let $u_{l,c,F}^{\mathrm{lo}}$ be the lower reference utility used by the experiment. Normalised regret is

$$r_T = \frac{u_{l,c,F}^* - u_l^*(\hat{z}_T, c, F)}{u_{l,c,F}^* - u_{l,c,F}^{\mathrm{lo}}}, \tag{3}$$

with lower values preferred.

The primary study endpoint averages the nine pre-registered context/family cells within each listener before population-level inference. This preserves the listener as the statistical unit and prevents the large number of within-listener rows from being treated as independent observations.

4. AudioTwin framework

4.1. Listener and observed audiogram

Each simulated listener has a seven-frequency true audiogram

$$a_l = [a_{250}, a_{500}, a_{1000}, a_{2000}, a_{4000}, a_{6000}, a_{8000}], \tag{4}$$

plus upper comfort limits and latent preference parameters. The fitting system observes a perturbed estimate

$$\hat{a}_l = a_l + \epsilon, \qquad \epsilon \sim \mathcal{N}(0, \sigma_a^2 I), \tag{5}$$

with $\sigma_a = 5$ dB in the final evaluation. The separation between a_l and $\hat{a}_l$ prevents the optimiser from receiving the exact hidden listener state.

4.2. Six-dimensional processing space

AudioTwin maps $z = (z_1, \ldots, z_6)$ to DSP controls. The dimensions represent overall gain offset, spectral tilt, compression-ratio scale, noise reduction, speech enhancement and compression speed. Gain is represented over ten bands centred at 250, 500, 750, 1000, 1500, 2000, 3000, 4000, 6000 and 8000 Hz.

For band k,

$$g_k(z) = \mathrm{clip}\left(g_k^{Rx}(\hat{a}_l) + b_1 z_1 + b_2 z_2 \log_2(f_k/1000), 0, g_k^{\max}\right). \tag{6}$$

Compression ratio is controlled as

$$CR_k(z) = \mathrm{clip}\left(CR_k^{Rx} 2^{2z_3}, 1, CR_{\max}\right), \tag{7}$$

so the lower extreme can reach linear compression. Noise-reduction and speech-enhancement strengths are monotone mappings from z_4 and z_5. Attack/release timing is interpolated logarithmically between fast and slow configurations through z_6.

The latent parameterisation is deliberately compact. It is not intended to reproduce every proprietary hearing-aid algorithm; rather, it provides a heterogeneous continuous space in which preference learning must coordinate spectral, dynamic and enhancement controls.

4.3. Deterministic feasible set

All methods operate under the same model-based constraints. A setting is admissible only if it satisfies limits on per-band gain, predicted output relative to upper comfort limits, adjacent-band spectral variation and maximum latent movement from the relevant anchor/previous setting. We denote the resulting set $\mathcal{S}(\hat{a}_l, c)$.

A conservative low-gain anchor is located first. Candidate settings are then projected from that anchor into the feasible region. Static baselines undergo the same projection as learned methods. Consequently, neither the baseline nor AudioTwin is evaluated at an unprojected setting that violates the frozen model constraints.

This design separates feasibility from acquisition: qEUBO, BALD and random selection are permitted to choose only among settings that have already passed deterministic projection.

4.4. Hidden preference oracle

The simulation oracle combines four components:

$$u_l^*(z, c, F) = w_A A(z, c) - w_C P_C(z, c) - w_D P_D(z) - w_Q P_Q(z, c), \quad (8)$$

where A is an audibility/intelligibility-like term, P_C penalises loudness discomfort, P_D penalises deviation from a listener-specific ideal gain curve and P_Q penalises processing/compression artefacts. Weights vary by listener and preference family.

Three families were defined before the final evaluation: *intelligibility*, *comfort* and *balanced*. A fourth *noise-sensitive* family includes extra compression-in-noise penalties and is reported only as a post-hoc robustness analysis because it was introduced after development diagnostics.

Preference observations include stochastic response noise. For candidates z_A and z_B,

$$P(A \succ B) = \frac{\lambda}{2} + (1 - \lambda)\Phi\left(\frac{u_l^*(z_A) - u_l^*(z_B)}{\sqrt{2}\sigma}\right), \quad (9)$$

where λ represents lapse-like random responses and σ controls comparison noise.

The oracle is intentionally analytic and computationally inexpensive. It is a controlled benchmark for optimisation, not a validated model of human auditory perception. The implications of this distinction are addressed in Section 9.

5. Preference model and acquisition

5.1. Laplace GP preference model

AudioTwin places a GP prior on latent utility,

$$f(z) \sim \mathcal{GP}(m(z), k(z, z')). \quad (10)$$

The prior mean

$$m(z) = -\gamma\|z\|^2 \quad (11)$$

creates a soft pull towards the prescription origin without hard-coding a development-derived preferred setting.

The covariance is Matérn-5/2:

$$k(z, z') = \sigma_f^2 \left(1 + \sqrt{5}r + \frac{5r^2}{3}\right) e^{-\sqrt{5}r}, \qquad r = \frac{\|z - z'\|}{\ell}. \tag{12}$$

For an observed comparison in which item i is preferred to item j,

$$P(i \succ j \mid f) = \Phi\left(\frac{f_i - f_j}{\sqrt{2}\sigma_n}\right). \tag{13}$$

The non-Gaussian posterior is approximated by a Laplace expansion about the MAP latent vector. Predictive covariance includes uncertainty propagated from the queried latent values. Model hyperparameters are selected periodically by maximising the Laplace-approximated marginal likelihood over a frozen grid: lengthscale $\{0.6, 1.0, 1.6\}$, signal variance $\{0.1, 0.3, 1.0\}$ and assumed preference-noise scale $\{0.05, 0.10, 0.20\}$.

5.2. qEUBO

For two posterior utilities f_i and f_j, qEUBO with $q = 2$ scores a pair by

$$\alpha_{\mathrm{EUBO}}(i, j) = \mathbb{E}[\max(f_i, f_j)]. \tag{14}$$

For a jointly Gaussian posterior this expectation is available in closed form. If $d = \mu_i - \mu_j$ and

$$\theta^2 = C_{ii} + C_{jj} - 2C_{ij}, \tag{15}$$

then with $\alpha = d/\theta$,

$$\mathbb{E}[\max(f_i, f_j)] = \mu_i \Phi(\alpha) + \mu_j \Phi(-\alpha) + \theta\phi(\alpha). \tag{16}$$

The selected pair maximises Eq. (16) among sufficiently separated feasible candidates.

5.3. BALD and GP-random controls

BALD approximates the mutual information between the comparison response and the latent preference function [15]. It provides an uncertainty-centred active policy with the same posterior model as qEUBO.

GP-random is a stronger control than an unmodelled random baseline. It fits the identical Laplace GP, uses the same candidate pools, minimum separation logic and recommendation rule, but selects admissible query pairs uniformly at random. qEUBO–GP-random differences therefore isolate the effect of acquisition selection more cleanly than qEUBO–static comparisons alone.

5.4. Candidate pools and recommendation

At each interaction the candidate pool contains the conservative anchor, the safely projected prescription, uniform feasible samples and local samples around the current posterior incumbent. At evaluation checkpoints the recommendation is the feasible candidate with highest posterior mean. Budgets are $T \in \{0, 5, 10, 20, 30, 50\}$.

At $T = 0$ the recommendation is exactly the safely projected prescription. This creates an intentionally conservative starting point: any subsequent benefit must be learned from preferences rather than inherited from a hand-crafted initial configuration.

6. Experimental protocol

6.1. Contexts, preference families and methods

The final study uses three contexts: noisy conversation, lecture and music. The primary population crosses them with the three pre-registered preference families (intelligibility, comfort and balanced), yielding nine primary cells per listener. The post-hoc noise-sensitive family is excluded from the primary estimate.

The learned methods are AudioTwin-qEUBO, AudioTwin-BALD and AudioTwin-GP-random. The static comparators are:

1. prescription: the safely projected prescription with default compression;
2. prescription-linear: prescription gain with linear compression;
3. prescription-slow: prescription with slow compression.

For each listener/context/family cell, the primary static comparator is the *best* of these three alternatives according to the hidden oracle. This is deliberately more difficult to beat than choosing one global baseline and protects against a result driven solely by a weak default compression choice.

6.2. Frozen development/final separation

Development used separate seeds, principally seed 424242 for the final development sweep. The final seed 777000111 was reserved. Before final-seed outcomes were inspected, the primary method, baselines, budgets, oracle families, final sample size, primary contrast, bootstrap procedure and analysis seed were recorded in the protocol and tagged in version control.

The final sample size was fixed at 128 simulated listeners. The choice used development-set variability only: the development qEUBO-versus-static effect at $T = 20$ was approximately -0.0566 with paired standard deviation approximately 0.158, suggesting roughly 82 listeners for 90% normal-approximation power at two-sided $\alpha = 0.05$. A larger $N = 128$ was chosen before exposing final outcomes to provide margin for sampling variability and subgroup summaries.

One original final draw (task 55) contained no feasible low-gain anchor under the frozen model constraints and failed before preference optimisation. Before inspecting performance outcomes, a deterministic rule was recorded: do not relax the constraint set and replace an infeasible draw with the next unused task ID. Task 55 was therefore replaced by task 128. The final analysable set remained $N = 128$.

6.3. Primary and secondary estimands

For each listener, regret is first averaged over the nine pre-registered context/family cells. The primary contrast is

$$\Delta_{20} = \bar{r}_{20}^{\text{qEUBO}} - \bar{r}^{\text{best static}}, \tag{17}$$

where negative values favour qEUBO.

The primary uncertainty interval is a non-parametric 95% listener-level bootstrap CI with 20,000 resamples and analysis RNG seed 20261011. Resampling is performed over listeners, not rows.

Pre-specified secondary analyses comprise the full regret trajectory, qEUBO versus GP-random at $T = 5$ and $T = 10$, qEUBO versus static at $T = 50$, BALD, and context/family breakdowns. The noise-sensitive family is explicitly labelled post-hoc.

6.4. Reproducibility

The final result bundle contains 128 listener files and 32,256 rows. A validation gate checks task IDs, listener IDs, contexts, families, methods, query budgets, row uniqueness and finite regret before inferential output is printed. The frozen final analysis was executed twice after the dataset was complete and produced byte-identical output.

Code, protocol, compact final summaries and manuscript sources are available at `https://github.com/alanvallavaraj/AudioTwin`. The publication code snapshot is tagged `publication-v1.0.0`; the frozen protocol/analysis state is tagged `final-protocol-v1.3`.

Table 1: Primary final-evaluation result. Lower normalised regret is better. The static value is the mean of the per-cell best of three prescription variants.

Method	Queries	Mean regret	Paired difference	95% CI
Best static	0	0.3212	–	–
AudioTwin-qEUBO	20	0.2405	−0.0807	[−0.1027, −0.0593]

Table 2: Paired listener-level differences in normalised regret relative to the best static comparator. Negative values favour the learned method.

	Query budget					
Method	0	5	10	20	30	50
qEUBO	+0.0551	-0.0294	-0.0568	-0.0807	-0.0972	-0.1234
BALD	+0.0551	+0.0285	-0.0079	-0.0506	-0.0506	-0.0754
GP-random	+0.0551	+0.0201	-0.0196	-0.0482	-0.0754	-0.1018

7. Results

7.1. Primary outcome

The per-cell best static comparator achieved mean normalised regret 0.3212. At the pre-specified primary endpoint of 20 pairwise queries, qEUBO achieved 0.2405. The paired mean difference was −0.0807 with 95% bootstrap CI [−0.1027, −0.0593] (Table 1). Relative to the static mean, this is a 25.1% reduction in mean regret.

The complete mean-regret curves are shown in Fig. 1. qEUBO begins at regret 0.3763 because the zero-query setting is the prescription rather than the retrospectively best static variant. It crosses below the best-static reference by five queries and improves monotonically at the reported checkpoints.

Table 2 reports paired differences relative to the best static comparator. At $T = 5$, the qEUBO interval is already entirely below zero (−0.0294, 95% CI [−0.0470, −0.0123]). The difference increases to −0.1234 at $T = 50$.

7.2. Acquisition efficiency

The matched qEUBO-versus-GP-random comparison isolates active query selection from GP fitting. At five queries, qEUBO reduced regret by 0.0495 relative to GP-random (95% CI [−0.0627, −0.0364]). At ten queries, the difference was −0.0371 (95% CI [−0.0489, −0.0252]). Thus the qEUBO advantage is clearest when the preference budget is small.




Figure 1: Mean normalised regret across the nine pre-registered cells as a function of pairwise preference budget. The dashed line is the best static comparator (mean regret 0.3212). All learned policies use the same Laplace GP preference model.

At larger budgets the GP-random policy partially catches up. At $T = 50$, mean regrets are 0.1978 for qEUBO and 0.2194 for GP-random. This is consistent with qEUBO primarily improving *query allocation efficiency*: with sufficient random comparisons, the shared GP model can eventually identify useful regions, whereas qEUBO reaches lower regret earlier.

7.3. Context heterogeneity

The primary $T = 20$ effect varies by context (Fig. 2). Noisy conversation shows a mean difference of -0.1102 (95% CI $[-0.1331, -0.0873]$) and lecture -0.1124 (95% CI $[-0.1415, -0.0835]$). Music is weaker at -0.0197 with CI $[-0.0443, +0.0047]$, which includes zero.

7.4. Preference-family heterogeneity

Effects also vary by preference objective (Fig. 3). Comfort shows the largest improvement: -0.1848 (95% CI $[-0.2171, -0.1533]$). The balanced family improves by -0.0458 (95% CI $[-0.0745, -0.0176]$). Intelligibility averaged across contexts is -0.0117 with CI $[-0.0420, +0.0189]$, providing no clear aggregate advantage at $T = 20$.




Figure 2: Context-specific qEUBO $T = 20$ paired regret difference relative to the per-cell best static comparator. Error bars are 95% listener-level bootstrap intervals. Negative values favour qEUBO.

7.5. Context-by-family analysis

Figure 4 and Table 3 expose the interaction behind the aggregate results. qEUBO improves all three preference families in noisy conversation and lecture. In music, comfort still improves strongly (-0.1345), balanced is essentially neutral ($+0.0001$), and intelligibility favours the static comparator ($+0.0754$, 95% CI $[+0.0371, +0.1132]$).

7.6. Post-hoc noise-sensitive robustness family

The noise-sensitive family was introduced after a development diagnostic and cannot support the primary claim. It is nevertheless informative as a harder robustness case. qEUBO remains worse than static at $T = 5$ ($+0.0633$, 95% CI $[+0.0339, +0.0922]$) and $T = 10$ ($+0.0300$, CI $[+0.0000, +0.0590]$), is indistinguishable at $T = 20$ and $T = 30$, and becomes clearly better only at $T = 50$ (-0.0446, CI $[-0.0738, -0.0158]$). This contrasts with the pre-registered population, where qEUBO is already superior by five queries.




Figure 3: Preference-family qEUBO $T = 20$ paired regret difference relative to best static. Negative values favour qEUBO.

8. Discussion

8.1. Main finding: decision-theoretic acquisition improves low-budget personalisation

The principal result is not simply that a GP can learn a simulated listener preference. Prior hearing-aid work already demonstrates that pairwise comparisons and Bayesian models can support personalisation [9–12]. The stronger result is that, under matched modelling conditions, *which comparisons are requested* materially changes the recommendation quality at small budgets.

At five queries, qEUBO is already better than the strengthened static reference, while BALD and GP-random remain worse than static on average. qEUBO also beats GP-random directly by nearly 0.05 normalised-regret units. At ten queries the qEUBO-versus-random advantage remains substantial. The convergence of policies at larger budgets further supports an efficiency interpretation: random exploration eventually supplies the GP with useful coverage, but qEUBO places early queries in regions that more directly improve the terminal recommendation.

This distinction matters in human-in-the-loop applications. A comparison is not free: it consumes attention, can induce fatigue and may become less reliable with repeated exposure. The practical target is therefore not merely




Figure 4: Context-by-family mean paired difference for qEUBO at $T = 20$ versus best static. Negative values favour qEUBO; positive values favour static fitting.

asymptotic preference-function recovery; it is acceptable decision quality after a small number of interactions. qEUBO's decision-theoretic objective is aligned with that target.

8.2. Strength of the static comparator

The primary baseline is intentionally favourable to static fitting. Each listener/context/family cell may retrospectively take the best result from the default prescription, linear compression or slow compression. AudioTwin therefore competes with an oracle-selected static variant rather than a single fixed prescription.

This design was motivated by development diagnostics showing that an unfavourable default compression configuration could create an artificial advantage for learned methods. Instead of leaving that weakness in place, the baseline family was strengthened before final-seed evaluation. As a consequence, the reported 25.1% reduction is harder to obtain but easier to interpret: qEUBO is learning listener/context-specific preferences beyond what can be captured by selecting among the three tested static prescriptions.

8.3. Why comfort is easier to improve than intelligibility

The large comfort effect and smaller intelligibility effect are plausible given the problem construction and application domain. A prescription

Table 3: Context-by-family qEUBO $T = 20$ differences versus best static.

Context	Family	Mean difference	95% CI
Noisy conversation	Intelligibility	-0.0448	$[-0.0833, -0.0063]$
Noisy conversation	Comfort	-0.2046	$[-0.2386, -0.1706]$
Noisy conversation	Balanced	-0.0811	$[-0.1166, -0.0461]$
Lecture	Intelligibility	-0.0656	$[-0.1051, -0.0260]$
Lecture	Comfort	-0.2152	$[-0.2607, -0.1709]$
Lecture	Balanced	-0.0564	$[-0.0963, -0.0164]$
Music	Intelligibility	+0.0754	$[+0.0371, +0.1132]$
Music	Comfort	-0.1345	$[-0.1646, -0.1048]$
Music	Balanced	+0.0001	$[-0.0358, +0.0368]$

rule is already designed to supply audibility and speech-oriented gain from audiometric information. The room for preference optimisation may therefore be smaller when the hidden objective is dominated by an intelligibility-like term.

Comfort is more idiosyncratic. Listener-specific upper limits, preferred gain offsets and processing penalties create heterogeneous optima that cannot be recovered from the audiogram alone. Pairwise preference learning has more information to add in this setting. This pattern is consistent with self-fitting studies showing that user-selected settings often remain near prescription-derived solutions while exhibiting systematic individual deviations [5, 8].

8.4. Context matters

Noisy conversation and lecture exhibit robust qEUBO gains, whereas music is weak overall. The context-by-family analysis makes the reason visible: music-comfort benefits strongly, but music-intelligibility is a clear negative result.

This failure case should not be treated as noise to be averaged away. It suggests at least three possible forms of model mismatch. First, the intelligibility-like oracle is speech-oriented and may create an unnatural objective when combined with the music context. Second, the six latent controls were chosen around hearing-aid speech-processing parameters and may not express music-relevant dimensions sufficiently. Third, a stationary GP with a single smooth kernel may be a poor approximation when local preference geometry differs substantially across acoustic domains.

A future system should therefore consider context-conditioned models or multi-task kernels rather than assuming that one preference surface transfers uniformly across contexts. The earlier multi-task preference-learning literature provides a natural starting point [9].

8.5. Relation to recent hearing-aid ML

The present results should be interpreted in the context of increasingly active machine-learning research on hearing-aid personalisation. Vyas et al. [10] demonstrated efficient pairwise identification over a discrete preset set; Ni et al. [11] improved training efficiency through multi-band Bayesian learning and included a small clinical validation; Ignatenko et al. [12] analysed sequential BO with pairwise comparison using hearing-aid fitting as a motivating application.

AudioTwin differs most clearly in experimental emphasis. It treats the final evaluation as a controlled acquisition-policy comparison with a frozen protocol, continuous multidimensional latent control, explicit feasibility projection and an oracle-strengthened static baseline. This allows the study to answer a machine-learning question—whether qEUBO improves recommendation regret under limited preference budgets—without claiming that the simulated utility constitutes clinical evidence.

8.6. Feasibility constraints and the rejected listener

The final evaluation includes a useful edge case. One simulated listener admitted no feasible low-gain anchor under the frozen constraints. Rather than weakening constraints after observing the failure, the task was recorded as infeasible and replaced using a deterministic rule defined before performance analysis.

This behaviour is desirable for safety-sensitive optimisation. An algorithm should be allowed to fail closed when the assumed feasible domain is empty. In a real hearing-care workflow, the corresponding response would not be automatic relaxation of model limits; it would be fallback to a verified configuration, additional measurement or professional review.

Again, these constraints are computational guardrails and should not be equated with regulatory or clinical safety guarantees.

8.7. Protocol discipline as part of applied ML evaluation

Applied optimisation studies are vulnerable to researcher degrees of freedom. Candidate spaces, baselines, oracle definitions, budgets and random

seeds can all be changed after preliminary results are seen. Such adaptation may be necessary during development, but it weakens confirmatory interpretation if the same outcomes are repeatedly reused.

The AudioTwin workflow therefore records development/final separation. A reserved final seed was not used during method development. The primary endpoint, sample size and bootstrap procedure were frozen before final outcome inspection. A development-discovered compression artefact was not inserted into the three pre-registered utility families; instead it was isolated into a post-hoc robustness family. These choices do not eliminate all design bias—the simulator itself was developed by the research team—but they reduce direct tuning to the reported final random draw.

9. Limitations

9.1. Simulation is not clinical validation

The most important limitation is that all 128 final listeners are simulated. The oracle contains plausible ingredients—audibility, comfort, ideal-gain deviation, compression preference and response noise—but it is not a human participant. Lower oracle regret demonstrates successful optimisation of the specified benchmark, not improved hearing outcomes.

This limitation is particularly important because recent hearing-aid personalisation studies include real participant data [10, 11]. AudioTwin should therefore be viewed as a methodological and reproducibility study that motivates, rather than replaces, a human-listener trial.

9.2. The oracle and learner share structural assumptions

Although the oracle is not directly exposed to the learner, both are smooth functions over the same latent DSP space. A Matérn GP is consequently a reasonable model class. Real preferences may include discontinuities, hysteresis, context drift, adaptation and non-stationary judgement noise. Future simulation studies should stress-test acquisition policies under explicit model misspecification.

9.3. Approximate optimum and normalised regret

The oracle optimum is computed numerically rather than analytically, using a random-plus-evolutionary search specified in the frozen experiment. Regret is therefore measured relative to an approximate feasible optimum. This is suitable for comparing methods under the same benchmark but introduces numerical approximation error into the absolute regret scale.

9.4. Known rather than learned constraints

AudioTwin projects candidates against known model constraints. It does not infer safety from observations and therefore does not solve the full safe-BO problem addressed by methods such as SafeOpt [14]. Applications with uncertain constraints would require a probabilistic constraint model and a different safety analysis.

9.5. Limited DSP and context model

The six-dimensional latent space omits many commercial hearing-aid features, including binaural coordination, adaptive directionality, feedback cancellation, source separation and modern neural speech enhancement. The three final contexts likewise cover only a small subset of real environments. The reported effects should not be extrapolated to a complete hearing-aid signal chain.

9.6. No computational-time or human-fatigue outcome

The study counts preference comparisons but does not model response time, fatigue or cognitive burden. Pairwise queries with similar candidates may be information-rich yet perceptually difficult. Human studies should jointly optimise statistical efficiency and usability.

10. Future work

The highest-priority next step is a prospective listening study. A suitable initial design would compare a verified prescription, conventional fine-tuning and AudioTwin-qEUBO within participants. Outcomes should include preference, speech recognition in noise, comfort, listening effort, test–retest stability and the number of comparisons required to reach a stable setting. Stimulus duration should be chosen with reference to evidence that preference reliability depends on the amount of speech presented [16].

A second direction is hierarchical preference learning. Existing work suggests that preference structure can be shared across listeners [9]; a population prior could reduce cold-start queries while retaining individual adaptation.

A third direction is explicit context transfer. Instead of fitting each context independently, a multi-task kernel could share statistical strength between noisy conversation and lecture while allowing music to retain a distinct latent function. The negative music-intelligibility result makes this a particularly testable hypothesis.

Finally, learned constraints and modern neural audio processing could be integrated. The optimisation layer could tune parameters of speech enhancement or source-separation systems, while a probabilistic safety/quality model excludes settings with unacceptable distortion. Such extensions would move AudioTwin from a controlled DSP testbed towards a broader human-centred machine-learning framework.

11. Conclusion

AudioTwin formulates personalised hearing-aid fitting as constrained preferential Bayesian optimisation. In a frozen final evaluation of 128 simulated listeners, qEUBO reduced mean normalised regret from 0.3212 for an oracle-strengthened static comparator to 0.2405 after 20 pairwise choices, a 25.1% reduction. The primary paired difference was -0.0807 with 95% listener-level bootstrap CI $[-0.1027, -0.0593]$.

More importantly for the machine-learning contribution, qEUBO outperformed a matched GP-random acquisition policy at five and ten comparisons. This demonstrates an early-budget benefit attributable to active query selection rather than GP preference modelling alone. Performance was heterogeneous: comfort-oriented and speech-oriented contexts showed the largest gains, whereas music-intelligibility favoured static fitting at the primary budget.

These results support qEUBO as a promising acquisition strategy for sparse, noisy personalisation problems with known feasibility constraints. They do not establish clinical benefit. The next evidential step is human-listener validation under realistic speech and acoustic conditions.

CRediT authorship contribution statement

Alan Vallavaraj: Conceptualisation, Methodology, Software, Validation, Formal analysis, Investigation, Data curation, Visualisation, Writing – original draft, Writing – review & editing, Project administration.

Funding

This research did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors.

Declaration of competing interest

The author declares no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Ethics statement

The reported final evaluation is a computational simulation and did not recruit human participants or use identifiable participant data. Human-participant ethics approval was therefore not required for the experiments reported here. Any prospective human-listener validation will require appropriate institutional ethics review and informed consent.

Data and code availability

The AudioTwin source code, frozen protocol, analysis implementation, compact final result summaries and LaTeX manuscript sources are available at `https://github.com/alanvallavaraj/AudioTwin`. The publication code snapshot is tagged `publication-v1.0.0`; the final evaluation protocol is tagged `final-protocol-v1.3`. Raw per-task HPC parquet outputs are not included in the public repository; the compact derived result summaries required to reproduce all manuscript statistics and plots are included under `publication/results/`.

Declaration of generative AI and AI-assisted technologies in the manuscript preparation process

During the preparation of this work, the author used ChatGPT (OpenAI) to assist with manuscript organisation, language refinement, LaTeX preparation and consistency checking. The author reviewed and edited the generated material, verified the reported numerical results against the frozen analysis outputs, and takes full responsibility for the content of the publication.

Acknowledgements

The author acknowledges computational resources used for the final simulation experiments and institutional research support from the University of Westminster. No human participant contributed data to the reported final evaluation.

References

[1] B. Shahriari, K. Swersky, Z. Wang, R. P. Adams, N. de Freitas, Taking the human out of the loop: A review of bayesian optimization, Proceedings of the IEEE 104 (1) (2016) 148–175. doi:10.1109/JPROC.2015.2494218.

[2] W. Chu, Z. Ghahramani, Preference learning with gaussian processes, in: Proceedings of the 22nd International Conference on Machine Learning, 2005, pp. 137–144. doi:10.1145/1102351.1102369.

[3] C. E. Rasmussen, C. K. I. Williams, Gaussian Processes for Machine Learning, MIT Press, 2006. doi:10.7551/mitpress/3206.001.0001.

[4] G. Keidser, H. Dillon, M. Flax, T. Ching, S. Brewer, The NAL-NL2 prescription procedure, Audiology Research 1 (1) (2011) e24. doi:10.4081/audiores.2011.e24.

[5] W. A. Dreschler, G. Keidser, E. Convery, H. Dillon, Client-based adjustments of hearing aid gain: The effect of different control configurations, Ear and Hearing 29 (2) (2008) 214–227. doi:10.1097/AUD.0b013e31816453a6.

[6] A. Boothroyd, C. Mackersie, A "goldilocks" approach to hearing-aid self-fitting: User interactions, American Journal of Audiology 26 (3S) (2017) 430–435. doi:10.1044/2017_AJA-16-0125.

[7] C. Mackersie, A. Boothroyd, A. Lithgow, A "goldilocks" approach to hearing-aid self-fitting: Ear-canal output and speech intelligibility index, Ear and Hearing 40 (1) (2019) 107–115. doi:10.1097/AUD.0000000000000617.

[8] A. T. Sabin, D. J. Van Tasell, B. Rabinowitz, S. Dhar, Validation of a self-fitting method for over-the-counter hearing aids, Trends in Hearing 24 (2020) 2331216519900589. doi:10.1177/2331216519900589.

[9] A. Birlutiu, P. C. Groot, T. Heskes, Multi-task preference learning with an application to hearing aid personalization, Neurocomputing 73 (7–9) (2010) 1177–1185. doi:10.1016/j.neucom.2009.11.025.

[10] D. Vyas, R. Brummet, Y. Anwar, J. Jensen, E. Jorgensen, Y.-H. Wu, O. Chipara, Personalizing over-the-counter hearing aids using pairwise

comparisons, Smart Health 23 (2022) 100231. doi:10.1016/j.smhl.2021.100231.

[11] A. Ni, E. Lobarinas, N. Kehtarnavaz, Efficient personalization of amplification in hearing aids via multi-band bayesian machine learning, IEEE Access 12 (2024) 112116–112123. doi:10.1109/ACCESS.2024.3441762.

[12] T. Ignatenko, K. Kondrashov, M. Cox, B. de Vries, On preference learning based on sequential bayesian optimization with pairwise comparison, Artificial Intelligence 348 (2025) 104400. doi:10.1016/j.artint.2025.104400.

[13] R. Astudillo, Z. J. Lin, E. Bakshy, P. I. Frazier, qEUBO: A decision-theoretic acquisition function for preferential bayesian optimization, in: Proceedings of the 26th International Conference on Artificial Intelligence and Statistics, Vol. 206 of Proceedings of Machine Learning Research, 2023, pp. 1093–1114.

[14] Y. Sui, A. Gotovos, J. Burdick, A. Krause, Safe exploration for optimization with gaussian processes, in: Proceedings of the 32nd International Conference on Machine Learning, Vol. 37 of Proceedings of Machine Learning Research, 2015, pp. 997–1005.

[15] N. Houlsby, F. Huszár, Z. Ghahramani, M. Lengyel, Bayesian active learning for classification and preference learning, arXiv preprint arXiv:1112.5745 (2011).

[16] W. M. Whitmer, B. Caswell-Midwinter, G. Naylor, The effect of stimulus duration on preferences for gain adjustments when listening to speech, International Journal of Audiology 61 (11) (2022) 940–947. doi:10.1080/14992027.2021.1998676.